

# Package ‘rPraat’

December 4, 2019

**Type** Package

**Title** Interface to Praat

**Version** 1.3

**Encoding** UTF-8

**Maintainer** Tomas Boril <borilt@gmail.com>

**Description** Read, write and manipulate 'Praat' TextGrid, PitchTier, Pitch, IntensityTier, Formant, Sound, and Collection files <<http://www.fon.hum.uva.nl/praat/>>.

**URL** <https://github.com/bbTomas/rPraat/>

**BugReports** <https://github.com/bbTomas/rPraat/issues>

**License** MIT + file LICENSE

**LazyData** TRUE

**Depends** R (>= 3.4.0)

**Imports** graphics (>= 3.1.0),  
dplyr (>= 0.7.8),  
stringr (>= 1.3.1),  
readr (>= 1.2.1),  
dygraphs (>= 1.1.1.6),  
tuneR (>= 1.3.3)

**RoxygenNote** 6.1.1

**Suggests** testthat

## R topics documented:

as.formant . . . . .	4
as.it . . . . .	4
as.pitch . . . . .	5
as.pt . . . . .	5
as.snd . . . . .	6
as.tg . . . . .	6
col.read . . . . .	7
col.write . . . . .	8
detectEncoding . . . . .	9
formant.cut . . . . .	9
formant.cut0 . . . . .	10
formant.plot . . . . .	11

formant.read . . . . .	12
formant.sample . . . . .	13
formant.toArray . . . . .	14
formant.toFrame . . . . .	14
formant.write . . . . .	15
ifft . . . . .	16
isInt . . . . .	16
isLogical . . . . .	17
isNum . . . . .	18
isString . . . . .	18
it.cut . . . . .	19
it.cut0 . . . . .	20
it.interpolate . . . . .	21
it.legendre . . . . .	22
it.legendreDemo . . . . .	23
it.legendreSynth . . . . .	23
it.plot . . . . .	24
it.read . . . . .	25
it.sample . . . . .	25
it.write . . . . .	26
pitch.cut . . . . .	27
pitch.cut0 . . . . .	28
pitch.plot . . . . .	29
pitch.read . . . . .	29
pitch.sample . . . . .	30
pitch.toArray . . . . .	31
pitch.toFrame . . . . .	32
pitch.write . . . . .	32
pt.cut . . . . .	33
pt.cut0 . . . . .	34
pt.Hz2ST . . . . .	35
pt.interpolate . . . . .	35
pt.legendre . . . . .	36
pt.legendreDemo . . . . .	37
pt.legendreSynth . . . . .	37
pt.plot . . . . .	38
pt.read . . . . .	39
pt.sample . . . . .	40
pt.write . . . . .	40
round2 . . . . .	41
seqM . . . . .	42
snd.cut . . . . .	43
snd.cut0 . . . . .	44
snd.plot . . . . .	45
snd.read . . . . .	46
snd.sample . . . . .	47
snd.write . . . . .	47
strTrim . . . . .	48
str_contains . . . . .	49
str_find . . . . .	49
str_find1 . . . . .	50
tg.boundaryMagnet . . . . .	51

tg.checkTierInd . . . . .	52
tg.countLabels . . . . .	52
tg.createNewTextGrid . . . . .	53
tg.cut . . . . .	54
tg.cut0 . . . . .	55
tg.duplicateTier . . . . .	56
tg.duplicateTierMergeSegments . . . . .	56
tg.findLabels . . . . .	58
tg.getEndTime . . . . .	59
tg.getIntervalDuration . . . . .	60
tg.getIntervalEndTime . . . . .	60
tg.getIntervalIndexAtTime . . . . .	61
tg.getIntervalStartTime . . . . .	62
tg.getLabel . . . . .	62
tg.getNumberOfIntervals . . . . .	63
tg.getNumberOfPoints . . . . .	64
tg.getNumberOfTiers . . . . .	64
tg.getPointIndexHigherThanTime . . . . .	65
tg.getPointIndexLowerThanTime . . . . .	65
tg.getPointIndexNearestTime . . . . .	66
tg.getPointTime . . . . .	67
tg.getStartTime . . . . .	67
tg.getTierName . . . . .	68
tg.getTotalDuration . . . . .	69
tg.insertBoundary . . . . .	69
tg.insertInterval . . . . .	70
tg.insertNewIntervalTier . . . . .	72
tg.insertNewPointTier . . . . .	73
tg.insertPoint . . . . .	74
tg.isIntervalTier . . . . .	74
tg.isPointTier . . . . .	75
tg.plot . . . . .	76
tg.read . . . . .	77
tg.removeIntervalBothBoundaries . . . . .	77
tg.removeIntervalLeftBoundary . . . . .	78
tg.removeIntervalRightBoundary . . . . .	79
tg.removePoint . . . . .	80
tg.removeTier . . . . .	81
tg.repairContinuity . . . . .	81
tg.sample . . . . .	82
tg.sampleProblem . . . . .	83
tg.setLabel . . . . .	83
tg.setTierName . . . . .	84
tg.write . . . . .	84

---

as.formant	<i>as.formant</i>
------------	-------------------

---

**Description**

Renames the `class(formant)[ "name" ]` attribute and sets `class(formant)[ "type" ] <- "Formant 2"` (if it is not already set)

**Usage**

```
as.formant(formant, name = "")
```

**Arguments**

formant	Formant 2 object
name	New name

**Value**

Formant 2 object

**Examples**

```
class(formant.sample())
class(as.formant(formant.sample(), name = "New Name"))
```

---

as.it	<i>as.it</i>
-------	--------------

---

**Description**

Renames the `class(it)[ "name" ]` attribute and sets `class(it)[ "type" ] <- "IntensityTier"` (if it is not already set)

**Usage**

```
as.it(it, name = "")
```

**Arguments**

it	IntensityTier object
name	New name

**Value**

IntensityTier object

**Examples**

```
class(it.sample())
class(as.it(it.sample(), name = "New Name"))
```

---

as.pitch	<i>as.pitch</i>
----------	-----------------

---

**Description**

Renames the `class(pitch)["name"]` attribute and sets `class(pitch)["type"] <- "Pitch 1"` (if it is not already set)

**Usage**

```
as.pitch(pitch, name = "")
```

**Arguments**

pitch	Pitch 1 object
name	New name

**Value**

Pitch 1 object

**Examples**

```
class(pitch.sample())
class(as.pitch(pitch.sample(), name = "New Name"))
```

---

as.pt	<i>as.pt</i>
-------	--------------

---

**Description**

Renames the `class(pt)["name"]` attribute and sets `class(pt)["type"] <- "PitchTier"` (if it is not already set)

**Usage**

```
as.pt(pt, name = "")
```

**Arguments**

pt	PitchTier object
name	New name

**Value**

PitchTier object

**Examples**

```
class(pt.sample())
class(as.pt(pt.sample(), name = "New Name"))
```

---

as.snd	<i>as.snd</i>
--------	---------------

---

**Description**

Renames the `class(snd){"name"}` attribute and sets `class(snd){"type"} <- "Sound"` (if it is not already set)

**Usage**

```
as.snd(snd, name = "")
```

**Arguments**

snd	snd object
name	New name

**Details**

At least, `$sig` and `$fs` members must be present in `snd` list.

If not present, it calculates `$t`, `$nChannels`, `$nBits` (default: 16), `$nSamples`, and `$duration` members of `snd` list

**Value**

snd object

**Examples**

```
class(snd.sample())
class(as.snd(snd.sample(), name = "New Name"))
```

---

as.tg	<i>as.tg</i>
-------	--------------

---

**Description**

Renames the `class(tg){"name"}` attribute and sets `class(tg){"type"} <- "TextGrid"` (if it is not already set)

**Usage**

```
as.tg(tg, name = "")
```

**Arguments**

tg	TextGrid object
name	New name

**Value**

TextGrid object

**Examples**

```
class(tg.sample())
class(as.tg(tg.sample(), name = "New Name"))
```

---

col.read	<i>col.read</i>
----------	-----------------

---

**Description**

Loads Collection from Praat in Text or Short text format. Collection may contain combination of TextGrids, PitchTiers, Pitch objects, Formant objects, and IntensityTiers.

**Usage**

```
col.read(fileName, encoding = "UTF-8")
```

**Arguments**

fileName	Input file name
encoding	File encoding (default: "UTF-8"), "auto" for auto-detect of Unicode encoding

**Value**

Collection object

**See Also**

[tg.read](#), [pt.read](#), [pitch.read](#), [formant.read](#), [it.read](#)

**Examples**

```
## Not run:
coll <- col.read("coll_text.Collection")
length(coll) # number of objects in collection
class(coll[[1]]["type"]) # 1st object type
class(coll[[1]]["name"]) # 1st object name
it <- coll[[1]] # 1st object
it.plot(it)

class(coll[[2]]["type"]) # 2nd object type
class(coll[[2]]["name"]) # 2nd object name
tg <- coll[[2]] # 2nd object
tg.plot(tg)
length(tg) # number of tiers in TextGrid
tg$word$label

class(coll[[3]]["type"]) # 3rd object type
class(coll[[3]]["name"]) # 3rd object type
pitch <- coll[[3]] # 3rd object
```

```

names(pitch)
pitch$nx # number of frames
pitch$t[4] # time instance of the 4th frame
pitch$frame[[4]] # 4th frame: pitch candidates
pitch$frame[[4]]$frequency[2]
pitch$frame[[4]]$strength[2]

class(coll[[4]]["type"]) # 4th object type
class(coll[[4]]["name"]) # 4th object name
pt <- coll[[4]] # 2nd object
pt.plot(pt)

## End(Not run)

```

---

col.write

*col.write*


---

## Description

Saves Collection of objects to a file (in UTF-8 encoding). `col` is list of objects, each item `col[[i]]` must contain `class(col[[i]]["type"])` ("TextGrid", "PitchTier", "IntensityTier", "Pitch 1", or "Formant 2") and `class(col[[i]]["name"])` (name of the object) parameters set. These parameters can be created easily using "as.something()" functions: `as.tg()`, `as.pt()`, `as.it()`, `as.pitch()`, `as.formant()`

## Usage

```
col.write(col, fileNameCollection, format = "short")
```

## Arguments

<code>col</code>	Collection object = list of objects ( <code>col[[1]]</code> , <code>col[[2]]</code> , etc.) with <code>class(col[[i]]["type"])</code> and <code>class(col[[i]]["name"])</code> parameters set
<code>fileNameCollection</code>	file name to be created
<code>format</code>	Output file format ("short" (short text format) or "text" (a.k.a. full text format))

## Details

Sound objects in `col.read()` and `col.write()` are not supported at this moment because they would occupy too much disc space in text format.

## See Also

[col.read](#)



**Examples**

```
## Not run:
col <- list(as.tg(tg.sample(), "My textgrid"), as.pt(pt.sample(), "My PitchTier 1"),
           as.pt(pt.Hz2ST(pt.sample()), "My PitchTier 2"), as.it(it.sample(), "My IntensityTier"),
           as.pitch(pitch.sample(), "My Pitch"), as.formant(formant.sample(), "My Formant"))
col.write(col, "my_collection.Collection")

## End(Not run)
```

---

detectEncoding	<i>detectEncoding</i>
----------------	-----------------------

---

**Description**

Detects unicode encoding of Praat text files

**Usage**

```
detectEncoding(fileName)
```

**Arguments**

fileName	Input file name
----------	-----------------

**Value**

detected encoding of the text input file

**Examples**

```
## Not run:
detectEncoding("demo/H.TextGrid")
detectEncoding("demo/H_UTF16.TextGrid")

## End(Not run)
```

---

formant.cut	<i>formant.cut</i>
-------------	--------------------

---

**Description**

Cut the specified interval from the Formant object and preserve time

**Usage**

```
formant.cut(formant, tStart = -Inf, tEnd = Inf)
```

**Arguments**

formant	Formant object (either in Frame or Array format)
tStart	beginning time of interval to be cut (default $-\text{Inf}$ = cut from the xmin of the Formant)
tEnd	final time of interval to be cut (default $\text{Inf}$ = cut to the xmax of the Formant)

**Value**

Formant object

**See Also**

[formant.cut0](#), [tg.cut](#), [tg.cut0](#), [formant.read](#), [formant.plot](#)

**Examples**

```
formant <- formant.sample()
formant2 <- formant.cut(formant, tStart = 3)
formant2_0 <- formant.cut0(formant, tStart = 3)
formant3 <- formant.cut(formant, tStart = 2, tEnd = 3)
formant3_0 <- formant.cut0(formant, tStart = 2, tEnd = 3)
formant4 <- formant.cut(formant, tEnd = 1)
formant4_0 <- formant.cut0(formant, tEnd = 1)
formant5 <- formant.cut(formant, tStart = -1, tEnd = 1)
formant5_0 <- formant.cut0(formant, tStart = -1, tEnd = 1)
## Not run:
formant.plot(formant)
formant.plot(formant2)
formant.plot(formant2_0)
formant.plot(formant3)
formant.plot(formant3_0)
formant.plot(formant4)
formant.plot(formant4_0)
formant.plot(formant5)
formant.plot(formant5_0)

## End(Not run)
```

---

`formant.cut0`

*formant.cut0*

---

**Description**

Cut the specified interval from the Formant object and shift time so that the new `xmin = 0`

**Usage**

```
formant.cut0(formant, tStart = -Inf, tEnd = Inf)
```

**Arguments**

formant	Formant object (either in Frame or Array format)
tStart	beginning time of interval to be cut (default -Inf = cut from the xmin of the Formant)
tEnd	final time of interval to be cut (default Inf = cut to the xmax of the Formant)

**Value**

Formant object

**See Also**

[formant.cut](#), [tg.cut](#), [tg.cut0](#), [formant.read](#), [formant.plot](#)

**Examples**

```
formant <- formant.sample()
formant2 <- formant.cut(formant, tStart = 3)
formant2_0 <- formant.cut0(formant, tStart = 3)
formant3 <- formant.cut(formant, tStart = 2, tEnd = 3)
formant3_0 <- formant.cut0(formant, tStart = 2, tEnd = 3)
formant4 <- formant.cut(formant, tEnd = 1)
formant4_0 <- formant.cut0(formant, tEnd = 1)
formant5 <- formant.cut(formant, tStart = -1, tEnd = 1)
formant5_0 <- formant.cut0(formant, tStart = -1, tEnd = 1)
## Not run:
formant.plot(formant)
formant.plot(formant2)
formant.plot(formant2_0)
formant.plot(formant3)
formant.plot(formant3_0)
formant.plot(formant4)
formant.plot(formant4_0)
formant.plot(formant5)
formant.plot(formant5_0)

## End(Not run)
```

---

formant.plot

*formant.plot*


---

**Description**

Plots interactive Formant object using dygraphs package.

**Usage**

```
formant.plot(formant, scaleIntensity = TRUE, drawBandwidth = TRUE,
  group = "")
```

**Arguments**

formant	Formant object
scaleIntensity	Point size scaled according to relative intensity
drawBandwidth	Draw formant bandwidth
group	[optional] character string, name of group for dygraphs synchronization

**See Also**

[formant.read](#), [formant.sample](#), [formant.toArray](#), [tg.plot](#)

**Examples**

```
## Not run:
formant <- formant.sample()
formant.plot(formant, drawBandwidth = TRUE)

## End(Not run)
```

---

formant.read	<i>formant.read</i>
--------------	---------------------

---

**Description**

Reads Formant object from Praat. Supported formats: text file, short text file.

**Usage**

```
formant.read(fileNameFormant, encoding = "UTF-8")
```

**Arguments**

fileNameFormant	file name of Formant object
encoding	File encoding (default: "UTF-8"), "auto" for auto-detect of Unicode encoding

**Value**

A Formant object represents formants as a function of time.

[ref: Praat help, <http://www.fon.hum.uva.nl/praat/manual/Formant.html>]

f\$xmin ... start time (seconds)

f\$xmax ... end time (seconds)

f\$nx ... number of frames

f\$dx ... time step = frame duration (seconds)

f\$x1 ... time associated with the first frame (seconds)

f\$t ... vector of time instances associated with all frames

f\$maxnFormants ... maximum number of formants in frame

f\$frame[[1]] to f\$frame[[f\$nx]] ... frames

f\$frame[[1]]\$intensity ... intensity of the frame  
 f\$frame[[1]]\$nFormants ... actual number of formants in this frame  
 f\$frame[[1]]\$frequency ... vector of formant frequencies (in Hz)  
 f\$frame[[1]]\$bandwidth ... vector of formant bandwidths (in Hz)

### See Also

[pitch.read](#), [pt.read](#), [tg.read](#), [it.read](#), [col.read](#)

### Examples

```
## Not run:
f <- formant.read('demo/maminka.Formant')
names(f)
f$nx
f$t[4]          # time instance of the 4th frame
f$frame[[4]]    # 4th frame: formants
f$frame[[4]]$frequency[2]
f$frame[[4]]$bandwidth[2]

## End(Not run)
```

---

formant.sample

*formant.sample*

---

### Description

Returns sample Formant object.

### Usage

```
formant.sample()
```

### Value

Formant

### See Also

[tg.sample](#), [pt.sample](#), [it.sample](#), [pitch.sample](#)

### Examples

```
formant <- formant.sample()
```

---

formant.toArray	<i>formant.toArray</i>
-----------------	------------------------

---

**Description**

formant.toArray

**Usage**

```
formant.toArray(formant)
```

**Arguments**

formant	Formant object
---------	----------------

**Value**

Formant object with frames converted to frequency and bandwidth arrays and intensity vector

**See Also**

[formant.read](#), [formant.plot](#)

**Examples**

```
formantArray <- formant.toArray(formant.sample())
formantArray$t[1:10]
formantArray$frequencyArray[, 1:10]
formantArray$bandwidthArray[, 1:10]
formantArray$intensityVector[1:10]
## Not run:
plot(formantArray$t, formantArray$frequencyArray[1, ]) # draw 1st formant track

## End(Not run)
```

---

formant.toFrame	<i>formant.toFrame</i>
-----------------	------------------------

---

**Description**

formant.toFrame

**Usage**

```
formant.toFrame(formantArray)
```

**Arguments**

formantArray	Formant object (array format)
--------------	-------------------------------

**Value**

Formant object with frames

**See Also**

[formant.toArray](#), [formant.read](#), [formant.plot](#)

**Examples**

```
formantArray <- formant.toArray(formant.sample())
formant <- formant.toFrame(formantArray)
```

---

formant.write	<i>formant.write</i>
---------------	----------------------

---

**Description**

Saves Formant to the file.

**Usage**

```
formant.write(formant, fileNameFormant, format = "short")
```

**Arguments**

formant	Formant object
fileNameFormant	Output file name
format	Output file format ("short" (default, short text format) or "text" (a.k.a. full text format))

**See Also**

[formant.read](#), [tg.read](#)

**Examples**

```
## Not run:
formant <- formant.sample()
formant.write(formant, "demo_output.Formant")

## End(Not run)
```

---

`ifft`*ifft*

---

**Description**

Inverse Fast Fourier Transform (discrete FT), Matlab-like behavior.

**Usage**

```
ifft(sig)
```

**Arguments**

sig                      input vector

**Details**

This really is the inverse of the fft function, so `ifft(fft(x)) == x`.

**Value**

output vector of the same length as the input vector

**See Also**

[fft](#), [Re](#), [Im](#), [Mod](#), [Conj](#)

**Examples**

```
ifft(fft(1:5))
```

---

`isInt`*isInt*

---

**Description**

Returns TRUE / FALSE whether it is exactly 1 integer number (in fact, the class can be numeric but the number must be integer), non-missing

**Usage**

```
isInt(num)
```

**Arguments**

num                      variable to be tested

**Value**

TRUE / FALSE



**See Also**

[isNum](#), [isLogical](#), [isString](#)

**Examples**

```
isInt(2)
isInt(2L)
isInt(-2)
isInt(-2L)
isInt(2.1)
isInt(-2.1)
isInt(1:5)
isInt(NA_integer_)
isInt(integer(0))
```

---

isLogical	<i>isLogical</i>
-----------	------------------

---

**Description**

Returns TRUE / FALSE whether it is exactly 1 logical value, non-missing

**Usage**

```
isLogical(logical)
```

**Arguments**

logical	variable to be tested
---------	-----------------------

**Value**

TRUE / FALSE

**See Also**

[isNum](#), [isInt](#), [isString](#)

**Examples**

```
isLogical(TRUE)
isLogical(FALSE)
isLogical(1)
isLogical(0)
isLogical(2)
isLogical(NA)
isLogical(NaN)
isLogical(logical(0))
```

---

`isNum`*isNum*

---

**Description**

Returns TRUE / FALSE whether it is exactly 1 number (numeric or integer vector of length 1, non-missing)

**Usage**

```
isNum(num)
```

**Arguments**

num                      variable to be tested

**Value**

TRUE / FALSE

**See Also**

[isInt](#), [isLogical](#), [isString](#)

**Examples**

```
isNum(2)
isNum(2L)
isNum(-2)
isNum(-2L)
isNum(2.1)
isNum(-2.1)
isNum(1:5)
isNum(NA_real_)
isNum(numeric(0))
```

---

`isString`*isString*

---

**Description**

Returns TRUE / FALSE whether it is exactly 1 character string (character vector of length 1, non-missing)

**Usage**

```
isString(string)
```

**Arguments**

string                   variable to be tested

**Value**

TRUE / FALSE

**See Also**[isInt](#), [isNum](#), [isLogical](#)**Examples**

```
isString("hello")
isString(2)
isString(c("hello", "world"))
isString(NA_character_)
```

---

<code>it.cut</code>	<i>it.cut</i>
---------------------	---------------

---

**Description**

Cut the specified interval from the IntensityTier and preserve time

**Usage**

```
it.cut(it, tStart = -Inf, tEnd = Inf)
```

**Arguments**

<code>it</code>	IntensityTier object
<code>tStart</code>	beginning time of interval to be cut (default <code>-Inf</code> = cut from the <code>tmin</code> of the IntensityTier)
<code>tEnd</code>	final time of interval to be cut (default <code>Inf</code> = cut to the <code>tmax</code> of the IntensityTier)

**Value**

IntensityTier object

**See Also**

[it.cut0](#), [it.read](#), [it.plot](#), [it.interpolate](#), [it.legendre](#), [it.legendreSynth](#), [it.legendreDemo](#)

**Examples**

```
it <- it.sample()
it2 <- it.cut(it, tStart = 0.3)
it2_0 <- it.cut0(it, tStart = 0.3)
it3 <- it.cut(it, tStart = 0.2, tEnd = 0.3)
it3_0 <- it.cut0(it, tStart = 0.2, tEnd = 0.3)
it4 <- it.cut(it, tEnd = 0.3)
it4_0 <- it.cut0(it, tEnd = 0.3)
it5 <- it.cut(it, tStart = -1, tEnd = 1)
it5_0 <- it.cut0(it, tStart = -1, tEnd = 1)
## Not run:
```

```

it.plot(it)
it.plot(it2)
it.plot(it2_0)
it.plot(it3)
it.plot(it3_0)
it.plot(it4)
it.plot(it4_0)
it.plot(it5)
it.plot(it5_0)

## End(Not run)

```

---

it.cut0

*it.cut0*


---

## Description

Cut the specified interval from the IntensityTier and shift time so that the new tmin = 0

## Usage

```
it.cut0(it, tStart = -Inf, tEnd = Inf)
```

## Arguments

it	IntensityTier object
tStart	beginning time of interval to be cut (default -Inf = cut from the tmin of the IntensityTier)
tEnd	final time of interval to be cut (default Inf = cut to the tmax of the IntensityTier)

## Value

IntensityTier object

## See Also

[it.cut](#), [it.read](#), [it.plot](#), [it.interpolate](#), [it.legendre](#), [it.legendreSynth](#), [it.legendreDemo](#)

## Examples

```

it <- it.sample()
it2 <- it.cut(it, tStart = 0.3)
it2_0 <- it.cut0(it, tStart = 0.3)
it3 <- it.cut(it, tStart = 0.2, tEnd = 0.3)
it3_0 <- it.cut0(it, tStart = 0.2, tEnd = 0.3)
it4 <- it.cut(it, tEnd = 0.3)
it4_0 <- it.cut0(it, tEnd = 0.3)
it5 <- it.cut(it, tStart = -1, tEnd = 1)
it5_0 <- it.cut0(it, tStart = -1, tEnd = 1)
## Not run:
it.plot(it)
it.plot(it2)
it.plot(it2_0)

```

```

it.plot(it3)
it.plot(it3_0)
it.plot(it4)
it.plot(it4_0)
it.plot(it5)
it.plot(it5_0)

## End(Not run)

```

---

it.interpolate

*it.interpolate*


---

## Description

Interpolates IntensityTier contour in given time instances.

## Usage

```
it.interpolate(it, t)
```

## Arguments

<code>it</code>	IntensityTier object
<code>t</code>	vector of time instances of interest

## Details

a) If  $t < \min(it\$t)$  (or  $t > \max(it\$t)$ ), returns the first (or the last) value of  $it\$i$ . b) If  $t$  is existing point in  $it\$t$ , returns the respective  $it\$f$ . c) If  $t$  is between two existing points, returns linear interpolation of these two points.

## Value

IntensityTier object

## See Also

[it.read](#), [it.write](#), [it.plot](#), [it.cut](#), [it.cut0](#), [it.legendre](#)

## Examples

```

it <- it.sample()
it2 <- it.interpolate(it, seq(it$t[1], it$t[length(it$t)], by = 0.001))
## Not run:
it.plot(it)
it.plot(it2)

## End(Not run)

```

---

it.legendre	<i>it.legendre</i>
-------------	--------------------

---

## Description

Interpolate the IntensityTier in npoints equidistant points and approximate it by Legendre polynomials

## Usage

```
it.legendre(it, npoints = 1000, npolynomials = 4)
```

## Arguments

it	IntensityTier object
npoints	Number of points of IntensityTier interpolation
npolynomials	Number of polynomials to be used for Legendre modelling

## Value

Vector of Legendre polynomials coefficients

## See Also

[it.legendreSynth](#), [it.legendreDemo](#), [it.cut](#), [it.cut0](#), [it.read](#), [it.plot](#), [it.interpolate](#)

## Examples

```
it <- it.sample()
it <- it.cut(it, tStart = 0.2, tEnd = 0.4) # cut IntensityTier and preserve time
c <- it.legendre(it)
print(c)
leg <- it.legendreSynth(c)
itLeg <- it
itLeg$t <- seq(itLeg$tmin, itLeg$tmax, length.out = length(leg))
itLeg$i <- leg
## Not run:
plot(it$t, it$i, xlab = "Time (sec)", ylab = "Intensity (dB)")
lines(itLeg$t, itLeg$i, col = "blue")

## End(Not run)
```

---

it.legendreDemo	<i>it.legendreDemo</i>
-----------------	------------------------

---

**Description**

Plots first four Legendre polynomials

**Usage**

```
it.legendreDemo()
```

**See Also**

[it.legendre](#), [it.legendreSynth](#), [it.read](#), [it.plot](#), [it.interpolate](#)

**Examples**

```
## Not run:  
it.legendreDemo()  
  
## End(Not run)
```

---

it.legendreSynth	<i>it.legendreSynth</i>
------------------	-------------------------

---

**Description**

Synthesize the contour from vector of Legendre polynomials c in npoints equidistant points

**Usage**

```
it.legendreSynth(c, npoints = 1000)
```

**Arguments**

c	Vector of Legendre polynomials coefficients
npoints	Number of points of IntensityTier interpolation

**Value**

Vector of values of synthesized contour

**See Also**

[it.legendre](#), [it.legendreDemo](#), [it.read](#), [it.plot](#), [it.interpolate](#)

**Examples**

```

it <- it.sample()
it <- it.cut(it, tStart = 0.2, tEnd = 0.4) # cut IntensityTier and preserve time
c <- it.legendre(it)
print(c)
leg <- it.legendreSynth(c)
itLeg <- it
itLeg$t <- seq(itLeg$tmin, itLeg$tmax, length.out = length(leg))
itLeg$i <- leg
## Not run:
plot(it$t, it$i, xlab = "Time (sec)", ylab = "Intensity (dB)")
lines(itLeg$t, itLeg$i, col = "blue")

## End(Not run)

```

---

*it.plot**it.plot*

---

**Description**

Plots interactive IntensityTier using dygraphs package.

**Usage**

```
it.plot(it, group = "", snd = NULL)
```

**Arguments**

<code>it</code>	IntensityTier object
<code>group</code>	[optional] character string, name of group for dygraphs synchronization
<code>snd</code>	[optional] Sound object

**See Also**

[it.read](#), [tg.plot](#), [it.cut](#), [it.cut0](#), [it.interpolate](#), [it.write](#)

**Examples**

```

## Not run:
it <- it.sample()
it.plot(it)

## End(Not run)

```



---

it.read

*it.read*


---

**Description**

Reads IntensityTier from Praat. Supported formats: text file, short text file.

**Usage**

```
it.read(fileNameIntensityTier, encoding = "UTF-8")
```

**Arguments**

fileNameIntensityTier

file name of IntensityTier

encoding

File encoding (default: "UTF-8"), "auto" for auto-detect of Unicode encoding

**Value**

IntensityTier object

**See Also**

[it.write](#), [it.plot](#), [it.cut](#), [it.cut0](#), [it.interpolate](#), [tg.read](#), [pt.read](#), [pitch.read](#), [formant.read](#), [col.read](#)

**Examples**

```
## Not run:
it <- it.read("demo/maminka.IntensityTier")
it.plot(it)

## End(Not run)
```

---

it.sample

*it.sample*


---

**Description**

Returns sample IntensityTier.

**Usage**

```
it.sample()
```

**Value**

IntensityTier

**See Also**[it.plot](#)**Examples**

```
it <- it.sample()
it.plot(it)
```

---

*it.write**it.write*

---

**Description**

Saves IntensityTier to file (in UTF-8 encoding). it is list with at least \$t and \$i vectors (of the same length). If there are no \$tmin and \$tmax values, there are set as min and max of \$t vector.

**Usage**

```
it.write(it, fileNameIntensityTier, format = "short")
```

**Arguments**

it	IntensityTier object
fileNameIntensityTier	file name to be created
format	Output file format ("short" (short text format - default), "text" (a.k.a. full text format))

**See Also**[it.read](#), [tg.write](#), [it.interpolate](#)**Examples**

```
## Not run:
it <- it.sample()
it.plot(it)
it.write(it, "demo/intensity.IntensityTier")

## End(Not run)
```

pitch.cut

*pitch.cut***Description**

Cut the specified interval from the Pitch object and preserve time

**Usage**

```
pitch.cut(pitch, tStart = -Inf, tEnd = Inf)
```

**Arguments**

pitch	Pitch object (either in Frame or Array format)
tStart	beginning time of interval to be cut (default -Inf = cut from the xmin of the Pitch)
tEnd	final time of interval to be cut (default Inf = cut to the xmax of the Pitch)

**Value**

Pitch object

**See Also**

[pitch.cut0](#), [tg.cut](#), [tg.cut0](#), [pitch.read](#), [pitch.plot](#)

**Examples**

```
pitch <- pitch.sample()
pitch2 <- pitch.cut(pitch, tStart = 3)
pitch2_0 <- pitch.cut0(pitch, tStart = 3)
pitch3 <- pitch.cut(pitch, tStart = 2, tEnd = 3)
pitch3_0 <- pitch.cut0(pitch, tStart = 2, tEnd = 3)
pitch4 <- pitch.cut(pitch, tEnd = 1)
pitch4_0 <- pitch.cut0(pitch, tEnd = 1)
pitch5 <- pitch.cut(pitch, tStart = -1, tEnd = 1)
pitch5_0 <- pitch.cut0(pitch, tStart = -1, tEnd = 1)
## Not run:
pitch.plot(pitch)
pitch.plot(pitch2)
pitch.plot(pitch2_0)
pitch.plot(pitch3)
pitch.plot(pitch3_0)
pitch.plot(pitch4)
pitch.plot(pitch4_0)
pitch.plot(pitch5)
pitch.plot(pitch5_0)

## End(Not run)
```

pitch.cut0

*pitch.cut0***Description**

Cut the specified interval from the Pitch object and shift time so that the new xmin = 0

**Usage**

```
pitch.cut0(pitch, tStart = -Inf, tEnd = Inf)
```

**Arguments**

pitch	Pitch object (either in Frame or Array format)
tStart	beginning time of interval to be cut (default -Inf = cut from the xmin of the Pitch)
tEnd	final time of interval to be cut (default Inf = cut to the xmax of the Pitch)

**Value**

Pitch object

**See Also**

[pitch.cut](#), [tg.cut](#), [tg.cut0](#), [pitch.read](#), [pitch.plot](#)

**Examples**

```
pitch <- pitch.sample()
pitch2 <- pitch.cut(pitch, tStart = 3)
pitch2_0 <- pitch.cut0(pitch, tStart = 3)
pitch3 <- pitch.cut(pitch, tStart = 2, tEnd = 3)
pitch3_0 <- pitch.cut0(pitch, tStart = 2, tEnd = 3)
pitch4 <- pitch.cut(pitch, tEnd = 1)
pitch4_0 <- pitch.cut0(pitch, tEnd = 1)
pitch5 <- pitch.cut(pitch, tStart = -1, tEnd = 1)
pitch5_0 <- pitch.cut0(pitch, tStart = -1, tEnd = 1)
## Not run:
pitch.plot(pitch)
pitch.plot(pitch2)
pitch.plot(pitch2_0)
pitch.plot(pitch3)
pitch.plot(pitch3_0)
pitch.plot(pitch4)
pitch.plot(pitch4_0)
pitch.plot(pitch5)
pitch.plot(pitch5_0)

## End(Not run)
```

---

pitch.plot	<i>pitch.plot</i>
------------	-------------------

---

**Description**

Plots interactive Pitch object using dygraphs package.

**Usage**

```
pitch.plot(pitch, scaleIntensity = TRUE, showStrength = FALSE,
           group = "", pt = NULL)
```

**Arguments**

pitch	Pitch object
scaleIntensity	Point size scaled according to relative intensity
showStrength	Show strength annotation
group	[optional] character string, name of group for dygraphs synchronization
pt	[optional] PitchTier object

**See Also**

[pitch.read](#), [pitch.sample](#), [pitch.toArray](#), [tg.plot](#), [pt.plot](#), [formant.plot](#)

**Examples**

```
## Not run:
pitch <- pitch.sample()
pitch.plot(pitch, scaleIntensity = TRUE, showStrength = TRUE)

pitch.plot(pitch, scaleIntensity = TRUE, showStrength = TRUE, pt = pt.sample())

## End(Not run)
```

---

pitch.read	<i>pitch.read</i>
------------	-------------------

---

**Description**

Reads Pitch object from Praat. Supported formats: text file, short text file.

**Usage**

```
pitch.read(fileNamePitch, encoding = "UTF-8")
```

**Arguments**

fileNamePitch	file name of Pitch object
encoding	File encoding (default: "UTF-8"), "auto" for auto-detect of Unicode encoding

**Value**

A Pitch object represents periodicity candidates as a function of time.

[ref: Praat help, <http://www.fon.hum.uva.nl/praat/manual/Pitch.html>]

p\$xmin ... start time (seconds)

p\$xmax ... end time (seconds)

p\$nx ... number of frames

p\$dx ... time step = frame duration (seconds)

p\$x1 ... time associated with the first frame (seconds)

p\$t ... vector of time instances associated with all frames

p\$ceiling ... a frequency above which a candidate is considered voiceless (Hz)

p\$maxnCandidates ... maximum number of candidates in frame

p\$frame[[1]] to p\$frame[[p\$nx]] ... frames

p\$frame[[1]]\$intensity ... intensity of the frame

p\$frame[[1]]\$nCandidates ... actual number of candidates in this frame

p\$frame[[1]]\$frequency ... vector of candidates' frequency (in Hz)

(for a voiced candidate), or 0 (for an unvoiced candidate)

p\$frame[[1]]\$strength ... vector of degrees of periodicity of candidates (between 0 and 1)

**See Also**

[pt.read](#), [tg.read](#), [it.read](#), [col.read](#)

**Examples**

```
## Not run:
p <- pitch.read('demo/sound.Pitch')
names(p)
p$nx
p$t[4]          # time instance of the 4th frame
p$frame[[4]]   # 4th frame: pitch candidates
p$frame[[4]]$frequency[2]
p$frame[[4]]$strength[2]

## End(Not run)
```

---

pitch.sample

*pitch.sample*

---

**Description**

Returns sample Pitch object.

**Usage**

```
pitch.sample()
```

**Value**

Pitch

**See Also**

[tg.sample](#), [pt.sample](#), [it.sample](#), [formant.sample](#)

**Examples**

```
pitch <- pitch.sample()
```

---

pitch.toArray	<i>pitch.toArray</i>
---------------	----------------------

---

**Description**

pitch.toArray

**Usage**

```
pitch.toArray(pitch)
```

**Arguments**

pitch                      Pitch object (frame format)

**Value**

Pitch object with frames converted to frequency and strength arrays and intensity vector

**See Also**

[pitch.toFrame](#), [pitch.read](#), [pitch.plot](#)

**Examples**

```
pitchArray <- pitch.toArray(pitch.sample())
pitchArray$t[1:10]
pitchArray$frequencyArray[, 1:10]
pitchArray$bandwidthArray[, 1:10]
pitchArray$intensityVector[1:10]
```

---

pitch.toFrame	<i>pitch.toFrame</i>
---------------	----------------------

---

**Description**

pitch.toFrame

**Usage**

```
pitch.toFrame(pitchArray)
```

**Arguments**

pitchArray	Pitch object (array format)
------------	-----------------------------

**Value**

Pitch object with frames

**See Also**

[pitch.toArray](#), [pitch.read](#), [pitch.plot](#)

**Examples**

```
pitchArray <- pitch.toArray(pitch.sample())  
pitch <- pitch.toFrame(pitchArray)
```

---

pitch.write	<i>pitch.write</i>
-------------	--------------------

---

**Description**

Saves Pitch to the file.

**Usage**

```
pitch.write(pitch, fileNamePitch, format = "short")
```

**Arguments**

pitch	Pitch object
fileNamePitch	Output file name
format	Output file format ("short" (default, short text format) or "text" (a.k.a. full text format))

**See Also**

[pitch.read](#), [pt.read](#)



**Examples**

```
## Not run:
pitch <- pitch.sample()
pitch.write(pitch, "demo_output.Pitch")

## End(Not run)
```

---

pt.cut	<i>pt.cut</i>
--------	---------------

---

**Description**

Cut the specified interval from the PitchTier and preserve time

**Usage**

```
pt.cut(pt, tStart = -Inf, tEnd = Inf)
```

**Arguments**

pt	PitchTier object
tStart	beginning time of interval to be cut (default -Inf = cut from the tmin of the PitchTier)
tEnd	final time of interval to be cut (default Inf = cut to the tmax of the PitchTier)

**Value**

PitchTier object

**See Also**

[pt.cut0](#), [tg.cut](#), [tg.cut0](#), [pt.read](#), [pt.plot](#), [pt.Hz2ST](#), [pt.interpolate](#), [pt.legendre](#), [pt.legendreSynth](#), [pt.legendreDemo](#)

**Examples**

```
pt <- pt.sample()
pt2 <- pt.cut(pt, tStart = 3)
pt2_0 <- pt.cut0(pt, tStart = 3)
pt3 <- pt.cut(pt, tStart = 2, tEnd = 3)
pt3_0 <- pt.cut0(pt, tStart = 2, tEnd = 3)
pt4 <- pt.cut(pt, tEnd = 1)
pt4_0 <- pt.cut0(pt, tEnd = 1)
pt5 <- pt.cut(pt, tStart = -1, tEnd = 1)
pt5_0 <- pt.cut0(pt, tStart = -1, tEnd = 1)
## Not run:
pt.plot(pt)
pt.plot(pt2)
pt.plot(pt2_0)
pt.plot(pt3)
pt.plot(pt3_0)
pt.plot(pt4)
pt.plot(pt4_0)
```

```
pt.plot(pt5)
pt.plot(pt5_0)

## End(Not run)
```

---

pt.cut0

*pt.cut0*


---

## Description

Cut the specified interval from the PitchTier and shift time so that the new tmin = 0

## Usage

```
pt.cut0(pt, tStart = -Inf, tEnd = Inf)
```

## Arguments

pt	PitchTier object
tStart	beginning time of interval to be cut (default -Inf = cut from the tmin of the PitchTier)
tEnd	final time of interval to be cut (default Inf = cut to the tmax of the PitchTier)

## Value

PitchTier object

## See Also

[pt.cut](#), [pt.read](#), [pt.plot](#), [pt.Hz2ST](#), [pt.interpolate](#), [pt.legendre](#), [pt.legendreSynth](#), [pt.legendreDemo](#)

## Examples

```
pt <- pt.sample()
pt2 <- pt.cut(pt, tStart = 3)
pt2_0 <- pt.cut0(pt, tStart = 3)
pt3 <- pt.cut(pt, tStart = 2, tEnd = 3)
pt3_0 <- pt.cut0(pt, tStart = 2, tEnd = 3)
pt4 <- pt.cut(pt, tEnd = 1)
pt4_0 <- pt.cut0(pt, tEnd = 1)
pt5 <- pt.cut(pt, tStart = -1, tEnd = 1)
pt5_0 <- pt.cut0(pt, tStart = -1, tEnd = 1)
## Not run:
pt.plot(pt)
pt.plot(pt2)
pt.plot(pt2_0)
pt.plot(pt3)
pt.plot(pt3_0)
pt.plot(pt4)
pt.plot(pt4_0)
pt.plot(pt5)
pt.plot(pt5_0)

## End(Not run)
```

---

pt.Hz2ST

*pt.Hz2ST*


---

**Description**

Converts Hz to Semitones with given reference (default 0 ST = 100 Hz).

**Usage**

```
pt.Hz2ST(pt, ref = 100)
```

**Arguments**

pt	PitchTier object
ref	reference value (in Hz) for 0 ST. Default: 100 Hz.

**Value**

PitchTier object

**See Also**

[pt.read](#), [pt.write](#), [pt.plot](#), [pt.interpolate](#), [pt.cut](#), [pt.cut0](#)

**Examples**

```
pt <- pt.sample()
pt2 <- pt.Hz2ST(pt, ref = 200)
## Not run:
pt.plot(pt) %>% dygraphs::dyAxis("y", label = "Frequency (Hz)")
pt.plot(pt2) %>% dygraphs::dyAxis("y", label = "Frequency (ST re 200 Hz)")

## End(Not run)
```

---

pt.interpolate

*pt.interpolate*


---

**Description**

Interpolates PitchTier contour in given time instances.

**Usage**

```
pt.interpolate(pt, t)
```

**Arguments**

pt	PitchTier object
t	vector of time instances of interest

**Details**

a) If  $t < \min(pt\$t)$  (or  $t > \max(pt\$t)$ ), returns the first (or the last) value of  $pt\$f$ . b) If  $t$  is existing point in  $pt\$t$ , returns the respective  $pt\$f$ . c) If  $t$  is between two existing points, returns linear interpolation of these two points.

**Value**

PitchTier object

**See Also**

[pt.read](#), [pt.write](#), [pt.plot](#), [pt.Hz2ST](#), [pt.cut](#), [pt.cut0](#), [pt.legendre](#)

**Examples**

```
pt <- pt.sample()
pt <- pt.Hz2ST(pt, ref = 100) # conversion of Hz to Semitones, reference 0 ST = 100 Hz.
pt2 <- pt.interpolate(pt, seq(pt$t[1], pt$t[length(pt$t)], by = 0.001))
## Not run:
pt.plot(pt)
pt.plot(pt2)

## End(Not run)
```

---

pt.legendre

pt.legendre

---

**Description**

Interpolate the PitchTier in npoints equidistant points and approximate it by Legendre polynomials

**Usage**

```
pt.legendre(pt, npoints = 1000, npolynomials = 4)
```

**Arguments**

pt	PitchTier object
npoints	Number of points of PitchTier interpolation
npolynomials	Number of polynomials to be used for Legendre modelling

**Value**

Vector of Legendre polynomials coefficients

**See Also**

[pt.legendreSynth](#), [pt.legendreDemo](#), [pt.cut](#), [pt.cut0](#), [pt.read](#), [pt.plot](#), [pt.Hz2ST](#), [pt.interpolate](#)

**Examples**

```
pt <- pt.sample()
pt <- pt.Hz2ST(pt)
pt <- pt.cut(pt, tStart = 3) # cut PitchTier from t = 3 sec and preserve time
c <- pt.legendre(pt)
print(c)
leg <- pt.legendreSynth(c)
ptLeg <- pt
ptLeg$t <- seq(ptLeg$tmin, ptLeg$tmax, length.out = length(leg))
ptLeg$f <- leg
## Not run:
plot(pt$t, pt$f, xlab = "Time (sec)", ylab = "F0 (ST re 100 Hz)")
lines(ptLeg$t, ptLeg$f, col = "blue")

## End(Not run)
```

---

pt.legendreDemo

*pt.legendreDemo*

---

**Description**

Plots first four Legendre polynomials

**Usage**

```
pt.legendreDemo()
```

**See Also**

[pt.legendre](#), [pt.legendreSynth](#), [pt.read](#), [pt.plot](#), [pt.Hz2ST](#), [pt.interpolate](#)

**Examples**

```
## Not run:
pt.legendreDemo()

## End(Not run)
```

---

pt.legendreSynth

*pt.legendreSynth*

---

**Description**

Synthesize the contour from vector of Legendre polynomials c in npoints equidistant points

**Usage**

```
pt.legendreSynth(c, npoints = 1000)
```

**Arguments**

<code>c</code>	Vector of Legendre polynomials coefficients
<code>npoints</code>	Number of points of PitchTier interpolation

**Value**

Vector of values of synthetized contour

**See Also**

[pt.legendre](#), [pt.legendreDemo](#), [pt.read](#), [pt.plot](#), [pt.Hz2ST](#), [pt.interpolate](#)

**Examples**

```
pt <- pt.sample()
pt <- pt.Hz2ST(pt)
pt <- pt.cut(pt, tStart = 3) # cut PitchTier from t = 3 sec and preserve time
c <- pt.legendre(pt)
print(c)
leg <- pt.legendreSynth(c)
ptLeg <- pt
ptLeg$t <- seq(ptLeg$tmin, ptLeg$tmax, length.out = length(leg))
ptLeg$f <- leg
## Not run:
plot(pt$t, pt$f, xlab = "Time (sec)", ylab = "F0 (ST re 100 Hz)")
lines(ptLeg$t, ptLeg$f, col = "blue")

## End(Not run)
```

---

`pt.plot`

*pt.plot*

---

**Description**

Plots interactive PitchTier using dygraphs package.

**Usage**

```
pt.plot(pt, group = "")
```

**Arguments**

<code>pt</code>	PitchTier object
<code>group</code>	[optional] character string, name of group for dygraphs synchronization

**See Also**

[pt.read](#), [pt.Hz2ST](#), [pt.cut](#), [pt.cut0](#), [pt.interpolate](#), [pt.write](#), [tg.plot](#), [pitch.plot](#), [formant.plot](#)

**Examples**

```
## Not run:
pt <- pt.sample()
pt.plot(pt)

## End(Not run)
```

---

pt.read

*pt.read*


---

**Description**

Reads PitchTier from Praat. Supported formats: text file, short text file, spreadsheet, headerless spreadsheet (headerless not recommended, it does not contain tmin and tmax info).

**Usage**

```
pt.read(fileNamePitchTier, encoding = "UTF-8")
```

**Arguments**

fileNamePitchTier	file name of PitchTier
encoding	File encoding (default: "UTF-8"), "auto" for auto-detect of Unicode encoding

**Value**

PitchTier object

**See Also**

[pt.write](#), [pt.plot](#), [pt.Hz2ST](#), [pt.cut](#), [pt.cut0](#), [pt.interpolate](#), [pt.legendre](#), [tg.read](#), [pitch.read](#), [formant.read](#), [it.read](#), [col.read](#)

**Examples**

```
## Not run:
pt <- pt.read("demo/H.PitchTier")
pt.plot(pt)

## End(Not run)
```

---

pt.sample

*pt.sample*


---

### Description

Returns sample PitchTier.

### Usage

```
pt.sample()
```

### Value

PitchTier

### See Also

[pt.plot](#)

### Examples

```
pt <- pt.sample()
pt.plot(pt)
```

---

pt.write

*pt.write*


---

### Description

Saves PitchTier to a file (in UTF-8 encoding). pt is a list with \$t and \$f vectors (of the same length) at least. If there are no \$tmin and \$tmax values, there are set as min and max of \$t vector.

### Usage

```
pt.write(pt, fileNamePitchTier, format = "spreadsheet")
```

### Arguments

pt	PitchTier object
fileNamePitchTier	file name to be created
format	Output file format ("short" (short text format), "text" (a.k.a. full text format), "spreadsheet" (default), "headerless" (not recommended, it does not contain tmin and tmax info))

### See Also

[pt.read](#), [tg.write](#), [pt.Hz2ST](#), [pt.interpolate](#)



**Examples**

```
## Not run:
pt <- pt.sample()
pt <- pt.Hz2ST(pt)    # conversion of Hz to Semitones, reference 0 ST = 100 Hz.
pt.plot(pt)
pt.write(pt, "demo/H_st.PitchTier")

## End(Not run)
```

round2

*round2***Description**

Rounds a number to the specified order. Round half away from zero (this is the difference from built-in round function.)

**Usage**

```
round2(x, order = 0)
```

**Arguments**

x	number to be rounded
order	0 (default) = units, -1 = 0.1, +1 = 10

**Value**

rounded number to the specified order

**See Also**

[round](#), [trunc](#), [ceiling](#), [floor](#)

**Examples**

```
round2(23.5)    # = 24, compare: round(23.5) = 24
round2(23.4)    # = 23
round2(24.5)    # = 25, compare: round(24.5) = 24
round2(-23.5)   # = -24, compare: round(-23.5) = -24
round2(-23.4)   # = -23
round2(-24.5)   # = -25, compare: round(-24.5) = -24
round2(123.456, -1) # 123.5
round2(123.456, -2) # 123.46
round2(123.456, 1)  # 120
round2(123.456, 2)  # 100
round2(123.456, 3)  # 0
round2(-123.456, -1) # -123.5
round2(-123.456, -2) # -123.46
round2(-123.456, 1) # -120
round2(-123.456, 2) # -100
round2(-123.456, 3) # 0
```

---

seqM	<i>seqM</i>
------	-------------

---

## Description

Matlab-like behaviour of colon operator or linspace for creating sequences, for-loop friendly.

## Usage

```
seqM(from = NA, to = NA, by = NA, length.out = NA)
```

## Arguments

from	starting value of the sequence (the first number)
to	end value of the sequence (the last number or the boundary number)
by	increment of the sequence (if specified, do not use the length.out parameter). If both by and length.out are not specified, then by = +1.
length.out	desired length of the sequence (if specified, do not use the by parameter)

## Details

Like seq() but with Matlab-like behavior ([: operator] with by or [linspace] with length.out).

If I create a for-loop, I would like to get an empty vector for 3:1 (I want a default step +1) and also an empty vector for seq(3,1,by = 1) (not an error). This is solved by this seqM function.

## Value

returns a vector of type "integer" or "double"

## Comparison

R: seqM		Matlab		R: seq
seqM(1, 3)	[1] 1 2 3	1:3	the same	the same
seqM(1, 3, by=.8)	[1] 1.0 1.8 2.6	1:.8:3	the same	the same
seqM(1, 3, by=5)	[1] 1	1:5:3	the same	the same
seqM(3, 1)	integer(0)	3:1	the same	[1] 3 2 1
seqM(3, 1, by=+1)	integer(0)	3:1:1	the same	Error: wrong 'by'
seqM(3, 1, by=-1)	[1] 3 2 1	3:-1:1	the same	the same
seqM(3, 1, by=-3)	[1] 3	3:-3:1	the same	the same
seqM(1, 3, len=5)	[1] 1.0 1.5 2.0 2.5 3.0	linspace(1,3,5)	the same	the same
seqM(1, 3, len=3)	[1] 1 2 3	linspace(1,3,3)	the same	the same
seqM(1, 3, len=2)	[1] 1 3	linspace(1,3,2)	the same	the same
seqM(1, 3, len=1)	[1] 3	linspace(1,3,1)	the same	[1] 1
seqM(1, 3, len=0)	integer(0) + warning	linspace(1,3,0)	the same without warning	the same without warning
seqM(3, 1, len=3)	[1] 3 2 1	linspace(3,1,3)	the same	the same

**See Also**

[round2](#), [isNum](#), [isInt](#), [ifft](#).

**Examples**

```
seqM(1, 3)
seqM(1, 3, by=.8)
seqM(1, 3, by=5)
seqM(3, 1)
seqM(3, 1, by=+1)
seqM(3, 1, by=-1)
seqM(3, 1, by=-3)
seqM(1, 3, len=5)
seqM(1, 3, len=3)
seqM(1, 3, len=2)
seqM(1, 3, len=1)
seqM(1, 3, len=0)
seqM(3, 1, len=3)
```

---

snd.cut

*snd.cut*

---

**Description**

Cut the specified interval from the Sound object and preserve time

**Usage**

```
snd.cut(snd, Start = -Inf, End = Inf, units = "seconds")
```

**Arguments**

snd	Sound object (list with \$sig and \$fs members at least)
Start	beginning sample/time of interval to be cut (default -Inf = cut from the beginning of the Sound)
End	final sample/time of interval to be cut (default Inf = cut to the end of the Sound)
units	Units of Start and End arguments: "samples" (starting from 1, i.e., 1 == index of the 1st sample) or "seconds" (starting from 0)

**Value**

Sound object

**See Also**

[snd.cut0](#), [tg.cut](#), [tg.cut0](#), [snd.read](#), [snd.plot](#)

**Examples**

```

snd <- snd.sample()
snd2 <- snd.cut(snd, Start = 0.3)
snd2_0 <- snd.cut0(snd, Start = 0.3)
snd3 <- snd.cut(snd, Start = 0.2, End = 0.3)
snd3_0 <- snd.cut0(snd, Start = 0.2, End = 0.3)
snd4 <- snd.cut(snd, End = 0.1)
snd4_0 <- snd.cut0(snd, End = 0.1)
snd5 <- snd.cut(snd, Start = -0.1, End = 0.1)
snd5_0 <- snd.cut0(snd, Start = -0.1, End = 0.1)
snd6 <- snd.cut(snd, End = 1000, units = "samples")
snd6_0 <- snd.cut0(snd, End = 1000, units = "samples")
## Not run:
snd.plot(snd)
snd.plot(snd2)
snd.plot(snd2_0)
snd.plot(snd3)
snd.plot(snd3_0)
snd.plot(snd4)
snd.plot(snd4_0)
snd.plot(snd5)
snd.plot(snd5_0)
snd.plot(snd6)
snd.plot(snd6_0)

## End(Not run)

```

snd.cut0

*snd.cut0***Description**

Cut the specified interval from the Sound object and and shift time so that the new `snd$t[1] = 0`

**Usage**

```
snd.cut0(snd, Start = -Inf, End = Inf, units = "seconds")
```

**Arguments**

<code>snd</code>	Sound object (list with <code>\$sig</code> and <code>\$fs</code> members at least)
<code>Start</code>	beginning sample/time of interval to be cut (default <code>-Inf</code> = cut from the beginning of the Sound)
<code>End</code>	final sample/time of interval to be cut (default <code>Inf</code> = cut to the end of the Sound)
<code>units</code>	Units of <code>Start</code> and <code>End</code> arguments: "samples" (starting from 1, i.e., 1 == index of the 1st sample) or "seconds" (starting from 0)

**Value**

Sound object

**See Also**

[snd.cut](#), [tg.cut](#), [tg.cut0](#), [snd.read](#), [snd.plot](#)

**Examples**

```
snd <- snd.sample()
snd2 <- snd.cut(snd, Start = 0.3)
snd2_0 <- snd.cut0(snd, Start = 0.3)
snd3 <- snd.cut(snd, Start = 0.2, End = 0.3)
snd3_0 <- snd.cut0(snd, Start = 0.2, End = 0.3)
snd4 <- snd.cut(snd, End = 0.1)
snd4_0 <- snd.cut0(snd, End = 0.1)
snd5 <- snd.cut(snd, Start = -0.1, End = 0.1)
snd5_0 <- snd.cut0(snd, Start = -0.1, End = 0.1)
snd6 <- snd.cut(snd, End = 1000, units = "samples")
snd6_0 <- snd.cut0(snd, End = 1000, units = "samples")
## Not run:
snd.plot(snd)
snd.plot(snd2)
snd.plot(snd2_0)
snd.plot(snd3)
snd.plot(snd3_0)
snd.plot(snd4)
snd.plot(snd4_0)
snd.plot(snd5)
snd.plot(snd5_0)
snd.plot(snd6)
snd.plot(snd6_0)

## End(Not run)
```

---

snd.plot

*snd.plot*

---

**Description**

Plots interactive Sound object using dygraphs package. If the sound is 2-channel (stereo), the 1st channel is plotted around mean value +1, the 2nd around mean value -1.

**Usage**

```
snd.plot(snd, group = "", stemPlot = FALSE)
```

**Arguments**

snd	Sound object (with \$sig and \$fs members at least)
group	[optional] character string, name of group for dygraphs synchronization
stemPlot	[optional] discrete style of plot using

**See Also**

[snd.read](#)

## Examples

```
## Not run:
snd <- snd.sample()
snd.plot(snd)

snd.plot(list(sig = sin(seq(0, 2*pi, length.out = 4000)), fs = 8000))

## End(Not run)
```

---

snd.read

*snd.read*


---

## Description

Loads sound file (.wav or .mp3) using tuneR package.

## Usage

```
snd.read(fileNameSound, fileType = "auto", from = 1, to = Inf,
  units = "samples")
```

## Arguments

fileNameSound	Sound file name (.wav or .mp3)
fileType	"wav", "mp3" or "auto"
from	Where to start reading in units (beginning "samples": 1, "seconds": 0)
to	Where to stop reading in units (Inf = end of the file)
units	Units of from and to arguments: "samples" (starting from 1) or "seconds" (starting from 0)

## Value

Sound object with normalized amplitude ( $\text{PCM} / 2^{(\text{nbits}-1)} - 1$ ) resulting to the range of  $[-1; +1]$ . In fact, the minimum value can be one quantization step lower (e.g. PCM 16bit: -32768). t ... vector of discrete time instances (seconds) sig ... signal matrix ( $\text{nrow}(\text{snd}\$sig) = \text{number of samples}$ ,  $\text{ncol}(\text{snd}\$sig) = \text{number of channels}$ , i.e.,  $\$sig[, 1]$  ... 1st channel) fs ... sample rate (Hz) nChannels ... number of signal channels ( $\text{ncol}(\text{snd}\$sig)$ ), 1 == mono, 2 == stereo nBits ... number of bits per one sample nSamples ... number of samples ( $\text{nrow}(\text{snd}\$sig)$ ) duration ... duration of signal (seconds),  $\text{snd}\$duration == \text{snd}\$nSamples / \text{snd}\$fs$

## Examples

```
## Not run:
snd <- snd.read("demo/H.wav")
snd.plot(snd)

## End(Not run)
```

---

`snd.sample`*snd.sample*

---

**Description**

Returns sample Sound object.

**Usage**

```
snd.sample()
```

**Value**

snd

**See Also**

[snd.plot](#)

**Examples**

```
snd <- snd.sample()
snd.plot(snd)
```

---

`snd.write`*snd.write*

---

**Description**

Saves Sound object to a file. `snd` is a list with `$sig` and `$fs` members at least. If `$nBits` is not present, default value of 16 bits is used. Vector `$t` is ignored. If the sound signal is 2-channel (stereo), `$sig` must be a two-column matrix (1st column corresponds to the left channel, 2nd column to the right channel). If the sound is 1-channel (mono), `$sig` can be either a numeric vector or a one-column matrix. optional `$t`, `$nChannels`, `$nSamples`, `$duration` vectors are ignored.

**Usage**

```
snd.write(snd, fileNameSound)
```

**Arguments**

<code>snd</code>	Sound object (with <code>\$sig</code> , <code>\$nBits</code> and <code>\$fs</code> members)
<code>fileNameSound</code>	file name to be created

**See Also**

[snd.read](#)

**Examples**

```
## Not run:
snd <- snd.sample()
snd.plot(snd)
snd.write(snd, "temp1.wav")

signal <- 0.8*sin(seq(0, 2*pi*440, length.out = 8000))
snd.write(list(sig = signal, fs = 8000, nBits = 16), "temp2.wav")

left <- 0.3*sin(seq(0, 2*pi*440, length.out = 4000))
righ <- 0.5*sin(seq(0, 2*pi*220, length.out = 4000))
snd.write(list(sig = matrix(c(left, right), ncol = 2), fs = 8000, nBits = 16), "temp3.wav")

## End(Not run)
```

strTrim

*strTrim***Description**

Trim leading and trailing whitespace in character string.

**Usage**

```
strTrim(string)
```

**Arguments**

string                      character string

**Details**

Like `str_trim()` in `stringr` package or `trimws()` in R3.2.0 but way faster.

Source: Hadley Wickham comment at <http://stackoverflow.com/questions/2261079/how-to-trim-leading-and-trailing-whitespace-in-r>

**Value**

returns a character string with removed leading and trailing whitespace characters.

**See Also**

[isString](#) for testing whether it is 1 character vector, [str\\_contains](#) for finding string in string without regexp, [str\\_find](#) for all indices without regexp, [str\\_find1](#) for the first index without regexp.

**Examples**

```
strTrim("        Hello World!        ")
```



---

str_contains	<i>str_contains</i>
--------------	---------------------

---

**Description**

Find string in another string (without regular expressions), returns TRUE / FALSE.

**Usage**

```
str_contains(string, patternNoRegex)
```

**Arguments**

string	string in which we try to find something
patternNoRegex	string we want to find, "as it is" - no regular expressions

**Value**

TRUE / FALSE

**See Also**

[str\\_find](#), [str\\_find1](#), [isString](#)

**Examples**

```
str_contains("Hello world", "wor") # TRUE
str_contains("Hello world", "WOR") # FALSE
str_contains(tolower("Hello world"), tolower("wor")) # TRUE
str_contains("Hello world", "") # TRUE
```

---

str_find	<i>str_find</i>
----------	-----------------

---

**Description**

Find string in another string (without regular expressions), returns indices of all occurrences.

**Usage**

```
str_find(string, patternNoRegex)
```

**Arguments**

string	string in which we try to find something
patternNoRegex	string we want to find, "as it is" - no regular expressions

**Value**

indices of all occurrences (1 = 1st character)

**See Also**

[str\\_find1](#), [str\\_contains](#), [isString](#)

**Examples**

```
str_find("Hello, hello, hello world", "ell") # 2 9 16
str_find("Hello, hello, hello world", "q")   # integer(0)
```

---

str_find1	<i>str_find1</i>
-----------	------------------

---

**Description**

Find string in another string (without regular expressions), returns indices of the first occurrence only.

**Usage**

```
str_find1(string, patternNoRegex)
```

**Arguments**

string                string in which we try to find something  
patternNoRegex    string we want to find, "as it is" - no regular expressions

**Value**

index of the first occurrence only (1 = 1st character)

**See Also**

[str\\_find](#), [str\\_contains](#), [isString](#)

**Examples**

```
str_find1("Hello, hello, hello world", "ell") # 2
str_find1("Hello, hello, hello world", "q")   # integer(0)
```

---

tg.boundaryMagnet	<i>tg.boundaryMagnet</i>
-------------------	--------------------------

---

## Description

Aligns boundaries of intervals in the target tier (typically: "word") to the closest boundaries in the pattern tier (typically: "phone"). If there is no boundary within the tolerance limit in the pattern tier, the boundary position in the target tier is kept at its original position.

## Usage

```
tg.boundaryMagnet(tg, targetTier, patternTier, boundaryTolerance = Inf,
  verbose = TRUE)
```

## Arguments

tg	TextGrid object
targetTier	index or "name" of the tier to be aligned
patternTier	index or "name" of the pattern tier
boundaryTolerance	if there is not any boundary in the pattern tier within this tolerance, the target boundary is kept at its position [default: Inf]
verbose	if TRUE, every boundary shift is printed [default: TRUE]

## Value

TextGrid object

## See Also

[tg.insertBoundary](#), [tg.insertInterval](#), [tg.duplicateTier](#)

## Examples

```
## Not run:
tg <- tg.sample()
tg <- tg.removeTier(tg, "phoneme")
tg <- tg.removeTier(tg, "syllable")
tg <- tg.removeTier(tg, "phrase")

# garble times in "word" tier a little
n <- length(tg$word$label)
deltaT <- runif(n - 1, min = -0.01, max = 0.015)
tg$word$t2[1: (n-1)] <- tg$word$t2[1: (n-1)] + deltaT
tg$word$t1[2: n] <- tg$word$t2[1: (n-1)]
tg.plot(tg)

# align "word" tier according to "phone tier"
tg2 <- tg.boundaryMagnet(tg, targetTier = "word", patternTier = "phone")
tg.plot(tg2)

## End(Not run)
```

---

tg.checkTierInd	<i>tg.checkTierInd</i>
-----------------	------------------------

---

### Description

Returns tier index. Input can be either index (number) or tier name (character string). It performs checks whether the tier exists.

### Usage

```
tg.checkTierInd(tg, tierInd)
```

### Arguments

tg	TextGrid object
tierInd	Tier index or "name"

### Value

Tier index

### See Also

[tg.getTierName](#), [tg.isIntervalTier](#), [tg.isPointTier](#), [tg.plot](#), [tg.getNumberOfTiers](#)

### Examples

```
tg <- tg.sample()
tg.checkTierInd(tg, 4)
tg.checkTierInd(tg, "word")
```

---

tg.countLabels	<i>tg.countLabels</i>
----------------	-----------------------

---

### Description

Returns number of labels with the specified label.

### Usage

```
tg.countLabels(tg, tierInd, label)
```

### Arguments

tg	TextGrid object
tierInd	tier index or "name"
label	character string: label to be counted

**Value**

integer number

**See Also**

[tg.findLabels](#), [tg.getLabel](#)

**Examples**

```
tg <- tg.sample()
tg.countLabels(tg, "phone", "a")
```

---

`tg.createNewTextGrid`    *tg.createNewTextGrid*

---

**Description**

Creates new and empty TextGrid. tMin and tMax specify the total start and end time for the TextGrid. If a new interval tier is added later without specified start and end, they are set to TextGrid start and end.

**Usage**

```
tg.createNewTextGrid(tMin, tMax)
```

**Arguments**

tMin	Start time of TextGrid
tMax	End time of TextGrid

**Details**

This empty TextGrid cannot be used for almost anything. At least one tier should be inserted using `tg.insertNewIntervalTier()` or `tg.insertNewPointTier()`.

**Value**

TextGrid object

**See Also**

[tg.insertNewIntervalTier](#), [tg.insertNewPointTier](#)

**Examples**

```
tg <- tg.createNewTextGrid(0, 5)
tg <- tg.insertNewIntervalTier(tg, 1, "word")
tg <- tg.insertInterval(tg, "word", 1, 2, "hello")
tg.plot(tg)
```

---

tg.cut	<i>tg.cut</i>
--------	---------------

---

## Description

Cut the specified time frame from the TextGrid and preserve time

## Usage

```
tg.cut(tg, tStart = -Inf, tEnd = Inf)
```

## Arguments

tg	TextGrid object
tStart	beginning time of time frame to be cut (default -Inf = cut from the tmin of the TextGrid)
tEnd	final time of time frame to be cut (default Inf = cut to the tmax of the TextGrid)

## Value

TextGrid object

## See Also

[tg.cut0](#), [pt.cut](#), [pt.cut0](#), [tg.read](#), [tg.plot](#), [tg.write](#), [tg.insertInterval](#)

## Examples

```
tg <- tg.sample()
tg2 <- tg.cut(tg, tStart = 3)
tg2_0 <- tg.cut0(tg, tStart = 3)
tg3 <- tg.cut(tg, tStart = 2, tEnd = 3)
tg3_0 <- tg.cut0(tg, tStart = 2, tEnd = 3)
tg4 <- tg.cut(tg, tEnd = 1)
tg4_0 <- tg.cut0(tg, tEnd = 1)
tg5 <- tg.cut(tg, tStart = -1, tEnd = 5)
tg5_0 <- tg.cut0(tg, tStart = -1, tEnd = 5)
## Not run:
tg.plot(tg)
tg.plot(tg2)
tg.plot(tg2_0)
tg.plot(tg3)
tg.plot(tg3_0)
tg.plot(tg4)
tg.plot(tg4_0)
tg.plot(tg5)
tg.plot(tg5_0)

## End(Not run)
```

tg.cut0

*tg.cut0***Description**

Cut the specified time frame from the TextGrid and shift time so that the new tmin = 0

**Usage**

```
tg.cut0(tg, tStart = -Inf, tEnd = Inf)
```

**Arguments**

tg	TextGrid object
tStart	beginning time of time frame to be cut (default -Inf = cut from the tmin of the TextGrid)
tEnd	final time of time frame to be cut (default Inf = cut to the tmax of the TextGrid)

**Value**

TextGrid object

**See Also**

[tg.cut](#), [pt.cut](#), [pt.cut0](#), [tg.read](#), [tg.plot](#), [tg.write](#), [tg.insertInterval](#)

**Examples**

```
tg <- tg.sample()
tg2 <- tg.cut(tg, tStart = 3)
tg2_0 <- tg.cut0(tg, tStart = 3)
tg3 <- tg.cut(tg, tStart = 2, tEnd = 3)
tg3_0 <- tg.cut0(tg, tStart = 2, tEnd = 3)
tg4 <- tg.cut(tg, tEnd = 1)
tg4_0 <- tg.cut0(tg, tEnd = 1)
tg5 <- tg.cut(tg, tStart = -1, tEnd = 5)
tg5_0 <- tg.cut0(tg, tStart = -1, tEnd = 5)
## Not run:
tg.plot(tg)
tg.plot(tg2)
tg.plot(tg2_0)
tg.plot(tg3)
tg.plot(tg3_0)
tg.plot(tg4)
tg.plot(tg4_0)
tg.plot(tg5)
tg.plot(tg5_0)

## End(Not run)
```

---

tg.duplicateTier	<i>tg.duplicateTier</i>
------------------	-------------------------

---

### Description

Duplicates tier originalInd to new tier with specified index newInd (existing tiers are shifted). It is highly recommended to set a name to the new tier (this can also be done later by tg.setTierName()). Otherwise, both original and new tiers have the same name which is permitted but not recommended. In such a case, we cannot use the comfort of using tier name instead of its index in other functions.

### Usage

```
tg.duplicateTier(tg, originalInd, newInd = Inf, newTierName = "")
```

### Arguments

tg	TextGrid object
originalInd	tier index or "name"
newInd	new tier index (1 = the first, Inf = the last [default])
newTierName	[optional but recommended] name of the new tier

### Value

TextGrid object

### See Also

[tg.duplicateTierMergeSegments](#), [tg.setTierName](#), [tg.removeTier](#), [tg.boundaryMagnet](#)

### Examples

```
tg <- tg.sample()
tg2 <- tg.duplicateTier(tg, "word", 1, "NEW")
tg.plot(tg2)
```

---

tg.duplicateTierMergeSegments	<i>tg.duplicateTierMergeSegments</i>
-------------------------------	--------------------------------------

---

### Description

Duplicate tier originalInd and merge segments (according to the pattern) to the new tier with specified index newInd (existing tiers are shifted). Typical use: create new syllable tier from phone tier. It merges phones into syllables according to separators in pattern.

### Usage

```
tg.duplicateTierMergeSegments(tg, originalInd, newInd = Inf, newTierName,
  pattern, sep = "-")
```



**Arguments**

tg	TextGrid object
originalInd	tier index or "name"
newInd	new tier index (1 = the first, Inf = the last [default])
newTierName	name of the new tier
pattern	merge segments pattern for the new tier (e.g., "he-llo-world")
sep	separator in pattern (default: "-")

**Details**

Note 1: there can be segments with empty labels in the original tier (pause), do not specify them in the pattern

Note 2: if there is an segment with empty label in the original tier in the place of separator in the pattern, the empty segment is duplicated into the new tier, i.e. at the position of the separator, there may or may not be an empty segment, if there is, it is duplicated. And they are not specified in the pattern.

Note 3: if the segment with empty label is not at the position corresponding to separator, it leads to error - the part specified in the pattern between separators cannot be split by empty segments

Note 4: beware of labels that appear empty but they are not (space, new line character etc.) - these segments are handled as classical non-empty labels. See example - one label is " ", therefore it must be specified in the pattern.

**Value**

TextGrid object

**See Also**

[tg.duplicateTier](#), [tg.setTierName](#), [tg.removeTier](#)

**Examples**

```
tg <- tg.sample()
tg <- tg.removeTier(tg, "syllable")
collapsed <- paste0(tg$phone$label, collapse = "") # get actual labels
print(collapsed) # all labels in collapsed form - copy the string, include separators -> pattern
pattern <- "ja:-ci-P\\ek-nu-t_so-?u-J\\e-la:S- -nej-dP\\i:f-naj-deZ-h\\ut_S-ku-?a-?a-ta-ma-na:"
tg2 <- tg.duplicateTierMergeSegments(tg, "phone", 1, "syll", pattern, sep = "-")
## Not run:
tg.plot(tg)
tg.plot(tg2)

## End(Not run)
```

---

tg.findLabels	<i>tg.findLabels</i>
---------------	----------------------

---

### Description

Find label or consecutive sequence of labels and returns their indices.

### Usage

```
tg.findLabels(tg, tierInd, labelVector, returnTime = FALSE)
```

### Arguments

tg	TextGrid object
tierInd	tier index or "name"
labelVector	character string (one label) or vector of character strings (consecutive sequence of labels) to be found
returnTime	If TRUE, return vectors of begin (t1) and end time (t2) for each found group of sequence of labels instead of indices (when FALSE = default).

### Value

If returnTime == FALSE, returns list of all occurrences, each member of the list is one occurrence and contains vector of label indices, if returnTime == TRUE, returns list with vectors t1 (begin) and t2 (end) for each found group of sequence of labels.

### See Also

[tg.countLabels](#), [tg.getLabel](#), [tg.duplicateTierMergeSegments](#)

### Examples

```
tg <- tg.sample()
i <- tg.findLabels(tg, "phoneme", "n")
i
length(i)
i[[1]]
i[[2]]
tg$phoneme$label[unlist(i)]

i <- tg.findLabels(tg, "phone", c("?", "a"))
i
length(i)
tg$phone$label[i[[1]]]
tg$phone$label[i[[2]]]
tg$phone$label[unlist(i)]

t <- tg.findLabels(tg, "phone", c("?", "a"), returnTime = TRUE)
t
t$t2[1] - t$t1[1] # duration of the first result
t$t2[2] - t$t1[2] # duration of the second result
```

```

i <- tg.findLabels(tg.sample(), "word", c("ti", "reknu", "co"))
i
length(i)
length(i[[1]])
i[[1]]
i[[1]][3]
tg$word$label[i[[1]]]

t <- tg.findLabels(tg.sample(), "word", c("ti", "reknu", "co"), returnTime = TRUE)
pt <- pt.sample()
tStart <- t$t1[1]
tEnd <- t$t2[1]
## Not run:
pt.plot(pt.cut(pt, tStart, tEnd))

## End(Not run)

```

---

tg.getEndTime	<i>tg.getEndTime</i>
---------------	----------------------

---

## Description

Returns end time. If tier index is specified, it returns end time of the tier, if it is not specified, it returns end time of the whole TextGrid.

## Usage

```
tg.getEndTime(tg, tierInd = 0)
```

## Arguments

tg	TextGrid object
tierInd	[optional] tier index or "name"

## Value

numeric

## See Also

[tg.getStartTime](#), [tg.getTotalDuration](#)

## Examples

```

tg <- tg.sample()
tg.getEndTime(tg)
tg.getEndTime(tg, "phone")

```

---

```
tg.getIntervalDuration
```

*tg.getIntervalDuration*

---

**Description**

Return duration (i.e., end - start time) of interval in interval tier.

**Usage**

```
tg.getIntervalDuration(tg, tierInd, index)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
index	index of interval

**Value**

numeric

**See Also**

[tg.getIntervalStartTime](#), [tg.getIntervalEndTime](#), [tg.getIntervalIndexAtTime](#), [tg.findLabels](#)

**Examples**

```
tg <- tg.sample()
tg.getIntervalDuration(tg, "phone", 5)
```

---

```
tg.getIntervalEndTime
```

*tg.getIntervalEndTime*

---

**Description**

Return end time of interval in interval tier.

**Usage**

```
tg.getIntervalEndTime(tg, tierInd, index)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
index	index of interval

**Value**

numeric

**See Also**[tg.getIntervalStartTime](#), [tg.getIntervalDuration](#), [tg.getIntervalIndexAtTime](#), [tg.findLabels](#)**Examples**

```
tg <- tg.sample()
tg.getIntervalEndTime(tg, "phone", 5)
```

---

```
tg.getIntervalIndexAtTime
  tg.getIntervalIndexAtTime
```

---

**Description**

Returns index of interval which includes the given time, i.e.  $tStart \leq time < tEnd$ . Tier index must belong to interval tier.

**Usage**

```
tg.getIntervalIndexAtTime(tg, tierInd, time)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
time	time which is going to be found in intervals

**Value**

integer

**See Also**[tg.getIntervalStartTime](#), [tg.getIntervalEndTime](#), [tg.getLabel](#), [tg.findLabels](#)**Examples**

```
tg <- tg.sample()
tg.getIntervalIndexAtTime(tg, "word", 0.5)
```

---

```
tg.getIntervalStartTime
      tg.getIntervalStartTime
```

---

**Description**

Returns start time of interval in interval tier.

**Usage**

```
tg.getIntervalStartTime(tg, tierInd, index)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
index	index of interval

**Value**

numeric

**See Also**

[tg.getIntervalEndTime](#), [tg.getIntervalDuration](#), [tg.getIntervalIndexAtTime](#), [tg.findLabels](#)

**Examples**

```
tg <- tg.sample()
tg.getIntervalStartTime(tg, "phone", 5)
```

---

```
tg.getLabel      tg.getLabel
```

---

**Description**

Return label of point or interval at the specified index.

**Usage**

```
tg.getLabel(tg, tierInd, index)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
index	index of point or interval

**Value**

character string

**See Also**

[tg.setLabel](#), [tg.countLabels](#), [tg.findLabels](#)

**Examples**

```
tg <- tg.sample()
tg.getLabel(tg, "phoneme", 4)
tg.getLabel(tg, "phone", 4)
```

---

tg.getNumberOfIntervals	
	<i>tg.getNumberOfIntervals</i>

---

**Description**

Returns number of intervals in the given interval tier.

**Usage**

```
tg.getNumberOfIntervals(tg, tierInd)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"

**Value**

integer

**See Also**

[tg.getNumberOfPoints](#)

**Examples**

```
tg <- tg.sample()
tg.getNumberOfIntervals(tg, "phone")
```

---

tg.getNumberOfPoints	<i>tg.getNumberOfPoints</i>
----------------------	-----------------------------

---

**Description**

Returns number of points in the given point tier.

**Usage**

```
tg.getNumberOfPoints(tg, tierInd)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"

**Value**

integer

**See Also**

[tg.getNumberOfIntervals](#)

**Examples**

```
tg <- tg.sample()
tg.getNumberOfPoints(tg, "phoneme")
```

---

tg.getNumberOfTiers	<i>tg.getNumberOfTiers</i>
---------------------	----------------------------

---

**Description**

Returns number of tiers.

**Usage**

```
tg.getNumberOfTiers(tg)
```

**Arguments**

tg	TextGrid object
----	-----------------

**Value**

integer

**See Also**

[tg.getTierName](#), [tg.isIntervalTier](#), [tg.isPointTier](#)



**Examples**

```
tg <- tg.sample()
tg.getNumberOfTiers(tg)
```

---

```
tg.getPointIndexHigherThanTime
      tg.getPointIndexHigherThanTime
```

---

**Description**

Returns index of point which is nearest the given time from right, i.e.  $\text{time} \leq \text{pointTime}$ . Tier index must belong to point tier.

**Usage**

```
tg.getPointIndexHigherThanTime(tg, tierInd, time)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
time	time which is going to be found in points

**Value**

integer

**See Also**

[tg.getPointIndexNearestTime](#), [tg.getPointIndexLowerThanTime](#), [tg.getLabel](#), [tg.findLabels](#)

**Examples**

```
tg <- tg.sample()
tg.getPointIndexHigherThanTime(tg, "phoneme", 0.5)
```

---

```
tg.getPointIndexLowerThanTime
      tg.getPointIndexLowerThanTime
```

---

**Description**

Returns index of point which is nearest the given time from left, i.e.  $\text{pointTime} \leq \text{time}$ . Tier index must belong to point tier.

**Usage**

```
tg.getPointIndexLowerThanTime(tg, tierInd, time)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
time	time which is going to be found in points

**Value**

integer

**See Also**

[tg.getPointIndexNearestTime](#), [tg.getPointIndexHigherThanTime](#), [tg.getLabel](#), [tg.findLabels](#)

**Examples**

```
tg <- tg.sample()
tg.getPointIndexLowerThanTime(tg, "phoneme", 0.5)
```

---

<code>tg.getPointIndexNearestTime</code>	<i>tg.getPointIndexNearestTime</i>
--	------------------------------------

---

**Description**

Returns index of point which is nearest the given time (from both sides). Tier index must belong to point tier.

**Usage**

```
tg.getPointIndexNearestTime(tg, tierInd, time)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
time	time which is going to be found in points

**Value**

integer

**See Also**

[tg.getPointIndexLowerThanTime](#), [tg.getPointIndexHigherThanTime](#), [tg.getLabel](#), [tg.findLabels](#)

**Examples**

```
tg <- tg.sample()
tg.getPointIndexNearestTime(tg, "phoneme", 0.5)
```

---

tg.getPointTime	<i>tg.getPointTime</i>
-----------------	------------------------

---

**Description**

Return time of point at the specified index in point tier.

**Usage**

```
tg.getPointTime(tg, tierInd, index)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
index	index of point

**Value**

numeric

**See Also**

[tg.getLabel](#), [tg.getPointIndexNearestTime](#), [tg.getPointIndexLowerThanTime](#),  
[tg.getPointIndexHigherThanTime](#), [tg.findLabels](#)

**Examples**

```
tg <- tg.sample()
tg.getPointTime(tg, "phoneme", 4)
```

---

tg.getStartTime	<i>tg.getStartTime</i>
-----------------	------------------------

---

**Description**

Returns start time. If tier index is specified, it returns start time of the tier, if it is not specified, it returns start time of the whole TextGrid.

**Usage**

```
tg.getStartTime(tg, tierInd = 0)
```

**Arguments**

tg	TextGrid object
tierInd	[optional] tier index or "name"

Value

numeric

See Also

[tg.getEndTime](#), [tg.getTotalDuration](#)

Examples

```
tg <- tg.sample()
tg.getStartTime(tg)
tg.getStartTime(tg, "phone")
```

---

tg.getTierName	<i>tg.getTierName</i>
----------------	-----------------------

---

Description

Returns name of the tier.

Usage

```
tg.getTierName(tg, tierInd)
```

Arguments

tg	TextGrid object
tierInd	tier index or "name"

Value

character string

See Also

[tg.setTierName](#), [tg.isIntervalTier](#), [tg.isPointTier](#)

Examples

```
tg <- tg.sample()
tg.getTierName(tg, 2)
```

---

tg.getTotalDuration	<i>tg.getTotalDuration</i>
---------------------	----------------------------

---

**Description**

Returns total duration. If tier index is specified, it returns duration of the tier, if it is not specified, it returns total duration of the TextGrid.

**Usage**

```
tg.getTotalDuration(tg, tierInd = 0)
```

**Arguments**

tg	TextGrid object
tierInd	[optional] tier index or "name"

**Value**

numeric

**See Also**

[tg.getStartTime](#), [tg.getEndTime](#)

**Examples**

```
tg <- tg.sample()
tg.getTotalDuration(tg)
tg.getTotalDuration(tg, "phone")
```

---

tg.insertBoundary	<i>tg.insertBoundary</i>
-------------------	--------------------------

---

**Description**

Inserts new boundary into interval tier. This creates a new interval, to which we can set the label (optional argument).

**Usage**

```
tg.insertBoundary(tg, tierInd, time, label = "")
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
time	time of the new boundary
label	[optional] label of the new interval

## Details

There are more possible situations which influence where the new label will be set.

a) New boundary into the existing interval (the most common situation): The interval is splitted into two parts. The left preserves the label of the original interval, the right is set to the new (optional) label.

b) On the left of existing interval (i.e., enlarging the tier size): The new interval starts with the new boundary and ends at the start of originally first existing interval. The label is set to the new interval.

c) On the right of existing interval (i.e., enlarging the tier size): The new interval starts at the end of originally last existing interval and ends with the new boundary. The label is set to the new interval. This is somewhat different behaviour than in a) and b) where the new label is set to the interval which is on the right of the new boundary. In c), the new label is set on the left of the new boundary. But this is the only logical possibility.

It is a nonsense to insert a boundary between existing intervals to a position where there is no interval. This is against the basic logic of Praat interval tiers where, at the beginning, there is one large empty interval from beginning to the end. And then, it is divided to smaller intervals by adding new boundaries. Nevertheless, if the TextGrid is created by external programmes, you may rarely find such discontinuities. In such a case, at first, use the `tgRepairContinuity()` function.

## Value

TextGrid object

## See Also

[tg.insertInterval](#), [tg.removeIntervalLeftBoundary](#), [tg.removeIntervalRightBoundary](#), [tg.removeIntervalBothBoundaries](#), [tg.boundaryMagnet](#), [tg.duplicateTierMergeSegments](#)

## Examples

```
tg <- tg.sample()
tg2 <- tg.insertNewIntervalTier(tg, 1, "INTERVALS")
tg2 <- tg.insertBoundary(tg2, "INTERVALS", 0.8)
tg2 <- tg.insertBoundary(tg2, "INTERVALS", 0.1, "Interval A")
tg2 <- tg.insertInterval(tg2, "INTERVALS", 1.2, 2.5, "Interval B")
## Not run:
tg.plot(tg2)

## End(Not run)
```

---

<code>tg.insertInterval</code>	<i>tg.insertInterval</i>
--------------------------------	--------------------------

---

## Description

Inserts new interval into an empty space in interval tier: a) Into an already existing interval with empty label (most common situation because, e.g., a new interval tier has one empty interval from beginning to the end. b) Outside of existing intervals (left or right), this may create another empty interval between.

**Usage**

```
tg.insertInterval(tg, tierInd, tStart, tEnd, label = "")
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
tStart	start time of the new interval
tEnd	end time of the new interval
label	[optional] label of the new interval

**Details**

In most cases, this function is the same as 1.) `tgInsertBoundary(tEnd)` and 2.) `tgInsertBoundary(tStart, "new label")`. But, additional checks are performed: a) `tStart` and `tEnd` belongs to the same empty interval, or b) both times are outside of existings intervals (both left or both right).

Intersection of the new interval with more already existing (even empty) does not make a sense and is forbidden.

In many situations, in fact, this function creates more than one interval. E.g., let's assume an empty interval tier with one empty interval from 0 to 5 sec. 1.) We insert a new interval from 1 to 2 with label "he". Result: three intervals, 0-1 "", 1-2 "he", 2-5 "". 2.) Then, we insert an interval from 7 to 8 with label "lot". Result: five intervals, 0-1 "", 1-2 "he", 2-5 "", 5-7 "", 7-8 "lot" Note: the empty 5-7 "" interval is inserted because we are going outside of the existing tier. 3.) Now, we insert a new interval exactly between 2 and 3 with label "said". Result: really only one interval is created (and only the right boundary is added because the left one already exists): 0-1 "", 1-2 "he", 2-3 "said", 3-5 "", 5-7 "", 7-8 "lot". 4.) After this, we want to insert another interval, 3 to 5: label "a". In fact, this does not create any new interval at all. Instead of that, it only sets the label to the already existing interval 3-5. Result: 0-1 "", 1-2 "he", 2-3 "said", 3-5 "a", 5-7 "", 7-8 "lot".

This function is not implemented in Praat (6.0.14). And it is very useful for adding separate intervals to an empty area in interval tier, e.g., result of voice activity detection algorithm. On the other hand, if we want continuously add new consequential intervals, `tgInsertBoundary()` may be more useful. Because, in the `tgInsertInterval()` function, if we calculate both boundaries separately for each interval, strange situations may happen due to numeric round-up errors, like  $3.14 \times 5 \neq 15.7$ . In such cases, it may be hard to obtain precisely consequential time instances. As  $3.14 \times 5$  is slightly larger than 15.7 (let's try to calculate  $15.7 - 3.14 \times 5$ ), if you calculate `tEnd` of the first interval as  $3.14 \times 5$  and `tStart` of the second interval as 15.7, this function refuse to create the second interval because it would be an intersection. In the opposite case (`tEnd` of the 1st: 15.7, `tStart` of the 2nd:  $3.14 \times 5$ ), it would create another "micro" interval between these two slightly different time instances. Instead of that, if you insert only one boundary using the `tgInsertBoundary()` function, you are safe that only one new interval is created. But, if you calculate the "15.7" (no matter how) and store in the variable and then, use this variable in the `tgInsertInterval()` function both for the `tEnd` of the 1st interval and `tStart` of the 2nd interval, you are safe, it works fine.

**Value**

TextGrid object

**See Also**

[tg.insertBoundary](#), [tg.removeIntervalLeftBoundary](#), [tg.removeIntervalRightBoundary](#), [tg.removeIntervalBothBoundaries](#), [tg.boundaryMagnet](#), [tg.duplicateTierMergeSegments](#)

**Examples**

```

tg <- tg.sample()
tg2 <- tg.insertNewIntervalTier(tg, 1, "INTERVALS")
tg2 <- tg.insertBoundary(tg2, "INTERVALS", 0.8)
tg2 <- tg.insertBoundary(tg2, "INTERVALS", 0.1, "Interval A")
tg2 <- tg.insertInterval(tg2, "INTERVALS", 1.2, 2.5, "Interval B")
## Not run:
tg.plot(tg2)

## End(Not run)

```

---

```

tg.insertNewIntervalTier
      tg.insertNewIntervalTier

```

---

**Description**

Inserts new interval tier to the specified index (existing tiers are shifted). The new tier contains one empty interval from beginning to end. Then, if we add new boundaries, this interval is divided to smaller pieces.

**Usage**

```

tg.insertNewIntervalTier(tg, newInd = Inf, newTierName, tMin = NA,
  tMax = NA)

```

**Arguments**

tg	TextGrid object
newInd	new tier index (1 = the first, Inf = the last [default])
newTierName	new tier name
tMin	[optional] start time of the new tier
tMax	[optional] end time of the new tier

**Value**

TextGrid object

**See Also**

[tg.insertInterval](#), [tg.insertNewPointTier](#), [tg.duplicateTier](#), [tg.duplicateTierMergeSegments](#), [tg.removeTier](#)

**Examples**

```

## Not run:
tg <- tg.sample()
tg2 <- tg.insertNewIntervalTier(tg, 1, "INTERVALS")
tg2 <- tg.insertBoundary(tg2, "INTERVALS", 0.8)
tg2 <- tg.insertBoundary(tg2, "INTERVALS", 0.1, "Interval A")
tg2 <- tg.insertInterval(tg2, "INTERVALS", 1.2, 2.5, "Interval B")

```



```

tg2 <- tg.insertNewIntervalTier(tg2, Inf, "LastTier")
tg2 <- tg.insertInterval(tg2, "LastTier", 1, 3, "This is the last tier")
tg.plot(tg2)

## End(Not run)

```

---

tg.insertNewPointTier    *tg.insertNewPointTier*

---

## Description

Inserts new point tier to the specified index (existing tiers are shifted).

## Usage

```
tg.insertNewPointTier(tg, newInd = Inf, newTierName)
```

## Arguments

tg	TextGrid object
newInd	new tier index (1 = the first, Inf = the last [default])
newTierName	new tier name

## Value

TextGrid object

## See Also

[tg.insertPoint](#), [tg.insertNewIntervalTier](#), [tg.duplicateTier](#), [tg.removeTier](#)

## Examples

```

## Not run:
tg <- tg.sample()
tg2 <- tg.insertNewPointTier(tg, 1, "POINTS")
tg2 <- tg.insertPoint(tg2, "POINTS", 3, "MY POINT")
tg2 <- tg.insertNewPointTier(tg2, Inf, "POINTS2") # the last tier
tg2 <- tg.insertPoint(tg2, "POINTS2", 2, "point in the last tier")
tg.plot(tg2)

## End(Not run)

```

---

tg.insertPoint	<i>tg.insertPoint</i>
----------------	-----------------------

---

**Description**

Inserts new point to point tier of the given index.

**Usage**

```
tg.insertPoint(tg, tierInd, time, label)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
time	time of the new point
label	time of the new point

**Value**

TextGrid object

**See Also**

[tg.removePoint](#), [tg.insertInterval](#), [tg.insertBoundary](#)

**Examples**

```
## Not run:
tg <- tg.sample()
tg2 <- tg.insertPoint(tg, "phoneme", 1.4, "NEW POINT")
tg.plot(tg2)

## End(Not run)
```

---

tg.isIntervalTier	<i>tg.isIntervalTier</i>
-------------------	--------------------------

---

**Description**

Returns TRUE if the tier is IntervalTier, FALSE otherwise.

**Usage**

```
tg.isIntervalTier(tg, tierInd)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"

**Value**

TRUE / FALSE

**See Also**

[tg.isPointTier](#), [tg.getTierName](#), [tg.findLabels](#)

**Examples**

```
tg <- tg.sample()
tg.isIntervalTier(tg, 1)
tg.isIntervalTier(tg, "word")
```

---

tg.isPointTier	<i>tg.isPointTier</i>
----------------	-----------------------

---

**Description**

Returns TRUE if the tier is PointTier, FALSE otherwise.

**Usage**

```
tg.isPointTier(tg, tierInd)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"

**Value**

TRUE / FALSE

**See Also**

[tg.isIntervalTier](#), [tg.getTierName](#), [tg.findLabels](#)

**Examples**

```
tg <- tg.sample()
tg.isPointTier(tg, 1)
tg.isPointTier(tg, "word")
```

tg.plot

*tg.plot***Description**

Plots interactive TextGrid using dygraphs package.

**Usage**

```
tg.plot(tg, group = "", pt = NULL, it = NULL, formant = NULL,
        formantScaleIntensity = TRUE, formantDrawBandwidth = TRUE,
        pitch = NULL, pitchScaleIntensity = TRUE,
        pitchShowStrength = FALSE, snd = NULL)
```

**Arguments**

tg	TextGrid object
group	[optional] character string, name of group for dygraphs synchronization
pt	[optional] PitchTier object
it	[optional] IntensityTier object
formant	[optional] Formant object
formantScaleIntensity	[optional] Point size scaled according to relative intensity
formantDrawBandwidth	[optional] Draw formant bandwidth
pitch	[optional] Pitch object
pitchScaleIntensity	[optional] Point size scaled according to relative intensity
pitchShowStrength	[optional] Show strength annotation
snd	[optional] Sound object

**See Also**

[tg.read](#), [pt.plot](#), [it.plot](#), [pitch.plot](#)

**Examples**

```
## Not run:
tg <- tg.sample()
tg.plot(tg)
tg.plot(tg.sample(), pt = pt.sample())

## End(Not run)
```

---

tg.read

*tg.read*


---

### Description

Loads TextGrid from Praat in Text or Short text format (UTF-8), it handles both Interval and Point tiers. Labels can may contain quotation marks and new lines.

### Usage

```
tg.read(fileNameTextGrid, encoding = "UTF-8")
```

### Arguments

fileNameTextGrid

Input file name

encoding

File encoding (default: "UTF-8"), "auto" for auto-detect of Unicode encoding

### Value

TextGrid object

### See Also

[tg.write](#), [tg.plot](#), [tg.repairContinuity](#), [tg.createNewTextGrid](#), [tg.findLabels](#), [tg.duplicateTierMergeSegments](#), [pt.read](#), [pitch.read](#), [formant.read](#), [it.read](#), [col.read](#)

### Examples

```
## Not run:
tg <- tg.read("demo/H.TextGrid")
tg.plot(tg)

## End(Not run)
```

---

tg.removeIntervalBothBoundaries

*tg.removeIntervalBothBoundaries*


---

### Description

Remove both left and right boundary of interval of the given index in Interval tier. In fact, this operation concatenate three intervals into one (and their labels). It cannot be applied to the first and the last interval because they contain beginning or end boundary of the tier. E.g., let's assume interval 1-2-3. We remove both boundaries of the 2nd interval. The result is one interval 123. If we do not want to concatenate labels (we wanted to remove the label including its interval), we can set the label of the second interval to the empty string "" before this operation. If we only want to remove the label of interval "without concatenation", i.e., the desired result is 1-empty-3, it is not this operation of removing boundaries. Just set the label of the second interval to the empty string "".

**Usage**

```
tg.removeIntervalBothBoundaries(tg, tierInd, index)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
index	index of the interval

**Value**

TextGrid object

**See Also**

[tg.removeIntervalLeftBoundary](#), [tg.removeIntervalRightBoundary](#), [tg.insertBoundary](#), [tg.insertInterval](#)

**Examples**

```
## Not run:
tg <- tg.sample()
tg.plot(tg)
tg2 <- tg.removeIntervalBothBoundaries(tg, "word", 3)
tg.plot(tg2)

## End(Not run)
```

---

```
tg.removeIntervalLeftBoundary
```

```
tg.removeIntervalLeftBoundary
```

---

**Description**

Remove left boundary of the interval of the given index in Interval tier. In fact, it concatenates two intervals into one (and their labels). It cannot be applied to the first interval because it is the start boundary of the tier. E.g., we have interval 1-2-3, we remove the left boundary of the 2nd interval, the result is two intervals 12-3. If we do not want to concatenate labels, we have to set the label to the empty string "" before this operation.

**Usage**

```
tg.removeIntervalLeftBoundary(tg, tierInd, index)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
index	index of the interval

**Value**

TextGrid object

**See Also**

[tg.removeIntervalRightBoundary](#), [tg.removeIntervalBothBoundaries](#), [tg.insertBoundary](#), [tg.insertInterval](#)

**Examples**

```
## Not run:
tg <- tg.sample()
tg.plot(tg)
tg2 <- tg.removeIntervalLeftBoundary(tg, "word", 3)
tg.plot(tg2)

## End(Not run)
```

---

`tg.removeIntervalRightBoundary`

*tg.removeIntervalRightBoundary*

---

**Description**

Remove right boundary of the interval of the given index in Interval tier. In fact, it concatenates two intervals into one (and their labels). It cannot be applied to the last interval because it is the end boundary of the tier. E.g., we have interval 1-2-3, we remove the right boundary of the 2nd interval, the result is two intervals 1-23. If we do not want to concatenate labels, we have to set the label to the empty string "" before this operation.

**Usage**

```
tg.removeIntervalRightBoundary(tg, tierInd, index)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
index	index of the interval

**Value**

TextGrid object

**See Also**

[tg.removeIntervalLeftBoundary](#), [tg.removeIntervalBothBoundaries](#), [tg.insertBoundary](#), [tg.insertInterval](#)

### Examples

```
## Not run:
tg <- tg.sample()
tg.plot(tg)
tg2 <- tg.removeIntervalRightBoundary(tg, "word", 3)
tg.plot(tg2)

## End(Not run)
```

---

tg.removePoint	<i>tg.removePoint</i>
----------------	-----------------------

---

### Description

Remove point of the given index from the point tier.

### Usage

```
tg.removePoint(tg, tierInd, index)
```

### Arguments

tg	TextGrid object
tierInd	tier index or "name"
index	index of point to be removed

### Value

TextGrid object

### See Also

[tg.insertPoint](#), [tg.getNumberOfPoints](#), [tg.removeIntervalBothBoundaries](#)

### Examples

```
tg <- tg.sample()
tg$phoneme$label
tg2 <- tg.removePoint(tg, "phoneme", 1)
tg2$phoneme$label
```



---

tg.removeTier	<i>tg.removeTier</i>
---------------	----------------------

---

**Description**

Removes tier of the given index.

**Usage**

```
tg.removeTier(tg, tierInd)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"

**Value**

TextGrid object

**See Also**

[tg.insertNewIntervalTier](#), [tg.insertNewPointTier](#), [tg.duplicateTier](#)

**Examples**

```
## Not run:
tg <- tg.sample()
tg.plot(tg)
tg2 <- tg.removeTier(tg, "word")
tg.plot(tg2)

## End(Not run)
```

---

tg.repairContinuity	<i>tg.repairContinuity</i>
---------------------	----------------------------

---

**Description**

Repairs problem of continuity of T2 and T1 in interval tiers. This problem is very rare and it should not appear. However, e.g., automatic segmentation tool Prague Labeller produces random numeric round-up errors featuring, e.g., T2 of preceding interval is slightly higher than the T1 of the current interval. Because of that, the boundary cannot be manually moved in Praat edit window.

**Usage**

```
tg.repairContinuity(tg, verbose = TRUE)
```

**Arguments**

tg	TextGrid object
verbose	[optional, default=TRUE] If FALSE, the function performs everything quietly.

**Value**

TextGrid object

**See Also**

[tg.sampleProblem](#)

**Examples**

```
## Not run:
tgProblem <- tg.sampleProblem()
tgNew <- tg.repairContinuity(tgProblem)
tg.write(tgNew, "demo_problem_OK.TextGrid")

## End(Not run)
```

---

tg.sample

*tg.sample*

---

**Description**

Returns sample TextGrid.

**Usage**

```
tg.sample()
```

**Value**

TextGrid

**See Also**

[tg.plot](#)

**Examples**

```
tg <- tg.sample()
tg.plot(tg)
```

---

tg.sampleProblem	<i>tg.sampleProblem</i>
------------------	-------------------------

---

**Description**

Returns sample TextGrid with continuity problem.

**Usage**

```
tg.sampleProblem()
```

**Value**

TextGrid

**See Also**

[tg.repairContinuity](#)

**Examples**

```
tg <- tg.sampleProblem()
tg2 <- tg.repairContinuity(tg)
tg2 <- tg.repairContinuity(tg2)
tg.plot(tg2)
```

---

tg.setLabel	<i>tg.setLabel</i>
-------------	--------------------

---

**Description**

Sets (changes) label of interval or point of the given index in the interval or point tier.

**Usage**

```
tg.setLabel(tg, tierInd, index, newLabel)
```

**Arguments**

tg	TextGrid object
tierInd	tier index or "name"
index	index of interval or point
newLabel	new "label"

**See Also**

[tg.getLabel](#)

Examples

```
tg <- tg.sample()
tg2 <- tg.setLabel(tg, "word", 3, "New Label")
tg.getLabel(tg2, "word", 3)
```

---

tg.setTierName	<i>tg.setTierName</i>
----------------	-----------------------

---

Description

Sets (changes) name of tier of the given index.

Usage

```
tg.setTierName(tg, tierInd, name)
```

Arguments

tg	TextGrid object
tierInd	tier index or "name"
name	new "name" of the tier

See Also

```
tg.getTierName
```

Examples

```
tg <- tg.sample()
tg2 <- tg.setTierName(tg, "word", "WORDTIER")
tg.getTierName(tg2, 4)
```

---

tg.write	<i>tg.write</i>
----------	-----------------

---

Description

Saves TextGrid to the file. TextGrid may contain both interval and point tiers (tg[[1]], tg[[2]], tg[[3]], etc.). If tier type is not specified in \$type, is assumed to be "interval". If specified, \$type have to be "interval" or "point". If there is no class(tg)["tmin"] and class(tg)["tmax"], they are calculated as min and max of all tiers. The file is saved in UTF-8 encoding.

Usage

```
tg.write(tg, fileNameTextGrid, format = "short")
```

**Arguments**

tg	TextGrid object
fileNameTextGrid	Output file name
format	Output file format ("short" (default, short text format) or "text" (a.k.a. full text format))

**See Also**

[tg.read](#), [pt.write](#)

**Examples**

```
## Not run:  
tg <- tg.sample()  
tg.write(tg, "demo_output.TextGrid")  
  
## End(Not run)
```

# Index

as.formant, 4  
as.it, 4  
as.pitch, 5  
as.pt, 5  
as.snd, 6  
as.tg, 6  
  
ceiling, 41  
col.read, 7, 8, 13, 25, 30, 39, 77  
col.write, 8  
Conj, 16  
  
detectEncoding, 9  
  
fft, 16  
floor, 41  
formant.cut, 9, 11  
formant.cut0, 10, 10  
formant.plot, 10, 11, 11, 14, 15, 29, 38  
formant.read, 7, 10–12, 12, 14, 15, 25, 39, 77  
formant.sample, 12, 13, 31  
formant.toArray, 12, 14, 15  
formant.toFrame, 14  
formant.write, 15  
  
ifft, 16, 43  
Im, 16  
isInt, 16, 17–19, 43  
isLogical, 17, 17, 18, 19  
isNum, 17, 18, 19, 43  
isString, 17, 18, 18, 48–50  
it.cut, 19, 20–22, 24, 25  
it.cut0, 19, 20, 21, 22, 24, 25  
it.interpolate, 19, 20, 21, 22–26  
it.legendre, 19–21, 22, 23  
it.legendreDemo, 19, 20, 22, 23, 23  
it.legendreSynth, 19, 20, 22, 23, 23  
it.plot, 19–23, 24, 25, 26, 76  
it.read, 7, 13, 19–24, 25, 26, 30, 39, 77  
it.sample, 13, 25, 31  
it.write, 21, 24, 25, 26  
  
Mod, 16  
  
pitch.cut, 27, 28  
pitch.cut0, 27, 28  
pitch.plot, 27, 28, 29, 31, 32, 38, 76  
pitch.read, 7, 13, 25, 27–29, 29, 31, 32, 39, 77  
pitch.sample, 13, 29, 30  
pitch.toArray, 29, 31, 32  
pitch.toFrame, 31, 32  
pitch.write, 32  
pt.cut, 33, 34–36, 38, 39, 54, 55  
pt.cut0, 33, 34, 35, 36, 38, 39, 54, 55  
pt.Hz2ST, 33, 34, 35, 36–40  
pt.interpolate, 33–35, 35, 36–40  
pt.legendre, 33, 34, 36, 36, 37–39  
pt.legendreDemo, 33, 34, 36, 37, 38  
pt.legendreSynth, 33, 34, 36, 37, 37  
pt.plot, 29, 33–38, 38, 39, 40, 76  
pt.read, 7, 13, 25, 30, 32–38, 39, 40, 77  
pt.sample, 13, 31, 40  
pt.write, 35, 36, 38, 39, 40, 85  
  
Re, 16  
round, 41  
round2, 41, 43  
  
seqM, 42  
snd.cut, 43, 45  
snd.cut0, 43, 44  
snd.plot, 43, 45, 45, 47  
snd.read, 43, 45, 46, 47  
snd.sample, 47  
snd.write, 47  
str\_contains, 48, 49, 50  
str\_find, 48, 49, 49, 50  
str\_find1, 48–50, 50  
strTrim, 48  
  
tg.boundaryMagnet, 51, 56, 70, 71  
tg.checkTierInd, 52  
tg.countLabels, 52, 58, 63  
tg.createNewTextGrid, 53, 77  
tg.cut, 10, 11, 27, 28, 33, 43, 45, 54, 55  
tg.cut0, 10, 11, 27, 28, 33, 43, 45, 54, 55  
tg.duplicateTier, 51, 56, 57, 72, 73, 81

tg.duplicateTierMergeSegments, 56, 56,  
     58, 70–72, 77  
 tg.findLabels, 53, 58, 60–63, 65–67, 75, 77  
 tg.getEndTime, 59, 68, 69  
 tg.getIntervalDuration, 60, 61, 62  
 tg.getIntervalEndTime, 60, 60, 61, 62  
 tg.getIntervalIndexAtTime, 60, 61, 61, 62  
 tg.getIntervalStartTime, 60, 61, 62  
 tg.getLabel, 53, 58, 61, 62, 65–67, 83  
 tg.getNumberOfIntervals, 63, 64  
 tg.getNumberOfPoints, 63, 64, 80  
 tg.getNumberOfTiers, 52, 64  
 tg.getPointIndexHigherThanTime, 65, 66,  
     67  
 tg.getPointIndexLowerThanTime, 65, 65,  
     66, 67  
 tg.getPointIndexNearestTime, 65, 66, 66,  
     67  
 tg.getPointTime, 67  
 tg.getStartTime, 59, 67, 69  
 tg.getTierName, 52, 64, 68, 75, 84  
 tg.getTotalDuration, 59, 68, 69  
 tg.insertBoundary, 51, 69, 71, 74, 78, 79  
 tg.insertInterval, 51, 54, 55, 70, 70, 72,  
     74, 78, 79  
 tg.insertNewIntervalTier, 53, 72, 73, 81  
 tg.insertNewPointTier, 53, 72, 73, 81  
 tg.insertPoint, 73, 74, 80  
 tg.isIntervalTier, 52, 64, 68, 74, 75  
 tg.isPointTier, 52, 64, 68, 75, 75  
 tg.plot, 12, 24, 29, 38, 52, 54, 55, 76, 77, 82  
 tg.read, 7, 13, 15, 25, 30, 39, 54, 55, 76, 77,  
     85  
 tg.removeIntervalBothBoundaries, 70, 71,  
     77, 79, 80  
 tg.removeIntervalLeftBoundary, 70, 71,  
     78, 78, 79  
 tg.removeIntervalRightBoundary, 70, 71,  
     78, 79, 79  
 tg.removePoint, 74, 80  
 tg.removeTier, 56, 57, 72, 73, 81  
 tg.repairContinuity, 77, 81, 83  
 tg.sample, 13, 31, 82  
 tg.sampleProblem, 82, 83  
 tg.setLabel, 63, 83  
 tg.setTierName, 56, 57, 68, 84  
 tg.write, 26, 40, 54, 55, 77, 84  
 trunc, 41