

# Analytic formulas for marginal feature attributions of oblivious decision trees

Khashayar Filom

SIAM Conference on Mathematics of Data Science  
October 2024

## 1 Overview: why feature attributions?

## 2 Challenges: how to compute feature attributions?

## 3 Solution in a special case: oblivious trees

# Explaining outcomes of a complex model

## Setup

- ▶ the features are random variables  $\mathbf{X} = (X_1, \dots, X_n)$ ;
- ▶ the input-output function of the model  $\mathbf{X} \mapsto f(\mathbf{X})$ ;
- ▶  $f$  can be a linear model, a random forest, a neural net etc.

# Explaining outcomes of a complex model

## Setup

- ▶ the features are random variables  $\mathbf{X} = (X_1, \dots, X_n)$ ;
- ▶ the input-output function of the model  $\mathbf{X} \mapsto f(\mathbf{X})$ ;
- ▶  $f$  can be a linear model, a random forest, a neural net etc.

## Goal

Interpreting the model via ranking the features based on **feature attributions**:

- ▶ ranking **globally** over the whole data;
- ▶ ranking features **locally**, i.e. for a given input  $\mathbf{x}$ .



# Explaining outcomes of a complex model

## Setup

- ▶ the features are random variables  $\mathbf{X} = (X_1, \dots, X_n)$ ;
- ▶ the input-output function of the model  $\mathbf{X} \mapsto f(\mathbf{X})$ ;
- ▶  $f$  can be a linear model, a random forest, a neural net etc.

## Goal

Interpreting the model via ranking the features based on **feature attributions**:

- ▶ ranking **globally** over the whole data; 
- ▶ ranking features **locally**, i.e. for a given input  $\mathbf{x}$ . 

ECOA/Regulation B require lenders to inform applicants of the primary reasons for decline or other adverse actions.

## Game-theoretic local feature attributions

Štrumbelj-Kononenko 2010, Lundberg-Lee 2017

A very popular approach is to think of features as players of a **game** and then quantify their contributions based on a **game value**.

## Game-theoretic local feature attributions

Štrumbelj-Kononenko 2010, Lundberg-Lee 2017

A very popular approach is to think of features as players of a **game** and then quantify their contributions based on a **game value**.

Three ingredients:

- ▶ features  $\mathbf{X}$  and model  $f$ ;
- ▶ games  $S \mapsto v(S; \mathbf{X}, f)(\mathbf{x})$  ( $S \subseteq \{1, \dots, n\}$ ) assigned to every point  $\mathbf{x}$ ;
- ▶ game value  $h$  quantifying contribution of  $i^{\text{th}}$  feature as  $h_i[v]$  at given  $\mathbf{x}$ .

## Game-theoretic local feature attributions

Štrumbelj-Kononenko 2010, Lundberg-Lee 2017

A very popular approach is to think of features as players of a **game** and then quantify their contributions based on a **game value**.

Three ingredients:

- ▶ features  $\mathbf{X}$  and model  $f$ ;

Examples)  $f$  is a piecewise constant/linear function implemented by a tree ensemble/a ReLU network.

- ▶ games  $S \mapsto v(S; \mathbf{X}, f)(\mathbf{x})$  ( $S \subseteq \{1, \dots, n\}$ ) assigned to every point  $\mathbf{x}$ ;  
Examples) the **conditional** game  $S \mapsto \mathbb{E}[f(\mathbf{X}) \mid \mathbf{X}_S = \mathbf{x}_S]$  "true to the data" and the **marginal** game  $S \mapsto \mathbb{E}[f(\mathbf{x}_S, \mathbf{X}_{-S})]$  "true to the model".

- ▶ game value  $h$  quantifying contribution of  $i^{\text{th}}$  feature as  $h_i[v]$  at given  $\mathbf{x}$ .

Example) the **Shapley value**:

$$\varphi_i[v] := \sum_{S \subseteq \{1, \dots, n\} \setminus \{i\}} \frac{|S|!(n - |S| - 1)!}{n!} (v(S \cup \{i\}) - v(S)).$$



1 Overview: why feature attributions?

2 Challenges: how to compute feature attributions?

3 Solution in a special case: oblivious trees

## Obstacles in computing game-theoretic local feature attributions

- **Features are almost never independent.**
- **Formulas for game values usually have exponentially many terms.**

## Obstacles in computing game-theoretic local feature attributions

- **Features are almost never independent.**

Conditional feature attributions (based on game  $S \mapsto \mathbb{E}[f(\mathbf{X}) \mid \mathbf{X}_S = \mathbf{x}_S]$ ) often differ from the marginal ones (based on game  $S \mapsto \mathbb{E}[f(\mathbf{x}_S, \mathbf{X}_{-S})]$ ).

- **Formulas for game values usually have exponentially many terms.**

## Obstacles in computing game-theoretic local feature attributions

### ■ Features are almost never independent.

Conditional feature attributions (based on game  $S \mapsto \mathbb{E}[f(\mathbf{X}) \mid \mathbf{X}_S = \mathbf{x}_S]$ ) often differ from the marginal ones (based on game  $S \mapsto \mathbb{E}[f(\mathbf{x}_S, \mathbf{X}_{-S})]$ ).

- ▶ Remedy: Grouping features based on dependencies and using **coalitional** variants of the Shapley value (e.g. the **Owen value**) unifies the two frameworks and yields more stable explanations  
[\[Miroshnikov-Kotsiopoulos-F.-Ravi Kannan 2022\]](#).

### ■ Formulas for game values usually have exponentially many terms.

## Obstacles in computing game-theoretic local feature attributions

### ■ Features are almost never independent.

Conditional feature attributions (based on game  $S \mapsto \mathbb{E}[f(\mathbf{X}) \mid \mathbf{X}_S = \mathbf{x}_S]$ ) often differ from the marginal ones (based on game  $S \mapsto \mathbb{E}[f(\mathbf{x}_S, \mathbf{X}_{-S})]$ ).

- ▶ Remedy: Grouping features based on dependencies and using **coalitional** variants of the Shapley value (e.g. the **Owen value**) unifies the two frameworks and yields more stable explanations  
[\[Miroshnikov-Kotsiopoulos-F.-Ravi Kannan 2022\]](#).

### ■ Formulas for game values usually have exponentially many terms.

E.g. the formula for the Shapley value has  $2^{n-1}$  terms ( $n$  can be as large as 100 for a credit card acquisition model).

# Obstacles in computing game-theoretic local feature attributions

## ■ Features are almost never independent.

Conditional feature attributions (based on game  $S \mapsto \mathbb{E}[f(\mathbf{X}) \mid \mathbf{X}_S = \mathbf{x}_S]$ ) often differ from the marginal ones (based on game  $S \mapsto \mathbb{E}[f(\mathbf{x}_S, \mathbf{X}_{-S})]$ ).

- ▶ Remedy: Grouping features based on dependencies and using **coalitional** variants of the Shapley value (e.g. the **Owen value**) unifies the two frameworks and yields more stable explanations  
[Miroshnikov-Kotsiopoulos-F.-Ravi Kannan 2022].

## ■ Formulas for game values usually have exponentially many terms.

E.g. the formula for the Shapley value has  $2^{n-1}$  terms ( $n$  can be as large as 100 for a credit card acquisition model).

- ▶ Remedy: Monte-Carlo approximation [Štrumbelj-Kononenko 2010 & 2014], [Kotsiopoulos-Miroshnikov-F.-Ravi Kannan 2023].

# Obstacles in computing game-theoretic local feature attributions

## ■ Features are almost never independent.

Conditional feature attributions (based on game  $S \mapsto \mathbb{E}[f(\mathbf{X}) \mid \mathbf{X}_S = \mathbf{x}_S]$ ) often differ from the marginal ones (based on game  $S \mapsto \mathbb{E}[f(\mathbf{x}_S, \mathbf{X}_{-S})]$ ).

- ▶ Remedy: Grouping features based on dependencies and using **coalitional** variants of the Shapley value (e.g. the **Owen value**) unifies the two frameworks and yields more stable explanations  
[Miroshnikov-Kotsiopoulos-F.-Ravi Kannan 2022].

## ■ Formulas for game values usually have exponentially many terms.

E.g. the formula for the Shapley value has  $2^{n-1}$  terms ( $n$  can be as large as 100 for a credit card acquisition model).

- ▶ Remedy: Monte-Carlo approximation [Štrumbelj-Kononenko 2010 & 2014], [Kotsiopoulos-Miroshnikov-F.-Ravi Kannan 2023].
- ▶ Remedy: Focusing on a specific type of models.

# Obstacles in computing game-theoretic local feature attributions

## ■ Features are almost never independent.

Conditional feature attributions (based on game  $S \mapsto \mathbb{E}[f(\mathbf{X}) \mid \mathbf{X}_S = \mathbf{x}_S]$ ) often differ from the marginal ones (based on game  $S \mapsto \mathbb{E}[f(\mathbf{x}_S, \mathbf{X}_{-S})]$ ).

- ▶ Remedy: Grouping features based on dependencies and using **coalitional** variants of the Shapley value (e.g. the **Owen value**) unifies the two frameworks and yields more stable explanations  
[Miroshnikov-Kotsiopoulos-F.-Ravi Kannan 2022].

## ■ Formulas for game values usually have exponentially many terms.

E.g. the formula for the Shapley value has  $2^{n-1}$  terms ( $n$  can be as large as 100 for a credit card acquisition model).

- ▶ Remedy: Monte-Carlo approximation [Štrumbelj-Kononenko 2010 & 2014], [Kotsiopoulos-Miroshnikov-F.-Ravi Kannan 2023].
- ▶ Remedy: Focusing on a specific type of models. ▶




1 Overview: why feature attributions?

2 Challenges: how to compute feature attributions?

3 Solution in a special case: oblivious trees

## Different boosting libraries construct trees differently.



Picture from [Medium](#).

- The CatBoost library utilizes **oblivious (symmetric) decision trees** as base learners [\[Dorogush-Ershov-Gulin 2018\]](#).
- Despite this constraint, ensembles of symmetric trees demonstrate competitive predictive power [\[Ferov-Modrý 2016\]](#), [\[Hancock-Khoshgoftaar 2020\]](#).

## Main result: a model-specific and inherently-interpretable approach

[F.-Miroshnikov-Kotsiopoulos-Ravi Kannan 2023] ([10.3934/ods.2024021](https://arxiv.org/abs/10.3934/ods.2024021))

Let  $\mathcal{T}$  be an ensemble of symmetric decision trees of depth  $\leq d$  trained on a dataset  $D$ . (Typically,  $D$  is very large and  $d \leq 10$ .)

## Main result: a model-specific and inherently-interpretable approach

[F.-Miroshnikov-Kotsiopoulos-Ravi Kannan 2023] ([10.3934/ods.2024021](https://arxiv.org/abs/10.3934/ods.2024021))

Let  $\mathcal{T}$  be an ensemble of symmetric decision trees of depth  $\leq d$  trained on a dataset  $D$ . (Typically,  $D$  is very large and  $d \leq 10$ .)

- There is **an explicit formula** for marginal Shapley values of  $\mathcal{T}$  solely in terms of the model's parameters. (In principle, it can be used to compute marginal Shapley values of any decision tree.)

## Main result: a model-specific and inherently-interpretable approach

[F.-Miroshnikov-Kotsiopoulos-Ravi Kannan 2023] ([10.3934/ods.2024021](https://arxiv.org/abs/10.3934/ods.2024021))

Let  $\mathcal{T}$  be an ensemble of symmetric decision trees of depth  $\leq d$  trained on a dataset  $D$ . (Typically,  $D$  is very large and  $d \leq 10$ .)

- ▶ There is **an explicit formula** for marginal Shapley values of  $\mathcal{T}$  solely in terms of the model's parameters. (In principle, it can be used to compute marginal Shapley values of any decision tree.)
- ▶ The formula **can be generalized** for an axiomatically characterized family of game values (including variants of Shapley such as Banzhaf or Owen).

## Main result: a model-specific and inherently-interpretable approach

[F.-Miroshnikov-Kotsiopoulos-Ravi Kannan 2023] ([10.3934/ods.2024021](https://arxiv.org/abs/10.3934/ods.2024021))

Let  $\mathcal{T}$  be an ensemble of symmetric decision trees of depth  $\leq d$  trained on a dataset  $D$ . (Typically,  $D$  is very large and  $d \leq 10$ .)

- ▶ There is **an explicit formula** for marginal Shapley values of  $\mathcal{T}$  solely in terms of the model's parameters. (In principle, it can be used to compute marginal Shapley values of any decision tree.)
- ▶ The formula **can be generalized** for an axiomatically characterized family of game values (including variants of Shapley such as Banzhaf or Owen).
- ▶ Based on this analytic solution, we designed **an algorithm for estimating marginal feature attributions** of  $\mathcal{T}$  according to certain precomputed look-up tables.

## Main result: a model-specific and inherently-interpretable approach

[F.-Miroshnikov-Kotsiopoulos-Ravi Kannan 2023] ([10.3394/iods.2024021](https://arxiv.org/abs/10.3394/iods.2024021))

Let  $\mathcal{T}$  be an ensemble of symmetric decision trees of depth  $\leq d$  trained on a dataset  $D$ . (Typically,  $D$  is very large and  $d \leq 10$ .)


- ▶ There is **an explicit formula** for marginal Shapley values of  $\mathcal{T}$  solely in terms of the model's parameters. (In principle, it can be used to compute marginal Shapley values of any decision tree.)
- ▶ The formula **can be generalized** for an axiomatically characterized family of game values (including variants of Shapley such as Banzhaf or Owen).
- ▶ Based on this analytic solution, we designed **an algorithm for estimating marginal feature attributions** of  $\mathcal{T}$  according to certain precomputed look-up tables.
- ▶ The algorithm is **fast** (the computation complexity is  $O(|\mathcal{T}| \cdot d)$ ) and **accurate** (variance of error  $\propto \frac{1}{|D|}$ ).

## What is special about oblivious (symmetric) trees?



## What is special about oblivious (symmetric) trees?


- For a tree  $T$ , marginal feature attributions based on a linear game value are piecewise constant, but only with respect to a grid partition  $\widetilde{\mathcal{P}}(T)$ , which is often finer than the tree's partition  $\mathcal{P}(T)$ . They coincide when  $T$  is symmetric.



Picture from [10.3934/fods.2024021](https://doi.org/10.3934/fods.2024021).

## What is special about oblivious (symmetric) trees?

- For a tree  $T$ , marginal feature attributions based on a linear game value are piecewise constant, but only with respect to a grid partition  $\widetilde{\mathcal{P}}(T)$ , which is often finer than the tree's partition  $\mathcal{P}(T)$ . They coincide when  $T$  is symmetric.



Picture from [10.3934/fods.2024021](https://doi.org/10.3934/fods.2024021).

- Game value computations can be simplified by exploiting the symmetry.