

MICPAT-2

Selective 2-zone paging station



The Apart MICPAT-2 is a sturdy table type paging microphone. It is ideal for use with CONCEPT1(T) and MA247(MR).

It has a flexible gooseneck and a high quality unidirectional dynamic microphone capsule. With MICPAT-2 you can make paging calls to maximum two zones simultaneously (zone 1 individual, zone 2 individual or both zones).

A clear LED indication for both the zones is integrated in the solid microphone base. The aluminium base is equipped with two push-to-talk switches.

TECHNICAL SPECIFICATIONS

| polar pattern | uni-directional | buttons | 2 push to-talk |
|--------------------------------|--------------------------|---|-----------------|
| indicator | 1 per button | zones | 2 |
| frequency range | 80 Hz - 12 kHz | nominal output level | 275 mV balanced |
| rated output impedance in ohms | 600 balanced open wire | mic stem lenght in mm | 310 |
| | | cable lenght in m | 5 |
| connector | | width in mm | 125 |
| cable type | 2 core + 2 core screened | Widthiniiii | 123 |
| | | depth in mm | 175 |
| height in mm | ht in mm 55 | Net weight product (kg) | 0,92 |
| weight in gr | 850 | 5 5 7 5 5 5 6 7 6 7 6 7 6 7 6 7 6 7 6 7 | -,- |



MORE PICTURES

