

# 1. Description

## 1.1. Project

Project Name	stm32f411.exti.hook.on
Board Name	custom
Generated with:	STM32CubeMX 6.12.0
Date	09/25/2024


### 1.2. MCU

MCU Series	STM32F4
MCU Line	STM32F411
MCU name	STM32F411CEUx
MCU Package	UFQFPN48
MCU Pin number	48

## 1.3. Core(s) information

Core(s)	Arm Cortex-M4

## 2. Pinout Configuration




# 3. Pins Configuration

Pin Number	Pin Name	Pin Type	Alternate	Label
UFQFPN48	(function after		Function(s)	
01 01 1110	reset)		r directori(e)	
4	•	Power		
2	VBAT PC13-ANTI_TAMP *	I/O	CRIO Quitaut	LED_PIN
5		1/0	GPIO_Output	LED_PIN
6	PH0 - OSC_IN PH1 - OSC_OUT	I/O	RCC_OSC_IN RCC_OSC_OUT	
7	NRST		KCC_03C_001	
8	VSSA	Reset Power		
9	VDDA	Power		
10	PA0-WKUP	I/O	CDIO EXTIN	BUITTON KEV
			GPIO_EXTI0	BUTTON_KEY
12	PA2 PA3	I/O I/O	USART2_TX	CONSOLE_TX CONSOLE_RX
13			USART2_RX	
14	PA4	1/0	I2S1_WS	I2S1_LRCK
15	PA5	1/0	I2S1_CK	I2S1_BCK
16	PA6	1/0	I2S2_MCK	I2S2_SCK
17	PA7	I/O	I2S1_SD	I2S1_DATA_OUT
22	VCAP1	Power		
23	VSS	Power		
24	VDD	Power	1000 14/0	1000 1 0014
25	PB12	1/0	12S2_WS	I2S2_LRCK
26	PB13	1/0	I2S2_CK	I2S2_BCK
28	PB15	1/0	I2S2_SD	I2S2_DATA_IN
34	PA13	I/O	SYS_JTMS-SWDIO	
35	VSS	Power		
36	VDD	Power	0)/0   ITO// 0)//0   //	
37	PA14	1/0	SYS_JTCK-SWCLK	DOMO OVALO
38	PA15	1/0	12S3_WS	PCM0_SYNC
39	PB3	1/0	I2S3_CK	PCM0_CLK
40	PB4	1/0	I2S3_ext_SD	PCM0_OUT
41	PB5	1/0	I2S3_SD	PCM0_INP
42	PB6	1/0	I2C1_SCL	
43	PB7	I/O	I2C1_SDA	
44	BOOT0	Boot		
47	VSS	Power		
48	VDD	Power		

<sup>\*</sup> The pin is affected with an I/O function

## 4. Clock Tree Configuration



Page 4

## 1. Power Consumption Calculator report

#### 1.1. Microcontroller Selection

Series	STM32F4
Line	STM32F411
MCU	STM32F411CEUx
Datasheet	DS10314_Rev6

### 1.2. Parameter Selection

Temperature	25
Vdd	1.7

### 1.3. Battery Selection

Battery	Li-SOCL2(A3400)
Capacity	3400.0 mAh
Self Discharge	0.08 %/month
Nominal Voltage	3.6 V
Max Cont Current	100.0 mA
Max Pulse Current	200.0 mA
Cells in series	1
Cells in parallel	1


### 1.4. Sequence

	1	
Step	Step1	Step2
Mode	RUN	STOP
Vdd	1.7	1.7
Voltage Source	Battery	Battery
Range	Scale1-High	No Scale
Fetch Type	SRAM	n/a
CPU Frequency	100 MHz	0 Hz
Clock Configuration	HSE PLL	Regulator_LPLV Flash-
		PwrDwn
Clock Source Frequency	4 MHz	0 Hz
Peripherals		
Additional Cons.	0 mA	0 mA
Average Current	12.7 mA	9 µA
Duration	0.1 ms	0.9 ms
DMIPS	125.0	0.0
Ta Max	104.31	105
Category	In DS Table	In DS Table

## 1.5. Results

Sequence Time	1 ms	Average Current	1.28 mA
Battery Life	3 months, 19	Average DMIPS	125.0 DMIPS
	days, 6 hours	-	

### 1.6. Chart



# 2. Software Project

### 2.1. Project Settings

Name	Value
Project Name	stm32f411.exti.hook.on.fds_i2s3
Project Folder	/Users/user/Projects/stm32f411.exti.hook.on.fds_i2s3
Toolchain / IDE	Makefile
Firmware Package Name and Version	STM32Cube FW_F4 V1.28.1
Application Structure	Advanced
Generate Under Root	No
Do not generate the main()	No
Minimum Heap Size	0x800
Minimum Stack Size	0x1200

### 2.2. Code Generation Settings

Name	Value
STM32Cube MCU packages and embedded software	Add necessary library files as reference in the toolchain project configuration file
Generate peripheral initialization as a pair of '.c/.h' files	Yes
Backup previously generated files when re-generating	No
Keep User Code when re-generating	Yes
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power	No
consumption)	
Enable Full Assert	Yes

### 2.3. Advanced Settings - Generated Function Calls

Rank	Function Name	Peripheral Instance Name
1	SystemClock_Config	RCC
2	MX_GPIO_Init	GPIO
3	MX_DMA_Init	DMA
4	MX_USART2_UART_Init	USART2
5	MX_I2S1_Init	12\$1
6	MX_I2S2_Init	12\$2
7	MX_RTC_Init	RTC
8	MX_I2C1_Init	I2C1
9	MX_I2S3_Init	12\$3

stm32f411.exti.hook.on Project Configuration Report

## 3. Peripherals and Middlewares Configuration

3.1. I2C1 I2C: I2C

#### 3.1.1. Parameter Settings:

#### **Master Features:**

I2C Speed Mode Standard Mode
I2C Clock Speed (Hz) 100000

**Slave Features:** 

Clock No Stretch Mode Disabled

Primary Address Length selection 7-bit

Dual Address Acknowledged Disabled

Primary slave address 16 \*

General Call address detection Disabled

#### 3.2. I2S1

Mode: Half-Duplex Master 3.2.1. Parameter Settings:

#### **Generic Parameters:**

Transmission Mode Mode Master Transmit

Communication Standard I2S Philips

Data and Frame Format 24 Bits Data on 32 Bits Frame \*

Selected Audio Frequency 48 KHz \*

Real Audio Frequency 48.023 KHz \*

Error between Selected and Real 0.04 % \*

**Clock Parameters:** 

Clock Source I2S PLL Clock

Clock Polarity Low

3.3. I2S2

Mode: Half-Duplex Master mode: Master Clock Output 3.3.1. Parameter Settings:

**Generic Parameters:** 

Transmission Mode Master Receive \*

Communication Standard I2S Philips

Data and Frame Format 24 Bits Data on 32 Bits Frame \*

Selected Audio Frequency 48 KHz \*

Real Audio Frequency 48.023 KHz \*

Error between Selected and Real 0.04 % \*

**Clock Parameters:** 

Clock Source I2S PLL Clock

Clock Polarity Low

3.4. I2S3

Mode: Full-Duplex Slave

3.4.1. Parameter Settings:

**Generic Parameters:** 

Transmission Mode Slave Receive \*

Communication Standard I2S Philips

Data and Frame Format 24 Bits Data on 32 Bits Frame \*

Selected Audio Frequency 48 KHz \*

Real Audio Frequency 48.023 KHz \*

Error between Selected and Real 0.04 % \*

**Clock Parameters:** 

Clock Source I2S PLL Clock

Clock Polarity Low

3.5. RCC

High Speed Clock (HSE): Crystal/Ceramic Resonator

3.5.1. Parameter Settings:

**System Parameters:** 

VDD voltage (V) 3.3
Instruction Cache Enabled
Prefetch Buffer Enabled

Data Cache Enabled

Flash Latency(WS) 3 WS (4 CPU cycle)

**RCC Parameters:** 

HSI Calibration Value 16

TIM Prescaler Selection Enabled \*

HSE Startup Timout Value (ms) 120 \*
LSE Startup Timout Value (ms) 5000

**Power Parameters:** 

Power Regulator Voltage Scale Power Regulator Voltage Scale 1

3.6. RTC

mode: Activate Clock Source

3.6.1. Parameter Settings:

General:

Hour Format Hourformat 24

Asynchronous Predivider value 127
Synchronous Predivider value 255

3.7. SYS

**Debug: Serial Wire** 

Timebase Source: SysTick

3.8. **USART2** 

**Mode: Asynchronous** 

3.8.1. Parameter Settings:

**Basic Parameters:** 

Baud Rate 115200

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

**Advanced Parameters:** 

Data Direction Receive and Transmit

Over Sampling 8 Samples \*

stm32f411.exti.hook.on Pro	ojec
Configuration Re	por

* User modified value		

# 4. System Configuration

## 4.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
I2C1	PB6	I2C1_SCL	Alternate Function Open Drain	Pull-up *	Very High	
	PB7	I2C1_SDA	Alternate Function Open Drain	Pull-up *	Very High	
I2S1	PA4	I2S1_WS	Alternate Function Push Pull	No pull-up and no pull-down	High *	I2S1_LRCK
	PA5	I2S1_CK	Alternate Function Push Pull	No pull-up and no pull-down	High *	I2S1_BCK
	PA7	12S1_SD	Alternate Function Push Pull	No pull-up and no pull-down	High *	I2S1_DATA_OUT
12S2	PA6	I2S2_MCK	Alternate Function Push Pull	No pull-up and no pull-down	High *	I2S2_SCK
	PB12	12S2_WS	Alternate Function Push Pull	No pull-up and no pull-down	Low	I2S2_LRCK
	PB13	12S2_CK	Alternate Function Push Pull	No pull-up and no pull-down	High *	I2S2_BCK
	PB15	12S2_SD	Alternate Function Push Pull	No pull-up and no pull-down	Medium *	I2S2_DATA_IN
I2S3	PA15	12S3_WS	Alternate Function Push Pull	No pull-up and no pull-down	High *	PCM0_SYNC
	PB3	12S3_CK	Alternate Function Push Pull	No pull-up and no pull-down	High *	PCM0_CLK
	PB4	I2S3_ext_SD	Alternate Function Push Pull	No pull-up and no pull-down	High *	PCM0_OUT
	PB5	12S3_SD	Alternate Function Push Pull	No pull-up and no pull-down	Medium *	PCM0_INP
RCC	PH0 - OSC_IN	RCC_OSC_IN	n/a	n/a	n/a	
	PH1 - OSC_OUT	RCC_OSC_OUT	n/a	n/a	n/a	
SYS	PA13	SYS_JTMS- SWDIO	n/a	n/a	n/a	
	PA14	SYS_JTCK- SWCLK	n/a	n/a	n/a	
USART2	PA2	USART2_TX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	CONSOLE_TX
	PA3	USART2_RX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	CONSOLE_RX
GPIO	PC13- ANTI_TAMP	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LED_PIN
	PA0-WKUP	GPIO_EXTI0	External Interrupt Mode with Rising edge trigger detection	Pull-down *	n/a	BUTTON_KEY

#### 4.2. DMA configuration

DMA request	Stream	Direction	Priority
SPI1_TX	DMA2_Stream2	Memory To Peripheral	Low
SPI2_RX	DMA1_Stream3	Peripheral To Memory	Low
I2S3_EXT_TX	DMA1_Stream5	Memory To Peripheral	Low
SPI3_RX	DMA1_Stream0	Peripheral To Memory	Low

#### SPI1\_TX: DMA2\_Stream2 DMA request Settings:

Mode: Circular \*
Use fifo: Disable
Peripheral Increment: Disable
Memory Increment: Enable \*
Peripheral Data Width: Half Word \*
Memory Data Width: Half Word \*

#### SPI2\_RX: DMA1\_Stream3 DMA request Settings:

Mode: Circular \*
Use fifo: Disable
Peripheral Increment: Disable
Memory Increment: Enable \*
Peripheral Data Width: Half Word \*
Memory Data Width: Half Word \*

#### I2S3\_EXT\_TX: DMA1\_Stream5 DMA request Settings:

Mode: Circular \*
Use fifo: Disable
Peripheral Increment: Disable
Memory Increment: Enable \*
Peripheral Data Width: Half Word \*
Memory Data Width: Half Word \*

### SPI3\_RX: DMA1\_Stream0 DMA request Settings:

Mode: Circular \*

Use fifo: Disable
Peripheral Increment: Disable

Memory Increment: Enable \*

Peripheral Data Width: Half Word \*

Memory Data Width: Half Word \*

## 4.3. NVIC configuration

## 4.3.1. NVIC

Interrupt Table	Enable	Preenmption Priority	SubPriority
Non maskable interrupt	true	0	0
Hard fault interrupt	true	0	0
Memory management fault	true	0	0
Pre-fetch fault, memory access fault	true	0	0
Undefined instruction or illegal state	true	0	0
System service call via SWI instruction	true	2	3
Debug monitor	true	2	3
Pendable request for system service	true	1	3
System tick timer	true	3	3
PVD interrupt through EXTI line 16	true	1	3
Flash global interrupt	true	2	1
RCC global interrupt	true	2	3
EXTI line0 interrupt	true	0	0
DMA1 stream0 global interrupt	true	0	0
DMA1 stream3 global interrupt	true	0	0
DMA1 stream5 global interrupt	true	0	0
I2C1 event interrupt	true	0	0
I2C1 error interrupt	true	0	0
SPI1 global interrupt	true	3	2
SPI2 global interrupt	true	3	2
USART2 global interrupt	true	1	1
SPI3 global interrupt	true	0	0
DMA2 stream2 global interrupt	true	0	0
FPU global interrupt	true	3	1

### 4.3.2. NVIC Code generation

Enabled interrupt Table	Select for init sequence ordering	Generate IRQ handler	Call HAL handler
Non maskable interrupt	false	true	false
Hard fault interrupt	false	true	false
Memory management fault	false	true	false
Pre-fetch fault, memory access fault	false	true	false
Undefined instruction or illegal state	false	true	false
System service call via SWI instruction	false	true	false
Debug monitor	false	true	false
Pendable request for system service	false	true	false
System tick timer	false	true	true


Enabled interrupt Table	Select for init sequence ordering	Generate IRQ handler	Call HAL handler
PVD interrupt through EXTI line 16	true	true	true
Flash global interrupt	true	true	true
RCC global interrupt	true	true	false
EXTI line0 interrupt	false	true	true
DMA1 stream0 global interrupt	false	true	true
DMA1 stream3 global interrupt	true	true	true
DMA1 stream5 global interrupt	false	true	true
I2C1 event interrupt	true	true	true
I2C1 error interrupt	true	true	true
SPI1 global interrupt	true	true	true
SPI2 global interrupt	true	true	true
USART2 global interrupt	true	true	true
SPI3 global interrupt	true	true	true
DMA2 stream2 global interrupt	true	true	true
FPU global interrupt	true	true	false

<sup>\*</sup> User modified value

## 5. System Views

5.1. Category view

5.1.1. Current



## 6. Docs & Resources

Type Link

BSDL files https://www.st.com/resource/en/bsdl\_model/stm32f411\_bsdl.zip

IBIS models https://www.st.com/resource/en/ibis\_model/stm32f411\_ibis.zip

System View https://www.st.com/resource/en/svd/stm32f4-svd.zip

Description

Presentations https://www.st.com/resource/en/product\_presentation/stm32-

stm8\_embedded\_software\_solutions.pdf

Presentations https://www.st.com/resource/en/product\_presentation/stm32\_eval-

tools\_portfolio.pdf

Presentations https://www.st.com/resource/en/product\_presentation/stm32\_stm8\_functi

onal-safety-packages.pdf

Presentations https://www.st.com/resource/en/product\_presentation/stm32-

stm8\_software\_development\_tools.pdf

Presentations https://www.st.com/resource/en/product\_presentation/microcontrollers-

stm32-family-overview.pdf

Presentations https://www.st.com/resource/en/product\_presentation/microcontrollers-

stm32h7rs-lines-overview.pdf

Brochures https://www.st.com/resource/en/brochure/products-and-solutions-for-plcs-

and-smart-i-os.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32f4x1.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32nucleo.pdf

Flyers https://www.st.com/resource/en/flyer/flstmcsuite.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32trust.pdf

Product https://www.st.com/resource/en/certification\_document/stm32\_authenticat

Certifications ion\_can.pdf

Application Notes https://www.st.com/resource/en/application\_note/an1709-emc-design-

guide-for-stm8-stm32-and-legacy-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an2606-stm32-

microcontroller-system-memory-boot-mode-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an2639-soldering-

- recommendations-and-package-information-for-leadfree-ecopack-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an2945-stm8s-and-stm32-mcus-a-consistent-832bit-product-line-for-painless-migration-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3070-managing-the-driver-enable-signal-for-rs485-and-iolink-communications-with-the-stm32s-usart-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3126-audio-and-waveform-generation-using-the-dac-in-stm32-products-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3154-can-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3155-usart-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3156-usb-dfu-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3364-migration-and-compatibility-guidelines-for-stm32-microcontroller-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3997-audio-playback-and-recording-using-the-stm32f4discovery-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3998-pdm-audio-software-decoding-on-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4031-using-the-stm32f2-stm32f4-and-stm32f7-series-dma-controller-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4221-i2c-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4229-how-to-implement-a-vocoder-solution-using-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4286-spi-protocol-

- used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4488-getting-started-with-stm32f4xxxx-mcu-hardware-development-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4566-extending-the-dac-performance-of-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4616-migrating-from-stm32f401-and-stm32f411-lines-to-stm32l4-series-and-stm32l4-series-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4646-peripheral-interconnections-on-stm32f401-and-stm32f411-lines-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4655-virtually-increasing-the-number-of-serial-communication-peripherals-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4739-stm32cube-firmware-examples-for-stm32f4-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4750-handling-of-soft-errors-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4776-generalpurpose-timer-cookbook-for-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4803-highspeed-si-simulations-using-ibis-and-boardlevel-simulations-using-hyperlynx-si-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4850-stm32-mcusspreadspectrum-clock-generation-principles-properties-andimplementation-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4904-migration-of-microcontroller-applications-from-stm32f1-series-to-stm32f4-access-lines-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4989-stm32-microcontroller-debug-toolbox-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4995-using-anelectromyogram-technique-to-detect-muscle-activity-

- stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5027-interfacing-pdm-digital-microphones-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5073-receiving-spdif-audio-stream-with-the-stm32f4f7h7-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4899-stm32-microcontroller-gpio-hardware-settings-and-lowpower-consumption-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5612-esd-protection-of-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4838-introduction-to-memory-protection-unit-management-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5852-migrating-from-stm32f401-stm32f410-and-stm32f411-to-stm32h503-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4879-introduction-to-usb-hardware-and-pcb-guidelines-using-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5225-introduction-to-usb-typec-power-delivery-for-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an2834-how-to-optimize-the-adc-accuracy-in-the-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5537-how-to-use-adcoversampling-techniques-to-improve-signaltonoise-ratio-on-stm32-mcusstmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5036-guidelines-for-thermal-management-on-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4230-introduction-to-random-number-generation-validation-using-the-nist-statistical-test-suite-for-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an2867-guidelines-for-

oscillator-design-on-stm8afals-and-stm32-mcusmpusstmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4013-introduction-to-timers-for-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4277-how-to-use-pwm-shutdown-for-motor-control-and-digital-power-conversion-on-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4759-introduction-to-using-the-hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4908-getting-startedwith-usart-automatic-baud-rater-detection-for-stm32-mcusstmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5156-introduction-to-security-for-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5543-guidelines-for-enhanced-spi-communication-on-stm32-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an1202\_freertos\_guide-for related Tools freertos-guide-stmicroelectronics.pdf
& Software

Application Notes https://www.st.com/resource/en/application\_note/an1602\_semihosting\_in for related Tools \_truestudio-how-to-do-semihosting-in-truestudio-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an1801\_stm32cubeprog for related Tools rammer\_in\_truestudio-installing-stm32cubeprogrammer-in-truestudio-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/atollic\_editing\_keyboard for related Tools \_shortcuts-atollic-editing-keyboard-shortcuts-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/stm32cubemx\_installatio

for related Tools n\_in\_truestudio-stm32cubemx-installation-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an2656-stm32f10xxx-

& Software

Application Notes https://www.st.com/resource/en/application\_note/an2790-tft-lcd-

for related Tools interfacing-with-the-highdensity-stm32f10xxx-fsmc-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3078-stm32-for related Tools inapplication-programming-over-the-ic-bus-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3116-stm32s-adc-

for related Tools modes-and-their-applications-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3174-implementing-for related Tools receivers-for-infrared-remote-control-protocols-using-stm32f10xxx-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an3241-qvga-tftlcd-for related Tools direct-drive-using-the-stm32f10xx-fsmc-peripheral-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3307-guidelines-for-for related Tools obtaining-iec-60335-class-b-certification-for-any-stm32-application-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an3965-

for related Tools stm32f40xstm32f41x-inapplication-programming-using-the-usart-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an3969-eeprom-

for related Tools emulation-in-stm32f40xstm32f41x-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4044-floating-point-for related Tools unit-demonstration-on-stm32-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4323-getting-started-

for related Tools with-stemwin-library-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4365-using-stm32f4-for related Tools mcu-power-modes-with-best-dynamic-efficiency-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4435-guidelines-for-for-related Tools obtaining-ulcsaiec-607301603351-class-b-certification-in-any-stm32-

& Software application-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4457-implementing-for related Tools an-emulated-uart-on-stm32f4-microcontrollers-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4499-stm32-for related Tools nrf51822-bluetooth-low-energy-system-solution-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4515-using-batch-for related Tools acquisition-mode-bam-to-maximize-power-efficiency-on-stm32f410-stm32f411-stm32f412-stm32f413-microcontroller-lines-

stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4657-stm32-for related Tools inapplication-programming-iap-using-the-usart-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4666-parallel-for related Tools synchronous-transmission-using-gpio-and-dma-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4678-full-duplex-spifor related Tools emulation-for-stm32f4-microcontrollers-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4701-proprietary-for related Tools code-readout-protection-on-microcontrollers-of-the-stm32f4-series-& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4739-stm32cube-for related Tools firmware-examples-for-stm32f4-series-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4758-proprietary-for related Tools code-readout-protection-on-stm32l4-stm32l4-stm32g4-and-stm32wb-

& Software series-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4841-digital-signal-for related Tools processing-for-stm32-microcontrollers-using-cmsis-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4968-proprietary-for related Tools code-read-out-protection-pcrop-on-stm32f72xxx-and-stm32f73xxx-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5056-integration-

for related Tools guide-for-the-xcubesbsfu-stm32cube-expansion-package-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5360-getting-started-

for related Tools with-projects-based-on-the-stm32mp1-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5361-getting-started-

for related Tools with-projects-based-on-dualcore-stm32h7-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5394-getting-started-

for related Tools with-projects-based-on-the-stm32l5-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5418-how-to-build-a-for related Tools simple-usbpd-sink-application-with-stm32cubemx-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an5426-migrating-for related Tools graphics-middleware-projects-from-stm32cubemx-540-to-stm32cubemx-

& Software 550-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5464-position-control-

for related Tools of-a-threephase-permanent-magnet-motor-using-xcubemcsdk-or-

& Software xcubemcsdkful-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5564-getting-started-

for related Tools with-projects-based-on-dualcore-stm32wl-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5698-adapting-the-for related Tools xcubestl-functional-safety-package-for-stm32-iec-61508-compliant-to-

& Software other-safety-standards-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5731-stm32cubemx-for related Tools and-stm32cubeide-threadsafe-solution-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4502-stm32-

for related Tools smbuspmbus-expansion-package-for-stm32cube-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an5952-how-to-use-for related Tools cmake-in-stm32cubeide-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an5054-how-to-perform-for related Tools secure-programming-using-stm32cubeprogrammer-stmicroelectronics.pdf

& Software

Design Notes & https://www.st.com/resource/en/design\_tip/dt0088-fir-filter-design-by-

Tips sampling-windowing-and-modulating-the-sinc-function-

stmicroelectronics.pdf

Design Notes & https://www.st.com/resource/en/design\_tip/dt0089-the-goertzel-algorithm-

Tips to-compute-individual-terms-of-the-discrete-fourier-transform-dft-

stmicroelectronics.pdf

Design Notes & https://www.st.com/resource/en/design\_tip/dt0091-lattice-wave-digital-

Tips filter-design-and-automatic-c-code-generation-stmicroelectronics.pdf

Design Notes & https://www.st.com/resource/en/design\_tip/dt0092-lattice-wave-digital-

Tips filter-test-and-performance-verification-stmicroelectronics.pdf

Device Option https://www.st.com/resource/en/device option list/opl stm32f411 512k.zi

Lists p

Errata Sheets https://www.st.com/resource/en/errata\_sheet/es0287-stm32f411xcxe-

device-errata-stmicroelectronics.pdf

Datasheet https://www.st.com/resource/en/datasheet/dm00115249.pdf

Programming https://www.st.com/resource/en/programming\_manual/pm0214-stm32-

Manuals cortexm4-mcus-and-mpus-programming-manual-stmicroelectronics.pdf

Reference https://www.st.com/resource/en/reference\_manual/rm0383-

Manuals stm32f411xce-advanced-armbased-32bit-mcus-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn0516-overview-of-the-

& Articles stm32f0xf100xxf103xx-and-stm32f2xxf30xf4xx-mcus-pmsm-singledual-

foc-sdk-v40-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1163-description-of-

& Articles wlcsp-for-microcontrollers-and-recommendations-for-its-use-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1204-tape-and-reel-

& Articles shipping-media-for-stm32-microcontrollers-in-bga-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1205-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-fpn-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1206-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-qfp-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1207-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-so-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1208-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-tssop-and-ssop-

packages-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1433-reference-device-

& Articles marking-schematics-for-stm32-microcontrollers-and-microprocessors-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical note/tn1489-security-bulletin-

& Articles tn1489stpsirt-physical-attacks-on-stm32-and-stm32cube-firmware-

stmicroelectronics.pdf