Diango Jango deploy



План

разделение настроек проекта uwsgi, nginx деплоймент управление статикой страницы 404, 500



https://docs.djangoproject.com/en/1.7/topics/ settings/

https://docs.djangoproject.com/en/1.7/howto/deployment/checklist/#critical-settings



settings

local_settings.py

SECRET KEY DEBUG, TEMPLATE_DEBUG ALLOWED HOSTS ADMINS, MANAGERS EMAIL BACKEND EMAIL_HOST, EMAIL_PORT, EMAIL_... DATABASES, CACHES, LOGGING MEDIA ROOT, STATIC ROOT



settings

local_settings.py

```
SECRET_KEY = 'real secret key'

DEBUG = False

TEMPLATE_DEBUG = DEBUG

ALLOWED_HOSTS = ['your-site.com']
```

settings.py

try:

from local_settings import *
except ImportError:
print "Warning! local_settings are not defined!"



https://docs.djangoproject.com/en/ 1.7/howto/deployment/



https://uwsgi.readthedocs.org/en/latest/tutorials/Django and nginx.html



uwsgi

pip install uwsgi

python manage.py runserver to

uwsgi --http:8000 --module pybursa.wsgi

touch uwsgi.ini

uwsgi --ini uwsgi.ini



http://wiki.nginx.org/Main

http://nginx.org/ru/docs/



nginx

sudo apt-get install nginx

nano /usr/local/etc/nginx/nginx.conf

nginx nginx -s stop



nginx

```
server {
  listen
        8002;
  server_name 127.0.0.1;
  charset utf-8;
  client_max_body_size 75M; # adjust to taste
  location/media {
    alias /Users/dixon/Documents/pybusa/11/pybursa/
media;}
  location /static {
    alias /Users/dixon/Documents/pybusa/11/pybursa/
static;}
  location / {
     proxy_pass http://127.0.0.1:8001;}
```

https://docs.djangoproject.com/en/ 1.7/howto/deployment/wsgi/ modwsgi/#serving-files

https://docs.djangoproject.com/en/ 1.7/ref/contrib/staticfiles/



static files

STATIC_URL = '/static/'

STATIC_ROOT = os.path.join(BASE_DIR, 'static_files')

STATICFILES_FINDERS = \
 ("django.contrib.staticfiles.finders.FileSystemFinder",
 "django.contrib.staticfiles.finders.AppDirectoriesFinder")

STATICFILES_DIRS = (os.path.join(BASE_DIR, 'static'),)

python manage.py collectstatic



https://docs.djangoproject.com/ en/1.7/ref/views/

https://docs.djangoproject.com/en/1.7/ref/urls/#handler400



404 500 views

Eсли DEBUG равен False, то вместо страниц с трейсом ошибки рендерятся соответствующие шаблоны:

400.html

403.html

404.html

500.html

handler400 = 'django.views.defaults.bad_request'

handler403 = 'django.views.defaults.permission_denied'

handler404 = 'django.views.defaults.page_not_found'

handler500 = 'django.views.defaults.server_error'

handler404 = 'pybursa.views.handler404'

