

Isso é CS50

Introdução do CS50 à Ciência da Computação

OpenCourseWare

Doar  (<https://cs50.harvard.edu/donate>)

David J. Malan (<https://cs.harvard.edu/malan/>)

malan@harvard.edu

 (<https://www.clubhouse.com/@davidjmalan>)  (<https://www.facebook.com/dmalan>) 

(<https://github.com/dmalan>)  (<https://www.instagram.com/davidjmalan/>) 

(<https://www.linkedin.com/in/malan/>)  (<https://orcid.org/0000-0001-5338-2522>) 

(<https://www.quora.com/profile/David-J-Malan>)  (<https://www.reddit.com/user/davidjmalan>) 

(<https://www.tiktok.com/@davidjmalan>)  (<https://davidjmalan.t.me/>) 

(<https://twitter.com/davidjmalan>)

Speller

Be sure to read this specification in its entirety before starting so you know what to do and how to do it!

For this problem, you'll implement a program that spell-checks a file, a la the below, using a hash table.

```
$ ./speller texts/lalaland.txt
MISSPELLED WORDS

[...]
AAAAAAAAAAAAAAAAAAAAAAAAAAAAHT
[...]
Shangri
[...]
fianc
[...]
Sebastian's
[...]

WORDS MISSPELLED:
WORDS IN DICTIONARY:
WORDS IN TEXT:
TIME IN load:
TIME IN check:
TIME IN size:
TIME IN unload:
TIME IN TOTAL:
```

Getting Started

Log into [code.cs50.io \(https://code.cs50.io/\)](https://code.cs50.io), click on your terminal window, and execute `cd` by itself. You should find that your terminal window's prompt resembles the below:

```
$
```

Next execute

```
wget https://cdn.cs50.net/2022/fall/psets/5/speller.zip
```

in order to download a ZIP called `speller.zip` into your codespace.

Then execute

```
unzip speller.zip
```

to create a folder called `speller`. You no longer need the ZIP file, so you can execute

```
rm speller.zip
```

and respond with “y” followed by Enter at the prompt to remove the ZIP file you downloaded.

Now type

```
cd speller
```

followed by Enter to move yourself into (i.e., open) that directory. Your prompt should now resemble the below.

```
speller/ $
```

Execute `ls` by itself, and you should see a few files and folders:

```
dictionaries/ dictionary.c dictionary.h keys/ Makefile speller.c speller50 texts/
```

If you run into any trouble, follow these same steps again and see if you can determine where you went wrong!

Distribution

Understanding

Theoretically, on input of size n , an algorithm with a running time of n is “asymptotically equivalent,” in terms of O , to an algorithm with a running time of $2n$. Indeed, when describing the running time of an algorithm, we typically focus on the dominant (i.e., most impactful) term (i.e., n in this case, since n could be much larger than 2). In the real world, though, the fact of the matter is that $2n$ feels twice as slow as n .

The challenge ahead of you is to implement the fastest spell checker you can! By “fastest,” though, we’re talking actual “wall-clock,” not asymptotic, time.

In `speller.c`, we’ve put together a program that’s designed to spell-check a file after loading a dictionary of words from disk into memory. That dictionary, meanwhile, is implemented in a file called `dictionary.c`. (It could just be implemented in `speller.c`, but as programs get more complex, it’s often convenient to break them into multiple files.) The prototypes for the functions therein, meanwhile, are defined not in `dictionary.c` itself but in `dictionary.h` instead. That way, both `speller.c` and `dictionary.c` can `#include` the file. Unfortunately, we didn’t quite get around to implementing the loading part. Or the checking part. Both (and a bit more) we leave to you! But first, a tour.

dictionary.h

Open up `dictionary.h`, and you’ll see some new syntax, including a few lines that mention `DICTIONARY_H`. No need to worry about those, but, if curious, those lines just ensure that, even though `dictionary.c` and `speller.c` (which you’ll see in a moment) `#include` this file, `clang` will only compile it once.

Next notice how we `#include` a file called `stdbool.h`. That’s the file in which `bool` itself is defined. You’ve not needed it before, since the CS50 Library used to `#include` that for you.

Also notice our use of `#define`, a “preprocessor directive” that defines a “constant” called `LENGTH` that has a value of `45`. It’s a constant in the sense that you can’t (accidentally) change it in your own code. In fact, `clang` will replace any mentions of `LENGTH` in your own code with, literally, `45`. In other words, it’s not a variable, just a find-and-replace trick.

Finally, notice the prototypes for five functions: `check`, `hash`, `load`, `size`, and `unload`. Notice how three of those take a pointer as an argument, per the `*`:

```
bool check(const char *word);
unsigned int hash(const char *word);
bool load(const char *dictionary);
```

Recall that `char *` is what we used to call `string`. So those three prototypes are essentially just:

```
bool check(const string word);
unsigned int hash(const string word);
bool load(const string dictionary);
```

And `const`, meanwhile, just says that those strings, when passed in as arguments, must remain constant; you won’t be able to change them, accidentally or otherwise!

dictionary.c

Now open up `dictionary.c`. Notice how, atop the file, we’ve defined a `struct` called `node` that represents a node in a hash table. And we’ve declared a global pointer array, `table`, which will (soon) represent the hash table you will use to keep track of words in the dictionary. The array contains `N` node pointers, and we’ve set `N` equal to `26` for now, to match with the default `hash` function as described below. You will likely want to increase this depending on your own implementation of `hash`.

Next, notice that we’ve implemented `load`, `check`, `size`, and `unload`, but only barely, just enough for the code to compile. Notice too that we’ve implemented `hash` with a sample algorithm based on the first letter

of the word. Your job, ultimately, is to re-implement those functions as cleverly as possible so that this spell checker works as advertised. And fast!

speller.c

Okay, next open up `speller.c` and spend some time looking over the code and comments therein. You won't need to change anything in this file, and you don't need to understand its entirety, but do try to get a sense of its functionality nonetheless. Notice how, by way of a function called `getrusage`, we'll be "benchmarking" (i.e., timing the execution of) your implementations of `check`, `load`, `size`, and `unload`. Also notice how we go about passing `check`, word by word, the contents of some file to be spell-checked. Ultimately, we report each misspelling in that file along with a bunch of statistics.

Notice, incidentally, that we have defined the usage of `speller` to be

```
Usage: speller [dictionary] text
```

where `dictionary` is assumed to be a file containing a list of lowercase words, one per line, and `text` is a file to be spell-checked. As the brackets suggest, provision of `dictionary` is optional; if this argument is omitted, `speller` will use `dictionaries/large` by default. In other words, running

```
./speller text
```

will be equivalent to running

```
./speller dictionaries/large text
```

where `text` is the file you wish to spell-check. Suffice it to say, the former is easier to type! (Of course, `speller` will not be able to load any dictionaries until you implement `load` in `dictionary.c`! Until then, you'll see `Could not load`.)

Within the default dictionary, mind you, are 143,091 words, all of which must be loaded into memory! In fact, take a peek at that file to get a sense of its structure and size. Notice that every word in that file appears in lowercase (even, for simplicity, proper nouns and acronyms). From top to bottom, the file is sorted lexicographically, with only one word per line (each of which ends with `\n`). No word is longer than 45 characters, and no word appears more than once. During development, you may find it helpful to provide `speller` with a `dictionary` of your own that contains far fewer words, lest you struggle to debug an otherwise enormous structure in memory. In `dictionaries/small` is one such dictionary. To use it, execute

```
./speller dictionaries/small text
```

where `text` is the file you wish to spell-check. Don't move on until you're sure you understand how `speller` itself works!

Odds are, you didn't spend enough time looking over `speller.c`. Go back one square and walk yourself through it again!

texts/

So that you can test your implementation of `speller`, we've also provided you with a whole bunch of texts, among them the script from *La La Land*, the text of the Affordable Care Act, three million bytes from Tolstoy,

some excerpts from *The Federalist Papers* and Shakespeare, and more. So that you know what to expect, open and skim each of those files, all of which are in a directory called `texts` within your `pset5` directory.

Now, as you should know from having read over `speller.c` carefully, the output of `speller`, if executed with, say,

```
./speller texts/lalaland.txt
```

will eventually resemble the below.

Below's some of the output you'll see. For information's sake, we've excerpted some examples of "misspellings." And lest we spoil the fun, we've omitted our own statistics for now.

```
MISSPELLED WORDS

[...]
AHHHHHHHHHHHHHHHHHHHHHHHHHHHHHT
[...]
Shangri
[...]
fianc
[...]
Sebastian's
[...]

WORDS MISSPELLED:
WORDS IN DICTIONARY:
WORDS IN TEXT:
TIME IN load:
TIME IN check:
TIME IN size:
TIME IN unload:
TIME IN TOTAL:
```

`TIME IN load` represents the number of seconds that `speller` spends executing your implementation of `load`. `TIME IN check` represents the number of seconds that `speller` spends, in total, executing your implementation of `check`. `TIME IN size` represents the number of seconds that `speller` spends executing your implementation of `size`. `TIME IN unload` represents the number of seconds that `speller` spends executing your implementation of `unload`. `TIME IN TOTAL` is the sum of those four measurements.

Note that these times may vary somewhat across executions of `speller`, depending on what else your codespace is doing, even if you don't change your code.

Incidentally, to be clear, by "misspelled" we simply mean that some word is not in the `dictionary` provided.

Makefile

And, lastly, recall that `make` automates compilation of your code so that you don't have to execute `clang` manually along with a whole bunch of switches. However, as your programs grow in size, `make` won't be able to infer from context anymore how to compile your code; you'll need to start telling `make` how to compile your program, particularly when they involve multiple source (i.e., `.c`) files, as in the case of this problem. And so we'll utilize a `Makefile`, a configuration file that tells `make` exactly what to do. Open up `Makefile`, and you should see four lines:

1. The first line tells `make` to execute the subsequent lines whenever you yourself execute `make speller` (or just `make`).

2. The second line tells `make` how to compile `speller.c` into machine code (i.e., `speller.o`).
3. The third line tells `make` how to compile `dictionary.c` into machine code (i.e., `dictionary.o`).
4. The fourth line tells `make` to link `speller.o` and `dictionary.o` in a file called `speller`.

Be sure to compile `speller` by executing `make speller` (or just `make`). Executing `make dictionary` won't work!

Specification

Alright, the challenge now before you is to implement, in order, `load`, `hash`, `size`, `check`, and `unload` as efficiently as possible using a hash table in such a way that `TIME IN load`, `TIME IN check`, `TIME IN size`, and `TIME IN unload` are all minimized. To be sure, it's not obvious what it even means to be minimized, inasmuch as these benchmarks will certainly vary as you feed `speller` different values for `dictionary` and for `text`. But therein lies the challenge, if not the fun, of this problem. This problem is your chance to design. Although we invite you to minimize space, your ultimate enemy is time. But before you dive in, some specifications from us.

- You may not alter `speller.c` or `Makefile`.
- You may alter `dictionary.c` (and, in fact, must in order to complete the implementations of `load`, `hash`, `size`, `check`, and `unload`), but you may not alter the declarations (i.e., prototypes) of `load`, `hash`, `size`, `check`, or `unload`. You may, though, add new functions and (local or global) variables to `dictionary.c`.
- You may change the value of `N` in `dictionary.c`, so that your hash table can have more buckets.
- You may alter `dictionary.h`, but you may not alter the declarations of `load`, `hash`, `size`, `check`, or `unload`.
- Your implementation of `check` must be case-insensitive. In other words, if `foo` is in dictionary, then `check` should return true given any capitalization thereof; none of `foo`, `fo0`, `f0o`, `f00`, `f0O`, `Foo`, `Fo0`, `F0o`, and `F00` should be considered misspelled.
- Capitalization aside, your implementation of `check` should only return `true` for words actually in `dictionary`. Beware hard-coding common words (e.g., `the`), lest we pass your implementation a `dictionary` without those same words. Moreover, the only possessives allowed are those actually in `dictionary`. In other words, even if `foo` is in `dictionary`, `check` should return `false` given `foo's` if `foo's` is not also in `dictionary`.
- You may assume that any `dictionary` passed to your program will be structured exactly like ours, alphabetically sorted from top to bottom with one word per line, each of which ends with `\n`. You may also assume that `dictionary` will contain at least one word, that no word will be longer than `LENGTH` (a constant defined in `dictionary.h`) characters, that no word will appear more than once, that each word will contain only lowercase alphabetical characters and possibly apostrophes, and that no word will start with an apostrophe.
- You may assume that `check` will only be passed words that contain (uppercase or lowercase) alphabetical characters and possibly apostrophes.
- Your spell checker may only take `text` and, optionally, `dictionary` as input. Although you might be inclined (particularly if among those more comfortable) to “pre-process” our default dictionary in order to derive an “ideal hash function” for it, you may not save the output of any such pre-processing to disk in order to load it back into memory on subsequent runs of your spell checker in order to gain an advantage.
- Your spell checker must not leak any memory. Be sure to check for leaks with `valgrind`.

- **The hash function you write should ultimately be your own, not one you search for online.** There are many ways to implement a hash function beyond using the first character (or characters) of a word. Consider a hash function that uses a sum of ASCII values or the length of a word. A good hash function tends to reduce “collisions” and has a fairly even distribution across hash table “buckets”.

Alright, ready to go?

- Implement `load`.
- Implement `hash`.
- Implement `size`.
- Implement `check`.
- Implement `unload`.

Walkthroughs

Note that there are 6 videos in the below playlist.

Though Speller’s walkthrough indicates it is reasonable to use a hash function found online, this video is from an older version of the problem where we allowed this. Per the specification above, the hash function you write should ultimately be your own; you **may not** use a hash function you find online. Be sure to cite any external sources you referenced in writing your hash function.

speller - CS50 Walkthroughs 2019



Hints

To compare two strings case-insensitively, you may find `strcasecmp` (<https://man.cs50.io/3/strcasecmp>) (declared in `strings.h`) useful! You’ll likely also want to ensure that your hash function is case-insensitive, such that `foo` and `FOO` have the same hash value.

Ultimately, be sure to `free` in `unload` any memory that you allocated in `load`! Recall that `valgrind` is your newest best friend. Know that `valgrind` watches for leaks while your program is actually running, so be sure to provide command-line arguments if you want `valgrind` to analyze `speller` while you use a particular `dictionary` and/or text, as in the below. Best to use a small text, though, else `valgrind` could take quite a while to run.

```
valgrind ./speller texts/cat.txt
```

If you run `valgrind` without specifying a `text` for `speller`, your implementations of `load` and `unload` won't actually get called (and thus analyzed).

If unsure how to interpret the output of `valgrind`, do just ask `help50` for help:

```
help50 valgrind ./speller texts/cat.txt
```

Testing

How to check whether your program is outting the right misspelled words? Well, you're welcome to consult the "answer keys" that are inside of the `keys` directory that's inside of your `speller` directory. For instance, inside of `keys/lalaland.txt` are all of the words that your program *should* think are misspelled.

You could therefore run your program on some text in one window, as with the below.

```
./speller texts/lalaland.txt
```

And you could then run the staff's solution on the same text in another window, as with the below.

```
./speller50 texts/lalaland.txt
```

And you could then compare the windows visually side by side. That could get tedious quickly, though. So you might instead want to "redirect" your program's output to a file, as with the below.

```
./speller texts/lalaland.txt > student.txt  
./speller50 texts/lalaland.txt > staff.txt
```

You can then compare both files side by side in the same window with a program like `diff`, as with the below.

```
diff -y student.txt staff.txt
```

Como alternativa, para economizar tempo, você pode apenas comparar a saída do seu programa (supondo que você o redirecionou para, por exemplo, `student.txt`) com uma das chaves de resposta sem executar a solução da equipe, como abaixo.

```
diff -y student.txt keys/lalaland.txt
```

Se a saída do seu programa corresponder à da pauta, `diff` serão exibidas duas colunas que devem ser idênticas, exceto, talvez, os tempos de execução na parte inferior. Porém, se as colunas forem diferentes, você verá um `>` ou `|` onde elas diferem. Por exemplo, se você ver

MISSPELLED WORDS	MISSPELLED WORDS
TECHNO	TECHNO
L	L
Prius	> Thelonious
	Prius
	> MIA
L	L

isso significa que seu programa (cuja saída está à esquerda) não pensa isso `Thelonious` ou `MIA` está com erros ortográficos, mesmo que a saída da pauta (à direita) pense, como está implícito na ausência de, digamos, `Thelonious` na coluna da esquerda e na presença de `Thelonious` na coluna da direita.

check50

Para testar seu código menos manualmente (embora ainda não exaustivamente), você também pode executar o seguinte.

```
check50 cs50/problems/2023/x/speller
```

Observe que `check50` também verificará se há vazamentos de memória, portanto, certifique-se de executar `valgrind` também.

estilo50

Execute o abaixo para avaliar o estilo do seu código usando `style50`.

```
style50 dictionary.c
```

Solução da equipe

Como avaliar o quão rápido (e correto) é o seu código? Bem, como sempre, sintá-se à vontade para brincar com a solução da equipe, como abaixo, e comparar seus números com os seus.

```
./speller50 texts/lalaland.txt
```

Como enviar

Em seu terminal, execute o abaixo para enviar seu trabalho.

```
submit50 cs50/problems/2023/x/speller
```

