

AlphaPaaS Approved Services Catalog

Reference: ASC · Version 5.3 · Effective 1 March 2026

Document owner	AlphaPaaS Cloud Broker — Architecture Governance
Approved by	AlphaInsure Group Architecture Board
Review cycle	Quarterly
Previous version	5.2 (December 2025)
Classification	Internal
Related standards	AHS, CKS, FIN, DCH

1. Purpose and scope

This catalog lists cloud services approved for use by AlphaInsure applications. Approval signifies that the service has completed security review, has an accepted private-connectivity pattern, and has a named Cloud Broker operational owner.

Services not listed in this catalog are not approved and **MUST NOT** be used in production. Requests for new services are submitted via the Cloud Broker service desk and reviewed quarterly.

2. Universal requirements

ASC-01	Only services listed in sections 3 and 4 of this catalog MAY be used for production workloads. Services listed in section 6 (not approved) MUST NOT be used for any environment.
ASC-02	All services MUST be provisioned in approved regions. Approved regions are EU-West, EU-Central, EU-North, and their Azure equivalents (West Europe, North Europe). Use of non-EU regions for EU data is prohibited.
ASC-03	Services MUST be consumed via private connectivity. Public endpoints MUST be disabled where the service supports disablement, and traffic MUST route through VPC endpoints, PrivateLink, Private Endpoints, or vWAN Hub as appropriate.
ASC-04	Services MUST encrypt data at rest. For Restricted data (see DCH), encryption MUST use a customer-managed key (CMK). For other classifications, a platform-managed key is acceptable.
ASC-05	Services MUST enforce encryption in transit using TLS 1.2 or higher. TLS 1.0 and 1.1 MUST be disabled. Plain-text protocols MUST NOT be exposed.
ASC-06	Services accessed by AlphaPaaS workloads MUST authenticate using workload identity (IAM roles assumed via OIDC, Azure managed identities). Long-lived credentials stored in secrets are prohibited.

3. Approved AWS services

Service	Approved tiers	Connectivity	Key requirements
RDS PostgreSQL / MySQL	All	Private subnet, no public access	KMS CMK for Restricted; Multi-AZ for Silver+; backup retention per ARS-15

Service	Approved tiers	Connectivity	Key requirements
Aurora PostgreSQL	All	Private subnet, no public access	KMS CMK; Multi-AZ for Silver+; backup per ARS-15
ElastiCache Redis	All	Private subnet, VPC only	TLS-in-transit required from Silver+; Multi-AZ for Silver+; AUTH token required
EFS	All	VPC mount targets, or assume-role pattern for cross-account	KMS encryption; FileSystem policy restricting principals; Multi-AZ mount targets
S3	All	VPC endpoint required for AlphaPaaS access	Default encryption (KMS for Restricted); Block Public Access; bucket policy restricting to VPC endpoint
ECR	All	VPC endpoint for pulls from within VPC	Image scanning enabled; tag immutability; KMS encryption
Secrets Manager	All	VPC endpoint	KMS CMK; automatic rotation enabled for Silver+; resource policy scoping access
Lambda	All	VPC-attached for private resources	Reserved concurrency documented; dead-letter queue required; IAM role least-privilege
SQS / SNS	All	VPC endpoints	KMS CMK for Restricted; DLQ for SQS; encryption-in-transit enforced
KMS	All	Regional service, no private endpoint required	CMK with automatic rotation; key policies scoped to consumer roles
CloudWatch Logs	All	VPC endpoint	KMS CMK for Restricted; retention per FIN-16

4. Approved Azure services

Service	Approved tiers	Connectivity	Key requirements
Azure Database for PostgreSQL Flexible Server	All	Private Endpoint required	Zone-redundant HA required for Silver+ (ARS-18); Public access DISABLED; TLS 1.2+ enforced; CMK via Key Vault for Restricted
Azure Database for MySQL Flexible Server	All	Private Endpoint required	Zone-redundant HA required for Silver+; Public access disabled
Azure Cache for Redis	All	Private Endpoint required	TLS-only access (non-SSL port disabled); AAD authentication preferred over access keys
Azure Files	All	Private Endpoint required	SMB 3.1.1; AES-128-GCM encryption; NTLM v2; Storage Account firewall set to 'Selected networks'
Azure Key Vault	All	Private Endpoint required	RBAC authorization model required (access policies deprecated); soft-delete + purge protection enabled; firewall restricting network access

Service	Approved tiers	Connectivity	Key requirements
Azure Storage (Blob)	All	Private Endpoint required	'Secure transfer required' enabled; minimum TLS 1.2; firewall set to 'Selected networks'; CMK for Restricted
Azure Container Registry	All	Private Endpoint required	Vulnerability scanning enabled; content trust / image signing for Silver+; dedicated service principal for pulls
Azure Functions	All	VNet integration for private resources	Always-on for production workloads; managed identity for service access
Azure Service Bus	All	Private Endpoint required	'Local authentication' disabled where supported; AAD authentication; TLS 1.2+ enforced
Azure Monitor / Log Analytics	All	Private Link scope for queries	CMK for workspace; retention per FIN-16

5. Cross-CSP connectivity

Cross-CSP service consumption is supported via the AlphaInsure vWAN Hub and dedicated interconnects. The following patterns are approved:

ASC-07 AWS-hosted AlphaPaaS workloads consuming Azure services MUST route via the vWAN Hub, resolving target FQDNs through AlphaPaaS private DNS zones that map to the service's Private Endpoint. Direct public-internet consumption is prohibited (see AHS-16).

ASC-08 Azure-hosted AlphaPaaS workloads consuming AWS services MUST route via the vWAN Hub and consume the service via a VPC endpoint in the OpenPaaS landing zone, or via the assume-role / Private Link pattern documented by the Cloud Broker.

6. Services not approved

The following services are explicitly not approved. Use requires a Cloud Broker waiver and Group Security sign-off.

Service	Reason
Amazon DynamoDB	Data residency controls insufficient for Restricted data; alternative: RDS / Aurora
Amazon SES	Outbound email must route via AlphaInsure managed email gateway
Azure Cosmos DB (serverless / public)	Public endpoint cannot be fully disabled for serverless tier; alternative: Cosmos DB with Private Endpoint or PostgreSQL Flex
Azure Storage (public blob)	Public blob access contravenes ASC-03; use private endpoints
Any service in a non-EU region	Contravenes ASC-02; applies even if the resource is empty or unused
Marketplace SaaS without DPA	No Data Processing Agreement on file; cannot process AlphaInsure data

IMPORTANT — Deprecation

Services marked "deprecated" in the Cloud Broker's quarterly review MUST NOT be used for new deployments. Existing deployments will be given a migration deadline, tracked in the Cloud Broker's technical debt register.

7. Requesting a new service

Requests for services not yet in this catalog are submitted via the Cloud Broker service desk. The review process covers: security assessment, data residency, private connectivity pattern, operational model, cost envelope, and allocation of an operational owner within the Cloud Broker. The review is targeted at six weeks from submission to catalog entry.

8. Related standards

- **AHS** — AlphaPaaS Application Hosting Standard
- **CKS** — AlphaPaaS Container & Kubernetes Security Standard
- **FIN** — AlphaPaaS FinOps & Cloud Cost Standard
- **DCH** — AlphaPaaS Data Classification & Handling Standard