Afrivate API (v1)

Download OpenAPI specification: Download

Afrivate API powers Afrivate's mobile and web platforms, managing user data, orders, carts, and more. Built for security and scalability, it includes features like JWT authentication, product management, order processing, payment integration, and real-time notifications. it ensures a seamless shopping experience

applications

applications_list

AUTHORIZATIONS: > *Bearer*

Responses

200

RESPONSE SCHEMA: application/json

```
Array [
```

id	integer (ID)
user	integer (User)
user_name	string (User name)
opportunity required	integer (Opportunity)
opportunity_title	string (Opportunity title)

status	string (Status) Enum: `"pending"` `"accepted"` `"rejected"`
cover_letter	string (Cover letter)
applied_at	string <date-time> (Applied at)
reviewed_at	string or null <date-time> (Reviewed at)

]

GET /applications/

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
[
  - {
      "id": 0,
      "user": 0,
      "user_name": "string",
      "opportunity": 0,
      "opportunity_title": "string",
      "status": "pending",
      "cover_letter": "string",
      "applied_at": "2019-08-24T14:15:22Z",
      "reviewed_at": "2019-08-24T14:15:22Z"
    }
]
```


applications_create

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

`opportunity` required	integer (Opportunity)
`cover_letter`	string (Cover letter)

Responses

201

RESPONSE SCHEMA: application/json

`id`	integer (ID)
`user`	integer (User)
`user_name`	string (User name)
`opportunity` required	integer (Opportunity)
`opportunity_title`	string (Opportunity title)
`status`	string (Status) Enum: `"pending"` `"accepted"` `"rejected"`
`cover_letter`	string (Cover letter)
`applied_at`	string <date-time> (Applied at)
`reviewed_at`	string or null <date-time> (Reviewed at)

POST `/applications/`

Request samples

Payload

Content type
application/json

Copy

```
{
    "opportunity": 0,
    "cover_letter": "string"
}
```

Response samples

201

Content type
application/json

Copy

```
{
    "id": 0,
    "user": 0,
    "user_name": "string",
    "opportunity": 0,
    "opportunity_title": "string",
    "status": "pending",
    "cover_letter": "string",
    "applied_at": "2019-08-24T14:15:22Z",
    "reviewed_at": "2019-08-24T14:15:22Z"
}
```

---

applications_read

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

id required	string

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)
user	integer (User)
user_name	string (User name)
opportunity required	integer (Opportunity)
opportunity_title	string (Opportunity title)
status	string (Status) Enum: "pending" "accepted" "rejected"
cover_letter	string (Cover letter)
applied_at	string <date-time> (Applied at)
reviewed_at	string or null <date-time> (Reviewed at)

GET /applications/{id}/

Response samples

200

Content type

application/json

Copy

```
{
    "id": 0,
    "user": 0,
    "user_name": "string",
    "opportunity": 0,
    "opportunity_title": "string",
    "status": "pending",
    "cover_letter": "string",
    "applied_at": "2019-08-24T14:15:22Z",
    "reviewed_at": "2019-08-24T14:15:22Z"
}
```


applications_update

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

id required	string

REQUEST BODY SCHEMA: application/json

opportunity required	integer (Opportunity)
cover_letter	string (Cover letter)

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)
user	integer (User)

user_name	string (User name)
opportunity required	integer (Opportunity)
opportunity_title	string (Opportunity title)
status	string (Status) Enum: "pending" "accepted" "rejected"
cover_letter	string (Cover letter)
applied_at	string <date-time> (Applied at)
reviewed_at	string or null <date-time> (Reviewed at)

PUT /applications/{id}/

Request samples

Payload

Content type
application/json

Copy

```
{
    "opportunity": 0,
    "cover_letter": "string"
}
```

Response samples

200

Content type
application/json

Copy

```
{
    "id": 0,
    "user": 0,
    "user_name": "string",
    "opportunity": 0,
    "opportunity_title": "string",
    "status": "pending",
    "cover_letter": "string",
    "applied_at": "2019-08-24T14:15:22Z",
    "reviewed_at": "2019-08-24T14:15:22Z"
}
```


applications_partial_update

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

id required	string

REQUEST BODY SCHEMA: application/json

opportunity required	integer (Opportunity)
cover_letter	string (Cover letter)

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)
user	integer (User)

`user_name`	string (User name)
`opportunity` required	integer (Opportunity)
`opportunity_title`	string (Opportunity title)
`status`	string (Status) Enum: `"pending"` `"accepted"` `"rejected"`
`cover_letter`	string (Cover letter)
`applied_at`	string <date-time> (Applied at)
`reviewed_at`	string or null <date-time> (Reviewed at)

PATCH `/applications/{id}/`

Request samples

Payload

Content type

application/json

Copy

```
{
    "opportunity": 0,
    "cover_letter": "string"
}
```

Response samples

200

Content type

application/json

Copy

```
{
    "id": 0,
    "user": 0,
    "user_name": "string",
    "opportunity": 0,
    "opportunity_title": "string",
    "status": "pending",
    "cover_letter": "string",
    "applied_at": "2019-08-24T14:15:22Z",
    "reviewed_at": "2019-08-24T14:15:22Z"
}
```


applications_delete

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

id required	string

Responses

— 204

DELETE /applications/{id}/

applications_change_status

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

id required	string

REQUEST BODY SCHEMA: application/json

opportunity required	integer (Opportunity)
cover_letter	string (Cover letter)

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)
user	integer (User)
user_name	string (User name)
opportunity required	integer (Opportunity)
opportunity_title	string (Opportunity title)
status	string (Status) Enum: "pending" "accepted" "rejected"
cover_letter	string (Cover letter)
applied_at	string <date-time> (Applied at)
reviewed_at	string or null <date-time> (Reviewed at)

PATCH /applications/{id}/change_status/

Request samples

Payload

Content type

application/json

Copy

```
{
    "opportunity": 0,
    "cover_letter": "string"
}
```

Response samples

200

Content type

application/json

Copy

```
{
    "id": 0,
    "user": 0,
    "user_name": "string",
    "opportunity": 0,
    "opportunity_title": "string",
    "status": "pending",
    "cover_letter": "string",
    "applied_at": "2019-08-24T14:15:22Z",
    "reviewed_at": "2019-08-24T14:15:22Z"
}
```

---

auth

auth_change-password_create

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

old_password required	string (Old password) non-empty
new_password required	string (New password) non-empty
confirm_password required	string (Confirm password) non-empty

Responses

201

RESPONSE SCHEMA: application/json

old_password required	string (Old password) non-empty
new_password required	string (New password) non-empty
confirm_password required	string (Confirm password) non-empty

POST /auth/change-password/

Request samples

Payload

Content type

application/json

Copy

```
{
    "old_password": "string",
    "new_password": "string",
    "confirm_password": "string"
}
```

Response samples

201

Content type
application/json

Copy

```
{
    "old_password": "string",
    "new_password": "string",
    "confirm_password": "string"
}
```

---

auth_forgot-password_create

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

email required	string <email> (Email) non-empty

Responses

201

RESPONSE SCHEMA: application/json

email required	string <email> (Email) non-empty

POST /auth/forgot-password/

Request samples

Payload

Content type
application/json

Copy

```
{
    "email": "user@example.com"
}
```

Response samples

201

Content type
application/json

Copy

```
{
    "email": "user@example.com"
}
```

auth_login_create

Check the credentials and return the REST Token if the credentials are valid and authenticated. Calls Django Auth login method to register User ID in Django session framework

Accept the following POST parameters: username, password Return the REST Framework Token Object's key.

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

`username`	string (Username)
`email`	string <email> (Email)
`password` required	string (Password) non-empty

Responses

201

RESPONSE SCHEMA: application/json

`username`	string (Username)
`email`	string <email> (Email)
`password` required	string (Password) non-empty

POST `/auth/login/`

Request samples

Payload

Content type

application/json

Copy

```
{
    "username": "string",
    "email": "user@example.com",
    "password": "string"
}
```

Response samples

201

Content type
application/json

Copy

```
{
    "username": "string",
    "email": "user@example.com",
    "password": "string"
}
```

Calls Django logout method and delete the Token object assigned to the current User object.

Accepts/Returns nothing.

AUTHORIZATIONS: > *Bearer*

Responses

— 200

GET /auth/logout/

Calls Django logout method and delete the Token object assigned to the current User object.

Accepts/Returns nothing.

AUTHORIZATIONS: > *Bearer*

Responses

— 201

POST /auth/logout/

Calls Django Auth SetPasswordForm save method.

Accepts the following POST parameters: new_password1, new_password2 Returns the success/fail message.

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

new_password1 required	string (New password1) [1 .. 128] characters
new_password2 required	string (New password2) [1 .. 128] characters

Responses

201

RESPONSE SCHEMA: application/json

new_password1 required	string (New password1) [1 .. 128] characters
new_password2 required	string (New password2) [1 .. 128] characters

POST /auth/password/change/

Request samples

Payload

Content type

application/json

Copy

```
{
    "new_password1": "string",
    "new_password2": "string"
}
```

Response samples

201

Content type

application/json

Copy

```
{
    "new_password1": "string",
    "new_password2": "string"
}
```

Calls Django Auth PasswordResetForm save method.

Accepts the following POST parameters: email Returns the success/fail message.

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

email required	string <email> (Email) non-empty

Responses

201

RESPONSE SCHEMA: application/json

email required	string <email> (Email) non-empty

POST /auth/password/reset/

Request samples

Payload

Content type

application/json

Copy

```
{
    "email": "user@example.com"
}
```

Response samples

201

Content type

application/json

Copy

```
{
    "email": "user@example.com"
}
```

Password reset e-mail link is confirmed, therefore this resets the user's password.

Accepts the following POST parameters: token, uid, new_password1, new_password2 Returns the success/fail message.

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

`new_password1` required	string (New password1) [1 .. 128] characters
`new_password2` required	string (New password2) [1 .. 128] characters
`uid` required	string (Uid) non-empty
`token` required	string (Token) non-empty

Responses

201

RESPONSE SCHEMA: application/json

new_password1 required	string (New password1) [1 .. 128] characters
new_password2 required	string (New password2) [1 .. 128] characters
uid required	string (Uid) non-empty
token required	string (Token) non-empty

POST /auth/password/reset/confirm/

Request samples

Payload

Content type

application/json

Copy

```
{
    "new_password1": "string",
    "new_password2": "string",
    "uid": "string",
    "token": "string"
}
```

Response samples

201

Content type

application/json

Copy

```
{
    "new_password1": "string",
    "new_password2": "string",
    "uid": "string",
    "token": "string"
}
```

auth_register_create

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

`username` required	string (Username) [1 .. 150] characters ^[\w.@+-]+$ Required. 150 characters or fewer. Letters, digits and @/./+/-/_ only.
`email` required	string <email> (Email) [1 .. 254] characters
`password` required	string (Password) [1 .. 128] characters
`role`	string (Role) Enum: `"enabler"` `"pathfinder"`
`password2` required	string (Password2) non-empty

Responses

201

RESPONSE SCHEMA: application/json

id	integer (ID)
username required	string (Username) [1 .. 150] characters ^[\w.@+-]+$ Required. 150 characters or fewer. Letters, digits and @/./+/-/_ only.
email required	string <email> (Email) [1 .. 254] characters
password required	string (Password) [1 .. 128] characters
role	string (Role) Enum: "enabler" "pathfinder"
password2 required	string (Password2) non-empty

POST /auth/register/

Request samples

Payload

Content type

application/json

Copy

```
{
    "username": "string",
    "email": "user@example.com",
    "password": "string",
    "role": "enabler",
    "password2": "string"
}
```

Response samples

201

Content type

application/json

Copy

```
{
    "id": 0,
    "username": "string",
    "email": "user@example.com",
    "password": "string",
    "role": "enabler",
    "password2": "string"
}
```

Registers a new user.

Accepts the following POST parameters: username, email, password1, password2.

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

`username` required	string (Username) [1 .. 150] characters
`email` required	string <email> (Email) non-empty
`password1` required	string (Password1) non-empty
`password2` required	string (Password2) non-empty

Responses

201

RESPONSE SCHEMA: application/json

`username` required	string (Username) [1 .. 150] characters
`email` required	string <email> (Email) non-empty
`password1` required	string (Password1) non-empty
`password2` required	string (Password2) non-empty

POST `/auth/registration/`

Request samples

Payload

Content type
application/json

Copy

```
{
    "username": "string",
    "email": "user@example.com",
    "password1": "string",
    "password2": "string"
}
```

Response samples

201

Content type
application/json

Copy

```
{
    "username": "string",
    "email": "user@example.com",
    "password1": "string",
```

```
    "password2": "string"
}
```

Resends another email to an unverified email.

Accepts the following POST parameter: email.

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

email required	string <email> (Email) non-empty

Responses

201

RESPONSE SCHEMA: application/json

email required	string <email> (Email) non-empty

POST /auth/registration/resend-email/

Request samples

Payload

Content type

application/json

Copy

```
{
    "email": "user@example.com"
}
```

Response samples

201

Content type
application/json

Copy

```
{
    "email": "user@example.com"
}
```

Verifies the email associated with the provided key.

Accepts the following POST parameter: key.

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

key required	string (Key) non-empty

Responses

201

RESPONSE SCHEMA: application/json

key required	string (Key) non-empty

POST /auth/registration/verify-email/

Request samples

Payload

Content type
application/json

Copy

```
{
    "key": "string"
}
```

Response samples

201

Content type
application/json

Copy

```
{
    "key": "string"
}
```

auth_token_create

Takes a set of user credentials and returns an access and refresh JSON web token pair to prove the authentication of those credentials.

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

email required	string (Email) non-empty
password required	string (Password) non-empty

Responses

201

RESPONSE SCHEMA: application/json

email required	string (Email) non-empty
password required	string (Password) non-empty

POST /auth/token/

Request samples

Payload

Content type

application/json

Copy

```
{
    "email": "string",
    "password": "string"
}
```

Response samples

201

Content type

application/json

Copy

```
{
    "email": "string",
    "password": "string"
}
```

---

auth_token_refresh_create

Takes a refresh type JSON web token and returns an access type JSON web token if the refresh token is valid.

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

refresh required	string (Refresh) non-empty

Responses

201

RESPONSE SCHEMA: application/json

refresh required	string (Refresh) non-empty
access	string (Access) non-empty

POST /auth/token/refresh/

Request samples

Payload

Content type
application/json

Copy

```
{
    "refresh": "string"
}
```

Response samples

201

Content type
application/json

Copy

```
{
    "refresh": "string",
    "access": "string"
}
```

Reads and updates UserModel fields Accepts GET, PUT, PATCH methods.

Default accepted fields: username, first_name, last_name Default display fields: pk, username, email, first_name, last_name Read-only fields: pk, email

Returns UserModel fields.

AUTHORIZATIONS: > *Bearer*

Responses

200

RESPONSE SCHEMA: application/json

pk	integer (ID)
email	string <email> (Email) non-empty
first_name	string (First name) <= 150 characters
last_name	string (Last name) <= 150 characters

GET /auth/user/

Response samples

200

Content type
application/json

Copy

```
{
    "pk": 0,
    "email": "user@example.com",
    "first_name": "string",
    "last_name": "string"
}
```

Reads and updates UserModel fields Accepts GET, PUT, PATCH methods.

Default accepted fields: username, first_name, last_name Default display fields: pk, username, email, first_name, last_name Read-only fields: pk, email

Returns UserModel fields.

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

`first_name`	string (First name) <= 150 characters
`last_name`	string (Last name) <= 150 characters

Responses

200

RESPONSE SCHEMA: application/json

`pk`	integer (ID)
`email`	string <email> (Email) non-empty
`first_name`	string (First name) <= 150 characters
`last_name`	string (Last name) <= 150 characters

PUT `/auth/user/`

Request samples

Payload

Content type
application/json

Copy

```
{
    "first_name": "string",
    "last_name": "string"
}
```

Response samples

200

Content type
application/json

Copy

```
{
    "pk": 0,
    "email": "user@example.com",
    "first_name": "string",
    "last_name": "string"
}
```

Reads and updates UserModel fields Accepts GET, PUT, PATCH methods.

Default accepted fields: username, first_name, last_name Default display fields: pk, username, email, first_name, last_name Read-only fields: pk, email

Returns UserModel fields.

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

first_name	string (First name) <= 150 characters
last_name	string (Last name) <= 150 characters

Responses

200

RESPONSE SCHEMA: application/json

pk	integer (ID)
email	string <email> (Email) non-empty
first_name	string (First name) <= 150 characters
last_name	string (Last name) <= 150 characters

PATCH /auth/user/

Request samples

Payload

Content type
application/json

Copy

```
{
    "first_name": "string",
    "last_name": "string"
}
```

Response samples

200

Content type

application/json

Copy

```
{
    "pk": 0,
    "email": "user@example.com",
    "first_name": "string",
    "last_name": "string"
}
```

---

auth_verify-email_list

AUTHORIZATIONS: > *Bearer*

Responses

200

RESPONSE SCHEMA: application/json

```
Array [
    token
    required
]
```

string (Token) [1 .. 64] characters

GET /auth/verify-email/

Response samples

200

Content type

application/json

Copy Expand all Collapse all


```
[
  - {
        "token": "string"
    }
]
```


auth_verify-email_create

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

token required	string (Token) [1 .. 64] characters

Responses

201

RESPONSE SCHEMA: application/json

token required	string (Token) [1 .. 64] characters

POST /auth/verify-email/

Request samples

Payload

Content type

application/json

Copy

```
{
    "token": "string"
}
```

Response samples

201

Content type

application/json

Copy

```
{
    "token": "string"
}
```

---

auth_verify-otp_create

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

email required	string <email> (Email) non-empty
otp required	string (Otp) [1 .. 6] characters

Responses

201

RESPONSE SCHEMA: application/json

email required	string <email> (Email) non-empty
otp required	string (Otp) [1 .. 6] characters

POST /auth/verify-otp/

Request samples

Payload

Content type

application/json

Copy

```
{
    "email": "user@example.com",
    "otp": "string"
}
```

Response samples

201

Content type

application/json

Copy

```
{
    "email": "user@example.com",
    "otp": "string"
}
```

bookmark

bookmark_bookmarks_list

AUTHORIZATIONS: > *Bearer*

Responses

200

RESPONSE SCHEMA: application/json

```
Array [
```

id	integer (ID)
opportunity >	object (Opportunity)
opportunity_id required	integer (Opportunity id)
created_at	string <date-time> (Created at)

```
]
```

GET /bookmark/bookmarks/

Response samples

200

Content type

application/json

Copy Expand all Collapse all


```
[
 - {
      "id": 0,
    + "opportunity": { … },
      "opportunity_id": 0,
      "created_at": "2019-08-24T14:15:22Z"
   }
]
```


bookmark_bookmarks_create

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

opportunity >	object (Opportunity)
opportunity_id required	integer (Opportunity id)

Responses

201

RESPONSE SCHEMA: application/json

id	integer (ID)
opportunity >	object (Opportunity)
opportunity_id required	integer (Opportunity id)

created_at	string <date-time> (Created at)

POST /bookmark/bookmarks/

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all

```
{
  - "opportunity": {
        "title": "string",
        "opportunity_type": "volunteering",
        "description": "string",
        "link": "http://example.com",
        "is_open": true
    },
    "opportunity_id": 0
}
```

Response samples

201

Content type

application/json

Copy Expand all Collapse all

```
{
    "id": 0,
```

```
    - "opportunity": {
          "id": 0,
          "title": "string",
          "opportunity_type": "volunteering",
          "description": "string",
          "link": "http://example.com",
          "posted_at": "2019-08-24T14:15:22Z",
          "is_open": true,
          "created_by_name": "string",
          "created_by": 0
      },
      "opportunity_id": 0,
      "created_at": "2019-08-24T14:15:22Z"
  }
```


bookmark_bookmarks_delete_delete

Remove a bookmarked opportunity for the authenticated user. DELETE /api/bookmarks/{bookmark_id}/

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

id required	string

Responses

— 204

DELETE /bookmark/bookmarks/{id}/delete/

bookmark_opportunities_saved_list

List all bookmarked opportunities for the authenticated user. GET /api/bookmarks/

AUTHORIZATIONS: > *Bearer*

Responses

200

RESPONSE SCHEMA: application/json

```
Array [
```

id	integer (ID)
opportunity >	object (Opportunity)
opportunity_id required	integer (Opportunity id)
created_at	string <date-time> (Created at)

```
]
```

GET /bookmark/opportunities/saved/

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
        "id": 0,
      + "opportunity": { … },
        "opportunity_id": 0,
        "created_at": "2019-08-24T14:15:22Z"
    }
]
```


---

bookmark_opportunities_saved_create

List all bookmarked opportunities for the authenticated user. GET /api/bookmarks/

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

`opportunity` >	object (Opportunity)
`opportunity_id` required	integer (Opportunity id)

Responses

201

RESPONSE SCHEMA: application/json

`id`	integer (ID)
`opportunity` >	object (Opportunity)
`opportunity_id` required	integer (Opportunity id)

created_at	string <date-time> (Created at)

POST /bookmark/opportunities/saved/

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all

```
{
  - "opportunity": {
        "title": "string",
        "opportunity_type": "volunteering",
        "description": "string",
        "link": "http://example.com",
        "is_open": true
    },
    "opportunity_id": 0
}
```

Response samples

201

Content type

application/json

Copy Expand all Collapse all

```
{
    "id": 0,
```

```
  - "opportunity": {
        "id": 0,
        "title": "string",
        "opportunity_type": "volunteering",
        "description": "string",
        "link": "http://example.com",
        "posted_at": "2019-08-24T14:15:22Z",
        "is_open": true,
        "created_by_name": "string",
        "created_by": 0
    },
    "opportunity_id": 0,
    "created_at": "2019-08-24T14:15:22Z"
}
```


---

notifynotifications

notifynotifications_list

AUTHORIZATIONS: > *Bearer*

Responses

200

RESPONSE SCHEMA: application/json

Array [

id	integer (ID)
title required	string (Title) [1 .. 200] characters

message	string or null (Message) non-empty
priority	string (Priority) Enum: "info" "warning" "critical"
type	string (Type) Enum: "system" "server" "personal"
link	string or null <uri> (Link) <= 200 characters
created_at	string <date-time> (Created at)

]

GET /notifynotifications/

Response samples

200

Content type

application/json

Copy Expand all Collapse all


```
[
  - {
      "id": 0,
      "title": "string",
      "message": "string",
      "priority": "info",
      "type": "system",
      "link": "http://example.com",
      "created_at": "2019-08-24T14:15:22Z"
    }
]
```

notifynotifications_create

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

`title` required	string (Title) [1 .. 200] characters
`message`	string or null (Message) non-empty
`priority`	string (Priority) Enum: `"info"` `"warning"` `"critical"`
`type`	string (Type) Enum: `"system"` `"server"` `"personal"`
`link`	string or null <uri> (Link) <= 200 characters

Responses

201

RESPONSE SCHEMA: application/json

`id`	integer (ID)
`title` required	string (Title) [1 .. 200] characters
`message`	string or null (Message) non-empty
`priority`	string (Priority) Enum: `"info"` `"warning"` `"critical"`
`type`	string (Type) Enum: `"system"` `"server"` `"personal"`
`link`	string or null <uri> (Link) <= 200 characters

created_at	string <date-time> (Created at)

POST /notifynotifications/

Request samples

Payload

Content type

application/json

Copy

```
{
    "title": "string",
    "message": "string",
    "priority": "info",
    "type": "system",
    "link": "http://example.com"
}
```

Response samples

201

Content type

application/json

Copy

```
{
    "id": 0,
    "title": "string",
    "message": "string",
    "priority": "info",
    "type": "system",
    "link": "http://example.com",
    "created_at": "2019-08-24T14:15:22Z"
}
```


notifynotifications_read

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

id required	integer A unique integer value identifying this notification.

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)
title required	string (Title) [1 .. 200] characters
message	string or null (Message) non-empty
priority	string (Priority) Enum: "info" "warning" "critical"
type	string (Type) Enum: "system" "server" "personal"

link	string or null <uri> (Link) <= 200 characters
created_at	string <date-time> (Created at)

GET /notifynotifications/{id}/

Response samples

200

Content type
application/json

Copy

```
{
    "id": 0,
    "title": "string",
    "message": "string",
    "priority": "info",
    "type": "system",
    "link": "http://example.com",
    "created_at": "2019-08-24T14:15:22Z"
}
```

notifynotifications_update

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

id required	integer A unique integer value identifying this notification.

REQUEST BODY SCHEMA: application/json

title required	string (Title) [1 .. 200] characters
message	string or null (Message) non-empty
priority	string (Priority) Enum: "info" "warning" "critical"
type	string (Type) Enum: "system" "server" "personal"
link	string or null <uri> (Link) <= 200 characters

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)
title required	string (Title) [1 .. 200] characters
message	string or null (Message) non-empty
priority	string (Priority) Enum: "info" "warning" "critical"
type	string (Type) Enum: "system" "server" "personal"
link	string or null <uri> (Link) <= 200 characters
created_at	string <date-time> (Created at)

PUT /notifynotifications/{id}/

Request samples

Payload

Content type

application/json

Copy

```
{
    "title": "string",
    "message": "string",
    "priority": "info",
    "type": "system",
    "link": "http://example.com"
}
```

Response samples

200

Content type

application/json

Copy

```
{
    "id": 0,
    "title": "string",
    "message": "string",
    "priority": "info",
    "type": "system",
    "link": "http://example.com",
    "created_at": "2019-08-24T14:15:22Z"
}
```

---

notifynotifications_delete

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

id required	integer A unique integer value identifying this notification.

Responses

— 204

DELETE /notifynotifications/{id}/

opportunities

opportunities_opportunities_list

AUTHORIZATIONS: > *Bearer*

QUERY PARAMETERS

opportunity_type	string
is_open	string
search	string A search term.
page	integer A page number within the paginated result set.
page_size	integer Number of results to return per page.

Responses

200

RESPONSE SCHEMA: application/json

count required	integer
next	string or null <uri>
previous	string or null <uri>
results › required	Array of objects (Opportunity)

GET /opportunities/opportunities/

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
{
    "count": 0,
    "next": "http://example.com",
    "previous": "http://example.com",
  - "results": [
      + { … }
    ]
}
```

opportunities_opportunities_create

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

`title` required	string (Title) [1 .. 255] characters
`opportunity_type`	string (Opportunity type) Enum: `"volunteering"` `"internship"` `"scholarship"` `"job"` `"grant"`
`description` required	string (Description) non-empty
`link` required	string <uri> (Link) [1 .. 200] characters
`is_open`	boolean (Is open)

Responses

201

RESPONSE SCHEMA: application/json

`id`	integer (ID)
`title` required	string (Title) [1 .. 255] characters
`opportunity_type`	string (Opportunity type) Enum: `"volunteering"` `"internship"` `"scholarship"` `"job"` `"grant"`
`description` required	string (Description) non-empty
`link` required	string <uri> (Link) [1 .. 200] characters
`posted_at`	string <date-time> (Posted at)

`is_open`	boolean (Is open)
`created_by_name`	string (Created by name)
`created_by`	integer or null (Created by)

POST `/opportunities/opportunities/`

Request samples

Payload

Content type
application/json

Copy

```
{
    "title": "string",
    "opportunity_type": "volunteering",
    "description": "string",
    "link": "http://example.com",
    "is_open": true
}
```

Response samples

201

Content type
application/json

Copy

```
{
    "id": 0,
    "title": "string",
    "opportunity_type": "volunteering",
    "description": "string",
    "link": "http://example.com",
```

```
    "posted_at": "2019-08-24T14:15:22Z",
    "is_open": true,
    "created_by_name": "string",
    "created_by": 0
}
```


---

opportunities_opportunities_mine_list

AUTHORIZATIONS: > *Bearer*

Responses

200

RESPONSE SCHEMA: application/json

Array [

id	integer (ID)
title required	string (Title) [1 .. 255] characters
opportunity_type	string (Opportunity type) Enum: "volunteering" "internship" "scholarship" "job" "grant"
description required	string (Description) non-empty
link required	string <uri> (Link) [1 .. 200] characters
posted_at	string <date-time> (Posted at)
is_open	boolean (Is open)
created_by_name	string (Created by name)
created_by	integer or null (Created by)

```
]
```

GET /opportunities/opportunities/mine/

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "id": 0,
      "title": "string",
      "opportunity_type": "volunteering",
      "description": "string",
      "link": "http://example.com",
      "posted_at": "2019-08-24T14:15:22Z",
      "is_open": true,
      "created_by_name": "string",
      "created_by": 0
   }
]
```


---

opportunities_opportunities_mine_create

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

title required	string (Title) [1 .. 255] characters
opportunity_type	string (Opportunity type)

Enum: "volunteering" "internship" "scholarship" "job" "grant"

description required	string (Description) non-empty
link required	string <uri> (Link) [1 .. 200] characters
is_open	boolean (Is open)

Responses

201

RESPONSE SCHEMA: application/json

id	integer (ID)
title required	string (Title) [1 .. 255] characters
opportunity_type	string (Opportunity type) Enum: "volunteering" "internship" "scholarship" "job" "grant"
description required	string (Description) non-empty
link required	string <uri> (Link) [1 .. 200] characters
posted_at	string <date-time> (Posted at)
is_open	boolean (Is open)
created_by_name	string (Created by name)
created_by	integer or null (Created by)

POST /opportunities/opportunities/mine/

Request samples

Payload

Content type
application/json

Copy

```
{
    "title": "string",
    "opportunity_type": "volunteering",
    "description": "string",
    "link": "http://example.com",
    "is_open": true
}
```

Response samples

201

Content type
application/json

Copy

```
{
    "id": 0,
    "title": "string",
    "opportunity_type": "volunteering",
    "description": "string",
    "link": "http://example.com",
    "posted_at": "2019-08-24T14:15:22Z",
    "is_open": true,
    "created_by_name": "string",
    "created_by": 0
}
```

opportunities_opportunities_read

Handles GET (Retrieve), PUT/PATCH (Update), and DELETE for a single opportunity. Enforces the IsOwnerOrReadOnly permission.

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

`id` required	integer A unique integer value identifying this opportunity.

Responses

200

RESPONSE SCHEMA: application/json

`id`	integer (ID)
`title` required	string (Title) [1 .. 255] characters
`opportunity_type`	string (Opportunity type) Enum: `"volunteering"` `"internship"` `"scholarship"` `"job"` `"grant"`
`description` required	string (Description) non-empty
`link` required	string <uri> (Link) [1 .. 200] characters
`posted_at`	string <date-time> (Posted at)
`is_open`	boolean (Is open)
`created_by_name`	string (Created by name)

created_by	integer or null (Created by)

GET /opportunities/opportunities/{id}/

Response samples

200

Content type

application/json

Copy


```
{
    "id": 0,
    "title": "string",
    "opportunity_type": "volunteering",
    "description": "string",
    "link": "http://example.com",
    "posted_at": "2019-08-24T14:15:22Z",
    "is_open": true,
    "created_by_name": "string",
    "created_by": 0
}
```


opportunities_opportunities_update

Handles GET (Retrieve), PUT/PATCH (Update), and DELETE for a single opportunity. Enforces the IsOwnerOrReadOnly permission.

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

id required	integer A unique integer value identifying this opportunity.

REQUEST BODY SCHEMA: application/json

title required	string (Title) [1 .. 255] characters
opportunity_type	string (Opportunity type) Enum: "volunteering" "internship" "scholarship" "job" "grant"
description required	string (Description) non-empty
link required	string <uri> (Link) [1 .. 200] characters
is_open	boolean (Is open)

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)
title required	string (Title) [1 .. 255] characters
opportunity_type	string (Opportunity type) Enum: "volunteering" "internship" "scholarship" "job" "grant"
description required	string (Description) non-empty
link required	string <uri> (Link) [1 .. 200] characters
posted_at	string <date-time> (Posted at)
is_open	boolean (Is open)

created_by_name	string (Created by name)
created_by	integer or null (Created by)

PUT /opportunities/opportunities/{id}/

Request samples

Payload

Content type
application/json

Copy

```
{
    "title": "string",
    "opportunity_type": "volunteering",
    "description": "string",
    "link": "http://example.com",
    "is_open": true
}
```

Response samples

200

Content type
application/json

Copy

```
{
    "id": 0,
    "title": "string",
    "opportunity_type": "volunteering",
    "description": "string",
    "link": "http://example.com",
    "posted_at": "2019-08-24T14:15:22Z",
    "is_open": true,
```

```
    "created_by_name": "string",
    "created_by": 0
}
```

---

opportunities_opportunities_partial_update

Handles GET (Retrieve), PUT/PATCH (Update), and DELETE for a single opportunity. Enforces the IsOwnerOrReadOnly permission.

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

`id` required	integer A unique integer value identifying this opportunity.

REQUEST BODY SCHEMA: application/json

`title` required	string (Title) [1 .. 255] characters
`opportunity_type`	string (Opportunity type) Enum: `"volunteering"` `"internship"` `"scholarship"` `"job"` `"grant"`
`description` required	string (Description) non-empty
`link` required	string <uri> (Link) [1 .. 200] characters
`is_open`	boolean (Is open)

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)
title required	string (Title) [1 .. 255] characters
opportunity_type	string (Opportunity type) Enum: "volunteering" "internship" "scholarship" "job" "grant"
description required	string (Description) non-empty
link required	string <uri> (Link) [1 .. 200] characters
posted_at	string <date-time> (Posted at)
is_open	boolean (Is open)
created_by_name	string (Created by name)
created_by	integer or null (Created by)

PATCH /opportunities/opportunities/{id}/

Request samples

Payload

Content type

application/json

Copy

```
{
    "title": "string",
    "opportunity_type": "volunteering",
    "description": "string",
    "link": "http://example.com",
    "is_open": true
}
```

Response samples

200

Content type

application/json

Copy


```
{
    "id": 0,
    "title": "string",
    "opportunity_type": "volunteering",
    "description": "string",
    "link": "http://example.com",
    "posted_at": "2019-08-24T14:15:22Z",
    "is_open": true,
    "created_by_name": "string",
    "created_by": 0
}
```


---

opportunities_opportunities_delete

Handles GET (Retrieve), PUT/PATCH (Update), and DELETE for a single opportunity. Enforces the IsOwnerOrReadOnly permission.

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

`id` required	integer A unique integer value identifying this opportunity.

Responses

— 204

DELETE /opportunities/opportunities/{id}/

profile

profile_credentials_list

a model viewset to handle CRUD operations on the credential model

AUTHORIZATIONS: > *Bearer*

Responses

200

RESPONSE SCHEMA: application/json

```
Array [
    id                  integer (ID)
    document_name       string (Document name)  [ 1 .. 100 ] characters
    required
    document            string <uri> (Document)
    is_verified         boolean (Is verified)
]
```

GET /profile/credentials/

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "id": 0,
      "document_name": "string",
      "document": "http://example.com",
      "is_verified": true
   }
]
```


---

profile_credentials_create

a model viewset to handle CRUD operations on the credential model

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

document_name required	string (Document name) [1 .. 100] characters

Responses

201

RESPONSE SCHEMA: application/json

id	integer (ID)
document_name required	string (Document name) [1 .. 100] characters
document	string <uri> (Document)
is_verified	boolean (Is verified)

POST /profile/credentials/

Request samples

Payload

Content type

application/json

Copy

```
{
    "document_name": "string"
}
```

Response samples

201

Content type

application/json

Copy

```
{
    "id": 0,
    "document_name": "string",
    "document": "http://example.com",
    "is_verified": true
}
```


---

profile_enablerprofile_read

view to handle CRUD operations on the profile model front-end can send the social link data as nested objects when creating a profile instance

AUTHORIZATIONS: > *Bearer*

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)
base_details > required	object (Profile)
social_links >	Array of objects (SocialLink)
name required	string (Name) [1 .. 100] characters
employees	integer or null (Employees) [-2147483648 .. 2147483647]
role	string or null (Role) <= 50 characters

GET /profile/enablerprofile/

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
{
    "id": 0,
  - "base_details": {
        "id": 0,
        "profile_pic": "http://example.com",
        "bio": "string",
        "contact_email": "user@example.com",
        "phone_number": "string",
        "address": "string",
        "state": "string",
        "country": "string",
        "website": "http://example.com",
        "created_at": "2019-08-24T14:15:22Z"
    },
  - "social_links": [
      + { … }
    ],
    "name": "string",
    "employees": -2147483648,
    "role": "string"
}
```


profile_enablerprofile_create

view to handle CRUD operations on the profile model front-end can send the social link data as nested objects when creating a profile instance

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

base_details > required	object (Profile)
social_links >	Array of objects (SocialLink)
name required	string (Name) [1 .. 100] characters
employees	integer or null (Employees) [-2147483648 .. 2147483647]
role	string or null (Role) <= 50 characters

Responses

201

RESPONSE SCHEMA: application/json

id	integer (ID)
base_details > required	object (Profile)
social_links >	Array of objects (SocialLink)
name required	string (Name) [1 .. 100] characters
employees	integer or null (Employees) [-2147483648 .. 2147483647]
role	string or null (Role) <= 50 characters

POST /profile/enablerprofile/

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all


```
{
  - "base_details": {
        "bio": "string",
        "contact_email": "user@example.com",
        "phone_number": "string",
        "address": "string",
        "state": "string",
        "country": "string",
        "website": "http://example.com"
    },
  - "social_links": [
      + { … }
    ],
    "name": "string",
    "employees": -2147483648,
    "role": "string"
}
```


Response samples

201

Content type

application/json

Copy Expand all Collapse all


```
{
    "id": 0,
```

```
  - "base_details": {
        "id": 0,
        "profile_pic": "http://example.com",
        "bio": "string",
        "contact_email": "user@example.com",
        "phone_number": "string",
        "address": "string",
        "state": "string",
        "country": "string",
        "website": "http://example.com",
        "created_at": "2019-08-24T14:15:22Z"
    },
  - "social_links": [
      + { … }
    ],
    "name": "string",
    "employees": -2147483648,
    "role": "string"
}
```


---

profile_enablerprofile_update

view to handle CRUD operations on the profile model front-end can send the social link data as nested objects when creating a profile instance

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

base_details > required	object (Profile)
social_links >	Array of objects (SocialLink)
name required	string (Name) [1 .. 100] characters
employees	integer or null (Employees) [-2147483648 .. 2147483647]
role	string or null (Role) <= 50 characters

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)
base_details > required	object (Profile)
social_links >	Array of objects (SocialLink)
name required	string (Name) [1 .. 100] characters
employees	integer or null (Employees) [-2147483648 .. 2147483647]
role	string or null (Role) <= 50 characters

PUT /profile/enablerprofile/

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all

```
{
  - "base_details": {
        "bio": "string",
        "contact_email": "user@example.com",
        "phone_number": "string",
        "address": "string",
        "state": "string",
        "country": "string",
        "website": "http://example.com"
    },
  - "social_links": [
      + { … }
    ],
    "name": "string",
    "employees": -2147483648,
    "role": "string"
}
```


Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
{
    "id": 0,
  - "base_details": {
        "id": 0,
        "profile_pic": "http://example.com",
        "bio": "string",
        "contact_email": "user@example.com",
        "phone_number": "string",
        "address": "string",
        "state": "string",
        "country": "string",
        "website": "http://example.com",
        "created_at": "2019-08-24T14:15:22Z"
    },
```

```
  - "social_links": [
      + { … }
    ],
    "name": "string",
    "employees": -2147483648,
    "role": "string"
}
```

---

profile_enablerprofile_partial_update

view to handle CRUD operations on the profile model front-end can send the social link data as nested objects when creating a profile instance

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

base_details > required	object (Profile)
social_links >	Array of objects (SocialLink)
name required	string (Name) [1 .. 100] characters
employees	integer or null (Employees) [-2147483648 .. 2147483647]
role	string or null (Role) <= 50 characters

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)

base_details > required	object (Profile)
social_links >	Array of objects (SocialLink)
name required	string (Name) [1 .. 100] characters
employees	integer or null (Employees) [-2147483648 .. 2147483647]
role	string or null (Role) <= 50 characters

PATCH /profile/enablerprofile/

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all


```
{
  - "base_details": {
        "bio": "string",
        "contact_email": "user@example.com",
        "phone_number": "string",
        "address": "string",
        "state": "string",
        "country": "string",
        "website": "http://example.com"
    },
  - "social_links": [
      + { … }
    ],
    "name": "string",
    "employees": -2147483648,
    "role": "string"
}
```

Response samples

200

Content type

application/json

Copy Expand all Collapse all


```
{
    "id": 0,
  - "base_details": {
        "id": 0,
        "profile_pic": "http://example.com",
        "bio": "string",
        "contact_email": "user@example.com",
        "phone_number": "string",
        "address": "string",
        "state": "string",
        "country": "string",
        "website": "http://example.com",
        "created_at": "2019-08-24T14:15:22Z"
    },
  - "social_links": [
      + { … }
    ],
    "name": "string",
    "employees": -2147483648,
    "role": "string"
}
```


---

profile_pathfinderprofile_read

View to handle CRUD operations on the pathfinder profile model front-end can send social link data as nested objects when creating a profile instance

AUTHORIZATIONS: > *Bearer*

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)
base_details > required	object (Profile)
social_links >	Array of objects (SocialLink)
skills >	Array of objects (Skill)
educations >	Array of objects (Education)
certifications >	Array of objects (Certification)
first_name required	string (First name) [1 .. 50] characters
last_name required	string (Last name) [1 .. 50] characters
other_name	string or null (Other name) <= 50 characters
title	string or null (Title) <= 100 characters e.g. Software Engineer, Data Scientist
about	string or null (About) <= 1000 characters
work_experience	string (Work experience)
languages	string or null (Languages) <= 200 characters English, French, Yoruba
gmail	string or null <email> (Gmail) <= 256 characters

GET /profile/pathfinderprofile/

Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
{
    "id": 0,
  - "base_details": {
        "id": 0,
        "profile_pic": "http://example.com",
        "bio": "string",
        "contact_email": "user@example.com",
        "phone_number": "string",
        "address": "string",
        "state": "string",
        "country": "string",
        "website": "http://example.com",
        "created_at": "2019-08-24T14:15:22Z"
    },
  - "social_links": [
      + { … }
    ],
  - "skills": [
      + { … }
    ],
  - "educations": [
      + { … }
    ],
  - "certifications": [
      + { … }
    ],
    "first_name": "string",
    "last_name": "string",
    "other_name": "string",
    "title": "string",
    "about": "string",
    "work_experience": "string",
    "languages": "string",
    "gmail": "user@example.com"
}
```


---

profile_pathfinderprofile_create

View to handle CRUD operations on the pathfinder profile model front-end can send social link data as nested objects when creating a profile instance

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

base_details > required	object (Profile)
social_links >	Array of objects (SocialLink)
skills >	Array of objects (Skill)
educations >	Array of objects (Education)
certifications >	Array of objects (Certification)
first_name required	string (First name) [1 .. 50] characters
last_name required	string (Last name) [1 .. 50] characters
other_name	string or null (Other name) <= 50 characters
title	string or null (Title) <= 100 characters e.g. Software Engineer, Data Scientist
about	string or null (About) <= 1000 characters
work_experience	string (Work experience)
languages	string or null (Languages) <= 200 characters English, French, Yoruba
gmail	string or null <email> (Gmail) <= 256 characters

Responses

201

RESPONSE SCHEMA: application/json

id	integer (ID)
base_details > required	object (Profile)
social_links >	Array of objects (SocialLink)
skills >	Array of objects (Skill)
educations >	Array of objects (Education)
certifications >	Array of objects (Certification)
first_name required	string (First name) [1 .. 50] characters
last_name required	string (Last name) [1 .. 50] characters
other_name	string or null (Other name) <= 50 characters
title	string or null (Title) <= 100 characters e.g. Software Engineer, Data Scientist
about	string or null (About) <= 1000 characters
work_experience	string (Work experience)
languages	string or null (Languages) <= 200 characters English, French, Yoruba
gmail	string or null <email> (Gmail) <= 256 characters

POST /profile/pathfinderprofile/

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all


```
{
  - "base_details": {
        "bio": "string",
        "contact_email": "user@example.com",
        "phone_number": "string",
        "address": "string",
        "state": "string",
        "country": "string",
        "website": "http://example.com"
    },
  - "social_links": [
      + { … }
    ],
  - "skills": [
      + { … }
    ],
  - "educations": [
      + { … }
    ],
  - "certifications": [
      + { … }
    ],
    "first_name": "string",
    "last_name": "string",
    "other_name": "string",
    "title": "string",
    "about": "string",
    "work_experience": "string",
    "languages": "string",
    "gmail": "user@example.com"
}
```


Response samples

201

Content type

application/json

Copy Expand all Collapse all

```
{
    "id": 0,
  - "base_details": {
        "id": 0,
        "profile_pic": "http://example.com",
        "bio": "string",
        "contact_email": "user@example.com",
        "phone_number": "string",
        "address": "string",
        "state": "string",
        "country": "string",
        "website": "http://example.com",
        "created_at": "2019-08-24T14:15:22Z"
    },
  - "social_links": [
      + { … }
    ],
  - "skills": [
      + { … }
    ],
  - "educations": [
      + { … }
    ],
  - "certifications": [
      + { … }
    ],
    "first_name": "string",
    "last_name": "string",
    "other_name": "string",
    "title": "string",
    "about": "string",
    "work_experience": "string",
    "languages": "string",
    "gmail": "user@example.com"
}
```


---

profile_pathfinderprofile_update

View to handle CRUD operations on the pathfinder profile model front-end can send social link data as nested objects when creating a profile instance

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

base_details > required	object (Profile)
social_links >	Array of objects (SocialLink)
skills >	Array of objects (Skill)
educations >	Array of objects (Education)
certifications >	Array of objects (Certification)
first_name required	string (First name) [1 .. 50] characters
last_name required	string (Last name) [1 .. 50] characters
other_name	string or null (Other name) <= 50 characters
title	string or null (Title) <= 100 characters e.g. Software Engineer, Data Scientist
about	string or null (About) <= 1000 characters
work_experience	string (Work experience)
languages	string or null (Languages) <= 200 characters English, French, Yoruba
gmail	string or null <email> (Gmail) <= 256 characters

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)
base_details > required	object (Profile)
social_links >	Array of objects (SocialLink)
skills >	Array of objects (Skill)
educations >	Array of objects (Education)
certifications >	Array of objects (Certification)
first_name required	string (First name) [1 .. 50] characters
last_name required	string (Last name) [1 .. 50] characters
other_name	string or null (Other name) <= 50 characters
title	string or null (Title) <= 100 characters e.g. Software Engineer, Data Scientist
about	string or null (About) <= 1000 characters
work_experience	string (Work experience)
languages	string or null (Languages) <= 200 characters English, French, Yoruba
gmail	string or null <email> (Gmail) <= 256 characters

PUT /profile/pathfinderprofile/

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all


```
{
  - "base_details": {
        "bio": "string",
        "contact_email": "user@example.com",
        "phone_number": "string",
        "address": "string",
        "state": "string",
        "country": "string",
        "website": "http://example.com"
    },
  - "social_links": [
      + { … }
    ],
  - "skills": [
      + { … }
    ],
  - "educations": [
      + { … }
    ],
  - "certifications": [
      + { … }
    ],
    "first_name": "string",
    "last_name": "string",
    "other_name": "string",
    "title": "string",
    "about": "string",
    "work_experience": "string",
    "languages": "string",
    "gmail": "user@example.com"
}
```


Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
{
    "id": 0,
  - "base_details": {
        "id": 0,
        "profile_pic": "http://example.com",
        "bio": "string",
        "contact_email": "user@example.com",
        "phone_number": "string",
        "address": "string",
        "state": "string",
        "country": "string",
        "website": "http://example.com",
        "created_at": "2019-08-24T14:15:22Z"
    },
  - "social_links": [
      + { … }
    ],
  - "skills": [
      + { … }
    ],
  - "educations": [
      + { … }
    ],
  - "certifications": [
      + { … }
    ],
    "first_name": "string",
    "last_name": "string",
    "other_name": "string",
    "title": "string",
    "about": "string",
    "work_experience": "string",
    "languages": "string",
    "gmail": "user@example.com"
}
```


---

profile_pathfinderprofile_partial_update

View to handle CRUD operations on the pathfinder profile model front-end can send social link data as nested objects when creating a profile instance

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

base_details > required	object (Profile)
social_links >	Array of objects (SocialLink)
skills >	Array of objects (Skill)
educations >	Array of objects (Education)
certifications >	Array of objects (Certification)
first_name required	string (First name) [1 .. 50] characters
last_name required	string (Last name) [1 .. 50] characters
other_name	string or null (Other name) <= 50 characters
title	string or null (Title) <= 100 characters e.g. Software Engineer, Data Scientist
about	string or null (About) <= 1000 characters
work_experience	string (Work experience)
languages	string or null (Languages) <= 200 characters English, French, Yoruba
gmail	string or null <email> (Gmail) <= 256 characters

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)
base_details > required	object (Profile)
social_links >	Array of objects (SocialLink)
skills >	Array of objects (Skill)
educations >	Array of objects (Education)
certifications >	Array of objects (Certification)
first_name required	string (First name) [1 .. 50] characters
last_name required	string (Last name) [1 .. 50] characters
other_name	string or null (Other name) <= 50 characters
title	string or null (Title) <= 100 characters e.g. Software Engineer, Data Scientist
about	string or null (About) <= 1000 characters
work_experience	string (Work experience)
languages	string or null (Languages) <= 200 characters English, French, Yoruba
gmail	string or null <email> (Gmail) <= 256 characters

PATCH /profile/pathfinderprofile/

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all


```
{
  - "base_details": {
        "bio": "string",
        "contact_email": "user@example.com",
        "phone_number": "string",
        "address": "string",
        "state": "string",
        "country": "string",
        "website": "http://example.com"
    },
  - "social_links": [
      + { … }
    ],
  - "skills": [
      + { … }
    ],
  - "educations": [
      + { … }
    ],
  - "certifications": [
      + { … }
    ],
    "first_name": "string",
    "last_name": "string",
    "other_name": "string",
    "title": "string",
    "about": "string",
    "work_experience": "string",
    "languages": "string",
    "gmail": "user@example.com"
}
```


Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
{
    "id": 0,
  - "base_details": {
        "id": 0,
        "profile_pic": "http://example.com",
        "bio": "string",
        "contact_email": "user@example.com",
        "phone_number": "string",
        "address": "string",
        "state": "string",
        "country": "string",
        "website": "http://example.com",
        "created_at": "2019-08-24T14:15:22Z"
    },
  - "social_links": [
      + { … }
    ],
  - "skills": [
      + { … }
    ],
  - "educations": [
      + { … }
    ],
  - "certifications": [
      + { … }
    ],
    "first_name": "string",
    "last_name": "string",
    "other_name": "string",
    "title": "string",
    "about": "string",
    "work_experience": "string",
    "languages": "string",
    "gmail": "user@example.com"
}
```


---

profile_profile_picture_read

View to handle profile picture retrieve and update for the current user's Profile.

AUTHORIZATIONS: > *Bearer*

Responses

200

RESPONSE SCHEMA: application/json

`id`	integer (ID)
`profile_pic`	string or null <uri> (Profile pic)

GET `/profile/profile/picture/`

Response samples

200

Content type
application/json

Copy

```
{
    "id": 0,
    "profile_pic": "http://example.com"
}
```

profile_profile_picture_partial_update

View to handle profile picture retrieve and update for the current user's Profile.

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: multipart/form-data

profile_pic required	string or null <binary>

Responses

200

RESPONSE SCHEMA: application/json

id	integer (ID)
profile_pic	string or null <uri> (Profile pic)

PATCH /profile/profile/picture/

Response samples

200

Content type
application/json

Copy

```
{
    "id": 0,
    "profile_pic": "http://example.com"
}
```

waitlist

waitlist_create

waitlist email submissions!!

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

email required	string <email> (Email) [1 .. 254] characters
name	string or null (Name) <= 255 characters

Responses

201

RESPONSE SCHEMA: application/json

email required	string <email> (Email) [1 .. 254] characters
name	string or null (Name) <= 255 characters

POST /waitlist/

Request samples

Payload

Content type

application/json

Copy

```
{
    "email": "user@example.com",
    "name": "string"
}
```

Response samples

201

Content type
application/json

Copy

```
{
    "email": "user@example.com",
    "name": "string"
}
```

---

waitlist_stats_list

Get waitlist statistics - Admin only

AUTHORIZATIONS: > *Bearer*

Responses

200

RESPONSE SCHEMA: application/json

Array [

total_signups required	integer (Total signups)
verified_signups required	integer (Verified signups)

signups_today required	integer (Signups today)
signups_this_week required	integer (Signups this week)
signups_this_month required	integer (Signups this month)

]

GET /waitlist/stats/

Response samples

200

Content type

application/json

Copy Expand all Collapse all


```
[
  - {
        "total_signups": 0,
        "verified_signups": 0,
        "signups_today": 0,
        "signups_this_week": 0,
        "signups_this_month": 0
    }
]
```