


ARTIFICIAL NEURAL NETWORKS

Prof. Alexander Huth

10/31/2017 

RECAP:

NONLINEAR METHODS

A NONLINEAR PROBLEM

x1	0	1	1	0
x2	0	0	1	1
y	0	0	1	0

$$y = f(x_1, x_2)$$

what is f ?

RECAP:

NONLINEAR METHODS

- * **Volterra series**
 - * Generic, *expensive*
- * **Kernel regression** (*samples, not features!*)
 - * Generic (w/ RBF or poly. kernel),
~linear regression (w/ linear kernel),
~Volterra series (w/ Volterra kernel)
 - * *Not expensive!*

RECAP: KERNEL REGRESSION

$$\hat{f}(z) = \sum_{i=1}^n \alpha_i k(z, X_i)$$


n ← sum across datapoints
weight ← α_i
kernel function ← $k(z, X_i)$

$$\hat{\alpha} = \underset{\alpha}{\operatorname{argmin}} \left[||Y - K\alpha||_2^2 + \lambda \alpha^\top K \alpha \right]$$

$$\text{where: } K_{ij} = k(X_i, X_j)$$

ARTIFICIAL NEURAL NETWORK

* Simplest version: a *perceptron*



$$y_i \in \{0, 1\}$$

$$X_i \in \mathcal{R}^p$$

$$\hat{y}_i = H(X_i w)$$

PERCEPTRON LEARNING

- * Due to Frank Rosenblatt (1958)
- * Usually defined as online learning rule (assuming each example will be fed in one-by-one)

PERCEPTRON LEARNING



At iteration t in the learning process:

$$\hat{y}_i^{(t)} = H(X_i w^{(t)})$$

$$\begin{aligned}\hat{y}_i^{(t)} &= H(X_i w^{(t)}) \\ w_j^{(t+1)} &= w_j^{(t)} + (y_i - \hat{y}_i^{(t)}) X_{ij}\end{aligned}$$

$$w_j^{(t+1)} = w_j^{(t)} + (y_i - \hat{y}_i^{(t)}) X_{ij}$$

PERCEPTRON LEARNING




h/t <https://github.com/ayusek/Perceptron-Animation>

PERCEPTRONS

- * “You dumdots, single perceptrons can’t even solve something as simple as XOR, how could they possibly recognize images or walk or talk or be conscious?!”
– Minsky & Papert, basically, 1969
- * → “AI winter” of 1974-1980

MULTILAYER ARTIFICIAL NEURAL NETWORKS



w = weights

a = activations

z = total input

g = activ. fxn

b = bias

MULTILAYER ARTIFICIAL NEURAL NETWORKS

- * Let $\hat{y} = a_k$ (the output),
 $X_i = a_i$ (the input)
- * Suppose g 's are fixed
- * How do we learn the w 's and b 's?

MULTILAYER ARTIFICIAL NEURAL NETWORKS

* Backpropagation!

MULTILAYER ARTIFICIAL NEURAL NETWORKS

- * Suppose number of hidden units = number of training samples
- * Suppose $w_{ij} = X_j$
- * *Suddenly..* a kernel regression neural network, with $k(a,b) = \tanh(a.b)$

NEXT TIME

- * Seminar-style paper discussion:

“Seeing it all: Convolutional network layers map the function of the human visual system”

by Eickenberg, Gramfort, Varoquaux, & Thirion (Neuroimage, 2017)

(PDF on github)

- * Who will lead discussion?