

LINKING ARTIFICIAL AND BIOLOGICAL NEURAL NETWORKS

Prof. Alexander Huth

4.7.2020

COURSE ADMIN / PROJECT

- * Proposal due **this** Thursday (April 9):
 - * ~1-2 paragraphs describing what you plan to do & who is in your group. Email to huth@cs.utexas.edu before class
- * Writeup (3-4 pages explaining background & what you did) due **May 5**
- * In-class presentations (5-10 minutes)
May 5 & 7

RECAP

- * **Deep** neural networks (i.e. with many hidden layers)
- * Trained using gradient **backpropagation**
- * Can do impressive things like **image classification** (e.g. **AlexNet**)
- * Using tricks like:
 - * **localized** receptive fields
 - * **convolution**
 - * **downsampling** (i.e. max pooling)

RECAP


- * Subtle switch from **system identification** to **system construction**
- * *System identification*: building functions to explicitly approximate **representations** used by a given computational system
- * *System construction*: building functions with (ideally) the same **behavior** or **goal** as a given computational system

RECAP: ALEXNET


- * Does it solve the problem the same way that our brains do?
- * How would we know?

RECAP: ALEXNET

- * Features learned by 1st layer of AlexNet





- * Receptive fields of V1 neurons from a macaque





CONSTRUCTION TO IDENTIFICATION

- * What would it mean for a constructed system (e.g. AlexNet) to solve a problem **similarly** to how an existing system (e.g. a brain) does?

CONSTRUCTION TO IDENTIFICATION

- * Recall Marr's levels of description:
- * **Computational:** both systems solve the same task 
- * **Algorithmic/Representational:** both systems use the same algorithm or representations **???**
- * **Implementation:** both systems use the same implementation (neurons, etc.) 

CONSTRUCTION TO IDENTIFICATION

- * Recall Marr's levels of description:
- * **Computational:** both systems solve the same task 
- * **Algorithmic/Representational:** both systems use the same algorithm or representations **???**
- * **Implementation:** both systems use the same implementation (neurons, etc.) 

CONSTRUCTION TO IDENTIFICATION

- * What would it mean for a constructed system (e.g. AlexNet) to solve a problem **similarly** to how an existing system (e.g. a brain) does?
- * *It would mean that both use the same algorithm or representations to solve the problem*
- * How do we test whether a system uses some representation?

CONSTRUCTION TO IDENTIFICATION

- * Key idea: *use the constructed system as a linearizing transform for system identification*

EXTRACTING REPRESENTATIONS FROM A NEURAL NETWORK

- * The **activations** at each layer of a deep neural network can serve as “**features**”
- * The **functions** that compute the activations (from the input) thus serve as **linearizing transformations**

EXTRACTING REPRESENTATIONS FROM A NEURAL NETWORK

* (“whiteboard” notes)

CONSTRUCTION TO IDENTIFICATION

1. Collect dataset of brain responses Y using stimuli X
2. Train/find artificial system
3. Extract activations $a(X)$ for the stimuli in the neuroscience experiment
4. Use activations as features in linearized encoding model: $Y = a(X) \cdot b$

CONSTRUCTION TO IDENTIFICATION

- * Key questions:
 - * Does this work at all?
 - * If so, is this trivial?
 - * Do activations from different layers predict different parts of the brain?
 - * Does this correspond to known computational hierarchies?
 - * If so, is *this* trivial?

FMRI EXAMPLE


- * Eickenberg, Gramfort, Varoquaux, & Thirion (2016) Seeing it all: convolutional network layers map the function of the human visual system.
Neuroimage

FMRI EXAMPLE

- * fMRI data come from experiment we discussed previously (see *Lecture 10*, Kay et al., Nature 2008)
- * Two human subjects viewed 1000s of images while BOLD signals were recorded from visual cortex using fMRI



FMRI EXAMPLE

- * Used “Overfeat” convolutional neural network (similar architecture to AlexNet)
- * Built model for each voxel using activations from each layer, then tested on held-out data





VISUAL CORTEX

- * **Connectivity** of areas in macaque visual cortex
- * Felleman & Van Essen (1991)




FMRI EXAMPLE



- * Lower layers of the network predict “earlier” visual areas, higher layers predict “later” visual areas!


FMRI EXAMPLE



FMRI EXAMPLE


- * ***Fingerprint***: summary model performance metric giving something like “best layer”

A Fingerprint summaries for Kay2008



Lower level  Higher level

B Fingerprint summaries for Huth2012



Lower level  Higher level

CONSTRUCTION TO IDENTIFICATION

- * Key questions:
 - * Does this work at all? *YES*
 - * If so, is this trivial? *HMM...*
 - * Do activations from different layers predict different parts of the brain? *YES*
 - * Does this correspond to known computational hierarchies? *YES*
 - * If so, is *this* trivial? *HMM...*

NEXT TIME

- * Recurrent neural networks (etc.) for modeling language