charge energy						output energy					trigger energy (N)				
_% 1.85	12.7	11.5	12.9	14.0	13.3	9.0	8.1	9.3	7.9	9.5	12.1	11.0	13.1	14.6	16.0
∯1.65	6.9	8.9	9.3	10.9	12.5	5.2	6.5	6.6	8.9	9.6	2.6	5.2	6.7	9.9	14.1
strength 1.45		5.8	7.6	9.2	11.5		4.4	5.9	7.5	8.7		0.8	2.3	4.8	7.7
961.25 1.05	2	•		7.2	9.3	30°			5.5	6.1	•	00		2.0	4.2
1.05	30°				6.7	3			4.5	3	0°			1.1	
_% 1.85	11.6	11.2	15.4	16.8	19.3	7.5	7.1	12.0	8.3	12.3	8.6	13.9	17.1	23.2	21.2
£1.65	7.8	11.8	13.0	12.4	13.4	5.2	8.1	9.1	6.6	9.2	2.6	6.3	10.4	11.9	11.4
strength 1.45		8.1	9.7	11.2	13.9		6.0	6.9	7.0	7.4		2.0	4.5	7.7	13.0
961.25 1.05	40°		7.6	8.6	10.1	4	00	5.6	6.0	7.2	400		1.3	4.5	6.4
1.05 ق				5.5	6.4	40°			4.1	4.5	40°			0.4	1.3
	.85	.75	.65	.55	.45	.85	.75	.65	.55	.45	.85		.65 dge l		
stroke length (mm)															
_% 1.85	7.0	7.0	7.0	7.5	7.5	7.0	7.0	8.0	8.5	9.0					
strength 1.45	5.0	5.5	6.0	7.0	7.0	6.0	6.5	7.5	8.0	9.0					
1.45		4.5	6.5	7.5	7.0		6.0	7.0	8.0	8.5					
961.25 1.05	24	n o		6.0	6.5		no	6.0	7.0	8.0					
1.05 ق	30°				7.0	40°			6.0	7.0					
	.85 .75 .65 .55 .45					.85	.75	.65	.55	.45	brid	lge le	engt	h %	