

CS 141 Homework 7 Report

Alexis Lauren Vu

TOTAL POINTS

30 / 30

QUESTION 1

Passing 30 pts

1.1 reference 10 / 10

✓ - **0 pts** Correct

- **2 pts** A = (0 1 2)

- **5 pts** A = (0 1 2)

- **3 pts** Did not select pages correctly

1.2 value-result 10 / 10

✓ - **0 pts** Correct

- **2 pts** A = (1 3 3)

- **5 pts** A = (1 3 3)

- **3 pts** Question not marked correctly.

1.3 name 10 / 10

✓ - **0 pts** Correct

- **2 pts** A = (1 5 2)

- **5 pts** A = (1 5 2)

- **3 pts** Question not selected correctly.

Programming Languages
Homework 7
Due Wednesday, February 26th at 2 AM

Download this homework assignment, and fill in your answers, then convert this document into pdf as a report to GradeScope. Be sure you know how to trace programs like this on paper; you will do it on the quiz and on the final.

1. [30] Consider the following procedure in Ada-like syntax (with 1-indexed arrays):

```
PROCEDURE Main IS
  i: integer := 3;
  type vector is array (1..3) of integer;
  a: vector := (3, 1, 2);
  PROCEDURE Put (v: vector) IS
    BEGIN
      Put_Line ("A = (");
      FOR i IN v'range LOOP
        Put_Line (v(i));
        Put_Line (" ");
      END LOOP;
      Put_Line (")");
    END Put;
  PROCEDURE Do_Something (t: mode integer) IS
    BEGIN
      i := i - 1;
      t := i + 1;
      a(t) := a(i) + 1;
      a(i) := a(t) + 1;
      i := i - 1;
      a(t) := t - 1;
      a(i) := a(t) - 1;
    END Do_Something;
  BEGIN
    Do_Something(a(i));
    Put (a);
  END Main;
```

What would be the output, assuming the parameter passing mode is pass by:

e.g. copy: value	A = (1 3 2)
a. reference	A = (0 1 2)
b. copy: value-result	A = (1 3 3)
c. name	A = (1 5 2)

1.1 reference 10 / 10

✓ - 0 pts Correct

- 2 pts $A = (0 \ 1 \ 2)$

- 5 pts $A = (0 \ 1 \ 2)$

- 3 pts Did not select pages correctly

Programming Languages
Homework 7
Due Wednesday, February 26th at 2 AM

Download this homework assignment, and fill in your answers, then convert this document into pdf as a report to GradeScope. Be sure you know how to trace programs like this on paper; you will do it on the quiz and on the final.

1. [30] Consider the following procedure in Ada-like syntax (with 1-indexed arrays):

```
PROCEDURE Main IS
  i: integer := 3;
  type vector is array (1..3) of integer;
  a: vector := (3, 1, 2);
  PROCEDURE Put (v: vector) IS
  BEGIN
    Put_Line ("A = (");
    FOR i IN v'range LOOP
      Put_Line (v(i));
      Put_Line (" ");
    END LOOP;
    Put_Line (")");
  END Put;
  PROCEDURE Do_Something (t: mode integer) IS
  BEGIN
    i := i - 1;
    t := i + 1;
    a(t) := a(i) + 1;
    a(i) := a(t) + 1;
    i := i - 1;
    a(t) := t - 1;
    a(i) := a(t) - 1;
  END Do_Something;
BEGIN
  Do_Something(a(i));
  Put (a);
END Main;
```

What would be the output, assuming the parameter passing mode is pass by:

e.g. copy: value	A = (1 3 2)
a. reference	A = (0 1 2)
b. copy: value-result	A = (1 3 3)
c. name	A = (1 5 2)

1.2 value-result 10 / 10

✓ - 0 pts Correct

- 2 pts $A = (1\ 3\ 3)$

- 5 pts $A = (1\ 3\ 3)$

- 3 pts Question not marked correctly.

Programming Languages
Homework 7
Due Wednesday, February 26th at 2 AM

Download this homework assignment, and fill in your answers, then convert this document into pdf as a report to GradeScope. Be sure you know how to trace programs like this on paper; you will do it on the quiz and on the final.

1. [30] Consider the following procedure in Ada-like syntax (with 1-indexed arrays):

```
PROCEDURE Main IS
  i: integer := 3;
  type vector is array (1..3) of integer;
  a: vector := (3, 1, 2);
  PROCEDURE Put (v: vector) IS
  BEGIN
    Put_Line ("A = (");
    FOR i IN v'range LOOP
      Put_Line (v(i));
      Put_Line (" ");
    END LOOP;
    Put_Line (")");
  END Put;
  PROCEDURE Do_Something (t: mode integer) IS
  BEGIN
    i := i - 1;
    t := i + 1;
    a(t) := a(i) + 1;
    a(i) := a(t) + 1;
    i := i - 1;
    a(t) := t - 1;
    a(i) := a(t) - 1;
  END Do_Something;
BEGIN
  Do_Something(a(i));
  Put (a);
END Main;
```

What would be the output, assuming the parameter passing mode is pass by:

e.g. copy: value	A = (1 3 2)
a. reference	A = (0 1 2)
b. copy: value-result	A = (1 3 3)
c. name	A = (1 5 2)

1.3 name 10 / 10

✓ - 0 pts Correct

- 2 pts $A = (1 \ 5 \ 2)$

- 5 pts $A = (1 \ 5 \ 2)$

- 3 pts Question not selected correctly.