



# Group 4

# Summarization Project



Alexis Kaldany  
Ricardo Diaz  
Sagar Tripathi



# Scope

---

Analyzing the relationship between the summary/text ratio and the effectiveness of the model. Our hypothesis is that there is no relationship between the summary/text ratio and the effectiveness of the model.



**HUGGING FACE**

***text\_ratio =***

*"summary\_words\_length"*  
*/ "text\_words\_length"*

# Dataset

---

These datasets contain face-to-face spoken dialogues that cover a wide range of daily-life topics, including schooling, work, medication, shopping, leisure, travel. Most conversations take place between friends, colleagues, and between service providers and customers.



text: text of dialogue.

summary: human written summary of the dialogue.

topic: human written topic/one liner of the dialogue.

id: unique file id of an example.


# EDA



# Dialogue between two people



---

After getting the top word count from the dataset we noticed the data is a dialogue is between two people.



# Difference between Part of Speech

In the summarize text the POS with more count are nouns, comparing to the normal text that has more verbs




# Metric Scores Distribution

The metric created `text_ratio`, which compares the difference between numbers of words in summarize and the text, has a normal distribution.

***text\_ratio*** =

*"summary\_words\_length" /*  
*"text\_words\_length"*



# Summarization Plan

---


1. Identify model for summarization task
2. Identify metrics to calculate effectiveness of model
3. Train the model till metrics plateau.
4. Run model on evaluation set and save predicted summaries
5. Compare predicted summaries to correct summaries to generate metrics which will be used for hypothesis testing



# Model Choice for Summarization Task

## T5 = Text-to-Text Transfer Transformer

- Tried a variety of models using AutoModel, decided on T5-small
  - "facebook/blenderbot\_small-90M", "bert-base-uncased", "t5", "t5-small"
- T5 is an encoder-decoder model pre-trained on a multi-task mixture of unsupervised and supervised tasks and for which each task is converted into a text-to-text format.
- T5 works well on a variety of tasks out-of-the-box by prepending a different prefix to the input corresponding to each task
  - for translation: "translate English to German: ..."
  - for summarization: "summarize: ...."
- T5-small pre-trained on "Colossal Clean Crawled Corpus (C4)"
- T5 is primarily a sequence to sequence model



Cola sentence= is sentence grammatically correct  
Stsb = sentence similarity

# Parameters and Training

---

- Parameters:
  - Learning Rate =  $2e-5$
  - Optimizer = AdamW algorithm
- Training
  - Number of Epochs = 5
  - Each epoch takes ~2 hours
- Evaluation
  - ROUGE-1
  - ROUGE-2
  - ROUGE-L

# ROUGE

- ROUGE = **R**ecall-**O**riented **U**nderstudy for **G**isting **E**valuation
- Compares an automatically produced summary or translation against a reference or a set of references (human-produced) summary or translation
- ROUGE-1 refers to the overlap of unigram (each word) between the system and reference summaries
- ROUGE-2 refers to the overlap of bigrams between the system and reference summaries
- ROUGE-L: Longest Common Subsequence (LCS)[3] based statistics. Longest common subsequence problem takes into account sentence level structure similarity naturally and identifies longest co-occurring in sequence n-grams automatically

I really loved reading the Hunger Games

Machine generated summary

I loved reading the Hunger Games

$$\text{ROUGE-1 recall} = \frac{\text{Num word matches}}{\text{Num words in reference}} = \frac{6}{6}$$

$$\text{ROUGE-1 precision} = \frac{\text{Num word matches}}{\text{Num words in summary}} = \frac{6}{7}$$

$$\text{ROUGE-1 F1-score} = 2 \left( \frac{\text{precision} \cdot \text{recall}}{\text{precision} + \text{recall}} \right)$$

# Examples of Output Improving

---

- Target = “#Person2# has trouble breathing. The doctor asks #Person2# about it and will send #Person2# to a pulmonary specialist.” (rouge-1= 1.0)
- Epoch 1= “#Person2# has **been** breathing **lately** # doctor **wills** #**Person1**# about #. ask send #Person1# to a pulmonary specialist.” (rouge-1=0.5882)
- Epoch 5= “#Person2# has **been** breathing **lately** # doctor tells #Person2# about #. tell send #Person2# to a pulmonary specialist.” (rouge-1 =0.7059)


# Effect of Feature on Target

---

- Feature:
  - Summary to text ratio referred as sum\_text\_ratio
- Targets:
  - Rouge1
  - Rouge2
  - RougeL
- Models Applied for evaluation:
  - Linear Regression

# Relationship between Feature and Target

Target variables have a strong positive correlation with one another, but there is no clear relation between the target variables and feature variable



# Observation of Model evaluation


## Linear Regression

Feature: Summary to text ratio

Target: Rouge1

$R^2$ : 0.018 & Adjusted  $R^2$ : 0.018

	coef	std err	t	P> t	[0.025	0.975]
const	0.5253	0.009	58.133	0.000	0.508	0.543
sum_text_ratio	0.3438	0.051	6.770	0.000	0.244	0.443





# Observation of Model evaluation


## Linear Regression

Feature: Summary to text ratio

Target: Rouge2

$R^2$ : 0.026 & Adjusted  $R^2$ : 0.026

	coef	std err	t	P> t	[0.025	0.975]
const	0.2152	0.011	19.720	0.000	0.194	0.237
sum_text_ratio	0.5003	0.061	8.156	0.000	0.380	0.621



# Observation of Model evaluation


## Linear Regression

Feature: Summary to text ratio

Target: RougeL

$R^2$ : 0.016 & Adjusted  $R^2$ : 0.016

	coef	std err	t	P> t	[0.025	0.975]
const	0.4979	0.009	53.086	0.000	0.480	0.516
sum_text_ratio	0.3410	0.053	6.468	0.000	0.238	0.444



# Conclusion/Inference from the Model:

---

## Conclusion from Linear Regression:

We reject the null hypothesis and accept the alternative hypothesis as  $p < 0.05$ . so, we can say that there is a relationship between Targets (Rouge1, Rouge2 and RougeL) and feature (Summary to text ratio).

As  $R^2$  (Rouge1: 0.018, Rouge2: 0.026, and RougeL: 0.016) and Adjusted  $R^2$  (Rouge1: 0.018, Rouge2: 0.026, and RougeL: 0.016) of the all target variables are near to zero but not zero. Hence, we can conclude that the response variables can be explained by the predictor variable so, there is some relationship between target variables and feature variable.