

# Intro to Neural Network (MLP)

Natural Language Processing

Lecture 6




THE GEORGE  
WASHINGTON  
UNIVERSITY


WASHINGTON, DC

# MLP - Perceptron


- Neurons Respond Slowly
  - $10^{-3}$  s compared to  $10^{-9}$  s for electrical circuits.
- The brain uses massively parallel computation
  - $\approx 10^{11}$  neurons in the brain.
  - $\approx 10^4$  connections per neurons.



# Single input model




# Transfer function




$$a = \text{hardlim}(n)$$

Hard Limit Transfer Function




$$a = \text{hardlim}(wp + b)$$

Single-Input *hardlim* Neuron



$$a = \text{purelin}(n)$$


Linear Transfer Function



$$a = \text{purelin}(wp + b)$$


Single-Input *purelin* Neuron

# Transfer function



$$a = \text{logsig}(n)$$



Log-Sigmoid Transfer Function



$$a = \text{logsig}(wp + b)$$


Single-Input  $\text{logsig}$  Neuron

# Multiple input neuron




Abbreviated Notation

# Layer of neurons






# Abbreviated notation




$$\mathbf{W} = \begin{bmatrix} w_{1,1} & w_{1,2} & \cdots & w_{1,R} \\ w_{2,1} & w_{2,2} & \cdots & w_{2,R} \\ \vdots & \vdots & & \vdots \\ w_{S,1} & w_{S,2} & \cdots & w_{S,R} \end{bmatrix}$$


$$\mathbf{p} = \begin{bmatrix} p_1 \\ p_2 \\ \vdots \\ p_R \end{bmatrix} \quad \mathbf{b} = \begin{bmatrix} b_1 \\ b_2 \\ \vdots \\ b_S \end{bmatrix} \quad \mathbf{a} = \begin{bmatrix} a_1 \\ a_2 \\ \vdots \\ a_S \end{bmatrix}$$

# Multilayer network





# Abbreviated notation





$$\mathbf{a} = \text{hardlims}(\mathbf{W}\mathbf{p} + \mathbf{b})$$

# Two input case



$$a = \text{hardlims}(n) = \text{hardlims}\left(\begin{bmatrix} 1 & 2 \end{bmatrix} \mathbf{p} + (-2)\right)$$

Decision Boundary



$$\mathbf{W}\mathbf{p} + b = 0 \quad \begin{bmatrix} 1 & 2 \end{bmatrix} \mathbf{p} + (-2) = 0$$

- Supervised learning: Network is provided with a set of examples of proper network behavior (inputs and targets)  
 $\{p_1, t_1\}, \{p_2, t_2\}, \dots, \{p_Q, t_Q\}$
- Reinforcement learning: Network is only provided with a grade, or score, which indicates network performance.
- Unsupervised learning: Only network inputs are available to the learning algorithm. Network learns to categorize (cluster) the inputs.

# Learning rule test problem


$$\{\mathbf{p}_1, \mathbf{t}_1\}, \{\mathbf{p}_2, \mathbf{t}_2\}, \dots, \{\mathbf{p}_Q, \mathbf{t}_Q\}$$

$$\left\{ \mathbf{p}_1 = \begin{bmatrix} 1 \\ 2 \end{bmatrix}, t_1 = 1 \right\} \quad \left\{ \mathbf{p}_2 = \begin{bmatrix} -1 \\ 2 \end{bmatrix}, t_2 = 0 \right\} \quad \left\{ \mathbf{p}_3 = \begin{bmatrix} 0 \\ -1 \end{bmatrix}, t_3 = 0 \right\}$$



Random initial weight:

$${}_1\mathbf{w} = \begin{bmatrix} 1.0 \\ -0.8 \end{bmatrix}$$



Present  $\mathbf{p}_1$  to the network:

$$a = \text{hardlim}({}_1\mathbf{w}^T \mathbf{p}_1) = \text{hardlim}\left(\begin{bmatrix} 1.0 & -0.8 \end{bmatrix} \begin{bmatrix} 1 \\ 2 \end{bmatrix}\right)$$

$$a = \text{hardlim}(-0.6) = 0$$

Incorrect Classification.



# Tentative learning rule


Set  ${}_1\mathbf{w}$  to  $\mathbf{p}_1$   $\times$   
– Not stable



Add  $\mathbf{p}_1$  to  ${}_1\mathbf{w}$   $\checkmark$

Tentative Rule: If  $t = 1$  and  $a = 0$ , then  ${}_1\mathbf{w}^{new} = {}_1\mathbf{w}^{old} + \mathbf{p}$

$${}_1\mathbf{w}^{new} = {}_1\mathbf{w}^{old} + \mathbf{p}_1 = \begin{bmatrix} 1.0 \\ -0.8 \end{bmatrix} + \begin{bmatrix} 1 \\ 2 \end{bmatrix} = \begin{bmatrix} 2.0 \\ 1.2 \end{bmatrix}$$




## Second input vector

$$a = \text{hardlim}({}_1\mathbf{w}^T \mathbf{p}_2) = \text{hardlim}\left(\begin{bmatrix} 2.0 & 1.2 \end{bmatrix} \begin{bmatrix} -1 \\ 2 \end{bmatrix}\right)$$

$$a = \text{hardlim}(0.4) = 1 \quad (\text{Incorrect Classification})$$

Modification to Rule: If  $t = 0$  and  $a = 1$ , then  ${}_1\mathbf{w}^{new} = {}_1\mathbf{w}^{old} - \mathbf{p}$

$${}_1\mathbf{w}^{new} = {}_1\mathbf{w}^{old} - \mathbf{p}_2 = \begin{bmatrix} 2.0 \\ 1.2 \end{bmatrix} - \begin{bmatrix} -1 \\ 2 \end{bmatrix} = \begin{bmatrix} 3.0 \\ -0.8 \end{bmatrix}$$




## Third input vector

$$a = \text{hardlim}({}_1\mathbf{w}^T \mathbf{p}_3) = \text{hardlim}\left(\begin{bmatrix} 3.0 & -0.8 \end{bmatrix} \begin{bmatrix} 0 \\ -1 \end{bmatrix}\right)$$

$$a = \text{hardlim}(0.8) = 1 \quad (\text{Incorrect Classification})$$

$${}_1\mathbf{w}^{new} = {}_1\mathbf{w}^{old} - \mathbf{p}_3 = \begin{bmatrix} 3.0 \\ -0.8 \end{bmatrix} - \begin{bmatrix} 0 \\ -1 \end{bmatrix} = \begin{bmatrix} 3.0 \\ 0.2 \end{bmatrix}$$



Patterns are now correctly classified.

$$\text{If } t = a, \text{ then } {}_1\mathbf{w}^{new} = {}_1\mathbf{w}^{old}.$$

# Unified learning rule

If  $t = 1$  and  $a = 0$ , then  ${}_1\mathbf{w}^{new} = {}_1\mathbf{w}^{old} + \mathbf{p}$

If  $t = 0$  and  $a = 1$ , then  ${}_1\mathbf{w}^{new} = {}_1\mathbf{w}^{old} - \mathbf{p}$

If  $t = a$ , then  ${}_1\mathbf{w}^{new} = {}_1\mathbf{w}^{old}$

$$e = t - a$$

If  $e = 1$ , then  ${}_1\mathbf{w}^{new} = {}_1\mathbf{w}^{old} + \mathbf{p}$

If  $e = -1$ , then  ${}_1\mathbf{w}^{new} = {}_1\mathbf{w}^{old} - \mathbf{p}$

If  $e = 0$ , then  ${}_1\mathbf{w}^{new} = {}_1\mathbf{w}^{old}$

$${}_1\mathbf{w}^{new} = {}_1\mathbf{w}^{old} + e\mathbf{p} = {}_1\mathbf{w}^{old} + (t - a)\mathbf{p}$$

$$b^{new} = b^{old} + e$$

A bias is a weight with an input of 1.

# Multiple neuron perceptrons

To update the  $i$ th row of the weight matrix:

$${}_i\mathbf{w}^{new} = {}_i\mathbf{w}^{old} + e_i\mathbf{p}$$

$$b_i^{new} = b_i^{old} + e_i$$

Matrix form:


$$\mathbf{W}^{new} = \mathbf{W}^{old} + \mathbf{e}\mathbf{p}^T$$

$$\mathbf{b}^{new} = \mathbf{b}^{old} + \mathbf{e}$$


## Linear Decision Boundary

$$\mathbf{w}^T \mathbf{p} + b = 0$$

## Linearly Inseparable Problems



- Exercise 1 to 2
- [Class-Ex-Lecture6.py](#)



# MLP - LMS Algorithm




# Basic optimization algorithm

$$\mathbf{x}_{k+1} = \mathbf{x}_k + \alpha_k \mathbf{p}_k$$

or

$$\Delta \mathbf{x}_k = (\mathbf{x}_{k+1} - \mathbf{x}_k) = \alpha_k \mathbf{p}_k$$



$\mathbf{p}_k$  - Search Direction

$\alpha_k$  - Learning Rate

Choose the next step so that the function decreases:

$$F(\mathbf{x}_{k+1}) < F(\mathbf{x}_k)$$

For small changes in  $\mathbf{x}$  we can approximate  $F(\mathbf{x})$ :

$$F(\mathbf{x}_{k+1}) = F(\mathbf{x}_k + \Delta\mathbf{x}_k) \approx F(\mathbf{x}_k) + \mathbf{g}_k^T \Delta\mathbf{x}_k$$

where

$$\mathbf{g}_k \equiv \nabla F(\mathbf{x}) \big|_{\mathbf{x} = \mathbf{x}_k}$$

If we want the function to decrease:

$$\mathbf{g}_k^T \Delta\mathbf{x}_k = \alpha_k \mathbf{g}_k^T \mathbf{p}_k < 0$$

We can maximize the decrease by choosing:

$$\mathbf{p}_k = -\mathbf{g}_k$$

$$\mathbf{x}_{k+1} = \mathbf{x}_k - \alpha_k \mathbf{g}_k$$


$$F(\mathbf{x}) = x_1^2 + 2x_1x_2 + 2x_2^2 + x_1$$

$$\mathbf{x}_0 = \begin{bmatrix} 0.5 \\ 0.5 \end{bmatrix} \quad \alpha = 0.1$$

$$\nabla F(\mathbf{x}) = \begin{bmatrix} \frac{\partial}{\partial x_1} F(\mathbf{x}) \\ \frac{\partial}{\partial x_2} F(\mathbf{x}) \end{bmatrix} = \begin{bmatrix} 2x_1 + 2x_2 + 1 \\ 2x_1 + 4x_2 \end{bmatrix} \quad \mathbf{g}_0 = \nabla F(\mathbf{x})|_{\mathbf{x}=\mathbf{x}_0} = \begin{bmatrix} 3 \\ 3 \end{bmatrix}$$

$$\mathbf{x}_1 = \mathbf{x}_0 - \alpha \mathbf{g}_0 = \begin{bmatrix} 0.5 \\ 0.5 \end{bmatrix} - 0.1 \begin{bmatrix} 3 \\ 3 \end{bmatrix} = \begin{bmatrix} 0.2 \\ 0.2 \end{bmatrix}$$

$$\mathbf{x}_2 = \mathbf{x}_1 - \alpha \mathbf{g}_1 = \begin{bmatrix} 0.2 \\ 0.2 \end{bmatrix} - 0.1 \begin{bmatrix} 1.8 \\ 1.2 \end{bmatrix} = \begin{bmatrix} 0.02 \\ 0.08 \end{bmatrix}$$



$$F(\mathbf{x}_{k+1}) = F(\mathbf{x}_k + \Delta\mathbf{x}_k) \approx F(\mathbf{x}_k) + \mathbf{g}_k^T \Delta\mathbf{x}_k + \frac{1}{2} \Delta\mathbf{x}_k^T \mathbf{A}_k \Delta\mathbf{x}_k$$

Take the gradient of this second-order approximation and set it equal to zero to find the stationary point:

$$\mathbf{g}_k + \mathbf{A}_k \Delta\mathbf{x}_k = \mathbf{0}$$

$$\Delta\mathbf{x}_k = -\mathbf{A}_k^{-1} \mathbf{g}_k$$

$$\mathbf{x}_{k+1} = \mathbf{x}_k - \mathbf{A}_k^{-1} \mathbf{g}_k$$

$$F(\mathbf{x}) = x_1^2 + 2x_1x_2 + 2x_2^2 + x_1$$


$$\mathbf{x}_0 = \begin{bmatrix} 0.5 \\ 0.5 \end{bmatrix}$$

$$\nabla F(\mathbf{x}) = \begin{bmatrix} \frac{\partial}{\partial x_1} F(\mathbf{x}) \\ \frac{\partial}{\partial x_2} F(\mathbf{x}) \end{bmatrix} = \begin{bmatrix} 2x_1 + 2x_2 + 1 \\ 2x_1 + 4x_2 \end{bmatrix}$$

$$\mathbf{g}_0 = \nabla F(\mathbf{x})|_{\mathbf{x}=\mathbf{x}_0} = \begin{bmatrix} 3 \\ 3 \end{bmatrix}$$

$$\mathbf{A} = \begin{bmatrix} 2 & 2 \\ 2 & 4 \end{bmatrix}$$



$$\mathbf{x}_1 = \begin{bmatrix} 0.5 \\ 0.5 \end{bmatrix} - \begin{bmatrix} 2 & 2 \\ 2 & 4 \end{bmatrix}^{-1} \begin{bmatrix} 3 \\ 3 \end{bmatrix} = \begin{bmatrix} 0.5 \\ 0.5 \end{bmatrix} - \begin{bmatrix} 1 & -0.5 \\ -0.5 & 0.5 \end{bmatrix} \begin{bmatrix} 3 \\ 3 \end{bmatrix} = \begin{bmatrix} 0.5 \\ 0.5 \end{bmatrix} - \begin{bmatrix} 1.5 \\ 0 \end{bmatrix} = \begin{bmatrix} -1 \\ 0.5 \end{bmatrix}$$



# Non-Quadratic Example


$$F(\mathbf{x}) = (x_2 - x_1)^4 + 8x_1x_2 - x_1 + x_2 + 3$$

Stationary Points:  $\mathbf{x}^1 = \begin{bmatrix} -0.42 \\ 0.42 \end{bmatrix}$      $\mathbf{x}^2 = \begin{bmatrix} -0.13 \\ 0.13 \end{bmatrix}$      $\mathbf{x}^3 = \begin{bmatrix} 0.55 \\ -0.55 \end{bmatrix}$






# Different Initial Conditions



# ADALINE Network



$$\mathbf{a} = \text{purelin}(\mathbf{W}\mathbf{p} + \mathbf{b}) = \mathbf{W}\mathbf{p} + \mathbf{b}$$

$$a_i = \text{purelin}(n_i) = \text{purelin}({}_i\mathbf{w}^T \mathbf{p} + b_i) = {}_i\mathbf{w}^T \mathbf{p} + b_i$$

$${}_i\mathbf{w} = \begin{bmatrix} w_{i,1} \\ w_{i,2} \\ \vdots \\ w_{i,R} \end{bmatrix}$$

Training Set:

$$\{\mathbf{p}_1, \mathbf{t}_1\}, \{\mathbf{p}_2, \mathbf{t}_2\}, \dots, \{\mathbf{p}_Q, \mathbf{t}_Q\}$$

Input:  $\mathbf{p}_q$       Target:  $\mathbf{t}_q$

Notation:

$$\mathbf{x} = \begin{bmatrix} 1 \\ \mathbf{w} \\ b \end{bmatrix} \quad \mathbf{z} = \begin{bmatrix} \mathbf{p} \\ 1 \end{bmatrix} \quad a = \mathbf{z}^T \mathbf{w} + b \quad \Rightarrow \quad a = \mathbf{x}^T \mathbf{z}$$

Mean Square Error:

$$F(\mathbf{x}) = E[e^2] = E[(t - a)^2] = E[(t - \mathbf{x}^T \mathbf{z})^2]$$

$$F(\mathbf{x}) = E[e^2] = E[(t - a)^2] = E[(t - \mathbf{x}^T \mathbf{z})^2]$$

$$F(\mathbf{x}) = E[t^2 - 2t\mathbf{x}^T \mathbf{z} + \mathbf{x}^T \mathbf{z} \mathbf{z}^T \mathbf{x}]$$

$$F(\mathbf{x}) = E[t^2] - 2\mathbf{x}^T E[t\mathbf{z}] + \mathbf{x}^T E[\mathbf{z} \mathbf{z}^T] \mathbf{x}$$

$$F(\mathbf{x}) = c - 2\mathbf{x}^T \mathbf{h} + \mathbf{x}^T \mathbf{R} \mathbf{x}$$

$$c = E[t^2] \quad \mathbf{h} = E[t\mathbf{z}] \quad \mathbf{R} = E[\mathbf{z} \mathbf{z}^T]$$

*The mean square error for the ADALINE Network is a quadratic function:*

$$F(\mathbf{x}) = c + \mathbf{d}^T \mathbf{x} + \frac{1}{2} \mathbf{x}^T \mathbf{A} \mathbf{x}$$

$$\mathbf{d} = -2\mathbf{h} \quad \mathbf{A} = 2\mathbf{R}$$

# Approximate Steepest Descent

Approximate mean square error (one sample):

$$\hat{F}(\mathbf{x}) = (t(k) - a(k))^2 = e^2(k)$$

Approximate (stochastic) gradient:

$$\hat{\nabla} F(\mathbf{x}) = \nabla e^2(k)$$

$$[\nabla e^2(k)]_j = \frac{\partial e^2(k)}{\partial w_{1,j}} = 2e(k) \frac{\partial e(k)}{\partial w_{1,j}} \quad j = 1, 2, \dots, R$$

$$[\nabla e^2(k)]_{R+1} = \frac{\partial e^2(k)}{\partial b} = 2e(k) \frac{\partial e(k)}{\partial b}$$

# Approximate Gradient Calculation

$$\frac{\partial e(k)}{\partial w_{1,j}} = \frac{\partial [t(k) - a(k)]}{\partial w_{1,j}} = \frac{\partial}{\partial w_{1,j}} [t(k) - (\mathbf{w}^T \mathbf{p}(k) + b)]$$

$$\frac{\partial e(k)}{\partial w_{1,j}} = \frac{\partial}{\partial w_{1,j}} \left[ t(k) - \left( \sum_{i=1}^R w_{1,i} p_i(k) + b \right) \right]$$

$$\frac{\partial e(k)}{\partial w_{1,j}} = -p_j(k) \qquad \frac{\partial e(k)}{\partial b} = -1$$

$$\hat{\nabla} F(\mathbf{x}) = \nabla e^2(k) = -2e(k)\mathbf{z}(k)$$

$$\mathbf{x}_{k+1} = \mathbf{x}_k - \alpha \nabla F(\mathbf{x}) \Big|_{\mathbf{x} = \mathbf{x}_k}$$

$$\mathbf{x}_{k+1} = \mathbf{x}_k + 2\alpha e(k)\mathbf{z}(k)$$

$$\mathbf{w}(k+1) = \mathbf{w}(k) + 2\alpha e(k)\mathbf{p}(k)$$

$$b(k+1) = b(k) + 2\alpha e(k)$$

$${}_i\mathbf{w}(k+1) = {}_i\mathbf{w}(k) + 2\alpha e_i(k)\mathbf{p}(k)$$

$$b_i(k+1) = b_i(k) + 2\alpha e_i(k)$$


Matrix Form:

$$\mathbf{W}(k+1) = \mathbf{W}(k) + 2\alpha \mathbf{e}(k)\mathbf{p}^T(k)$$

$$\mathbf{b}(k+1) = \mathbf{b}(k) + 2\alpha \mathbf{e}(k)$$




- Exercise 3 to 4
- [Class-Ex-Lecture6.py](#)



# MLP -Backpropagation

# Multilayer Network



$$\mathbf{a}^{m+1} = \mathbf{f}^{m+1}(\mathbf{W}^{m+1} \mathbf{a}^m + \mathbf{b}^{m+1}) \quad m = 0, 2, \dots, M-1$$

$$\mathbf{a}^0 = \mathbf{p}$$

$$\mathbf{a} = \mathbf{a}^M$$

## Training Set

$$\{\mathbf{p}_1, \mathbf{t}_1\}, \{\mathbf{p}_2, \mathbf{t}_2\}, \dots, \{\mathbf{p}_Q, \mathbf{t}_Q\}$$

## Mean Square Error

$$F(\mathbf{x}) = E[e^2] = E[(t - a)^2]$$

## Vector Case

$$F(\mathbf{x}) = E[\mathbf{e}^T \mathbf{e}] = E[(\mathbf{t} - \mathbf{a})^T (\mathbf{t} - \mathbf{a})]$$

## Approximate Mean Square Error (Single Sample)

$$\hat{F}(\mathbf{x}) = (\mathbf{t}(k) - \mathbf{a}(k))^T (\mathbf{t}(k) - \mathbf{a}(k)) = \mathbf{e}^T(k) \mathbf{e}(k)$$

## Approximate Steepest Descent

$$w_{i,j}^m(k+1) = w_{i,j}^m(k) - \alpha \frac{\partial \hat{F}}{\partial w_{i,j}^m} \quad b_i^m(k+1) = b_i^m(k) - \alpha \frac{\partial \hat{F}}{\partial b_i^m}$$

$$\frac{df(n(w))}{dw} = \frac{df(n)}{dn} \times \frac{dn(w)}{dw}$$

Example

$$f(n) = \cos(n) \quad n = e^{2w} \quad f(n(w)) = \cos(e^{2w})$$

$$\frac{df(n(w))}{dw} = \frac{df(n)}{dn} \times \frac{dn(w)}{dw} = (-\sin(n))(2e^{2w}) = (-\sin(e^{2w}))(2e^{2w})$$

Application to Gradient Calculation

$$\frac{\partial \hat{F}}{\partial w_{i,j}^m} = \frac{\partial \hat{F}}{\partial n_i^m} \times \frac{\partial n_i^m}{\partial w_{i,j}^m} \quad \frac{\partial \hat{F}}{\partial b_i^m} = \frac{\partial \hat{F}}{\partial n_i^m} \times \frac{\partial n_i^m}{\partial b_i^m}$$

$$n_i^m = \sum_{j=1}^{S^{m-1}} w_{i,j}^m a_j^{m-1} + b_i^m$$

$$\frac{\partial n_i^m}{\partial w_{i,j}^m} = a_j^{m-1} \qquad \frac{\partial n_i^m}{\partial b_i^m} = 1$$

Sensitivity

$$s_i^m \equiv \frac{\partial \hat{F}}{\partial n_i^m}$$

Gradient

$$\frac{\partial \hat{F}}{\partial w_{i,j}^m} = s_i^m a_j^{m-1} \qquad \frac{\partial \hat{F}}{\partial b_i^m} = s_i^m$$

$$w_{i,j}^m(k+1) = w_{i,j}^m(k) - \alpha s_i^m a_j^{m-1} \quad b_i^m(k+1) = b_i^m(k) - \alpha s_i^m$$

$$\mathbf{W}^m(k+1) = \mathbf{W}^m(k) - \alpha \mathbf{s}^m (\mathbf{a}^{m-1})^T \quad \mathbf{b}^m(k+1) = \mathbf{b}^m(k) - \alpha \mathbf{s}^m$$

$$\mathbf{s}^m \equiv \frac{\partial \hat{F}}{\partial \mathbf{n}^m} = \begin{bmatrix} \frac{\partial \hat{F}}{\partial n_1^m} \\ \frac{\partial \hat{F}}{\partial n_2^m} \\ \vdots \\ \frac{\partial \hat{F}}{\partial n_{s^m}^m} \end{bmatrix}$$

Next Step: Compute the Sensitivities (Backpropagation)

# Jacobian Matrix

$$\frac{\partial \mathbf{n}^{m+1}}{\partial \mathbf{n}^m} \equiv \begin{bmatrix} \frac{\partial n_1^{m+1}}{\partial n_1^m} & \frac{\partial n_1^{m+1}}{\partial n_2^m} & \dots & \frac{\partial n_1^{m+1}}{\partial n_{S^m}^m} \\ \frac{\partial n_2^{m+1}}{\partial n_1^m} & \frac{\partial n_2^{m+1}}{\partial n_2^m} & \dots & \frac{\partial n_2^{m+1}}{\partial n_{S^m}^m} \\ \vdots & \vdots & & \vdots \\ \frac{\partial n_{S^{m+1}}^{m+1}}{\partial n_1^m} & \frac{\partial n_{S^{m+1}}^{m+1}}{\partial n_2^m} & \dots & \frac{\partial n_{S^{m+1}}^{m+1}}{\partial n_{S^m}^m} \end{bmatrix}$$

$$\frac{\partial \mathbf{n}^{m+1}}{\partial \mathbf{n}^m} = \mathbf{W}^{m+1} \mathbf{F}^m(\mathbf{n}^m)$$

$$\frac{\partial n_i^{m+1}}{\partial n_j^m} = \frac{\partial \left( \sum_{l=1}^{S^m} w_{i,l}^{m+1} a_l^m + b_i^{m+1} \right)}{\partial n_j^m} = w_{i,j}^{m+1} \frac{\partial a_j^m}{\partial n_j^m}$$

$$\frac{\partial n_i^{m+1}}{\partial n_j^m} = w_{i,j}^{m+1} \frac{\partial f^m(n_j^m)}{\partial n_j^m} = w_{i,j}^{m+1} f'^m(n_j^m)$$

$$f'^m(n_j^m) = \frac{\partial f^m(n_j^m)}{\partial n_j^m}$$

$$\mathbf{F}^m(\mathbf{n}^m) = \begin{bmatrix} f^m(n_1^m) & 0 & \dots & 0 \\ 0 & f^m(n_2^m) & \dots & 0 \\ \vdots & \vdots & & \vdots \\ 0 & 0 & \dots & f^m(n_{S^m}^m) \end{bmatrix}$$



# Backpropagation (Sensitivities)

$$\mathbf{s}^m = \frac{\partial \hat{F}}{\partial \mathbf{n}^m} = \left( \frac{\partial \mathbf{n}^{m+1}}{\partial \mathbf{n}^m} \right)^T \frac{\partial \hat{F}}{\partial \mathbf{n}^{m+1}} = \dot{\mathbf{F}}^m(\mathbf{n}^m) (\mathbf{W}^{m+1})^T \frac{\partial \hat{F}}{\partial \mathbf{n}^{m+1}}$$

$$\mathbf{s}^m = \dot{\mathbf{F}}^m(\mathbf{n}^m) (\mathbf{W}^{m+1})^T \mathbf{s}^{m+1}$$

The sensitivities are computed by starting at the last layer, and then propagating backwards through the network to the first layer.

$$\mathbf{s}^M \rightarrow \mathbf{s}^{M-1} \rightarrow \dots \rightarrow \mathbf{s}^2 \rightarrow \mathbf{s}^1$$

## Initialization (Last Layer)

$$s_i^M = \frac{\partial \hat{F}}{\partial n_i^M} = \frac{\partial (\mathbf{t} - \mathbf{a})^T (\mathbf{t} - \mathbf{a})}{\partial n_i^M} = \frac{\partial \sum_{j=1}^{S^M} (t_j - a_j)^2}{\partial n_i^M} = -2(t_i - a_i) \frac{\partial a_i}{\partial n_i^M}$$

$$\frac{\partial a_i}{\partial n_i^M} = \frac{\partial a_i^M}{\partial n_i^M} = \frac{\partial f^M(n_i^M)}{\partial n_i^M} = f^M(n_i^M)$$

$$s_i^M = -2(t_i - a_i) f^M(n_i^M)$$

$$\mathbf{s}^M = -2\mathbf{F}^M(\mathbf{n}^M)(\mathbf{t} - \mathbf{a})$$

## Forward Propagation

$$\mathbf{a}^0 = \mathbf{p}$$

$$\mathbf{a}^{m+1} = \mathbf{f}^{m+1}(\mathbf{W}^{m+1} \mathbf{a}^m + \mathbf{b}^{m+1}) \quad m = 0, 2, \dots, M-1$$

$$\mathbf{a} = \mathbf{a}^M$$

## Backpropagation


$$\mathbf{s}^M = -2\mathbf{F}^M(\mathbf{n}^M)(\mathbf{t} - \mathbf{a})$$

$$\mathbf{s}^m = \mathbf{F}^m(\mathbf{n}^m)(\mathbf{W}^{m+1})^T \mathbf{s}^{m+1} \quad m = M-1, \dots, 2, 1$$

## Weight Update


$$\mathbf{W}^m(k+1) = \mathbf{W}^m(k) - \alpha \mathbf{s}^m (\mathbf{a}^{m-1})^T \quad \mathbf{b}^m(k+1) = \mathbf{b}^m(k) - \alpha \mathbf{s}^m$$

- Exercise 5 to 5
- [Class-Ex-Lecture6.py](#)




# RELU - Poslin

# Transfer (activation) functions (1)




$$a = \text{hardlim}(n)$$

Hard Limit Transfer Function




$$a = \text{hardlim}(wp + b)$$

Single-Input *hardlim* Neuron



$$a = \text{purelin}(n)$$


Linear Transfer Function



$$a = \text{purelin}(wp + b)$$


Single-Input *purelin* Neuron

# Transfer (activation) functions (2)




$$a = \text{logsig}(n)$$

Log-Sigmoid Transfer Function




$$a = \text{logsig}(wp + b)$$

Single-Input *logsig* Neuron



$$a = \text{poslin}(n)$$

Positive Linear Function



$$a = \text{poslin}(wp + b)$$

Single-Input *poslin* Neuron

## Transfer (activation) functions (3)

Softmax

$$a_i = f_i(\mathbf{n}) = \frac{e^{n_i}}{\sum_{j=1}^S e^{n_j}}$$

Used at the output layer of a pattern recognition network with multiple output neurons.



## Training Set

$$\{\mathbf{p}_1, \mathbf{t}_1\}, \{\mathbf{p}_2, \mathbf{t}_2\}, \dots, \{\mathbf{p}_Q, \mathbf{t}_Q\}$$

## Performance Indices

### *Mean Square Error*

$$F(\mathbf{x}) = \frac{1}{QS^M} \sum_{q=1}^Q \sum_{i=1}^{S^M} (t_{i,q} - a_{i,q}^M)^2$$

### *Cross Entropy*

$$F(\mathbf{x}) = - \sum_{q=1}^Q \sum_{i=1}^{S^M} t_{i,q} \ln \frac{a_{i,q}^M}{t_{i,q}}$$

# Example transfer function derivatives


## Poslin

$$\dot{\mathbf{F}}^m(\mathbf{n}^m) = \begin{bmatrix} \text{hardlim}(n_1^m) & 0 & \cdots & 0 \\ 0 & \text{hardlim}(n_2^m) & \cdots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \cdots & \text{hardlim}(n_{S^m}^m) \end{bmatrix}$$

## Softmax





$$\dot{\mathbf{F}}^m(\mathbf{n}^m) = \begin{bmatrix} a_1^m \left( \sum_{i=1}^{S^m} a_i^m - a_1^m \right) & -a_1^m a_2^m & \cdots & -a_1^m a_{S^m}^m \\ -a_2^m a_1^m & a_2^m \left( \sum_{i=1}^{S^m} a_i^m - a_2^m \right) & \cdots & -a_2^m a_{S^m}^m \\ \vdots & \vdots & \ddots & \vdots \\ -a_{S^m}^m a_1^m & -a_{S^m}^m a_2^m & \cdots & a_{S^m}^m \left( \sum_{i=1}^{S^m} a_i^m - a_{S^m}^m \right) \end{bmatrix}$$

# Poslin network




# Poslin network function

$$\mathbf{W}^1 = \begin{bmatrix} 1 & 1 \end{bmatrix}^T, \mathbf{b}^1 = \begin{bmatrix} -1 & 1 \end{bmatrix}^T$$
$$\mathbf{W}^2 = \begin{bmatrix} -1 & 1 \end{bmatrix}, \mathbf{b}^2 = \begin{bmatrix} 0 \end{bmatrix}$$





# 2D poslin network




$$\mathbf{W}^1 = \begin{bmatrix} 1 & -1 & -1 & 1 \\ 1 & -1 & 1 & -1 \end{bmatrix}^T, \mathbf{b}^1 = [-1 \quad 3 \quad 1 \quad 1]^T$$

$$\mathbf{W}^2 = [-1 \quad -1 \quad -1 \quad -1], \mathbf{b}^2 = [5]$$

# 2D Poslin network surface and decision boundary



# Summary (backpropagation)



$$\frac{\partial \hat{F}(\mathbf{x})}{\partial \mathbf{n}^1} = \frac{\partial \mathbf{a}^1}{\partial \mathbf{n}^1} \times \frac{\partial \mathbf{n}^2}{\partial \mathbf{a}^1} \times \frac{\partial \mathbf{a}^2}{\partial \mathbf{n}^2} \times \frac{\partial \mathbf{n}^3}{\partial \mathbf{a}^2} \times \frac{\partial \mathbf{a}^3}{\partial \mathbf{n}^3} \times \frac{\partial \hat{F}(\mathbf{x})}{\partial \mathbf{a}^3}$$

$$\frac{\partial \hat{F}(\mathbf{x})}{\partial \mathbf{n}^m} = \frac{\partial \mathbf{a}^m}{\partial \mathbf{n}^m} \times \frac{\partial \mathbf{n}^{m+1}}{\partial \mathbf{a}^m} \times \frac{\partial \hat{F}(\mathbf{x})}{\partial \mathbf{n}^{m+1}} = \dot{\mathbf{F}}(\mathbf{n}^m) (\mathbf{W}^{m+1})^T \frac{\partial \hat{F}(\mathbf{x})}{\partial \mathbf{n}^{m+1}}$$