International
IOR Rectifier

PD - 95397

IRF7509PbF

HEXFET® Power MOSFET

- Generation V Technology
- Ultra Low On-Resistance
- Dual N and P Channel MOSFET
- Very Small SOIC Package
- Low Profile (<1.1mm)
- Available in Tape & Reel
- Fast Switching
- Lead-Free



Top View

	N-Ch	P-Ch
V_{DSS}	30V	-30V
$R_{DS(on)}$	0.11Ω	0.20Ω

Description

Fifth Generation HEXFETs from International Rectifier utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. This benefit, combined with the fast switching speed and ruggedized device design that HEXFET Power MOSFETs are well known for, provides the designer with an extremely efficient and reliable device for use in a wide variety of applications.

The new Micro8 package, with half the footprint area of the standard SO-8, provides the smallest footprint available in an SOIC outline. This makes the Micro8 an ideal device for applications where printed circuit board space is at a premium. The low profile (<1.1mm) of the Micro8 will allow it to fit easily into extremely thin application environments such as portable electronics and PCMCIA cards.


Micro8

Absolute Maximum Ratings

	Parameter	Max.		Units
		N-Channel	P-Channel	
V_{DS}	Drain-Source Voltage	30	-30	V
I_D @ T_A = 25°C	Continuous Drain Current, V_{GS}	2.7	-2.0	A
I_D @ T_A = 70°C	Continuous Drain Current, V_{GS}	2.1	-1.6	A
I_{DM}	Pulsed Drain Current①	21	-16	A
P_D @T_A = 25°C	Maximum Power Dissipation④	1.25		W
P_D @T_A = 70°C	Maximum Power Dissipation④	0.8		W
	Linear Derating Factor	10		mW/°C
V_{GS}	Gate-to-Source Voltage	± 20		V
V_{GSM}	Gate-to-Source Voltage Single Pulse tp<10µS	30		V
dv/dt	Peak Diode Recovery dv/dt ②	5.0		V/ns
T_J , T_{STG}	Junction and Storage Temperature Range	-55 to + 150		°C
	Soldering Temperature, for 10 seconds	240 (1.6mm from case)		

Thermal Resistance

	Parameter	Max.	Units
$R_{\theta JA}$	Maximum Junction-to-Ambient ④	100	°C/W

6/15/04

Electrical Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter		Min.	Typ.	Max.	Units	Conditions
$V_{(BR)DSS}$	Drain-to-Source Breakdown Voltage	N-Ch	30	—	—	V	V_{GS} = 0V, I_D = 250µA
		P-Ch	-30	—	—		V_{GS} = 0V, I_D = -250µA
$\Delta V_{(BR)DSS}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	N-Ch	—	0.059	—	V/°C	Reference to 25°C, I_D = 1mA
		P-Ch	—	-0.039	—		Reference to 25°C, I_D = -1mA
$R_{DS(ON)}$	Static Drain-to-Source On-Resistance	N-Ch	—	0.09	0.110	Ω	V_{GS} = 10V, I_D = 1.7A ④
			—	0.14	0.175		V_{GS} = 4.5V, I_D = 0.85A ④
		P-Ch	—	0.17	0.20		V_{GS} = -10V, I_D =-1.2A ④
			—	0.30	0.40		V_{GS} = -4.5V, I_D =-0.6A ④
$V_{GS(th)}$	Gate Threshold Voltage	N-Ch	1.0	—	—	V	V_{DS} = V_{GS}, I_D = 250µA
		P-Ch	-1.0	—	—		V_{DS} = V_{GS}, I_D = -250µA
g_{fs}	Forward Transconductance	N-Ch	1.9	—	—	S	V_{DS} = 10V, I_D = 0.85A ④
		P-Ch	0.92	—	—		V_{DS} = -10V, I_D = -0.6A ④
I_{DSS}	Drain-to-Source Leakage Current	N-Ch	—	—	1.0	µA	V_{DS} = 24 V, V_{GS} = 0V
		P-Ch	—	—	-1.0		V_{DS} = -24V, V_{GS} = 0V
		N-Ch	—	—	25		V_{DS} = 24 V, V_{GS} = 0V, T_J = 125°C
		P-Ch	—	—	-25		V_{DS} = -24V, V_{GS} = 0V, T_J = 125°C
I_{GSS}	Gate-to-Source Forward Leakage	N-P	—	—	±100		V_{GS} = ± 20V
Q_g	Total Gate Charge	N-Ch	—	7.8	12	nC	N-Channel I_D = 1.7A, V_{DS} = 24V, V_{GS} = 10V ④ P-Channel I_D = -1.2A, V_{DS} = -24V, V_{GS} = -10V
		P-Ch	—	7.5	11		
Q_{gs}	Gate-to-Source Charge	N-Ch	—	1.2	1.8		
		P-Ch	—	1.3	1.9		
Q_{gd}	Gate-to-Drain ("Miller") Charge	N-Ch	—	2.5	3.8		
		P-Ch	—	2.5	3.7		
$t_{d(on)}$	Turn-On Delay Time	N-Ch	—	4.7	—	ns	N-Channel V_{DD} = 15V, I_D = 1.7A, R_G = 6.1Ω, R_D = 8.7Ω ④ P-Channel V_{DD} = -15V, I_D = -1.2A, R_G = 6.2Ω, R_D = 12Ω
		P-Ch	—	9.7	—		
t_r	Rise Time	N-Ch	—	10	—		
		P-Ch	—	12	—		
$t_{d(off)}$	Turn-Off Delay Time	N-Ch	—	12	—		
		P-Ch	—	19	—		
t_f	Fall Time	N-Ch	—	5.3	—		
		P-Ch	—	9.3	—		
C_{iss}	Input Capacitance	N-Ch	—	210	—	pF	N-Channel V_{GS} = 0V, V_{DS} = 25V, f = 1.0MHz ③ P-Channel V_{GS} = 0V, V_{DS} = -25V, f = 1.0MHz
		P-Ch	—	180	—		
C_{oss}	Output Capacitance	N-Ch	—	80	—		
		P-Ch	—	87	—		
C_{rss}	Reverse Transfer Capacitance	N-Ch	—	32	—		
		P-Ch	—	42	—		

Source-Drain Ratings and Characteristics

	Parameter		Min.	Typ.	Max.	Units	Conditions
I_S	Continuous Source Current (Body Diode)	N-Ch	—	—	1.25	A	
		P-Ch	—	—	-1.25		
I_{SM}	Pulsed Source Current (Body Diode) ①	N-Ch	—	—	21		
		P-Ch	—	—	-16		
V_{SD}	Diode Forward Voltage	N-Ch	—	—	1.2	V	T_J = 25°C, I_S = 1.7A, V_{GS} = 0V ③
		P-Ch	—	—	-1.2		T_J = 25°C, I_S = -1.8A, V_{GS} = 0V ③
t_{rr}	Reverse Recovery Time	N-Ch	—	40	60	ns	N-Channel T_J = 25°C, I_F = 1.7A, di/dt = 100A/µs P-Channel ③ T_J = 25°C, I_F = -1.2A, di/dt = -100A/µs
		P-Ch	—	30	45		
Q_{rr}	Reverse Recovery Charge	N-Ch	—	48	72	nC	
		P-Ch	—	37	55		

Notes:

① Repetitive rating; pulse width limited by max. junction temperature. (See fig. 21)

② N-Channel I_{SD} ≤ 1.7A, di/dt ≤ 120A/µs, V_{DD} ≤ $V_{(BR)DSS}$, T_J ≤ 150°C
P-Channel I_{SD} ≤ -1.2A, di/dt ≤ 160A/µs, V_{DD} ≤ $V_{(BR)DSS}$, T_J ≤ 150°C

③ Pulse width ≤ 300µs; duty cycle ≤ 2%.

④ Surface mounted on FR-4 board, t ≤ 10sec.



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. Typical Transfer Characteristics



Fig 4. Typical Source-Drain Diode Forward Voltage



Fig 5. Normalized On-Resistance Vs. Temperature



Fig 6. Typical On-Resistance Vs. Drain Current



Fig 7. Typical On-Resistance Vs. Gate Voltage



Fig 8. Maximum Safe Operating Area



Fig 9. Typical Capacitance Vs. Drain-to-Source Voltage



Fig 10. Typical Gate Charge Vs. Gate-to-Source Voltage



Fig 11. Typical Output Characteristics



Fig 12. Typical Output Characteristics



Fig 13. Typical Transfer Characteristics



Fig 14. Typical Source-Drain Diode Forward Voltage



Fig 15. Normalized On-Resistance Vs. Temperature



Fig 16. Typical On-Resistance Vs. Drain Current

P - Channel



Fig 17. Typical On-Resistance Vs. Gate Voltage



Fig 18. Maximum Safe Operating Area



Fig 19. Typical Capacitance Vs. Drain-to-Source Voltage



Fig 20. Typical Gate Charge Vs. Gate-to-Source Voltage

N-P - Channel



Fig 21. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

Micro8 Package Outline

Dimensions are shown in milimeters (inches)



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.036	.044	0.91	1.11
A1	.004	.008	0.10	0.20
B	.010	.014	0.25	0.36
C	.005	.007	0.13	0.18
D	.116	.120	2.95	3.05
e	.0256 BASIC		0.65 BASIC	
e1	.0128 BASIC		0.33 BASIC	
E	.116	.120	2.95	3.05
H	.188	.198	4.78	5.03
L	.016	.026	0.41	0.66
θ	0°	6°	0°	6°

NOTES:
1 DIMENSIONING AND TOLERANCING PER ANSI Y14.5M-1982.
2 CONTROLLING DIMENSION : INCH.
3 DIMENSIONS DO NOT INCLUDE MOLD FLASH.

Micro8 Part Marking Information

EXAMPLE: THIS IS AN IRF7501



WW = (1-26) IF PRECEDED BY LAST DIGIT OF CALENDAR YEAR

YEAR	Y	WORK WEEK	W
2001	1	01	A
2002	2	02	B
2003	3	03	C
2004	4	04	D
2005	5		
2006	6		
2007	7		
2008	8		
2009	9		
2010	0	24	X
		25	Y
		26	Z

WW = (27-52) IF PRECEDED BY A LETTER

YEAR	Y	WORK WEEK	W
2001	A	27	A
2002	B	28	B
2003	C	29	C
2004	D	30	D
2005	E		
2006	F		
2007	G		
2008	H		
2009	J		
2010	K	50	X
		51	Y
		52	Z

Micro8 Tape & Reel Information

Dimensions are shown in millimeters (inches)



NOTES:
1. OUTLINE CONFORMS TO EIA-481 & EIA-541.
2. CONTROLLING DIMENSION : MILLIMETER.



NOTES :
1. CONTROLLING DIMENSION : MILLIMETER.
2. OUTLINE CONFORMS TO EIA-481 & EIA-541.

Data and specifications subject to change without notice.
This product has been designed and qualified for the Consumer market.
Qualification Standards can be found on IR's Web site.

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903
Visit us at www.irf.com for sales contact information.06/04

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie") .

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office (**www.infineon.com**).

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Infineon:
IRF7509TRPBF