

# Does God play Tetris? - Team reference document

## Program submission checklist:

1. Works on sample inputs given.
2. Works on other sensible inputs.
3. Works on pathological inputs/corner cases.
4. Works in time on the largest possible inputs.
5. Works within memory limit (if given) use -Xmx128m for a limit of 128mb for example.
6. Compiles! (with warnings on! -Xlint)
7. No debug outputs!

## Code

### Big sample

```
import java.io.*;
import java.util.*;
import java.math.*;
public class samplecode {
    public static void debug(String s) {
        System.out.printf(">>>%s>>>\n", s); //Comment this out to kill n birds with two /
    }
    public static void main(String[] args) throws Exception {
        BufferedReader br = new BufferedReader(new InputStreamReader(System.in));
        String s1 = br.readLine();
        int a = Integer.parseInt(s1.split(" ")[0]);
        String[] arr = s1.split(" ");

        // Does God play Tetris? used java.util.Collections, it's super effective!

        // A comparator can be defined by
        class MyClassCmp implements Comparator<MyClass> {
            // Should return a negative integer, zero, or a positive integer as the first
            argument is less than, equal to, or greater than the second respectively
            public int compare(MyClass a, MyClass b) {
                return a.a - b.a; }
            // As far as I can tell this may not be neccessary, but probably best to do anyway
            public boolean equals(MyClass a, MyClass b) {
                return a.a == b.a; }
        }
        // To change an array to a list we can do
        List<String> arrayaslist = Arrays.asList(arr);
        // Or make a general list
        List<MyClass> list = new LinkedList<MyClass>();
        List<MyClass> list2 = new Vector<MyClass>();
        // If we have a comparator already we can do
        Collections.sort(arrayaslist); // or maybe
        Collections.sort(list, new MyClassCmp());
        // If we have a sorted list we can do
        MyClass target = new MyClass(3);
        Collections.binarySearch(list, target, new MyClassCmp());
        SortedSet<MyClass> set = new TreeSet<MyClass>(new MyClassCmp());
        // We can also find maximums
        List<Integer> arr2= new ArrayList<Integer>();
        arr2.add(2);
        arr2.add(5);
        arr2.add(1);
        arr2.add(3);
        int b = Collections.max(arr2);
```

```

// We can work with arbitrary precision integers as follows:
BigInteger numb = new BigInteger("1223423784329545891238471293812391254651");
numb = numb.add(BigInteger.valueOf(3));
debug(numb.toString());

// In places where code should never be reached we can debug (and submit) with
// assert(false); there, this way we will get an exception rather than dodge
// behaviour.
debug(arr[0]);
}
// Custom classes declared within the main like this:
static class MyClass {
    int a;
    MyClass(int A) {
        a = A; }
}
}

```

## Graphs

```

import java.util.*;
// This is wrapped up real nice in a class so it's super duper easy to use
// and because typing code of any length is O(1)
public class Graph {
    HashMap<String, LinkedList<String>> adjacents = new HashMap<String, LinkedList<String>>();
    // Add an edge (u, v)
    public void add(String u, String v) {
        if (u.equals(v)) {
            if (!adjacents.containsKey(u)) {
                LinkedList<String> newList = new LinkedList<String>();
                adjacents.put(u, newList);
                return;
            }
        }
        if (adjacents.containsKey(u)) {
            if (!adjacents.get(u).contains(v)) {
                adjacents.get(u).add(v);
            }
        } else {
            LinkedList<String> newList = new LinkedList<String>();
            newList.add(v);
            adjacents.put(u, newList);
        }
        if (adjacents.containsKey(v)) {
            if (!adjacents.get(v).contains(u)) {
                adjacents.get(v).add(u);
            }
        } else {
            LinkedList<String> newList = new LinkedList<String>();
            newList.add(u);
            adjacents.put(v, newList);
        }
    }
    // Tests whether (u, v) is an edge
    public boolean edge(String u, String v) {
        return (adjacents.containsKey(u) && adjacents.get(u).contains(v));
    }
    // Returns the degree of node u
    public int degree(String u) {
        return adjacents.containsKey(u) ? adjacents.get(u).size() : -1;
    }
    // BFS
    public void bfs(String root) {
        LinkedList<String> processed = new LinkedList<String>();
        String current = root;
        //while (adjacents.get(current)) {
        //    ...
        //}
    }
}

```

```

    }
}

```

## Max-Flow

```

import java.util.*;
public class fordfulkerson
{
    static int fordFulkerson(int[][] cap, int[][] fnet, int n, int s, int t) {
        //ASSUMES: cap[u][v] stores capacity of edge (u,v). cap[u][v] = 0 for no edge.
        //Initialise the flow network so that fnet[u][v] = 0 for all u,v
        int flow = 0; //no flow yet
        while (true) {
            //Find an augmenting path using BFS
            int[] prev = new int[n];
            Arrays.fill(prev, -1);
            LinkedList<Integer> queue = new LinkedList<Integer>();
            prev[s] = -2;
            queue.add(s);
            while (!queue.isEmpty() && prev[t] == -1) {
                int u = queue.poll();
                for (int v = 0; v < n; v++) {
                    if (prev[v] == -1) { //not seen yet
                        if (fnet[v][u] > 0 || fnet[u][v] < cap[u][v]) {
                            prev[v] = u;
                            queue.add(v);
                        }
                    }
                }
            }
            //See if we couldn't find any path to t (t has no parents)
            if (prev[t] == -1) break;
            //Get the bottleneck capacity;
            int bot = Integer.MAX_VALUE;
            for (int v = t, u = prev[v]; u >= 0; v = u, u = prev[v]) {
                if (fnet[v][u] > 0) //prefer a backward edge over a forward
                    bot = bot < fnet[v][u] ? bot : fnet[v][u];
                else //must be a forward edge otherwise
                    bot = bot < cap[u][v] - fnet[u][v] ? bot : cap[u][v] - fnet[u][v];
            }
            //update the flow network
            for (int v = t, u = prev[v]; u >= 0; v = u, u = prev[v]) {
                if (fnet[v][u] > 0) //backward edge -> subtract
                    fnet[v][u] -= bot;
                else //forward edge -> add
                    fnet[u][v] += bot;
            }
            //Sent 'bot' amount of flow from s to v, so update the flow
            flow += bot;
        }
        return flow;
    }
}

```

## Shortest path

```

import java.util.*;
public class shortpath {
    public static int INF = Integer.MAX_VALUE;
    public static void bellmanFord(Vector<Edge> edges, int nnodes, int source) {
        int[] distance = new int[nnodes];
        Arrays.fill(distance, INF);
        distance[source] = 0;
        for (int i = 0; i < nnodes; ++i) {
            for (int j = 0; j < edges.size(); ++j) {
                if (distance[edges.get(j).source] == INF) continue;
                int newDistance = distance[edges.get(j).source] + edges.get(j).weight;
                if (newDistance < distance[edges.get(j).destination])
                    distance[edges.get(j).destination] = newDistance;
            }
        }
        for (int i = 0; i < edges.size(); ++i) {

```

```

    if (distance[edges.get(i).source] != INF && distance[edges.get(i).destination] >
        distance[edges.get(i).source] + edges.get(i).weight) {
        System.out.println("Negative edge weight cycles detected!");
        return;
    }
}
for (int i = 0; i < distance.length; ++i) {
    if (distance[i] == INF)
        System.out.println("There's no path between " + source + " and " + i);
    else
        System.out.println("The shortest distance between nodes " + source + " and " + i
            + " is " + distance[i]);
}
}
static class Edge {
    int source; // source node
    int destination; // destination node
    int weight; // weight of the edge
    public Edge() {} // default constructor
    public Edge(int s, int d, int w) { source = s; destination = d; weight = w; }
}
}

```

Min spanning tree

Gale-Shapley

```

import java.util.*;
public class galeshape {
    int m, n;
    boolean[][] graph;
    boolean seen[];
    int matchL[]; //What left vertex i is matched to (or -1 if unmatched)
    int matchR[]; //What right vertex j is matched to (or -1 if unmatched)
    int maximumMatching() {
        //Read input and populate graph[][]
        //Set m to be the size of L, n to be the size of R
        Arrays.fill(matchL, -1);
        Arrays.fill(matchR, -1);
        int count = 0;
        for (int i = 0; i < m; i++) {
            Arrays.fill(seen, false);
            if (bpm(i)) count++;
        }
        return count;
    }
    boolean bpm(int u) {
        //try to match with all vertices on right side
        for (int v = 0; v < n; v++) {
            if (!graph[u][v] || seen[v]) continue;
            seen[v] = true;
            //match u and v, if v is unassigned, or if v's match on the left side can be
            //reassigned to another right vertex
            if (matchR[v] == -1 || bpm(matchR[v])) {
                matchL[u] = v;
                matchR[v] = u;
                return true;
            }
        }
    }
    return false;
}
}

```

## Number theory

GCD

```

public class gcd {
    static int gcd(int a, int b) {
        int c = 0;
    }
}

```

```

    while(a!=0 && b!=0) {
        c = b;
        b = a%b;
        a = c;
    }
    return a+b;
}
static int arrGCD(int[] a) {
    int g = a[0];
    for (int i = 0; i < a.length; i++) {
        g = gcd(a[i], g);
        if (g == 1) break;
    }
    return g;
}
}

```

$$\text{lcm}(a, b) = ab / \text{gcd}(a, b)$$

Sieve of Eratosthenes

```

public class sieve {
    public static boolean[] iscompslessthan(int n) {
        boolean[] iscomp = new boolean[n];
        for (int i = 2; i < Math.sqrt((double)n) + 1; i++) {
            if (iscomp[i]) continue;
            for (int j = i*i; j < n; j+=i) {
                iscomp[j] = true;
            }
        }
        return iscomp;
    }
}

```

## Dynamic programming

Discrete knapsack problem

```

import java.util.*;
public class knapsack
{
    public static List<Integer> zerooneknapsack(List<Integer> values, List<Integer> weights, int W)
    {
        int numItems = values.size();
        int maxWeight = Collections.max(weights);
        int[][] B = new int[numItems+1][maxWeight+1];
        for (int k = 0; k < numItems; k++) {
            for (int w = maxWeight; w >= weights.get(k); w--)
                if (values.get(k) + B[k][w-weights.get(k)] > B[k][w])
                    B[k+1][w] = values.get(k) + B[k][w-weights.get(k)];
            else
                B[k+1][w] = B[k][w];
            for (int w = 0; w < weights.get(k); w++)
                B[k+1][w] = B[k][w];
        }
        ArrayList<Integer> retval = new ArrayList<Integer>();
        // The maximum value is now B[numItems][maxWeight]
        // For items used, code is
        for (int k = numItems-1, remainingWeight=maxWeight; k >= 0; k--) {
            if (remainingWeight >= weights.get(k))
                if (B[k+1][remainingWeight] == (values.get(k) + B[k][remainingWeight - weights.get(k)]))
                {
                    retval.add(k);
                    remainingWeight -= weights.get(k);
                }
        }
        return retval;
    }
}

```

## Matching

```

public class kmp {
    static int[] createTable(char[] w) {
        int[] t = new int[w.length];
        int i = 2;
        int j = 0;
        t[0] = -1;
        while (i < w.length) {
            if (w[i-1] == w[j]) t[i++] = j++ + 1;
            else if (j > 0) j = t[j];
            else t[i++] = j = 0;
        }
        return t;
    }
    static int searchKMP(char[] w, char[] s, int[] t) {
        int m = 0;
        int i = 0;
        while ((m + i < s.length) && (i < w.length)) {
            if (s[m+i] == w[i]) i++;
            else {
                m += i - t[i];
                if (i > 0) i = t[i];
            }
        }
        return (i == w.length) ? m : -1;
    }
}

```

Suffix arrays!

## Geometry

Centroid of set of point  $C = (x_1 + x_2 + \dots + x_k)/k$ . Centroid of figure, triangulate into right triangles  $X_1, \dots, X_n$  and compute  $C_x = (\sum C_{ix} A_i) / \sum A_i$ ,  $C_y = (\sum C_{iy} A_i) / \sum A_i$  where the centroid of a right triangle perpendicular to the axis is  $b/3, h/3$ .

Simple data structures

```

public class Point implements Comparable<Point> {
    int x; int y;
    public int compareTo(Point p) {return (x-p.x == 0) ? y-p.y : x-p.x;} // left-bottommost
    public float cross(Point p) {return x*p.y - p.x*y;}
}

```

Convex hull, can be used for: furthest points, polygon containment ( $P$  inside  $Q$  iff  $\text{hull}(Q) = \text{hull}(P \cup Q)$ ),

```

import java.util.*;
public class convexhull
{
    static final double eps = 0.0000000001;
    static int isAnti(Point x0, Point x1, Point x2) {
        double a = (x1.x-x0.x)*(x2.y-x0.y)-(x2.x-x0.x)*(x1.y-x0.y);
        if (a > eps || -a > eps) return a > 0 ? -1 : 1;
        return 0;
    }
    static int isCloser(Point x0, Point x1, Point x2) {
        double d1 = (x0.x-x1.x)*(x0.x-x1.x) + (x0.y-x1.y)*(x0.y-x1.y);
        double d2 = (x0.x-x2.x)*(x0.x-x2.x) + (x0.y-x2.y)*(x0.y-x2.y);
        if (d1-d2 > eps || d2-d1 > eps) return d1 < d2 ? -1 : 1;
        return 0;
    }
    public static List<Point> hull(List<Point> points) {
        Collections.sort(points);
        final Point p0 = points.get(0);
        points.remove(p0);
        Collections.sort(points, new Comparator<Point>() {

```

```

    public int compare(Point p1, Point p2) {
        int a = isAnti(p0,p1,p2);
        if (a != 0) return a;
        return isCloser(p0,p1,p2);
    });
    int m = points.size();
    for (int i = 1; i < m; i++) { // Remove colinears
        if (isAnti(p0, points.get(i-1), points.get(i)) == 0) {
            points.remove(i-1);
            m--;
        }
    }
    LinkedList<Point> hull = new LinkedList<Point>();
    if (m < 2) return hull; // All colinear, no hull
    hull.push(p0);
    hull.push(points.get(0));
    hull.push(points.get(1));
    for (int i = 2; i < m; i++) {
        while (isAnti(hull.get(0), hull.get(1), points.get(i)) <= 0) {
            hull.pop();
        }
        hull.push(points.get(i));
    }
    return hull;
}
//Andrew monotone chain is faster still...
}

```

Closest pair of points

```

import java.util.*;
public class closestpoints {
    public static Point[] closestPair(Point[] arr){
        Point[] ret = {arr[0], arr[1]};
        Arrays.sort(arr);
        return ret;
    }
}

```

## Pseudocode

### BFS

```

procedure BFS(G,v) is
    create a queue Q
    create a set V
    enqueue v onto Q
    add v to V
    while Q is not empty loop
        t ← Q.dequeue()
        if t is what we are looking for then
            return t
        end if
        for all edges e in G.adjacentEdges(t) loop
            u ← G.adjacentVertex(t,e)
            if u is not in V then
                add u to V
                enqueue u onto Q
            end if
        end loop
    end loop
    return none
end BFS

```

### DFS

```

procedure DFS(G,v):
  label v as discovered
  for all edges e in G.adjacentEdges(v) do
    if edge e is unexplored then
      w ← G.adjacentVertex(v,e)
      if vertex w is unexplored then
        label e as a discovered edge
        recursively call DFS(G,w)
      else
        label e as a back edge
  label v as explored

```

## Dijkstra

```

function Dijkstra(Graph, source):
  for each vertex v in Graph:
    dist[v] := infinity;           // Initializations
    source to v as not yet computed // Mark distances from
    visited[v] := false;           // Mark all nodes as
    unvisited                       unvisited
    previous[v] := undefined;       // Previous node in optimal
    path from source
  end for

  dist[source] := 0;               // Distance from source to
  itself is zero
  insert source into Q;             // Start off with the source
  node

  while Q is not empty:           // The main loop
    u := vertex in Q with smallest distance in dist[] and has not been visited;
    // Source node in first case
    remove u from Q;
    visited[u] := true             // mark this node as visited

    for each neighbor v of u:
      alt := dist[u] + dist_between(u, v); // accumulate shortest dist
      from source
      if alt < dist[v] && !visited[v]:
        dist[v] := alt;           // keep the shortest dist
        from src to v
        previous[v] := u;
        insert v into Q;           // Add unvisited v into the
        Q to be processed
      end if
    end for
  end while
  return dist;
endfunction

```

## Bellman-Ford

```

procedure BellmanFord(list vertices, list edges, vertex source)
  // This implementation takes in a graph, represented as lists of vertices and edges,
  // and fills two arrays (distance and predecessor) with shortest-path information

  // Step 1: initialize graph
  for each vertex v in vertices:
    if v is source then distance[v] := 0
    else distance[v] := infinity
    predecessor[v] := null

  // Step 2: relax edges repeatedly
  for i from 1 to size(vertices)-1:
    for each edge (u, v) with weight w in edges:
      if distance[u] + w < distance[v]:
        distance[v] := distance[u] + w

```



```

predecessor[v] := u

// Step 3: check for negative-weight cycles
for each edge (u, v) with weight w in edges:
    if distance[u] + w < distance[v]:
        error "Graph contains a negative-weight cycle"

```

## Ford-Fulkerson

Inputs: Graph  $G$  with flow capacity  $c$ , a source node  $s$ , and a sink node  $t$

Output: A flow  $f$  from  $s$  to  $t$  which is a maximum

$f(u, v) < -0$  for all edges  $(u, v)$  While there is a path  $p$  from  $s$  to  $t$  in  $G_f$ , such that  $c_f(u, v) > 0$  for all edges  $(u, v)$  in  $p$ : Find  $c_f(p) = \min\{c_f(u, v) : (u, v) \in p\}$  For each edge  $(u, v) \in p$   $f(u, v) < -f(u, v) + c_f(p)$  (Send flow along the path)  $f(v, u) < -f(v, u) - c_f(p)$  (The flow might be "returned" later)

## Topological Sort

$L \leftarrow$  Empty list that will contain the sorted elements  $S \leftarrow$  Set of all nodes with no incoming edges while  $S$  is non-empty do remove a node  $n$  from  $S$  insert  $n$  into  $L$  for each node  $m$  with an edge  $e$  from  $n$  to  $m$  do remove edge  $e$  from the graph if  $m$  has no other incoming edges then insert  $m$  into  $S$  if graph has edges then return error (graph has at least one cycle) else return  $L$  (a topologically sorted order)

## Longest Common Substring

```

function LCSUBSTR(S[1..m], T[1..n])
    L := array(1..m, 1..n)
    z := 0
    ret := {}
    for i := 1..m
        for j := 1..n
            if S[i] == T[j]
                if i == 1 or j == 1
                    L[i, j] := 1
                else
                    L[i, j] := L[i-1, j-1] + 1
            if L[i, j] > z
                z := L[i, j]
                ret := {S[i-z+1..i]}
            elif L[i, j] == z
                ret := ret union {S[i-z+1..i]}
        else L[i, j] = 0;
    return ret

```

## Point-in-Polygon Test

One simple way of finding whether the point is inside or outside a simple polygon is to test how many times a ray, starting from the point and going ANY fixed direction, intersects the edges of the polygon. If the point in question is not on the boundary of the polygon, the number of intersections is an even number if the point is outside, and it is odd if inside.

## Polygon Stuff

A convex polygon is trivial to triangulate in linear time, by adding diagonals from one vertex to all other vertices. The total number of ways to triangulate a convex  $n$ -gon by non-intersecting diagonals is the  $(n-2)$ -th Catalan number

## Delaunay Triangulation

The most straightforward way of efficiently computing the Delaunay triangulation is to repeatedly add one vertex at a time, retriangulating the affected parts of the graph. When a vertex  $v$  is added, we split

in three the triangle that contains  $v$ , then we apply the flip algorithm. Done naively, this will take  $O(n)$  time: we search through all the triangles to find the one that contains  $v$ , then we potentially flip away every triangle. Then the overall runtime is  $O(n^2)$ .

## Edit Distance

$\text{len\_s}$  and  $\text{len\_t}$  are the number of characters in string  $s$  and  $t$  respectively

```

int LevenshteinDistance(string s, int len_s, string t, int len_t)
{
    /* test for degenerate cases of empty strings */
    if (len_s == 0) return len_t;
    if (len_t == 0) return len_s;

    /* test if last characters of the strings match */
    if (s[len_s-1] == t[len_t-1]) cost = 0;
    else cost = 1;

    /* return minimum of delete char from s, delete char from t, and delete char from both */
    return minimum(LevenshteinDistance(s, len_s - 1, t, len_t) + 1,
                  LevenshteinDistance(s, len_s, t, len_t - 1) + 1,
                  LevenshteinDistance(s, len_s - 1, t, len_t - 1) + cost);
}

```

## Formulae

$$\sum_{i=1}^n i = \frac{n(n+1)}{2}, \quad \sum_{i=1}^n i^2 = \frac{n(n+1)(2n+1)}{6}, \quad \sum_{i=1}^n i^3 = \frac{n^2(n+1)^2}{4}.$$

In general:

$$\sum_{i=1}^n i^m = \frac{1}{m+1} \left[ (n+1)^{m+1} - 1 - \sum_{i=1}^n ((i+1)^{m+1} - i^{m+1} - (m+1)i^m) \right]$$

$$\sum_{i=1}^{n-1} i^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k n^{m+1-k}.$$

Geometric series:

$$\sum_{i=0}^n c^i = \frac{c^{n+1} - 1}{c - 1}, \quad c \neq 1, \quad \sum_{i=0}^{\infty} c^i = \frac{1}{1 - c}, \quad \sum_{i=1}^{\infty} c^i = \frac{c}{1 - c}, \quad |c| < 1,$$

$$\sum_{i=0}^n i c^i = \frac{n c^{n+2} - (n+1) c^{n+1} + c}{(c-1)^2}, \quad c \neq 1, \quad \sum_{i=0}^{\infty} i c^i = \frac{c}{(1-c)^2}, \quad |c| < 1.$$

Harmonic series:

$$H_n = \sum_{i=1}^n \frac{1}{i}, \quad \sum_{i=1}^n i H_i = \frac{n(n+1)}{2} H_n - \frac{n(n-1)}{4}.$$

$$\sum_{i=1}^n H_i = (n+1) H_n - n, \quad \sum_{i=1}^n \binom{i}{m} H_i = \binom{n+1}{m+1} \left( H_{n+1} - \frac{1}{m+1} \right).$$