

# Examples Slot 6

*Dora Simon*

*September 10, 2018*

## Example

```
library(ggplot2)
diamonds_df<-as.data.frame(diamonds)
head(diamonds_df)
```

```
##   carat      cut color clarity depth table price     x     y     z
## 1  0.23    Ideal     E    SI2   61.5     55   326  3.95  3.98  2.43
## 2  0.21  Premium     E    SI1   59.8     61   326  3.89  3.84  2.31
## 3  0.23     Good     E    VS1   56.9     65   327  4.05  4.07  2.31
## 4  0.29  Premium     I    VS2   62.4     58   334  4.20  4.23  2.63
## 5  0.31     Good     J    SI2   63.3     58   335  4.34  4.35  2.75
## 6  0.24 Very Good     J   VVS2   62.8     57   336  3.94  3.96  2.48
```


## Example

```
summary(diamonds_df$carat)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
## 0.2000  0.4000  0.7000  0.7979  1.0400  5.0100
```


## Example

```
ggplot(data=diamonds_df)
```




## Example

```
ggplot(data=diamonds_df) + geom_point(mapping=aes(x=carat, y=price))
```




## Example

```
ggplot(data = diamonds_df) +  
  geom_point(mapping = aes(x = carat, y = price, color = clarity))
```




## Example

```
ggplot(data = diamonds_df) +  
  geom_point(mapping = aes(x = carat, y = price, alpha = clarity))
```




## Example

```
ggplot(data = diamonds_df) +  
  geom_point(mapping = aes(x = carat, y = price,  
                           color = clarity > 'VS2'))
```




## Example

```
ggplot(data = diamonds_df) +  
  geom_point(mapping = aes(x = carat, y = price)) +  
  facet_wrap(~ cut, nrow=2)
```



## Example


```
ggplot(data = diamonds_df) +  
  geom_point(mapping = aes(x = carat, y = price)) +  
  facet_grid(clarity ~ cut)
```



## Example


```
ggplot(data = diamonds_df) +  
  geom_smooth(mapping = aes(x = carat, y = price))
```






## Example

```
ggplot(data = diamonds_df) +  
  geom_smooth(mapping = aes(x = carat, y = price, color=cut))
```




## Example

```
ggplot(data = diamonds_df, mapping = aes(x = carat, y = price)) +  
  geom_point(size = 0.2, alpha = 0.5) +  
  geom_smooth()
```




## Example

```
ggplot(data = diamonds_df) +  
  geom_bar(mapping = aes(x=clarity))
```




## Example

```
ggplot(data = diamonds_df, mapping = aes(x=clarity)) +  
  geom_bar()
```




## Example

```
ggplot(data = diamonds_df) +  
  geom_bar(mapping = aes(x = cut, fill = clarity),  
            position = "fill")
```




## Example

```
ggplot(data = diamonds_df) +  
  geom_bar(mapping = aes(x = cut, fill = clarity),  
            position = "dodge")
```



## Example

```
ggplot(data = diamonds_df) +  
  geom_point(mapping = aes(x = carat, y = price)) +  
  coord_trans(x = "log", y = "log")
```




## Example

```
ggplot(data = diamonds_df) +  
  geom_point(mapping = aes(x = carat, y = price, color = clarity)) +  
  labs(title = "Relationship between weight and price of diamonds",  
        x = "Weight in carat",  
        y = "Price in dollars",  
        color = "Clarity")
```



Relationship between weight and price of diamonds



### Example

```
ggplot(data = diamonds_df) +  
  geom_point(mapping = aes(x = carat, y = price, color = clarity)) +  
  scale_x_continuous(breaks = seq(0, 5, 0.5)) +  
  scale_color_discrete(labels = seq(1, 8))
```

