

Coding Interview Patterns

Python Templates for Muscle Memory

Version: September 28, 2025

This printable reference collects the most frequently used patterns in modern software engineering interviews. Each template is concise, type hinted, and commented so you can rewrite it from memory.¹

Contents

1	How to Use This Guide	2
2	Core Patterns & Complete Python Templates	2
2.1	Depth-First Search (DFS)	2
2.2	Breadth-First Search (BFS)	3
2.3	Topological Sort (Kahn’s Algorithm)	3
2.4	Two Pointers	3
2.5	Sliding Window	4
2.6	Binary Search	5
2.7	Dynamic Programming	6
2.8	Backtracking	7
2.9	Heap Operations (<code>heapq</code>)	7
2.10	Union-Find (Disjoint Set Union)	8
2.11	Trie (Prefix Tree)	9
2.12	Special Algorithms	9
3	Pattern Recognition Guide (When to Use What)	11
4	Time & Space Complexity Notes	11
5	Daily Practice Routine (45–90 minutes)	12
6	4-Week Study Schedule	12
7	Tips for Muscle Memory	13

¹Patterns consolidated from widely used interview references such as Educative’s “Grokking the Coding Interview” and Tech Interview Handbook.

How to Use This Guide

- **Daily reps:** Pick 3–5 patterns, close the guide, and handwrite/type them from memory.
- **Say it out loud:** For each line, state what it does and the complexity.
- **Space repetition:** Rotate patterns; increase difficulty by removing comments.
- **Drills:** After templating, solve 1–2 problems per pattern (e.g., from LeetCode).

Core Patterns & Complete Python Templates

Depth-First Search (DFS)

Recursive DFS (Graph/Tree)

Listing 1: Recursive DFS

```
1 from typing import List, Dict, Set
2
3 def dfs_recursive(graph: Dict[int, List[int]], start: int) -> List[int]:
4     visited: Set[int] = set()
5     order: List[int] = []
6
7     def dfs(u: int) -> None:
8         if u in visited:
9             return
10        visited.add(u)
11        order.append(u)
12        for v in graph.get(u, []):
13            dfs(v)
14
15    dfs(start)
16    return order
```

Iterative DFS (Using Stack)

Listing 2: Iterative DFS

```
1 from typing import List, Dict
2
3 def dfs_iterative(graph: Dict[int, List[int]], start: int) -> List[int]:
4     stack: List[int] = [start]
5     visited = set()
6     order: List[int] = []
7
8     while stack:
9         u = stack.pop()
10        if u in visited:
11            continue
12        visited.add(u)
13        order.append(u)
14        # push neighbors in reverse to mimic recursive order if needed
15        for v in reversed(graph.get(u, [])):
```

```

16         if v not in visited:
17             stack.append(v)
18     return order

```

Breadth-First Search (BFS)

Listing 3: BFS for shortest layers in unweighted graphs

```

1 from collections import deque
2 from typing import List, Dict
3
4 def bfs(graph: Dict[int, List[int]], start: int) -> List[int]:
5     q = deque([start])
6     visited = {start}
7     order: List[int] = []
8
9     while q:
10         u = q.popleft()
11         order.append(u)
12         for v in graph.get(u, []):
13             if v not in visited:
14                 visited.add(v)
15                 q.append(v)
16     return order

```

Topological Sort (Kahn's Algorithm)

Listing 4: Kahn's algorithm for DAGs

```

1 from collections import deque, defaultdict
2 from typing import List, Tuple
3
4 def topo_sort_kahn(n: int, edges: List[Tuple[int, int]]) -> List[int]:
5     indeg = [0] * n
6     g = defaultdict(list)
7     for u, v in edges:
8         g[u].append(v)
9         indeg[v] += 1
10    q = deque([i for i in range(n) if indeg[i] == 0])
11    order: List[int] = []
12    while q:
13        u = q.popleft()
14        order.append(u)
15        for v in g[u]:
16            indeg[v] -= 1
17            if indeg[v] == 0:
18                q.append(v)
19    return order # if len(order) < n, there is a cycle

```

Two Pointers

Opposite Ends (Sorted array/string)

Listing 5: Two pointers from both ends

```
1 from typing import List
2
3 def two_sum_sorted(nums: List[int], target: int) -> List[int]:
4     i, j = 0, len(nums) - 1
5     while i < j:
6         s = nums[i] + nums[j]
7         if s == target:
8             return [i, j]
9         if s < target:
10            i += 1
11        else:
12            j -= 1
13    return []
```

Fast/Slow (Cycle detection)

Listing 6: Floyd's Tortoise and Hare

```
1 from typing import Optional
2
3 class ListNode:
4     def __init__(self, val: int = 0, nxt: 'Optional[ListNode]' = None):
5         self.val = val
6         self.next = nxt
7
8 def has_cycle(head: Optional[ListNode]) -> bool:
9     slow, fast = head, head
10    while fast and fast.next:
11        slow = slow.next
12        fast = fast.next.next
13        if slow is fast:
14            return True
15    return False
```

Sliding Window

Fixed Size

Listing 7: Max sum over a window of size k

```
1 from typing import List
2
3 def max_window_sum(nums: List[int], k: int) -> int:
4     cur = sum(nums[:k])
5     best = cur
6     for i in range(k, len(nums)):
7         cur += nums[i] - nums[i - k]
8         best = max(best, cur)
9     return best
```

Variable Size (Longest substring with at most K distinct)

Listing 8: Generic variable-size window

```
1 from collections import Counter
2 from typing import Dict
3
4 def longest_at_most_k_distinct(s: str, k: int) -> int:
5     count: Dict[str, int] = Counter()
6     left = 0
7     best = 0
8     for right, ch in enumerate(s):
9         count[ch] += 1
10        while len(count) > k:
11            left_ch = s[left]
12            count[left_ch] -= 1
13            if count[left_ch] == 0:
14                del count[left_ch]
15            left += 1
16        best = max(best, right - left + 1)
17    return best
```

Binary Search

Standard (Exact Match)

Listing 9: Binary search on sorted array

```
1 from typing import List
2
3 def binary_search(nums: List[int], target: int) -> int:
4     lo, hi = 0, len(nums) - 1
5     while lo <= hi:
6         mid = (lo + hi) // 2
7         if nums[mid] == target:
8             return mid
9         if nums[mid] < target:
10            lo = mid + 1
11        else:
12            hi = mid - 1
13    return -1
```

First/Last Occurrence (Lower/Upper Bound)

Listing 10: Lower and upper bound

```
1 from typing import List, Tuple
2
3 def lower_upper_bound(nums: List[int], target: int) -> Tuple[int, int]:
4     # first index >= target
5     lo, hi = 0, len(nums)
6     while lo < hi:
7         mid = (lo + hi) // 2
8         if nums[mid] < target:
```

```

9         lo = mid + 1
10        else:
11            hi = mid
12        first = lo if lo < len(nums) and nums[lo] == target else -1
13
14        # first index > target
15        lo, hi = 0, len(nums)
16        while lo < hi:
17            mid = (lo + hi) // 2
18            if nums[mid] <= target:
19                lo = mid + 1
20            else:
21                hi = mid
22        last = lo - 1 if lo - 1 >= 0 and nums[lo - 1] == target else -1
23        return first, last

```

Dynamic Programming

1D DP (Bottom-Up)

Listing 11: Classic 1D DP (e.g., climb stairs)

```

1 from typing import List
2
3 def dp_1d(n: int) -> int:
4     if n <= 1:
5         return 1
6     dp = [0] * (n + 1)
7     dp[0] = dp[1] = 1
8     for i in range(2, n + 1):
9         dp[i] = dp[i - 1] + dp[i - 2]
10    return dp[n]

```

2D DP (Grid Paths with Obstacles)

Listing 12: 2D DP grid template

```

1 from typing import List
2
3 def dp_2d(grid: List[List[int]]) -> int:
4     m, n = len(grid), len(grid[0])
5     dp = [[0] * n for _ in range(m)]
6     dp[0][0] = 1 if grid[0][0] == 0 else 0
7     for i in range(m):
8         for j in range(n):
9             if grid[i][j] == 1 or (i == 0 and j == 0):
10                continue
11            top = dp[i - 1][j] if i > 0 else 0
12            left = dp[i][j - 1] if j > 0 else 0
13            dp[i][j] = top + left
14    return dp[m - 1][n - 1]

```

Backtracking

General Template

Listing 13: Backtracking skeleton

```
1 from typing import List
2
3 def backtrack_template(choices: List[int]) -> List[List[int]]:
4     path: List[int] = []
5     res: List[List[int]] = []
6
7     def backtrack(start: int = 0) -> None:
8         # record if path is a complete solution
9         res.append(path.copy())
10        for i in range(start, len(choices)):
11            # choose
12            path.append(choices[i])
13            # explore
14            backtrack(i + 1) # or backtrack(start) for permutations with used[]
15            # un-choose
16            path.pop()
17
18    backtrack(0)
19    return res
```

Permutations

Listing 14: flagPermutations using used[] flag

```
1 from typing import List
2
3 def permutations(nums: List[int]) -> List[List[int]]:
4     res: List[List[int]] = []
5     used = [False] * len(nums)
6     path: List[int] = []
7
8     def dfs() -> None:
9         if len(path) == len(nums):
10            res.append(path.copy())
11            return
12        for i, x in enumerate(nums):
13            if used[i]:
14                continue
15            used[i] = True
16            path.append(x)
17            dfs()
18            path.pop()
19            used[i] = False
20
21    dfs()
22    return res
```

Heap Operations (heapq)

Listing 15: Min-heap, max-heap idioms, k-way merge

```

1 import heapq
2 from typing import Iterable, List, Tuple
3
4 # Min-heap
5 h: List[int] = []
6 for x in [5, 1, 4]:
7     heapq.heappush(h, x)
8 smallest = heapq.heappop(h)
9
10 # Max-heap via negation
11 h_max: List[int] = []
12 for x in [5, 1, 4]:
13     heapq.heappush(h_max, -x)
14 max_val = -heapq.heappop(h_max)
15
16 # Heapify existing list
17 arr = [7, 2, 6]
18 heapq.heapify(arr) # in-place, O(n)
19
20 # Merge k sorted lists
21 def merge_k_sorted(lists: List[List[int]]) -> List[int]:
22     out: List[int] = []
23     heap: List[Tuple[int, int, int]] = [] # (val, list_idx, elem_idx)
24     for i, lst in enumerate(lists):
25         if lst:
26             heapq.heappush(heap, (lst[0], i, 0))
27     while heap:
28         val, i, j = heapq.heappop(heap)
29         out.append(val)
30         if j + 1 < len(lists[i]):
31             heapq.heappush(heap, (lists[i][j + 1], i, j + 1))
32     return out

```

Union-Find (Disjoint Set Union)

Listing 16: Path compression + union by rank

```

1 from typing import List
2
3 class DSU:
4     def __init__(self, n: int):
5         self.parent = list(range(n))
6         self.rank = [0] * n
7
8     def find(self, x: int) -> int:
9         if self.parent[x] != x:
10             self.parent[x] = self.find(self.parent[x]) # path compression
11         return self.parent[x]
12
13     def union(self, x: int, y: int) -> bool:
14         rx, ry = self.find(x), self.find(y)
15         if rx == ry:

```



```

16         return False
17     if self.rank[rx] < self.rank[ry]:
18         self.parent[rx] = ry
19     elif self.rank[rx] > self.rank[ry]:
20         self.parent[ry] = rx
21     else:
22         self.parent[ry] = rx
23         self.rank[rx] += 1
24     return True

```

Trie (Prefix Tree)

Listing 17: Trie with insert/search/prefix

```

1 from typing import Dict
2
3 class TrieNode:
4     def __init__(self):
5         self.children: Dict[str, TrieNode] = {}
6         self.end = False
7
8 class Trie:
9     def __init__(self):
10         self.root = TrieNode()
11
12     def insert(self, word: str) -> None:
13         node = self.root
14         for ch in word:
15             if ch not in node.children:
16                 node.children[ch] = TrieNode()
17             node = node.children[ch]
18         node.end = True
19
20     def search(self, word: str) -> bool:
21         node = self.root
22         for ch in word:
23             if ch not in node.children:
24                 return False
25             node = node.children[ch]
26         return node.end
27
28     def starts_with(self, prefix: str) -> bool:
29         node = self.root
30         for ch in prefix:
31             if ch not in node.children:
32                 return False
33             node = node.children[ch]
34         return True

```

Special Algorithms

Kadane's Algorithm (Maximum Subarray)

Listing 18: Kadane in $O(n)$

```

1 from typing import List
2
3 def kadane(nums: List[int]) -> int:
4     best = cur = nums[0]
5     for x in nums[1:]:
6         cur = max(x, cur + x)
7         best = max(best, cur)
8     return best

```

Prefix Sum

Listing 19: Prefix sums and range queries

```

1 from typing import List
2
3 def prefix_sums(nums: List[int]) -> List[int]:
4     ps = [0]
5     for x in nums:
6         ps.append(ps[-1] + x)
7     return ps # ps[i] = sum(nums[:i])
8
9 # sum of nums[l:r] (l inclusive, r exclusive)
10 def range_sum(ps: List[int], l: int, r: int) -> int:
11     return ps[r] - ps[l]

```

Monotonic Stack

Listing 20: Next greater element (increasing stack)

```

1 from typing import List
2
3 def next_greater(nums: List[int]) -> List[int]:
4     res = [-1] * len(nums)
5     stack: List[int] = [] # indices, stack maintains decreasing values
6     for i, x in enumerate(nums):
7         while stack and nums[stack[-1]] < x:
8             j = stack.pop()
9             res[j] = x
10        stack.append(i)
11    return res

```

Cyclic Sort (Arrays with 1..n)

Listing 21: Place numbers at correct indices

```

1 from typing import List
2
3 def cyclic_sort(nums: List[int]) -> None:
4     i = 0
5     n = len(nums)
6     while i < n:
7         j = nums[i] - 1

```

```

8         if 0 <= j < n and nums[i] != nums[j]:
9             nums[i], nums[j] = nums[j], nums[i]
10        else:
11            i += 1
12 # in-place; useful for finding missing/duplicate numbers in 1..n

```

Pattern Recognition Guide (When to Use What)

- **Two Pointers:** Sorted arrays/strings; pair sums; palindrome checks; removing duplicates in-place.
- **Sliding Window:** Substrings/subarrays asking for longest/shortest/# satisfying constraints; streaming data.
- **Binary Search:** Sorted arrays; monotonic predicates (“can we?” decision problems); answer-search on range.
- **BFS:** Shortest path in unweighted graphs; nearest/levels; minimum steps.
- **DFS:** Connectivity; components; recursion on trees; cycle detection (directed via color/stack).
- **Topological Sort:** Prerequisites; ordering tasks; detect cycles in DAG.
- **Union-Find:** Dynamic connectivity; components after unions; cycle detection in undirected graphs; Kruskal MST.
- **Trie:** Prefix queries; autocomplete; word break; dictionary problems.
- **DP (1D/2D):** Overlapping subproblems with optimal substructure; sequences; knapsack; edit distance; grid paths.
- **Backtracking:** Generate all valid configurations under constraints (permutations, subsets, N-Queens, parentheses).
- **Heap:** Top- k / k -way merge / running median; scheduling by priority.
- **Kadane/Prefix Sum:** Max subarray; quick range sums; difference arrays.
- **Monotonic Stack:** Next greater/smaller; histogram area; sliding window min/max (deque).
- **Cyclic Sort:** Arrays containing $1..n$ to find missing/duplicate numbers quickly.

Time & Space Complexity Notes

- DFS/BFS: $O(V + E)$ time, $O(V)$ space (visited + recursion/queue).
- Topo Sort (Kahn): $O(V + E)$ time, $O(V)$ space.
- Two Pointers/Sliding Window: Usually $O(n)$ time, $O(1)$ or $O(K)$ space.
- Binary Search: $O(\log n)$ time, $O(1)$ space.
- DP: Depends on states; 1D often $O(n)$, 2D often $O(mn)$; can optimize space by rolling arrays.
- Backtracking: Exponential in solutions; prune aggressively.

- Heaps: Push/pop $O(\log n)$; heapify $O(n)$; k-way merge $O(N \log k)$.
- Union-Find: $\alpha(n)$ inverse Ackermann for amortized almost-constant ops.
- Trie: Insert/search $O(L)$ where L is word length; space proportional to stored characters.
- Monotonic Stack/Deque: Each element in/out once $\Rightarrow O(n)$ time, $O(n)$ space.

Daily Practice Routine (45–90 minutes)

1. **Warm-up (5 min)**: Rewrite 1–2 templates from memory (rotate daily).
2. **Focused Drill (25–45 min)**: Solve 2 problems of the day’s pattern. After each, restate the approach and complexity.
3. **Spaced Repetition (10 min)**: Flash-review 3 older problems; explain aloud without coding.
4. **Retrospective (5 min)**: Note mistakes and update your trigger words for pattern recognition.

4-Week Study Schedule

Week 1: Fundamentals

Two Pointers, Sliding Window, Binary Search, Prefix Sum, Kadane.

- Day 1–2: Two Pointers (pairs, palindromes, dedupe)
- Day 3–4: Sliding Window (fixed/variable, substrings)
- Day 5: Binary Search (bounds, predicate search)
- Day 6: Prefix Sums + Kadane
- Day 7: Mixed review quiz + rewrite 5 templates

Week 2: Graphs & Sets

DFS (rec/iter), BFS, Topological Sort, Union-Find.

- Day 8–9: DFS/BFS on trees/graphs; shortest paths (unweighted)
- Day 10: Cycle detection; components; bipartite check
- Day 11: Topological Sort (Kahn) + prerequisites problems
- Day 12: Union-Find (dynamic connectivity, Kruskal-style)
- Day 13: Heaps (top-k, k-way merge)
- Day 14: Review + mock

Week 3: DP & Backtracking

1D/2D DP, classic sequences, and generation problems.

- Day 15–16: 1D DP (climb stairs, house robber, coin change)

- Day 17–18: 2D DP (grid paths, edit distance, LCS)
- Day 19: State compression / rolling arrays
- Day 20: Backtracking (subsets, permutations, combos)
- Day 21: Review + speed drills

Week 4: Mastery & Patterns Mix

Tries, Monotonic Stack, Cyclic Sort, mixed sets, and timed mocks.

- Day 22: Trie (prefix queries, word search)
- Day 23: Monotonic Stack (NGE, histogram, daily temps)
- Day 24: Cyclic Sort (missing/duplicate in 1..n)
- Day 25–26: Mixed sets under time pressure
- Day 27: Full mock (70 min) + analysis
- Day 28: Final review + rewrite all templates once

Tips for Muscle Memory

- Build mental *triggers*: e.g., “longest/shortest subarray/substring” \Rightarrow sliding window.
- Keep idioms ready: bounds patterns for binary search; deque for window min/max; DSU for connectivity.
- Practice explaining: interviewers value clarity and tradeoffs as much as code.
- Track your misses: create a “red list” of patterns you consistently forget.

This reference is intentionally compact. Recopy it until it becomes automatic. Good luck!