

# **ClickUp Backend Interview Document Event Processing**

Complete Preparation Guide - November 30, 2024 (v2)

November 30, 2025

## **Contents**

# 1 Interview Overview

## 1.1 What to Expect

**Interview Type:** Backend Live Coding (60 minutes)

**Format:**

- CodeSignal platform (browser-based IDE)
- No pre-written test suite
- You must test your own code
- Recommended languages: Python, JavaScript, TypeScript
- Focus on correctness, edge cases, and code quality

**Problem Domain:**

- Event processing in memory
- Document state management (similar to Google Docs)
- Real-time collaborative editing
- ClickUp's core functionality

## 1.2 Success Criteria

1. **Correctness:** Handle all test cases including edge cases
2. **Code Quality:** Clean, readable, well-structured code
3. **Communication:** Think out loud, explain your approach
4. **Testing:** Demonstrate testing strategy
5. **Problem-Solving:** Handle follow-up questions and variations

## 2 CRITICAL: Questions to Ask First!

### Pro Tips

Before you start coding, ask these clarifying questions:

1. **lastUpdated behavior:** "Should lastUpdated be set to the timestamp of the latest event, or should it be incremented by 1?"
  - The examples show inconsistent behavior - clarify this!
  - Most logical: use the latest event's timestamp
2. **Invalid line numbers:** "What should happen if startLine is 0 or negative?"
  - Skip the event? Return error? Assume line 1?
3. **Event validation:** "Should I validate event structure and handle malformed events?"
  - Missing required fields?
  - Unknown event types?
4. **Same timestamp:** "If multiple events have the same timestamp, what determines their order?"
  - Use event\_id as tiebreaker?
  - Stable sort (preserve original order)?
5. **Document mutation:** "Should I modify the input document in place or return a new copy?"
  - Safer to return a copy
  - But in-place is more efficient
6. **Content initialization:** "If document doesn't have a content field initially, should I initialize it as empty string?"
7. **Trailing newlines:** "Should the final content have a trailing newline character?"

These questions show you think critically and catch ambiguities!

### 3 Core Problem: Document Event Processor

#### Problem

**Context:** ClickUp has a feature that allows users to create documents similar to Google Docs. Changes are tracked through batches of events.

**Task:** Process events on a document and return the correctly updated document.

#### Data Structures:

##### Document:

```
{
  title: string,
  content: string,          // Lines separated by \n
  lastUpdated: timestamp,
  createdOn: timestamp
}
```

##### Event:

```
{
  event_id: number,
  event_name: string,      // Case-insensitive: "append", "APPEND", "Append"
  payload: object,
  timestamp: timestamp
}
```

#### Event Types:

1. **append** - Add content to a specific line

```
payload: {
  newContent: string,
  startLine: number      // 1-indexed (line 1 = first line)
}
```

**Important:** If content exists at that line, **append** newContent to the end of that line (don't replace!).

2. **delete** - Delete all content from document

```
payload: {} // Empty
```

#### Requirements:

- Process events in timestamp order (may arrive out-of-order)
- Update document.lastUpdated to latest event timestamp
- Handle case-insensitive event names
- Return updated document object

### Important Edge Cases & Gotchas

**IMPORTANT NOTE:** The provided examples show lastUpdated incrementing by 1 (123456789  $\rightarrow$  123456790), but event timestamps are in the billions (1641024000001). This appears to be an inconsistency in the problem statement.

**Most logical interpretation:** Set lastUpdated to the timestamp of the most recent event.

**Action:** Ask the interviewer to clarify this behavior before coding!

## 4 Examples with Step-by-Step Trace

### 4.1 Example 1: Multiple Appends

Input:

```
1 events = [  
2   {"event_id": 1, "event_name": "append",  
3     "payload": {"newContent": "Line 1 ", "startLine": 1},  
4     "timestamp": 1641024000001},  
5   {"event_id": 2, "event_name": "APPEND",  
6     "payload": {"newContent": "Line 2 ", "startLine": 2},  
7     "timestamp": 1641024000002},  
8   {"event_id": 3, "event_name": "APPEND",  
9     "payload": {"newContent": "Line 3 ", "startLine": 3},  
10    "timestamp": 1641024000003}  
11 ]  
12  
13 document = {"title": "Lorem Ipsum", "lastUpdated": 123456789, "  
    createdOn": 123456789}
```

#### Step-by-Step Execution:

Initial state:

```
lines = []  
lastUpdated = 123456789
```

After Event 1 (append to line 1):

```
lines = ["Line 1 "]  
lastUpdated = 1641024000001
```

After Event 2 (append to line 2):

```
lines = ["Line 1 ", "Line 2 "]  
lastUpdated = 1641024000002
```

After Event 3 (append to line 3):

```
lines = ["Line 1 ", "Line 2 ", "Line 3 "]  
lastUpdated = 1641024000003
```

Final: Join lines with "\n"

```
content = "Line 1 \nLine 2 \nLine 3 "
```

#### Expected Output:

```
1 {  
2   "title": "Lorem Ipsum",  
3   "content": "Line 1 \nLine 2 \nLine 3 ",  
4   "lastUpdated": 1641024000003,  
5   "createdOn": 123456789  
6 }
```

### 4.2 Example 2: Delete Event

Input:

```
1 events = [{"event_id": 1, "event_name": "delete", "timestamp":  
    1641024000000}]
```

```
2
3 document = {
4   "title": "Lorem Ipsum",
5   "content": "This is Lorem ipsum",
6   "lastUpdated": 123456789,
7   "createdOn": 123456789
8 }
```

### Step-by-Step:

Initial state:

```
lines = ["This is Lorem ipsum"]
```

After Event 1 (delete):

```
lines = []
content = ""
lastUpdated = 1641024000000
```

### Expected Output:

```
1 {
2   "title": "Lorem Ipsum",
3   "content": "",
4   "lastUpdated": 1641024000000,
5   "createdOn": 123456789
6 }
```

## 5 Solution Strategy

### 5.1 Approach

1. **Sort events by timestamp** (handle out-of-order delivery)
2. **Initialize content** as list of lines
3. **Process each event** in order:
  - For **append**: Update/create line at specified position
  - For **delete**: Clear all content
4. **Join lines** back into string with `\n`
5. **Update lastUpdated** to latest event timestamp
6. **Return updated document**

### 5.2 Key Insights

- Use **list for lines** -  $O(1)$  indexing, easy modification
- Handle **1-indexed lines** (convert to 0-indexed: `line_idx = start_line - 1`)
- **Extend list** with empty strings if `startLine` exceeds current length
- Event names are **case-insensitive** (use `.lower()`)
- **Append, don't replace** - use `lines[idx] += new.content`
- Return a **copy** to avoid modifying input (safer)

### 5.3 Why List Over String Manipulation?

- **Strings are immutable** in Python - expensive to modify
- **List operations** are  $O(1)$  for append and indexed assignment
- **Only convert** to string once at the end
- Much more efficient for multiple operations





## 6 Complete Solution

### Solution

#### Clean Production-Ready Implementation

```
1 def execute(events, document):
2     """
3     Process document events and return updated document.
4
5     This solution handles:
6     - Out-of-order events (sorts by timestamp)
7     - Case-insensitive event names
8     - Line gaps (fills with empty strings)
9     - Multiple appends to same line
10    - Document without initial content
11
12    Args:
13        events: List of event dictionaries
14        document: Document dictionary
15
16    Returns:
17        New document dictionary with processed changes
18    """
19    # Handle empty events - return unchanged
20    if not events:
21        return document
22
23    # Sort events by timestamp (handle out-of-order delivery)
24    sorted_events = sorted(events, key=lambda e: e["timestamp"])
25
26    # Initialize content as list of lines
27    content = document.get("content", "")
28    lines = content.split("\n") if content else []
29
30    # Track latest timestamp for lastUpdated
31    latest_timestamp = document.get("lastUpdated", 0)
32
33    # Process each event in chronological order
34    for event in sorted_events:
35        event_name = event["event_name"].lower()
36        timestamp = event["timestamp"]
37
38        if event_name == "append":
39            payload = event["payload"]
40            new_content = payload["newContent"]
41            start_line = payload["startLine"] # 1-indexed
42
43            # Convert to 0-indexed
44            line_idx = start_line - 1
45
46            # Extend lines list if necessary (fill gaps with empty
47            # strings)
48            while len(lines) <= line_idx:
49                lines.append("")
50
51            # Append to existing line content (don't replace!)
52            lines[line_idx] += new_content
53
54        elif event_name == "delete":
55            # Clear all content
56            lines = []
57
58    # Update to most recent timestamp
59    latest_timestamp = max(latest_timestamp, timestamp)
```



## 7 Robust Version with Validation

### Solution

#### Enterprise Version with Error Handling

```
1 def execute_robust(events, document):
2     """
3     Robust version with comprehensive validation and error
4     handling.
5     Use this if interviewer asks about production considerations.
6     """
7     # Validate inputs
8     if not events:
9         return document.copy()
10
11     if not isinstance(events, list):
12         raise ValueError("events must be a list")
13
14     if not isinstance(document, dict):
15         raise ValueError("document must be a dictionary")
16
17     # Sort by timestamp (with fallback for missing timestamps)
18     sorted_events = sorted(events, key=lambda e: e.get("timestamp", 0))
19
20     # Initialize content
21     content = document.get("content", "")
22     lines = content.split("\n") if content else []
23
24     # Remove trailing empty line if present (from content ending
25     # in \n)
26     if lines and lines[-1] == "":
27         lines = lines[:-1]
28
29     latest_timestamp = document.get("lastUpdated", 0)
30
31     # Process each event with validation
32     for event in sorted_events:
33         # Validate event structure
34         if not isinstance(event, dict):
35             continue # Skip malformed events
36
37         event_name = event.get("event_name", "").lower()
38         timestamp = event.get("timestamp", 0)
39         payload = event.get("payload", {})
40
41         if event_name == "append":
42             # Validate payload
43             new_content = payload.get("newContent", "")
44             start_line = payload.get("startLine", 1)
45
46             # Validate line number (must be positive)
47             if start_line < 1:
48                 continue # Skip invalid line numbers
49
50             line_idx = start_line - 1
51
52             # Extend lines if needed
53             while len(lines) <= line_idx:
54                 lines.append("")
55
56             # Append content
57             lines[line_idx] += new_content
```



## 8 Critical Edge Cases

### Important Edge Cases & Gotchas

#### YOU MUST HANDLE THESE:

##### 1. Empty Events List

```
1 events = []
2 # Should return document unchanged
```

##### 2. Out-of-Order Events - CRITICAL!

```
1 events = [
2     {"event_id": 2, ..., "timestamp": 102}, # Second
3     {"event_id": 1, ..., "timestamp": 101}  # First
4 ]
5 # Must sort by timestamp before processing!
```

##### 3. Case-Insensitive Event Names

```
1 "append", "APPEND", "Append", "aPpEnD" # All valid
2 # Use event_name.lower() for comparison
```

##### 4. Multiple Appends to Same Line - MUST APPEND, NOT REPLACE!

```
1 events = [
2     {"payload": {"newContent": "Hello ", "startLine": 1},
3     ...},
4     {"payload": {"newContent": "World", "startLine": 1}, ...}
5 ]
6 # Result: lines[0] = "Hello World" NOT "World"
```

##### 5. Gap in Line Numbers

```
1 events = [{"payload": {"newContent": "Line5", "startLine": 5},
2     ...}]
3 # Result: lines = ["", "", "", "", "Line5"]
4 # Fill gaps with empty strings!
```

##### 6. Delete Then Append

```
1 events = [
2     {"event_name": "delete", "timestamp": 100},
3     {"event_name": "append", "payload": {..., "startLine": 1},
4     "timestamp": 101}
5 ]
6 # Delete clears lines = [], then append starts fresh
```

##### 7. Document Without Content Field

```
1 document = {"title": "Test", "lastUpdated": 0, "createdOn": 0}
2 # No "content" key initially
3 # Use document.get("content", "") to handle safely
```

##### 8. Empty Payload or Missing Fields

```
1 {"event_name": "delete", "timestamp": 100}
2 # Delete has no payload - that's valid
3 # Use payload.get("key", default) for safety
```

##### 9. Line Number 0 or Negative



## 9 Comprehensive Test Suite

### Test Cases

```
1 def test_document_processor():
2     """Complete test suite covering all edge cases."""
3
4     print("Running comprehensive test suite...")
5
6     # Test 1: Basic append to empty document
7     print("\n[Test 1] Basic append")
8     events = [{
9         "event_id": 1,
10        "event_name": "append",
11        "payload": {"newContent": "Hello", "startLine": 1},
12        "timestamp": 100
13    }]
14    doc = {"title": "Test", "lastUpdated": 0, "createdOn": 0}
15    result = execute(events, doc)
16    assert result["content"] == "Hello", f"Expected 'Hello', got {
17        'result['content']}"
18    assert result["lastUpdated"] == 100, f"Expected 100, got {
19        result['lastUpdated']}"
20    print("        Passed")
21
22    # Test 2: Multiple appends to different lines
23    print("\n[Test 2] Multiple lines")
24    events = [
25        {"event_id": 1, "event_name": "append",
26         "payload": {"newContent": "Line1", "startLine": 1},
27         "timestamp": 100},
28        {"event_id": 2, "event_name": "append",
29         "payload": {"newContent": "Line2", "startLine": 2},
30         "timestamp": 101}
31    ]
32    doc = {"title": "Test", "lastUpdated": 0, "createdOn": 0}
33    result = execute(events, doc)
34    assert result["content"] == "Line1\nLine2"
35    print("        Passed")
36
37    # Test 3: Multiple appends to SAME line (critical!)
38    print("\n[Test 3] Same line appends (CRITICAL)")
39    events = [
40        {"event_id": 1, "event_name": "append",
41         "payload": {"newContent": "Hello ", "startLine": 1},
42         "timestamp": 100},
43        {"event_id": 2, "event_name": "append",
44         "payload": {"newContent": "World", "startLine": 1},
45         "timestamp": 101}
46    ]
47    doc = {"title": "Test", "lastUpdated": 0, "createdOn": 0}
48    result = execute(events, doc)
49    assert result["content"] == "Hello World", \
50        f"Must APPEND not replace! Got: '{result['content']}'"
51    print("        Passed")
52
53    # Test 4: Delete event
54    print("\n[Test 4] Delete clears all content")
55    events = [{"event_id": 1, "event_name": "delete", "timestamp":
56        100}]
57    doc = {"title": "Test", "content": "Some content",
58        "lastUpdated": 0, "createdOn": 0}
59    result = execute(events, doc)
60    assert result["content"] == ""
```





## 10 Debugging Strategy

### Pro Tips

#### If Your Tests Are Failing:

##### 1. Add Debug Prints

```
1 for event in sorted_events:
2     print(f"Processing: {event['event_name']} at line {event.
      get('payload', {}).get('startLine')}")
3     print(f"Lines before: {lines}")
4     # ... process event ...
5     print(f"Lines after: {lines}")
6     print()
```

##### 2. Check Event Sorting

```
1 print("Events before sorting:")
2 for e in events:
3     print(f"    {e['event_id']}: timestamp={e['timestamp']}")
4
5 sorted_events = sorted(events, key=lambda e: e["timestamp"])
6
7 print("\nEvents after sorting:")
8 for e in sorted_events:
9     print(f"    {e['event_id']}: timestamp={e['timestamp']}")
```

##### 3. Verify Line Indexing

```
1 print(f"startLine={start_line} (1-indexed)")
2 print(f"line_idx={line_idx} (0-indexed)")
3 print(f"lines length before: {len(lines)}")
4 # ... extend lines ...
5 print(f"lines length after: {len(lines)}")
```

##### 4. Check Append vs Replace

```
1 print(f"Line {line_idx} before: '{lines[line_idx]}'")
2 lines[line_idx] += new_content # Should use +=, not =
3 print(f"Line {line_idx} after: '{lines[line_idx]}'")
```

##### 5. Verify Final Join

```
1 print(f"Lines array: {lines}")
2 content = "\n".join(lines)
3 print(f"Joined content: '{content}'")
4 print(f"Content length: {len(content)}")
```

#### Common Mistakes:

- Forgetting to sort events by timestamp
- Using = instead of += for append
- Off-by-one error with 1-indexed vs 0-indexed
- Not handling case-insensitive event names
- Creating extra empty lines with improper split/join

## 11 Follow-Up Questions & Variations

### 11.1 Expected Follow-Ups

#### 1. What if events can arrive significantly out of order?

- Current solution handles this with sorting
- For streaming: use priority queue or buffering window
- Trade-off: latency vs correctness

#### 2. How would you handle millions of events?

- Batch processing
- Periodic snapshots + incremental updates
- Event sourcing pattern
- Compaction/aggregation of old events

#### 3. What about concurrent editing by multiple users?

- Operational Transform (OT)
- Conflict-free Replicated Data Types (CRDTs)
- Last-write-wins with timestamps
- Use `event_id` as tiebreaker

#### 4. How would you optimize for very large documents?

- Rope data structure instead of list
- Lazy loading of content
- Chunk-based storage
- Only process visible viewport

#### 5. What if we add more event types?

- `insert`: Insert at character position within line
- `delete_range`: Delete specific line range
- `replace`: Replace content at line
- `format`: Apply formatting (bold, italic)

### 11.2 Variation 1: Insert at Character Position

New Event Type:

```
1 {  
2   "event_name": "insert",  
3   "payload": {  
4     "newContent": "text",  
5     "startLine": 2,  
6     "position": 5  # Character position in line (0-indexed)  
7   },  
8   "timestamp": 100  
9 }
```

Implementation:

```

1 elif event_name == "insert":
2     new_content = payload["newContent"]
3     start_line = payload["startLine"]
4     position = payload["position"]
5
6     line_idx = start_line - 1
7     while len(lines) <= line_idx:
8         lines.append("")
9
10    line = lines[line_idx]
11    # Insert at character position
12    lines[line_idx] = line[:position] + new_content + line[position:]

```

### 11.3 Variation 2: Delete Specific Lines

New Event Type:

```

1 {
2     "event_name": "delete_range",
3     "payload": {
4         "startLine": 2,
5         "endLine": 4      # Inclusive
6     },
7     "timestamp": 100
8 }

```

Implementation:

```

1 elif event_name == "delete_range":
2     start_line = payload["startLine"]
3     end_line = payload["endLine"]
4
5     start_idx = start_line - 1
6     end_idx = end_line - 1
7
8     # Delete lines in range
9     if start_idx < len(lines):
10        del lines[start_idx:min(end_idx + 1, len(lines))]

```

### 11.4 Variation 3: Replace Line Content

New Event Type:

```

1 {
2     "event_name": "replace",
3     "payload": {
4         "newContent": "completely new text",
5         "startLine": 3
6     },
7     "timestamp": 100
8 }

```

Implementation:

```

1 elif event_name == "replace":
2     new_content = payload["newContent"]
3     start_line = payload["startLine"]
4

```

```
5     line_idx = start_line - 1
6     while len(lines) <= line_idx:
7         lines.append("")
8
9     # Replace entire line (use = instead of +=)
10    lines[line_idx] = new_content
```

## 12 Alternative Implementations

### 12.1 JavaScript/TypeScript Version

```
1 function execute(events, document) {
2   // Handle empty events
3   if (!events || events.length === 0) {
4     return { ...document };
5   }
6
7   // Sort by timestamp
8   const sortedEvents = [...events].sort((a, b) =>
9     a.timestamp - b.timestamp
10  );
11
12  // Initialize content
13  let content = document.content || "";
14  let lines = content ? content.split("\n") : [];
15
16  let latestTimestamp = document.lastUpdated || 0;
17
18  // Process events
19  for (const event of sortedEvents) {
20    const eventName = event.event_name.toLowerCase();
21    const timestamp = event.timestamp;
22
23    if (eventName === "append") {
24      const { newContent, startLine } = event.payload;
25      const lineIdx = startLine - 1;
26
27      // Extend lines array if needed
28      while (lines.length <= lineIdx) {
29        lines.push("");
30      }
31
32      // Append to line
33      lines[lineIdx] += newContent;
34
35    } else if (eventName === "delete") {
36      lines = [];
37    }
38
39    latestTimestamp = Math.max(latestTimestamp, timestamp);
40  }
41
42  // Return new document (don't mutate input)
43  return {
44    ...document,
45    content: lines.join("\n"),
46    lastUpdated: latestTimestamp
47  };
48 }
49
50 // TypeScript version with types
51 interface Event {
52   event_id: number;
53   event_name: string;
54   payload: {
```

```

55         newContent?: string;
56         startLine?: number;
57     };
58     timestamp: number;
59 }
60
61 interface Document {
62     title: string;
63     content?: string;
64     lastUpdated: number;
65     createdOn: number;
66 }
67
68 function executeTyped(events: Event[], document: Document): Document {
69     // Same implementation as above
70     // TypeScript provides compile-time type safety
71 }

```

## 12.2 Object-Oriented Approach

```

1  class DocumentProcessor:
2      """OOP approach for document event processing."""
3
4      def __init__(self, document):
5          self.document = document.copy()
6          self.lines = self._init_lines()
7
8      def _init_lines(self):
9          """Initialize lines from document content."""
10         content = self.document.get("content", "")
11         return content.split("\n") if content else []
12
13     def process_events(self, events):
14         """Process all events and return updated document."""
15         if not events:
16             return self.document
17
18         sorted_events = sorted(events, key=lambda e: e["timestamp"])
19
20         for event in sorted_events:
21             self._process_event(event)
22
23         return self._finalize()
24
25     def _process_event(self, event):
26         """Process single event based on type."""
27         event_name = event["event_name"].lower()
28
29         if event_name == "append":
30             self._handle_append(event)
31         elif event_name == "delete":
32             self._handle_delete(event)
33         # Easy to add more event types here
34
35     def _handle_append(self, event):
36         """Handle append event."""
37         payload = event["payload"]

```

```

38     new_content = payload["newContent"]
39     start_line = payload["startLine"]
40
41     line_idx = start_line - 1
42
43     # Extend lines if needed
44     while len(self.lines) <= line_idx:
45         self.lines.append("")
46
47     self.lines[line_idx] += new_content
48     self.document["lastUpdated"] = event["timestamp"]
49
50     def _handle_delete(self, event):
51         """Handle delete event."""
52         self.lines = []
53         self.document["lastUpdated"] = event["timestamp"]
54
55     def _finalize(self):
56         """Finalize and return document."""
57         self.document["content"] = "\n".join(self.lines)
58         return self.document
59
60
61 # Usage
62 def execute(events, document):
63     processor = DocumentProcessor(document)
64     return processor.process_events(events)

```



## 13 System Design Discussion

### 13.1 Real-World ClickUp Architecture

In production, ClickUp likely uses:

#### 1. Event Store / Event Sourcing

- Kafka or similar for event streaming
- Permanent event log (source of truth)
- Can replay events to rebuild state
- Enables time-travel debugging

#### 2. CRDT (Conflict-free Replicated Data Types)

- Handle concurrent edits from multiple users
- Eventual consistency without conflicts
- Examples: Yjs, Automerge
- Used by: Figma, Notion, Google Docs

#### 3. Operational Transform (OT)

- Transform conflicting operations
- Maintain causal ordering
- More complex but deterministic
- Used by: Google Docs originally

#### 4. Snapshot + Delta Pattern

- Store periodic snapshots
- Apply only recent events
- Faster recovery and queries
- Reduce memory usage

#### 5. WebSocket for Real-time Sync

- Push events to all connected clients
- Low latency updates
- Handle reconnection gracefully

### 13.2 Scalability Challenges

- **Large Documents:** Millions of characters, thousands of lines
- **High Event Rate:** Hundreds of events per second per document
- **Many Concurrent Users:** 10+ people editing simultaneously
- **Offline Support:** Sync when reconnected, handle conflicts
- **Undo/Redo:** Maintain operation history efficiently
- **Performance:** Sub-second response time even for large docs

### 13.3 Data Structures for Large Documents

- **Rope:** Tree-based string for efficient insertions/deletions
- **Gap Buffer:** Used by Emacs, good for cursor-based editing
- **Piece Table:** Used by VS Code, great for undo/redo
- **CRDT Text:** Yjs uses linked list with tombstones

## 14 Interview Execution Strategy

### 14.1 Time Allocation (60 minutes)

- **5 min:** Clarify requirements, ask questions, confirm understanding
- **3 min:** Discuss approach, mention data structures, complexity
- **2 min:** Write function signature and comments
- **25 min:** Implement core solution (clean, working code)
- **10 min:** Write and run tests (catch bugs early!)
- **5 min:** Add error handling and edge cases
- **10 min:** Follow-up questions, optimizations, discussion

### 14.2 Before You Code

#### Pro Tips

##### The First 5 Minutes Are Critical!

##### 1. Clarify Requirements

- "Should lastUpdated use the event timestamp or increment?"
- "What happens with invalid line numbers?"
- "Should I validate event structure?"

##### 2. Confirm Examples

- Walk through Example 1 verbally
- Confirm expected output matches your understanding
- Note any inconsistencies in examples

##### 3. Discuss Approach

- "I'll sort events by timestamp first..."
- "I'll use a list for lines for  $O(1)$  indexing..."
- "Time complexity will be  $O(n \log n)$  for sorting..."

##### 4. Mention Edge Cases

- "I'll need to handle out-of-order events..."
- "Case-insensitive event names..."
- "Multiple appends to same line..."

**This shows you're thinking critically and builds trust!**

### 14.3 While Coding

#### 1. Think Out Loud

- "Now I'll sort the events by timestamp..."

- "Converting to 0-indexed here because Python lists..."
- "Using += here to append, not replace..."

## 2. Write Clean Code

- Descriptive variable names: `line_idx`, not `i`
- Add comments for non-obvious logic
- Consistent spacing and formatting

## 3. Handle Errors Gracefully

- Use `.get()` for optional dictionary keys
- Check for `None`/empty before processing
- Validate inputs if time permits

## 4. Ask If Stuck

- "I'm debating between X and Y, which would you prefer?"
- "Should I prioritize robustness or simplicity here?"
- Don't sit in silence - communicate!

# 14.4 After Coding

## 1. Test Immediately

- Run provided examples first
- Test edge cases (empty, out-of-order, same line)
- Fix any bugs found

## 2. Walk Through Code

- Explain your solution at high level
- Point out key design decisions
- Mention trade-offs considered

## 3. Discuss Improvements

- "For production, I'd add validation..."
- "Could optimize with rope data structure..."
- "Would need CRDT for real-time collaboration..."

## 4. Handle Follow-Ups

- Be ready for variations (insert, delete range)
- Explain how to extend solution
- Discuss system design implications

## 15 Communication Checklist

### 15.1 Before Interview

- ☐ Practiced core solution multiple times (can code in 20-25 min)
- ☐ Memorized critical edge cases
- ☐ Tested with all provided examples
- ☐ Understand time/space complexity
- ☐ Reviewed follow-up variations
- ☐ Comfortable with both Python and JavaScript
- ☐ Practiced explaining thought process out loud
- ☐ Prepared clarifying questions to ask

### 15.2 During Interview - Execution

- ☐ Asked clarifying questions upfront
- ☐ Confirmed understanding of examples
- ☐ Explained approach before coding
- ☐ Thought out loud while implementing
- ☐ Handled edge cases explicitly
- ☐ Wrote clean, readable code
- ☐ Tested code with examples
- ☐ Discussed complexity analysis
- ☐ Proposed optimizations
- ☐ Asked intelligent follow-up questions

### 15.3 During Interview - Communication

- ☐ Maintained conversational tone
- ☐ Explained reasoning for decisions
- ☐ Asked for feedback/hints when stuck
- ☐ Admitted when unsure (don't fake it)
- ☐ Showed enthusiasm and engagement
- ☐ Treated interviewer as collaborator

## 16 Quick Reference Card

### 16.1 Key Points to Remember

1. **ALWAYS** sort events by timestamp first!
2. Use list for lines (not string manipulation)
3. Lines are 1-indexed in problem, 0-indexed in Python
4. Case-insensitive event names - use `.lower()`
5. **APPEND** to line with `+=`, DON'T REPLACE with `=`
6. Fill gaps with empty strings when extending
7. Update `lastUpdated` to latest event timestamp
8. Return a copy - don't mutate input document

### 16.2 Common Mistakes to Avoid

- Forgetting to sort events
- Not handling case-insensitive event names
- Using `=` instead of `+=` for append (replaces instead of appends!)
- Off-by-one errors with 1-indexed vs 0-indexed
- Not handling empty events or missing content
- Modifying input document directly
- Not testing edge cases

### 16.3 Python Quick Reference

```
1 # Safe dictionary access
2 content = document.get("content", "") # Default empty string
3 payload = event.get("payload", {})    # Default empty dict
4
5 # Case-insensitive comparison
6 event_name = event["event_name"].lower()
7
8 # List operations
9 lines = []
10 lines.append("new")                # Add to end
11 lines[idx] += "text"               # Append to existing
12 while len(lines) <= idx:          # Extend with gaps
13     lines.append("")
14
15 # String operations
16 lines = content.split("\n")        # Split into list
17 content = "\n".join(lines)         # Join back to string
18
19 # Sorting
20 sorted_events = sorted(events, key=lambda e: e["timestamp"])
21
22 # List comprehension
23 valid = [e for e in events if e.get("timestamp") is not None]
```

## 17 Final Preparation Checklist

### 17.1 Technical Readiness

- ☐ Can implement solution in under 25 minutes
- ☐ All 12+ test cases pass without bugs
- ☐ Understand why each edge case matters
- ☐ Can explain time/space complexity
- ☐ Know how to extend for new event types
- ☐ Comfortable with alternative approaches (OOP, JS)

### 17.2 Interview Skills

- ☐ Practiced asking clarifying questions
- ☐ Can explain approach before coding
- ☐ Comfortable thinking out loud
- ☐ Know how to debug when tests fail
- ☐ Can discuss system design implications
- ☐ Ready for follow-up variations

### 17.3 Day Before Interview

- ☐ Do one final practice run (timed, 30 min)
- ☐ Review edge cases one more time
- ☐ Read through this guide's key sections
- ☐ Prepare 2-3 questions to ask interviewer
- ☐ Get good sleep - fresh mind is critical!

### 17.4 Interview Day

- ☐ Test internet connection and mic/camera
- ☐ Have this guide open for reference (if allowed)
- ☐ Water nearby, comfortable environment
- ☐ Positive mindset - you've got this!

---

**You Are Ready!**

You've prepared thoroughly. You know the solution inside-out. You understand the edge cases. You can handle follow-ups. Now trust your preparation and show them what you can do!

**Remember:**

- The interviewer wants you to succeed
- They're evaluating how you think, not just coding speed
- Communication matters as much as the solution
- It's okay to ask questions - that's smart!
- One bug doesn't fail you - recovery matters

**Good luck with your ClickUp interview!**