

Sistema de Servicio Social

Proyectos Solidarios

GET GET - Obtener todos los proyectos

https://mhnvuuyhkanakywjjpl.supabase.co/rest/v1/proyectos_solidarios

API Endpoint: Get Solidarity Projects

Method

GET

Endpoint

https://mhnvuuyhkanakywjjpl.supabase.co/rest/v1/proyectos_solidarios

Description

This endpoint retrieves a list of solidarity projects. It returns essential details about each project, including its ID, acceptance profile, objectives, activities, and other relevant information.

Request Parameters

This endpoint does not require any request parameters.

Response Format

On a successful request, the API will return a JSON array containing objects with the following fields:

- **id_proyecto:** (integer) Unique identifier for the project.
- **cupos:** (integer) Number of available spots for the project.
- **perfil_aceptacion:** (string) Acceptance profile for participants.
- **proyecto:** (string) Name of the project.
- **objetivo_ps:** (string) Objective of the solidarity project.
- **num_pmt:** (string) Number of the project management team.
- **ods_ps:** (integer) Related Sustainable Development Goals (SDGs).

- **actividades:** (string) Activities involved in the project.
- **detalles_horario:** (string) Schedule details for the project.
- **habilidades:** (string) Required skills for participants.
- **modalidad:** (string) Mode of participation (e.g., online, in-person).
- **lugar_trabajo:** (string) Work location for the project.
- **duracion:** (string) Duration of the project.
- **horas:** (integer) Total hours required for participation.
- **tipo_inscripcion:** (string) Type of registration for the project.
- **ruta_maps:** (string) Link to the project location on maps.
- **crn:** (integer) Course reference number.
- **grupo:** (string) Group associated with the project.
- **clave:** (string) Key identifier for the project.
- **periodo_academico:** (string) Academic period relevant to the project.
- **fecha_pue:** (string) Date of publication for the project.
- **pregunta_1:** (string) First question related to the project.
- **pregunta_2:** (string) Second question related to the project.
- **pregunta_3:** (string) Third question related to the project.
- **carreras:** (string) Associated careers or fields of study.
- **correo:** (string) Contact email for inquiries.

Response Example

A successful response will return a JSON array similar to the following:

```
json
[{"id_proyecto": 0,
 "cupos": 0,
 "perfil_aceptacion": "",
 "proyecto": "",
 "objetivo_ps": "",
 "num_pmt": "",
 "ods_ps": 0,
 "actividades": "",
 "detalles_horario": ""},
```

HEADERS

Authorization

Bearer

eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZil6Im1obnZ1dXI5aGthbmFrExdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsFUWpLUhUBROdC4mMTeBGmpfJ8QQw

GET GET - Obtener proyecto específico

https://mhnuuyykanakywjpl.supabase.co/rest/v1/proyectos_solidarios?id_proyecto=eq.1

Get Project Details

This endpoint retrieves detailed information about a specific solidarity project based on the provided project ID.

Request

- **Method:** GET
- **URL:** https://mhnuuyykanakywjpl.supabase.co/rest/v1/proyectos_solidarios
- **Query Parameters:**
 - `id_proyecto` : The ID of the project you want to retrieve. It should be in the format `eq.{project_id}` where `{project_id}` is the unique identifier of the project.

Response

The response will contain the details of the requested project in JSON format. The structure of the response typically includes the following fields:

- `id` : The unique identifier of the project.
- `nombre` : The name of the project.
- `descripcion` : A brief description of the project.
- `fecha_inicio` : The start date of the project.
- `fecha_fin` : The end date of the project.
- `estado` : The current status of the project.
- `beneficiarios` : Information about the beneficiaries of the project.

Ensure to handle the response appropriately based on the structure provided.

HEADERS

Authorization

Bearer

eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIslnJlZi6Im
1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM
5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4m
MTeBGmpfJ8QQw

apikey

eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9eyJpc3MiOiJzdXBhYmFzZSIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM

5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

PARAMS

id_proyecto eq.1

POST POST - Crear nuevo proyecto

https://mhnuuyykanakywjjpl.supabase.co/rest/v1/proyectos_solidarios

API Endpoint: Create Solidarity Projects

This endpoint allows users to create new solidarity projects by submitting relevant details through an HTTP POST request. The request body must contain specific information about the project, including its objectives, activities, and participant requirements.

Request Body Format

The request body should be in JSON format and include the following parameters:

- **cupos** (integer): The number of available spots for participants.
- **perfil_aceptacion** (string): The profile of individuals accepted for the project.
- **proyecto** (string): The name of the project.
- **objetivo_ps** (string): The main objective of the project.
- **num_pmt** (string): The period of the project.
- **ods_ps** (integer): The related sustainable development goal.
- **actividades** (string): The activities involved in the project.
- **detalles_horario** (string): The schedule details for the project.
- **habilidades** (string): Required skills for participants.
- **modalidad** (string): The mode of participation (e.g., in-person).
- **lugar_trabajo** (string): The location where the project will take place.
- **duracion** (string): The duration of the project.
- **horas** (integer): The total number of hours involved in the project.
- **tipo_inscripcion** (string): The type of registration process.
- **ruta_maps** (string): A URL link to the project location on Google Maps.
- **crn** (integer): The course reference number.
- **grupo** (integer): The group number associated with the project.
- **clave** (string): A unique key for the project.
- **periodo_academico** (string): The academic period during which the project takes place.

- **fecha_pue** (string): The dates for the project.
- **pregunta_1** (string): A question related to the participant's knowledge.
- **pregunta_2** (string): A question regarding previous experience with communities.
- **pregunta_3** (string): A question about how the participant would contribute to the project.
- **carreras** (string): The fields of study relevant to the project.
- **correo** (string): The email address for communication.

Response Structure

Upon successful creation of the solidarity project, the API will return a response containing confirmation of the project details. The structure of the response typically includes:

- **status** (string): Indicates the success or failure of the request.
- **message** (string): A descriptive message providing additional context.
- **data** (object): An object containing the details of the created project, which may include the same parameters submitted in the request.

Ensure that all required fields are filled out correctly to avoid errors during the project creation process.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSlzInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSl6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
----------------------	--

apikey	eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSlzInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSl6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
---------------	--

Content-Type	application/json
---------------------	------------------

Body raw (json)

```
json
{
  "cupos": 25,
  "perfil_aceptacion": "Estudiantes de carreras de salud",
  "proyecto": "Apoyo Nutricional Comunitario",
  "objetivo_ps": "Brindar educación nutricional a familias de bajos recursos en comunidades ru:",
  "num_pmt": "Periodo 2",
  "ods_ps": 2,
  "actividades": "Talleres de cocina saludable, evaluaciones nutricionales, huertos urbanos.",
  "detalles_horario": "Martes y jueves de 2 pm a 6 pm"
}
```

```
----- . ----- , ----- - - - - - p - - ,  
"habilidades": "Conocimientos básicos de nutrición y comunicación efectiva",  
"modalidad": "Presencial",  
"lugar_trabajo": "Centro Comunitario San José",  
"duracion": "6 semanas",  
"horas": 144,  
"tipo_inscripcion": "Por postulación",  
"ruta_maps": "https://www.google.com/maps/dir/.../centro-comunitario-san-jose",  
"crn": 61283,  
"grupo": 105,  
"clave": "WA1069",  
"periodo_academico": "Febrero-Junio 2025",  
"fecha_pue": "Del 10 de marzo al 21 de abril",  
"pregunta_1": "¿Qué conocimientos tienes sobre nutrición?",  
"pregunta_2": "¿Has trabajado con comunidades vulnerables?",  
"pregunta_3": "¿Cómo contribuirías al proyecto?",  
"carreras": "IB, IBT, IQA",  
"correo": "nutricion.comunitaria@tec.mx"  
}
```

DELETE DELETE - Eliminar proyecto

https://mhnvuuyhkanakywjjpl.supabase.co/rest/v1/proyectos_solidarios?id_proyecto=eq.1

Delete Project Endpoint

This endpoint is used to delete a specific project identified by its unique project ID. The request removes the project from the system, ensuring that it is no longer accessible or retrievable.

Request Parameters

- **id_proyecto** (query parameter): This is a required parameter that specifies the unique identifier of the project to be deleted. It should be provided in the format `eq.{project_id}`, where `{project_id}` is the ID of the project you wish to remove.

Example Request

Plain Text

```
DELETE https://mhnvuuyhkanakywjjpl.supabase.co/rest/v1/proyectos\_solidarios?id\_proyecto=eq.1
```

Response Structure

Upon successful deletion, the response will typically include a status code indicating the result of the operation. A successful deletion will return a `204 No Content` status, indicating that the request was processed successfully and there is no additional content to return.

In case of an error (e.g., if the project ID does not exist), the response may include an appropriate error status code along with a message detailing the issue.

Expected Response Codes

- **204 No Content:** The project was successfully deleted.
- **404 Not Found:** The specified project ID does not exist.
- **400 Bad Request:** The request was malformed or missing required parameters.

This endpoint is essential for managing projects within the system, allowing users to maintain an up-to-date project list by removing those that are no longer needed.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSlzInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBslwicm9sZSl6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSlzInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBslwicm9sZSl6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

PARAMS

id_proyecto	eq.1
-------------	------

Postulaciones

GET GET - Obtener todas las postulaciones

<https://mhnuuyykanakywjjpl.supabase.co/rest/v1/postulacion>

Endpoint Description

This endpoint retrieves information related to the "postulacion" resource. It is designed to fetch data that may include various attributes associated with the applications or submissions made by users.

Request Format

- **Method:** GET
- **URL:** <https://mhnuuyykanakywjjpl.supabase.co/rest/v1/postulacion>

Response Structure

The response will return a JSON object containing details about the "postulacion" resource. The exact structure of the response will depend on the data available, but it typically includes keys representing various attributes of the resource.

Example Response

```
json

{
  "id": "string",
  "status": "string",
  "created_at": "string",
  "updated_at": "string",
  ...
}
```

Notes

- Ensure that the request is made to the correct endpoint to retrieve the desired data.
- The response will provide the necessary details for further processing or display in the application.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

GET GET - Obtener postulación de estudiante específico

https://mhnuuyyhanakywjjpl.supabase.co/rest/v1/postulacion?email=eq.a01734271@tec.mx&select=estatus,id_proyecto

Endpoint Description

This endpoint retrieves the application status and project ID associated with a specific email address.

Request Parameters

- **email** (string): The email address of the user whose application status is being queried. It is required and should be formatted correctly.
- **select** (string): A comma-separated list of fields to be included in the response. In this case, it specifies that the `estatus` (status) and `id_proyecto` (project ID) should be returned.

Expected Response

The response will include a JSON object containing the following fields:

- **estatus**: The current status of the application.
- **id_proyecto**: The ID of the associated project.

Notes

- Ensure that the email provided is valid and corresponds to an existing application.
- The response will return an array of objects, even if there is only one matching record.
- If no application is found for the provided email, the response may return an empty array.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

PARAMS

email	eq.a01734271@tec.mx
select	estatus,id_proyecto

POST POST - Crear nueva postulación

<https://mhnuuyyhanakywjjpl.supabase.co/rest/v1/postulacion>

POST /postulacion

This endpoint allows users to submit an application for a specific project. The request requires a JSON payload containing various parameters related to the applicant's information and their responses to specific questions.

Request Body Parameters

- **matricula** (string): The unique enrollment number of the applicant.
- **id_proyecto** (integer): The ID of the project the applicant is applying for.
- **respuesta_1** (string): The applicant's response to the first question regarding their knowledge or skills.
- **respuesta_2** (string): The applicant's response to the second question about their previous participation in related activities.
- **respuesta_3** (string): The applicant's response to the third question regarding their expectations from the project.
- **estatus** (string): The current status of the application (e.g., "postulado").
- **nombre** (string): The full name of the applicant.
- **carrera** (string): The career or field of study of the applicant.
- **email** (string): The email address of the applicant for communication purposes.
- **numero** (string): The contact number of the applicant.

Expected Response

Upon successful submission of the application, the API will return a confirmation response indicating the status of the application. The exact structure of the response may vary, but it typically includes a success message and any relevant identifiers for the application.

Notes

- Ensure that all required fields are filled out accurately to avoid validation errors.
- The `estatus` field is set to "postulado" by default upon submission.
- This endpoint is essential for tracking applications and managing project participation.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCI6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSlzInJlZi6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCI6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSlzInJlZi6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
Content-Type	application/json

Body raw (json)

json

```
{  
  "matricula": "a01734271",  
  "id_proyecto": 1,  
  "respuesta_1": "Tengo conocimientos básicos de primeros auxilios y me apasiona ayudar a los demás.",  
  "respuesta_2": "Sí, he participado en brigadas de salud en mi comunidad",  
  "respuesta_3": "Espero desarrollar mis habilidades interpersonales y contribuir al bienestar de la sociedad.",  
  "estatus": "postulado",  
  "nombre": "María Fernanda González",  
  "carrera": "IBT",  
  "email": "a01734271@tec.mx",  
  "numero": "2464701196"  
}
```

DELETE DELETE - Eliminar postulación

<https://mhnvuuyykanakywjjpl.supabase.co/rest/v1/postulacion?matricula=eq.a01734271>

DELETE /postulacion

This endpoint is used to delete a specific postulacion (application) identified by the provided matricula (registration number).

Request Parameters

- matricula:** This is a query parameter that specifies the unique registration number of the postulacion to be deleted. The value should be formatted as `eq.<registration_number>`.

Expected Request Format

This endpoint does not require a request body; the deletion is performed based solely on the matricula query parameter.

Response Structure

Upon successful deletion, the server will return a response indicating the status of the operation. The response typically includes:

- status:** A confirmation message indicating whether the deletion was successful.
- message:** Additional information about the deletion process.

Example Response

json

```
{  
  "status": "Success",  
  "message": "Postulacion deleted successfully."}
```

```
        "status": "success",
        "message": "Postulacion deleted successfully."
    }
```

Ensure that the provided matricula is valid and corresponds to an existing postulacion to avoid errors during the deletion process.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9eyJpc3MiOiJzdXBhYmFzZSIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9eyJpc3MiOiJzdXBhYmFzZSIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

PARAMS

matricula	eq.a01734271
-----------	--------------

Socioformadores

GET GET - Obtener todos los socioformadores

<https://mhnuuyyhanakywjpl.supabase.co/rest/v1/socioformador>

Get Socioformador

This endpoint retrieves a list of socioformador entities from the server. The request does not require any parameters and is performed using the HTTP GET method.

Request

- **Method:** GET
- **URL:** <https://mhnuuyyhanakywjpl.supabase.co/rest/v1/socioformador>

Response

The expected response is a JSON object containing an array of socioformador entries. Each entry in the array will typically

Include details relevant to the socioformador, such as identifiers and attributes associated with each entity.

Notes

- Ensure that the base URL is correctly set before making the request.
- The response will be in JSON format and should be parsed accordingly.
- This endpoint may be subject to authentication and authorization checks, so ensure that appropriate credentials are provided if required.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSlzInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBslwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSlzInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBslwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

GET GET - Obtener socioformador específico

https://mhnvuuyyhanakywjpl.supabase.co/rest/v1/socioformador?id_socioformador=eq.165

Get Socioformador

This endpoint retrieves a list of socioformadores from the system.

Request Parameters

- **None:** This GET request does not require any parameters.

Expected Response

The response will contain a JSON object with the following structure:

- **socioformadores:** An array of socioformador objects, each containing details about individual socioformadores.

Notes

- Ensure that you have the necessary permissions to access this endpoint.
- The response will return an empty array if no socioformadores are found.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9eyJpc3MiOiJzdXBhYmFzZSlslnJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9eyJpc3MiOiJzdXBhYmFzZSlslnJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

PARAMS

id_socioformador	eq.165
------------------	--------

POST POST - Crear nuevo socioformador

<https://mhnvuuyyhkanakywjjpl.supabase.co/rest/v1/socioformador>

Add Socioformador

This endpoint allows you to add a new socioformador (trainer) to a specific project.

Request Method

POST

Endpoint

<https://mhnvuuyyhkanakywjjpl.supabase.co/rest/v1/socioformador>

Request Parameters

The request body must be in JSON format and include the following parameters:

- **correo** (string): The email address of the socioformador. This should be a valid email format.
- **id_proyecto** (integer): The ID of the project to which the socioformador is being added. This should correspond to an existing project in the system.

Expected Response Format

On a successful request, the API will respond with a confirmation message and details of the newly created socioformador. The response will typically be in JSON format, containing relevant details such as the ID of the newly

created socioformador and a success status.

Ensure that the provided email is unique and that the project ID exists within the database to avoid errors during the request.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9eyJpc3MiOiJzdXBhYmFzZSlsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9eyJpc3MiOiJzdXBhYmFzZSlsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
Content-Type	application/json

Body raw (json)

```
json

{
  "correo": "nutricion.comunitaria@tec.mx",
  "id_proyecto": 2
}
```

DELETE DELETE - Eliminar socioformador

https://mhnvuuyyhanakywjpl.supabase.co/rest/v1/socioformador?id_socioformador=eq.165

DELETE /socioformador

This endpoint is used to delete a specific socioformador (trainer) record from the system. The deletion is identified by the unique `id_socioformador` parameter provided in the query string.

Request Parameters

- **id_socioformador** (required): This is a query parameter that specifies the unique identifier of the socioformador to be deleted. It should be provided in the format `eq.{id}` where `{id}` is the unique ID of the socioformador.

Example Request

Plain Text

```
DELETE https://mhnvuuyyhanakywjjpl.supabase.co/rest/v1/socioformador?id_socioformador=eq.165
```

Response Structure

Upon a successful deletion, the server typically responds with a status code indicating the result of the operation. A successful deletion usually returns a `204 No Content` status, indicating that the request was processed successfully and there is no additional content to return.

In case of an error (e.g., if the specified `id_socioformador` does not exist), the server may return a `404 Not Found` status along with an error message detailing the reason for the failure.

Expected Response Codes

- **204 No Content:** Indicates that the socioformador was successfully deleted.
- **404 Not Found:** Indicates that the socioformador with the specified ID does not exist.

This endpoint is essential for managing socioformador records, allowing for the removal of entries that are no longer needed or relevant.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSlsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSlsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

PARAMS

<code>id_socioformador</code>	eq.165
-------------------------------	--------

ODS (Objetivos de Desarrollo Sostenible)

<https://mhnvuuyykanakywjjpl.supabase.co/rest/v1/ods>

API Endpoint: Retrieve ODS Data

This endpoint allows users to retrieve data from the ODS (Operational Data Store). It is designed to fetch a collection of records related to the ODS.

Request Method

- GET

Request Parameters

This endpoint does not require any input parameters in the request.

Response Structure

Upon a successful request, the response will include a JSON object containing the following structure:

- **data**: An array of ODS records, where each record may contain various fields relevant to the ODS.
- **status**: A string indicating the success or failure of the request.
- **message**: A descriptive message providing additional context about the response.

Example Response

```
json

{
  "data": [
    {
      "id": "1",
      "name": "Sample Data 1",
      "value": "Example Value 1"
    },
    {
      "id": "2",
      "name": "Sample Data 2",
      "value": "Example Value 2"
    }
  ]
}
```

This endpoint is useful for applications that need to access and display ODS data for further processing or analysis.

HEADERS

Authorization

Bearer

eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIslnJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9s7SI6ImFub24iLCJpYXQiOjE3NDQzMzM

5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4m
MTeBGmpfJ8QQw

apikey

eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIslnJlZil6Im
1obrnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM
5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4m
MTeBGmpfJ8QQw

GET GET - Obtener ODS específico

https://mhnuuyykanakywjjpl.supabase.co/rest/v1/ods?id_ods=eq.1

Endpoint Description

This endpoint retrieves information about a specific object from the ODS (Operational Data Store) based on the provided identifier.

Request Format

- **Method:** GET
- **URL:** <https://mhnuuyykanakywjjpl.supabase.co/rest/v1/ods>
- **Query Parameter:**
 - `id_ods` : This is a required query parameter that specifies the unique identifier of the ODS object you want to retrieve. In this case, it is set to `eq.1`, which indicates that you are looking for the object with an ID equal to 1.

Expected Response Format

The response will return a JSON object containing the details of the requested ODS object. The structure of the response will include various attributes related to the ODS, which may include metadata, status, and other relevant information, depending on the implementation.

Make sure to handle the response appropriately, as it may vary based on the existence of the specified `id_ods`.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

PARAMS

<code>id_ods</code>	eq.1
---------------------	------

POST POST - Crear nuevo ODS

<https://mhnvuuyyhkanakywjjpl.supabase.co/rest/v1/ods>

Add ODS

This endpoint allows you to create a new ODS (Sustainable Development Goal) entry in the system.

Request Method

- POST

Endpoint

- <https://mhnvuuyyhkanakywjjpl.supabase.co/rest/v1/ods>

Request Body

The request body must be in JSON format and include the following parameters:

- **nombre_ods** (string): The name of the ODS you want to add. This is a required field.
- **link_logo** (string): A URL link to the logo associated with the ODS. This is also a required field.

Example Request Body

```
json

{
  "nombre_ods": "Hambre Cero",
  "link_logo": "http://www.un.org/sustainabledevelopment"
}
```

Expected Response

On a successful request, the server will respond with a confirmation message and details of the newly created ODS entry. The response format will typically be in JSON, containing relevant information about the created ODS.

Make sure to handle any potential errors that may arise from invalid input or server issues.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZiI6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM
---------------	---

```
5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4m  
MTeBGmpfJ8QQw
```

apikey eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9eyJpc3MiOiJzdXBhYmFzZSIslnJlZil6Im
1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM
5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4m
MTeBGmpfJ8QQw

Content-Type application/json

Body raw (json)

```
json
```

```
{  
  "nombre_ods": "Hambre Cero",  
  "link_logo": "http://www.un.org/sustainabledevelopment/es/wp-content/uploads/sites/3/2016/01/  
}
```

DELETE DELETE - Eliminar ODS

https://mhnvuuyykanakywjpl.supabase.co/rest/v1/ods?id_ods=eq.1

DELETE Request to Remove an ODS Entry

This endpoint allows you to delete an ODS (Operational Data Store) entry based on its unique identifier.

Request Parameters

- **id_ods** (query parameter): The unique identifier of the ODS entry you wish to delete. It should be specified in the format `eq.{id}` where `{id}` is the identifier of the ODS entry.

Example Request

```
Plain Text
```

```
DELETE https://mhnvuuyykanakywjpl.supabase.co/rest/v1/ods?id\_ods=eq.1
```

Expected Response

Upon successful deletion, the API will return a response indicating the status of the operation. Typically, a successful deletion will return a `204 No Content` status code, indicating that the request was processed successfully and there is no content to return.

Notes

- Ensure that you have the necessary permissions to delete the ODS entry.
- Deleting an ODS entry is irreversible; proceed with caution.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9eyJpc3MiOiJzdXBhYmFzZSlzInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBslwicm9sZSl6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9eyJpc3MiOiJzdXBhYmFzZSlzInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBslwicm9sZSl6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

PARAMS

id_ods	eq.1
--------	------

Carreras

GET GET - Obtener todas las carreras

<https://mhnvuuyykanakywjpl.supabase.co/rest/v1/carrera>

Endpoint: Retrieve Carrera Information

Method: `GET`

URL: <https://mhnvuuyykanakywjpl.supabase.co/rest/v1/carrera>

This endpoint is used to retrieve information related to "carrera".

Request Parameters

This endpoint does not require any query parameters in the request.

Expected Response Format

The response will be in JSON format and will contain the following fields:

- **id:** Unique identifier for the carrera.
- **name:** Name of the carrera.
- **description:** A brief description of the carrera.
- **duration:** Duration of the carrera in years.
- **status:** Current status of the carrera (e.g., active, inactive).

The response will provide a comprehensive overview of the carrera details, enabling users to understand the available carreras in the system.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9eyJpc3MiOiJzdXBhYmFzZIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9eyJpc3MiOiJzdXBhYmFzZIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

GET GET - Obtener carrera específica

https://mhnvuuyykanakywjjpl.supabase.co/rest/v1/carrera?id_carrera=eq.1

Endpoint Description

This endpoint retrieves information about a specific "carrera" (course) based on the provided identifier. The request is made using an HTTP GET method, and it allows users to fetch details related to a particular course in the system.

Request Format

- **Method:** GET
- **URL:** https://mhnvuuyykanakywjjpl.supabase.co/rest/v1/carrera?id_carrera=eq.1
- **Query Parameters:**
 - **id_carrera :** This parameter is used to specify the unique identifier of the carrera you wish to retrieve. In this case, it is set to **eq.1**, indicating that the request is targeting the carrera with an ID of 1.

Expected Response Structure

The response will contain the details of the specified carrera in a structured format. Although the exact response structure is not provided, it typically includes key attributes such as:

- `id` : The unique identifier of the carrera.
- `nombre` : The name of the carrera.
- `descripcion` : A description of the carrera.
- `duracion` : The duration of the carrera.
- `fecha_inicio` : The start date of the carrera.
- `fecha_fin` : The end date of the carrera.

The response will be in JSON format, allowing for easy parsing and integration with client applications.

Summary

Use this endpoint to fetch detailed information about a specific carrera by providing its unique identifier in the query string. Ensure that the `id_carrera` parameter is correctly formatted to retrieve the desired data.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSlslnJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSl6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSlslnJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSl6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

PARAMS

id_carrera	eq.1
-------------------	------

POST POST - Crear nueva carrera

<https://mhnuuyykanakywjjpl.supabase.co/rest/v1/carrera>

Endpoint: Add Carrera

This endpoint allows users to add a new "carrera" (program or course) to the system.

Request

- **Method:** POST
- **URL:** <https://mhnuuyykanakywjjpl.supabase.co/rest/v1/carrera>
- **Request Body Format:** The request body must be in JSON format. It should include the following key:

- `carrera` (string): The name of the carrera you wish to add.

Example Request Body:

```
json

{
  "carrera": "IRS"
}
```

Response

Upon a successful request, the server will respond with a confirmation message indicating that the carrera has been added. The expected response format is typically in JSON, containing relevant details about the newly created carrera.

Make sure to handle any errors that may arise from invalid input or server issues.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
Content-Type	application/json

Body raw (json)

```
json

{
  "carrera": "IRS"
}
```

DELETE DELETE - Eliminar carrera

https://mhnuuyyhanakywjjpl.supabase.co/rest/v1/carrera?id_carrera=eq.1

DELETE /carrera

This endpoint is used to delete a specific "carrera" (course) from the system based on the provided identifier.

Purpose

The primary purpose of this request is to remove a course entry from the database. This action is typically performed by an administrator or a user with appropriate permissions.

Input Parameters

- **id_carrera** (query parameter): This is a required parameter that specifies the unique identifier of the "carrera" to be deleted. The value should be provided in the format `eq.{id}`, where `{id}` is the identifier of the course.

Example Request

Plain Text

```
DELETE https://mhnuuyyhanakywjjpl.supabase.co/rest/v1/carrera?id\_carrera=eq.1
```

Response Structure

Upon successful deletion, the server will typically respond with a confirmation message or status indicating the result of the operation. The response may vary depending on the implementation, but it generally includes:

- A status code indicating success (e.g., 204 No Content) or failure (e.g., 404 Not Found if the course does not exist).
- An optional message providing additional context about the deletion operation.

Ensure that you handle the response appropriately in your application to confirm the deletion or to manage any errors that may arise.

HEADERS

Authorization

Bearer

```
eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
```

apikey

```
eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
```

PARAMS

id_carrera

eq.1

Endpoints Adicionales

GET GET - Proyectos por carrera

https://mhnvuuyyhkanakywjjpl.supabase.co/rest/v1/proyectos_solidarios?carreras=like.*IBT*

Endpoint Description

This endpoint retrieves a list of solidarity projects filtered by the specified career criteria. The request allows users to search for projects associated with a particular career by using a query parameter.

Request

- **Method:** GET
- **URL:** [https://mhnvuuyyhkanakywjjpl.supabase.co/rest/v1/proyectos_solidarios?
carreras=like.*IBT*](https://mhnvuuyyhkanakywjjpl.supabase.co/rest/v1/proyectos_solidarios?carreras=like.*IBT*)

Query Parameters

- **carreras** (string): A search parameter used to filter the projects based on the career. The example value `like.*IBT*` indicates that the search will include projects related to careers that contain "IBT".

Response

The response will return a JSON object containing a list of solidarity projects that match the specified career criteria. The structure of the response typically includes:

- **projects** (array): An array of project objects, each containing details about the project.
 - **id** (integer): The unique identifier for the project.
 - **name** (string): The name of the project.
 - **description** (string): A brief description of the project.
 - **career** (string): The career associated with the project.
 - **status** (string): The current status of the project (e.g., active, completed).

Example Response Structure

json

```
{  
  "projects": [  
    {  
      "id": 1,  
      "name": "Project A",  
      "description": "A solidarity project.",  
      "career": "Engineering",  
      "status": "Active"  
    },  
    {  
      "id": 2,  
      "name": "Project B",  
      "description": "A solidarity project.",  
      "career": "Medicine",  
      "status": "Completed"  
    }  
  ]  
}
```

```

    "name": "Project A",
    "description": "Description of Project A",
    "career": "IBT",
    "status": "active"
},
{
  ...
}

```

This endpoint is useful for users looking to find solidarity projects related to specific careers, allowing for targeted searches and efficient retrieval of relevant information.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSlzInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSlzInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

PARAMS

carreras	like.*IBT*
----------	------------

GET GET - Postulaciones por estatus

<https://mhnvuuyykanakywjjpl.supabase.co/rest/v1/postulacion?estatus=eq.postulado>

API Endpoint: Retrieve Postulation Status

GET <https://mhnvuuyykanakywjjpl.supabase.co/rest/v1/postulacion?estatus=eq.postulado>

This endpoint is designed to retrieve information about postulations that have a specific status, particularly those that are marked as "postulado".

Query Parameters

- estatus** : This parameter is used to filter the postulations based on their status. The value should be set to `eq.postulado` to fetch only those postulations that are currently in the "postulado" state.

Response Structure

The response will contain a list of postulation objects, each representing a postulation that matches the specified status.

The response will contain a list of postulation objects, each representing a postulation that matches the specified status.

The structure of the response typically includes the following fields:

- `id` : Unique identifier for the postulation.
- `nombre` : The name associated with the postulation.
- `fecha` : The date when the postulation was created.
- `estatus` : The current status of the postulation.

The response will be in JSON format and will provide an array of postulations that meet the criteria defined by the query parameter.

HEADERS

Authorization	Bearer eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSlsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
apikey	eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSlsInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

PARAMS

estatus	eq.postulado
----------------	--------------

GET GET - Proyectos con JOIN a socioformadores

[https://mhnvuuyyhanakywjpl.supabase.co/rest/v1/proyectos_solidarios?select=*,socioformador\(*\)](https://mhnvuuyyhanakywjpl.supabase.co/rest/v1/proyectos_solidarios?select=*,socioformador(*))

Endpoint Description

This endpoint retrieves a list of "proyectos solidarios" (solidarity projects) along with their associated "socioformador" (trainer) information.

Request Parameters

- **select**: This query parameter allows you to specify which fields to return in the response. The value `*` indicates that all fields of the "proyectos solidarios" should be included, while `socioformador(*)` requests all fields of the associated "socioformador" records.

Expected Response

The response will return a JSON object containing an array of "proyectos solidarios". Each project object will include all specified fields, along with a nested object for "socioformador" that contains the relevant details about the trainer associated with each project.

Notes

- Ensure that the `select` parameter is formatted correctly to retrieve the desired fields.
- The response structure will depend on the fields available in the database for both "proyectos solidarios" and "socioformador".
- This endpoint is useful for fetching comprehensive data about solidarity projects and their trainers in a single request.

HEADERS

Authorization

Bearer
eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSlzInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSl6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

apikey

eyJhbGciOiJIUzI1NilsInR5cCl6IkpxVCJ9.eyJpc3MiOiJzdXBhYmFzZSlzInJlZil6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSl6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCl6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw

PARAMS

select

`*,socioformador(*)`

PATCH PATCH - Actualizar estatus de postulación

<https://mhnuuyykanakywjpl.supabase.co/rest/v1/postulacion?matricula=eq.a01734271>

PATCH Request to Update Application Status

This endpoint allows you to update the status of a specific application identified by the `matricula` parameter.

Request Details

- **Method:** `PATCH`
- **Endpoint:** `https://mhnuuyykanakywjpl.supabase.co/rest/v1/postulacion?matricula=eq.a01734271`

Query Parameters

- `matricula` : A unique identifier for the application you wish to update. In this case, it is set to `eq.a01734271`.

Request Body

The request body must be in JSON format and includes the following key:

- `estatus` (string): The new status of the application. In this example, it is set to `"aceptado"`.

Expected Response Format

Upon a successful request, you can expect a response indicating the result of the operation. The response will typically include confirmation of the updated status or any relevant information regarding the success of the operation.

Make sure to handle any potential errors that may arise during the request, such as invalid `matricula` values or issues with the provided status.

HEADERS

<code>Authorization</code>	Bearer eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZiI6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
<code>apikey</code>	eyJhbGciOiJIUzI1NilsInR5cCI6IkpXVCJ9.eyJpc3MiOiJzdXBhYmFzZSIsInJlZiI6Im1obnZ1dXI5aGthbmFreXdqanBsliwicm9sZSI6ImFub24iLCJpYXQiOjE3NDQzMzM5MTEsImV4cCI6MjA1OTcwOTkxMX0.5SobtW6f5oHTWsF_UWpLUhUBROdC4mMTeBGmpfJ8QQw
<code>Content-Type</code>	application/json

PARAMS

<code>matricula</code>	<code>eq.a01734271</code>
------------------------	---------------------------

Body raw (json)

json

```
{  
  "estatus": "aceptado"  
}
```