

LTL: Linear Temporal Logic


- ▶ Computation Tree
- ▶ Linear Temporal Logic
- ▶ Using Temporal Formulas
- ▶ Equivalences of Temporal Formulas

Computation Tree


Let $\mathbb{S} = (S, In, T, \mathcal{X}, dom)$ be a transition system and $s \in S$ be a state. The **computation tree for \mathbb{S} starting at s** is the following (possibly infinite) tree.

1. The **nodes** of the tree are labeled by states in S .
2. The **root** of the tree is labeled by s .
3. For every node s' in the tree, its **children** are exactly such nodes $s'' \in S$ that $(s', s'') \in T$.


Computation Trees and Paths



Computation Trees and Paths




Computation Trees and Paths




A **computation path** for \mathbb{S} : any branch s_0, s_1, \dots in the tree.

Computation Trees and Paths



A **computation path** for \mathbb{S} : any branch s_0, s_1, \dots in the tree.


Computation Trees and Paths



A **computation path** for \mathbb{S} : any branch s_0, s_1, \dots in the tree.


Computation

Every path in the computation tree corresponds to a **computation**:




Computation

Every path in the computation tree corresponds to a **computation**:




Computation

Every path in the computation tree corresponds to a **computation**:




Computation

Every path in the computation tree corresponds to a **computation**:



Computation

Every path in the computation tree corresponds to a **computation**:



Properties

- ▶ **Computation paths** for a transition system are **exactly all branches** in the computation trees for this transition system.
- ▶ Let n be a node in a computation tree C for \mathbb{S} labeled by s' . Then the **subtree of C rooted at s' is the computation tree for \mathbb{S} starting at s'** . In other words, every subtree of a computation tree rooted at some node is itself a computation tree.
- ▶ For every transition system \mathbb{S} and state s there exists a **unique computation tree** for \mathbb{S} starting at s , up to the order of children.

Properties

- ▶ Computation paths for a transition system are exactly all branches in the computation trees for this transition system.
- ▶ Let n be a node in a computation tree C for \mathbb{S} labeled by s' . Then the subtree of C rooted at s' is the computation tree for \mathbb{S} starting at s' . In other words, every subtree of a computation tree rooted at some node is itself a computation tree.
- ▶ For every transition system \mathbb{S} and state s there exists a unique computation tree for \mathbb{S} starting at s , up to the order of children.

Properties

- ▶ Computation paths for a transition system are exactly all branches in the computation trees for this transition system.
- ▶ Let n be a node in a computation tree C for \mathbb{S} labeled by s' . Then the subtree of C rooted at s' is the computation tree for \mathbb{S} starting at s' . In other words, every subtree of a computation tree rooted at some node is itself a computation tree.
- ▶ For every transition system \mathbb{S} and state s there exists a unique computation tree for \mathbb{S} starting at s , up to the order of children.

LTL

Linear Temporal Logic is a logic for reasoning about properties of computation paths.

Formulas are built in the same way as in propositional logic, with the following additions:

1. If F is a formula, then $\bigcirc F$, $\Box F$, and $\Diamond F$ are formulas;
2. If F and G are formulas, then $F \mathbf{U} G$ and $F \mathbf{R} G$ are formulas.

LTL

Linear Temporal Logic is a logic for reasoning about properties of computation paths.

Formulas are built in the same way as in propositional logic, with the following additions:

1. If F is a formula, then $\bigcirc F$, $\Box F$, and $\Diamond F$ are formulas;
2. If F and G are formulas, then $F \cup G$ and $F \mathcal{R} G$ are formulas.

LTL


Linear Temporal Logic is a logic for reasoning about properties of computation paths.

Formulas are built in the same way as in propositional logic, with the following additions:

1. If F is a formula, then $\bigcirc F$, $\Box F$, and $\Diamond F$ are formulas;
2. If F and G are formulas, then $F \mathbf{U} G$ and $F \mathbf{R} G$ are formulas.

\bigcirc	next
\Box	always (in future)
\Diamond	sometimes (in future)
\mathbf{U}	until
\mathbf{R}	release

Semantics (intuitive)



Semantics

Unlike propositional formulas, LTL formulas express properties of **computations** or **computation paths**.

Let $\pi = s_0, s_1, s_2 \dots$ be a sequence of states and F be an LTL formula.



We define the notion **F is true on π** (or **F holds on π**), denoted by $\pi \models F$, by induction on F as follows.


For all $i = 0, 1, \dots$ denote by π_i the sequence of states $s_i, s_{i+1}, s_{i+2} \dots$ (note that $\pi_0 = \pi$).

To define $\pi \models F$ we will use $\pi_i \models G$ for some i and G . We will sometimes (slightly informally) say that **G is true in s_i** or **G holds in s_i** to mean that G is true on π_i .

Semantics

Unlike propositional formulas, LTL formulas express properties of **computations** or **computation paths**.

Let $\pi = s_0, s_1, s_2 \dots$ be a sequence of states and F be an LTL formula.



We define the notion F is true on π (or F holds on π), denoted by $\pi \models F$, by induction on F as follows.


For all $i = 0, 1, \dots$ denote by π_i the sequence of states $s_i, s_{i+1}, s_{i+2} \dots$ (note that $\pi_0 = \pi$).

To define $\pi \models F$ we will use $\pi_i \models G$ for some i and G . We will sometimes (slightly informally) say that G is true in s_i or G holds in s_i to mean that G is true on π_i .

Semantics

Unlike propositional formulas, LTL formulas express properties of **computations** or **computation paths**.

Let $\pi = s_0, s_1, s_2 \dots$ be a sequence of states and F be an LTL formula.



We define the notion **F is true on π** (or **F holds on π**), denoted by $\pi \models F$, by induction on F as follows.


For all $i = 0, 1, \dots$ denote by π_i the sequence of states $s_i, s_{i+1}, s_{i+2} \dots$ (note that $\pi_0 = \pi$).

To define $\pi \models F$ we will use $\pi_i \models G$ for some i and G . We will sometimes (slightly informally) say that **G is true in s_i** or **G holds in s_i** to mean that G is true on π_i .

Semantics

Unlike propositional formulas, LTL formulas express properties of **computations** or **computation paths**.

Let $\pi = s_0, s_1, s_2 \dots$ be a sequence of states and F be an LTL formula.



We define the notion **F is true on π** (or **F holds on π**), denoted by $\pi \models F$, by induction on F as follows.


For all $i = 0, 1, \dots$ denote by π_i the sequence of states $s_i, s_{i+1}, s_{i+2} \dots$ (note that $\pi_0 = \pi$).

To define $\pi \models F$ we will use $\pi_i \models G$ for some i and G . We will sometimes (slightly informally) say that **G is true in s_i** or **G holds in s_i** to mean that G is true on π_i .

Semantics

Unlike propositional formulas, LTL formulas express properties of **computations** or **computation paths**.

Let $\pi = s_0, s_1, s_2 \dots$ be a sequence of states and F be an LTL formula.



We define the notion **F is true on π** (or **F holds on π**), denoted by $\pi \models F$, by induction on F as follows.


For all $i = 0, 1, \dots$ denote by π_i the sequence of states $s_i, s_{i+1}, s_{i+2} \dots$ (note that $\pi_0 = \pi$).

To define $\pi \models F$ we will use $\pi_i \models G$ for some i and G . We will sometimes (slightly informally) say that **G is true in s_i** or **G holds in s_i** to mean that G is true on π_i .

Semantics

Unlike propositional formulas, LTL formulas express properties of **computations** or **computation paths**.

Let $\pi = s_0, s_1, s_2 \dots$ be a sequence of states and F be an LTL formula.



We define the notion **F is true on π** (or **F holds on π**), denoted by $\pi \models F$, by induction on F as follows.


For all $i = 0, 1, \dots$ denote by π_i the sequence of states $s_i, s_{i+1}, s_{i+2} \dots$ (note that $\pi_0 = \pi$).

To define $\pi \models F$ we will use $\pi_i \models G$ for some i and G . We will sometimes (slightly informally) say that **G is true in s_i** or **G holds in s_i** to mean that G is true on π_i .

Semantics

Unlike propositional formulas, LTL formulas express properties of **computations** or **computation paths**.

Let $\pi = s_0, s_1, s_2 \dots$ be a sequence of states and F be an LTL formula.



We define the notion **F is true on π** (or **F holds on π**), denoted by $\pi \models F$, by induction on F as follows.


For all $i = 0, 1, \dots$ denote by π_i the sequence of states $s_i, s_{i+1}, s_{i+2} \dots$ (note that $\pi_0 = \pi$).

To define $\pi \models F$ we will use $\pi_i \models G$ for some i and G . We will sometimes (slightly informally) say that **G is true in s_i** or **G holds in s_i** to mean that G is true on π_i .

Semantics

Unlike propositional formulas, LTL formulas express properties of **computations** or **computation paths**.

Let $\pi = s_0, s_1, s_2 \dots$ be a sequence of states and F be an LTL formula.



We define the notion **F is true on π** (or **F holds on π**), denoted by $\pi \models F$, by induction on F as follows.

For all $i = 0, 1, \dots$ denote by π_i the sequence of states $s_i, s_{i+1}, s_{i+2} \dots$ (note that $\pi_0 = \pi$).

To define $\pi \models F$ we will use $\pi_i \models G$ for some i and G . We will sometimes (slightly informally) say that **G is true in s_i** or **G holds in s_i** to mean that G is true on π_i .

Semantics, formally

The semantics of propositional connectives is standard.

Atomic formulas are true iff they are true in s_0 .

The semantics of formulas built using propositional connectives on π is the same as in propositional logic where all subformulas are also evaluated on π .

1. $\pi \models \top$ and $\pi \not\models \perp$.
2. $\pi \models x = v$ if $s_0 \models x = v$.
3. $\pi \models F_1 \wedge \dots \wedge F_n$ if for all $j = 1, \dots, n$ we have $\pi \models F_j$;
 $\pi \models F_1 \vee \dots \vee F_n$ if for some $j = 1, \dots, n$ we have $\pi \models F_j$.
4. $\pi \models \neg F$ if $\pi \not\models F$.
5. $\pi \models F \rightarrow G$ if either $\pi \not\models F$ or $\pi \models G$;
 $\pi \models F \leftrightarrow G$ if either both $\pi \not\models F$ and $\pi \not\models G$ or both $\pi \models F$ and $\pi \models G$.

Semantics, formally

The semantics of propositional connectives is standard.

Atomic formulas are true iff they are true in s_0 .

The semantics of formulas built using propositional connectives on π is the same as in propositional logic where all subformulas are also evaluated on π .

1. $\pi \models \top$ and $\pi \not\models \perp$.
2. $\pi \models x = v$ if $s_0 \models x = v$.
3. $\pi \models F_1 \wedge \dots \wedge F_n$ if for all $j = 1, \dots, n$ we have $\pi \models F_j$;
 $\pi \models F_1 \vee \dots \vee F_n$ if for some $j = 1, \dots, n$ we have $\pi \models F_j$.
4. $\pi \models \neg F$ if $\pi \not\models F$.
5. $\pi \models F \rightarrow G$ if either $\pi \not\models F$ or $\pi \models G$;
 $\pi \models F \leftrightarrow G$ if either both $\pi \not\models F$ and $\pi \not\models G$ or both $\pi \models F$ and $\pi \models G$.

Semantics, formally

The semantics of propositional connectives is standard.

Atomic formulas are true iff they are true in s_0 .

The semantics of formulas built using propositional connectives on π is the same as in propositional logic where all subformulas are also evaluated on π .

1. $\pi \models \top$ and $\pi \not\models \perp$.
2. $\pi \models x = v$ if $s_0 \models x = v$.
3. $\pi \models F_1 \wedge \dots \wedge F_n$ if for all $j = 1, \dots, n$ we have $\pi \models F_j$;
 $\pi \models F_1 \vee \dots \vee F_n$ if for some $j = 1, \dots, n$ we have $\pi \models F_j$.
4. $\pi \models \neg F$ if $\pi \not\models F$.
5. $\pi \models F \rightarrow G$ if either $\pi \not\models F$ or $\pi \models G$;
 $\pi \models F \leftrightarrow G$ if either both $\pi \not\models F$ and $\pi \not\models G$ or both $\pi \models F$ and $\pi \models G$.

Semantics, formally

The semantics of propositional connectives is standard.

Atomic formulas are true iff they are true in s_0 .

The semantics of formulas built using propositional connectives on π is the same as in propositional logic where all subformulas are also evaluated on π .

1. $\pi \models \top$ and $\pi \not\models \perp$.
2. $\pi \models x = v$ if $s_0 \models x = v$.
3. $\pi \models F_1 \wedge \dots \wedge F_n$ if for all $j = 1, \dots, n$ we have $\pi \models F_j$;
 $\pi \models F_1 \vee \dots \vee F_n$ if for some $j = 1, \dots, n$ we have $\pi \models F_j$.
4. $\pi \models \neg F$ if $\pi \not\models F$.
5. $\pi \models F \rightarrow G$ if either $\pi \not\models F$ or $\pi \models G$;
 $\pi \models F \leftrightarrow G$ if either both $\pi \not\models F$ and $\pi \not\models G$ or both $\pi \models F$ and $\pi \models G$.

Semantics, formally

The semantics of propositional connectives is standard.

Atomic formulas are true iff they are true in s_0 .

The semantics of formulas built using propositional connectives on π is the same as in propositional logic where all subformulas are also evaluated on π .

1. $\pi \models \top$ and $\pi \not\models \perp$.
2. $\pi \models x = v$ if $s_0 \models x = v$.
3. $\pi \models F_1 \wedge \dots \wedge F_n$ if for all $j = 1, \dots, n$ we have $\pi \models F_j$;
 $\pi \models F_1 \vee \dots \vee F_n$ if for some $j = 1, \dots, n$ we have $\pi \models F_j$.
4. $\pi \models \neg F$ if $\pi \not\models F$.
5. $\pi \models F \rightarrow G$ if either $\pi \not\models F$ or $\pi \models G$;
 $\pi \models F \leftrightarrow G$ if either both $\pi \not\models F$ and $\pi \not\models G$ or both $\pi \models F$ and $\pi \models G$.

Semantics, formally

The semantics of propositional connectives is standard.

Atomic formulas are true iff they are true in s_0 .

The semantics of formulas built using propositional connectives on π is the same as in propositional logic where all subformulas are also evaluated on π .

1. $\pi \models \top$ and $\pi \not\models \perp$.
2. $\pi \models x = v$ if $s_0 \models x = v$.
3. $\pi \models F_1 \wedge \dots \wedge F_n$ if for all $j = 1, \dots, n$ we have $\pi \models F_j$;
 $\pi \models F_1 \vee \dots \vee F_n$ if for some $j = 1, \dots, n$ we have $\pi \models F_j$.
4. $\pi \models \neg F$ if $\pi \not\models F$.
5. $\pi \models F \rightarrow G$ if either $\pi \not\models F$ or $\pi \models G$;
 $\pi \models F \leftrightarrow G$ if either both $\pi \not\models F$ and $\pi \not\models G$ or both $\pi \models F$ and $\pi \models G$.

Semantics of temporal operators

6. $\pi \models \bigcirc F$ if $\pi_1 \models F$;


$\pi \models \Diamond F$ if for some $k \geq 0$ we have $\pi_k \models F$;

$\pi \models \Box F$ if for all $i \geq 0$ we have $\pi_i \models F$.

7. $\pi \models F \cup G$ if for some $k \geq 0$ we have $\pi_k \models G$ and

$\pi_0 \models F, \dots, \pi_{k-1} \models F$;

$\pi \models F R G$ if for all $k \geq 0$, either $\pi_k \models G$ or there exists $j < k$ such that $\pi_j \models F$.



Semantics of temporal operators

6. $\pi \models \bigcirc F$ if $\pi_1 \models F$;
 $\pi \models \Diamond F$ if for some $k \geq 0$ we have $\pi_k \models F$;
 $\pi \models \Box F$ if for all $i \geq 0$ we have $\pi_i \models F$.
7. $\pi \models F \cup G$ if for some $k \geq 0$ we have $\pi_k \models G$ and $\pi_0 \models F, \dots, \pi_{k-1} \models F$;
 $\pi \models F R G$ if for all $k \geq 0$, either $\pi_k \models G$ or there exists $j < k$ such that $\pi_j \models F$.



Semantics of temporal operators

6. $\pi \models \bigcirc F$ if $\pi_1 \models F$;
 $\pi \models \Diamond F$ if for some $k \geq 0$ we have $\pi_k \models F$;
 $\pi \models \Box F$ if for all $i \geq 0$ we have $\pi_i \models F$.
7. $\pi \models F \cup G$ if for some $k \geq 0$ we have $\pi_k \models G$ and $\pi_0 \models F, \dots, \pi_{k-1} \models F$;
 $\pi \models F \mathbf{R} G$ if for all $k \geq 0$, either $\pi_k \models G$ or there exists $j < k$ such that $\pi_j \models F$.

 s_0 s_1 s_2 s_{k-1} s_k s_{k+1} $\Box F$  \dots  \dots

Semantics of temporal operators

6. $\pi \models \bigcirc F$ if $\pi_1 \models F$;
 $\pi \models \Diamond F$ if for some $k \geq 0$ we have $\pi_k \models F$;
 $\pi \models \Box F$ if for all $i \geq 0$ we have $\pi_i \models F$.
7. $\pi \models F \mathbf{U} G$ if for some $k \geq 0$ we have $\pi_k \models G$ and
 $\pi_0 \models F, \dots, \pi_{k-1} \models F$;
 $\pi \models F \mathbf{R} G$ if for all $k \geq 0$, either $\pi_k \models G$ or there exists $j < k$
such that $\pi_j \models F$.

s_0

s_1

s_2

s_{k-1}

s_k

s_{k+1}


$F \mathbf{U} G$



Semantics of temporal operators


6. $\pi \models \bigcirc F$ if $\pi_1 \models F$;
 $\pi \models \Diamond F$ if for some $k \geq 0$ we have $\pi_k \models F$;
 $\pi \models \Box F$ if for all $i \geq 0$ we have $\pi_i \models F$.
7. $\pi \models F \cup G$ if for some $k \geq 0$ we have $\pi_k \models G$ and $\pi_0 \models F, \dots, \pi_{k-1} \models F$;
 $\pi \models F \mathbf{R} G$ if for all $k \geq 0$, either $\pi_k \models G$ or there exists $j < k$ such that $\pi_j \models F$.

$s_0 \qquad s_1 \qquad s_2 \qquad \qquad s_{k-1} \qquad s_k \qquad s_{k+1}$



Semantics of temporal operators

6. $\pi \models \bigcirc F$ if $\pi_1 \models F$;
 $\pi \models \Diamond F$ if for some $k \geq 0$ we have $\pi_k \models F$;
 $\pi \models \Box F$ if for all $i \geq 0$ we have $\pi_i \models F$.
7. $\pi \models F \cup G$ if for some $k \geq 0$ we have $\pi_k \models G$ and $\pi_0 \models F, \dots, \pi_{k-1} \models F$;
 $\pi \models F R G$ if for all $k \geq 0$, either $\pi_k \models G$ or there exists $j < k$ such that $\pi_j \models F$.



Standard properties

Two LTL formulas F and G are called **equivalent**, denoted $F \equiv G$, if for every path π we have $\pi \models F$ if and only if $\pi \models G$.

Consider a transition system S . We are interested in checking the following properties of LTL formulas

For an LTL formula F we can consider two kinds of properties of S :

1. does F hold on **some** computation path for S from an initial state?
2. does F hold on **all** computation paths for S from an initial state?

Standard properties

Two LTL formulas F and G are called equivalent, denoted $F \equiv G$, if for every path π we have $\pi \models F$ if and only if $\pi \models G$.

Consider a transition system \mathbb{S} . We are interested in checking the following properties of LTL formulas

For an LTL formula F we can consider two kinds of properties of \mathbb{S} :

1. does F hold on some computation path for \mathbb{S} from an initial state?
2. does F hold on all computation paths for \mathbb{S} from an initial state?

Standard properties

Two LTL formulas F and G are called equivalent, denoted $F \equiv G$, if for every path π we have $\pi \models F$ if and only if $\pi \models G$.

Consider a transition system \mathbb{S} . We are interested in checking the following properties of LTL formulas

For an LTL formula F we can consider two kinds of properties of \mathbb{S} :

1. does F hold on **some** computation path for \mathbb{S} from an initial state?
2. does F hold on **all** computation paths for \mathbb{S} from an initial state?

Precedences of Connectives and Temporal Operators

Connective	Precedence
$\neg, \bigcirc, \Diamond, \Box$	6
U, R	5
\wedge	4
\vee	3
\rightarrow	2
\leftrightarrow	1

Expressing Some Properties

1. F never holds in two consecutive states.

Expressing Some Properties

1. F never holds in two consecutive states. $\Box(F \rightarrow \bigcirc \neg F)$

Expressing Some Properties

1. F never holds in two consecutive states. $\Box(F \rightarrow \bigcirc \neg F)$
2. If F holds in a state s , it also holds in all states after s .

Expressing Some Properties

1. F never holds in two consecutive states. $\Box(F \rightarrow \bigcirc \neg F)$
2. If F holds in a state s , it also holds in all states after s .
 $\Box(F \rightarrow \Box F)$

Expressing Some Properties

1. F never holds in two consecutive states. $\Box(F \rightarrow \bigcirc \neg F)$
2. If F holds in a state s , it also holds in all states after s .
 $\Box(F \rightarrow \Box F)$
3. F holds in at most one state.

Expressing Some Properties

1. F never holds in two consecutive states. $\Box(F \rightarrow \bigcirc \neg F)$
2. If F holds in a state s , it also holds in all states after s .
 $\Box(F \rightarrow \Box F)$
3. F holds in at most one state. $\Box(F \rightarrow \bigcirc \Box \neg F)$

Expressing Some Properties

1. F never holds in two consecutive states. $\Box(F \rightarrow \bigcirc \neg F)$
2. If F holds in a state s , it also holds in all states after s .
 $\Box(F \rightarrow \Box F)$
3. F holds in at most one state. $\Box(F \rightarrow \bigcirc \Box \neg F)$
4. F holds in at least two states.

Expressing Some Properties

1. F never holds in two consecutive states. $\Box(F \rightarrow \bigcirc \neg F)$
2. If F holds in a state s , it also holds in all states after s .
 $\Box(F \rightarrow \Box F)$
3. F holds in at most one state. $\Box(F \rightarrow \bigcirc \Box \neg F)$
4. F holds in at least two states. $\Diamond(F \wedge \bigcirc \Diamond F)$

Expressing Some Properties

1. F never holds in two consecutive states. $\Box(F \rightarrow \bigcirc \neg F)$
2. If F holds in a state s , it also holds in all states after s .
 $\Box(F \rightarrow \Box F)$
3. F holds in at most one state. $\Box(F \rightarrow \bigcirc \Box \neg F)$
4. F holds in at least two states. $\Diamond(F \wedge \bigcirc \Diamond F)$
5. Unless s_i is the first state of the path, if F holds in state s_i , then G must hold in at least one of the two states just before s_i , that is s_{i-1} and s_{i-2} .

Expressing Some Properties

1. F never holds in two consecutive states. $\Box(F \rightarrow \bigcirc \neg F)$
2. If F holds in a state s , it also holds in all states after s .
 $\Box(F \rightarrow \Box F)$
3. F holds in at most one state. $\Box(F \rightarrow \bigcirc \Box \neg F)$
4. F holds in at least two states. $\Diamond(F \wedge \bigcirc \Diamond F)$
5. Unless s_i is the first state of the path, if F holds in state s_i , then G must hold in at least one of the two states just before s_i , that is s_{i-1} and s_{i-2} . $(\bigcirc F \rightarrow G) \wedge \Box(\bigcirc \bigcirc F \rightarrow G \vee \bigcirc G)$

Expressing Some Properties

1. F never holds in two consecutive states. $\Box(F \rightarrow \bigcirc \neg F)$
2. If F holds in a state s , it also holds in all states after s .
 $\Box(F \rightarrow \Box F)$
3. F holds in at most one state. $\Box(F \rightarrow \bigcirc \Box \neg F)$
4. F holds in at least two states. $\Diamond(F \wedge \bigcirc \Diamond F)$
5. Unless s_i is the first state of the path, if F holds in state s_i , then G must hold in at least one of the two states just before s_i , that is s_{i-1} and s_{i-2} . $(\bigcirc F \rightarrow G) \wedge \Box(\bigcirc \bigcirc F \rightarrow G \vee \bigcirc G)$
6. F happens infinitely often.

Expressing Some Properties

1. F never holds in two consecutive states. $\Box(F \rightarrow \bigcirc \neg F)$
2. If F holds in a state s , it also holds in all states after s .
 $\Box(F \rightarrow \Box F)$
3. F holds in at most one state. $\Box(F \rightarrow \bigcirc \Box \neg F)$
4. F holds in at least two states. $\Diamond(F \wedge \bigcirc \Diamond F)$
5. Unless s_i is the first state of the path, if F holds in state s_i , then G must hold in at least one of the two states just before s_i , that is s_{i-1} and s_{i-2} . $(\bigcirc F \rightarrow G) \wedge \Box(\bigcirc \bigcirc F \rightarrow G \vee \bigcirc G)$
6. F happens infinitely often. $\Box \Diamond F$

Expressing Some Properties

1. F never holds in two consecutive states. $\Box(F \rightarrow \bigcirc \neg F)$
2. If F holds in a state s , it also holds in all states after s .
 $\Box(F \rightarrow \Box F)$
3. F holds in at most one state. $\Box(F \rightarrow \bigcirc \Box \neg F)$
4. F holds in at least two states. $\Diamond(F \wedge \bigcirc \Diamond F)$
5. Unless s_i is the first state of the path, if F holds in state s_i , then G must hold in at least one of the two states just before s_i , that is s_{i-1} and s_{i-2} . $(\bigcirc F \rightarrow G) \wedge \Box(\bigcirc \bigcirc F \rightarrow G \vee \bigcirc G)$
6. F happens infinitely often. $\Box \Diamond F$
7. F holds in each even state and does not hold in each odd state (states are counted from 0).

Expressing Some Properties

1. F never holds in two consecutive states. $\Box(F \rightarrow \bigcirc \neg F)$
2. If F holds in a state s , it also holds in all states after s .
 $\Box(F \rightarrow \Box F)$
3. F holds in at most one state. $\Box(F \rightarrow \bigcirc \Box \neg F)$
4. F holds in at least two states. $\Diamond(F \wedge \bigcirc \Diamond F)$
5. Unless s_i is the first state of the path, if F holds in state s_i , then G must hold in at least one of the two states just before s_i , that is s_{i-1} and s_{i-2} . $(\bigcirc F \rightarrow G) \wedge \Box(\bigcirc \bigcirc F \rightarrow G \vee \bigcirc G)$
6. F happens infinitely often. $\Box \Diamond F$
7. F holds in each even state and does not hold in each odd state (states are counted from 0). $F \wedge \Box(F \leftrightarrow \bigcirc \neg F)$.

Meaning of Some Formulas

► $\diamond \square F$;

Meaning of Some Formulas

- ▶ $\Diamond \Box F$;
- ▶ $\Box (F \rightarrow \bigcirc F)$;

Meaning of Some Formulas

- ▶ $\Diamond \Box F$;
- ▶ $\Box (F \rightarrow \bigcirc F)$;
- ▶ $\neg F \mathbf{U} \Box F$;

Meaning of Some Formulas

- ▶ $\Diamond \Box F$;
- ▶ $\Box (F \rightarrow \bigcirc F)$;
- ▶ $\neg F \mathbf{U} \Box F$;
- ▶ $F \mathbf{U} \neg F$;

Meaning of Some Formulas

- ▶ $\Diamond \Box F$;
- ▶ $\Box (F \rightarrow \bigcirc F)$;
- ▶ $\neg F \mathbf{U} \Box F$;
- ▶ $F \mathbf{U} \neg F$;
- ▶ $\Diamond F \wedge \Box (F \rightarrow \bigcirc F)$;

Meaning of Some Formulas

- ▶ $\Diamond \Box F$;
- ▶ $\Box (F \rightarrow \bigcirc F)$;
- ▶ $\neg F \mathbf{U} \Box F$;
- ▶ $F \mathbf{U} \neg F$;
- ▶ $\Diamond F \wedge \Box (F \rightarrow \bigcirc F)$;
- ▶ $\Box \Diamond F$;

Meaning of Some Formulas

- ▶ $\Diamond \Box F$;
- ▶ $\Box (F \rightarrow \bigcirc F)$;
- ▶ $\neg F \mathbf{U} \Box F$;
- ▶ $F \mathbf{U} \neg F$;
- ▶ $\Diamond F \wedge \Box (F \rightarrow \bigcirc F)$;
- ▶ $\Box \Diamond F$;
- ▶ $F \wedge \Box (F \leftrightarrow \neg \bigcirc F)$;

Some useful properties

- ▶ **Reachability and safety properties.**

Let **unsafe** describe states which are **unsafe**.

Then $\Box \neg \text{unsafe}$ express a safety requirement.

Ex: $\Box \neg (\text{disp} = \text{beer} \wedge \text{customer} = \text{prof})$

- ▶ **Mutual exclusion.** Two processes are not in the critical section.

Ex: $\Box \neg (\text{critical}_1 \wedge \text{critical}_2)$

- ▶ **Fairness.** Ex: $\Box (\text{customer} = \text{student} \rightarrow \Diamond \text{customer} = \text{prof})$

- ▶ **Responsiveness:** every request will be eventually acknowledged

Ex: $\Box (\text{request} \rightarrow (\text{request} \text{ U } \text{ack}))$

- ▶ **Alternation.** Ex: $A \wedge \Box (A \leftrightarrow \neg \bigcirc A)$

Some useful properties

- ▶ **Reachability and safety properties.**

Let **unsafe** describe states which are **unsafe**.

Then $\Box \neg \text{unsafe}$ express a safety requirement.

Ex: $\Box \neg (\text{disp} = \text{beer} \wedge \text{customer} = \text{prof})$

- ▶ **Mutual exclusion.** Two processes are not in the critical section.

Ex: $\Box \neg (\text{critical}_1 \wedge \text{critical}_2)$

- ▶ **Fairness.** Ex: $\Box (\text{customer} = \text{student} \rightarrow \Diamond \text{customer} = \text{prof})$

- ▶ **Responsiveness:** every request will be eventually acknowledged

Ex: $\Box (\text{request} \rightarrow (\text{request} \text{ U } \text{ack}))$

- ▶ **Alternation.** Ex: $A \wedge \Box (A \leftrightarrow \neg \bigcirc A)$

Some useful properties

- ▶ **Reachability and safety properties.**

Let **unsafe** describe states which are **unsafe**.

Then $\Box \neg \text{unsafe}$ express a safety requirement.

Ex: $\Box \neg (\text{disp} = \text{beer} \wedge \text{customer} = \text{prof})$

- ▶ **Mutual exclusion.** Two processes are not in the critical section.

Ex: $\Box \neg (\text{critical}_1 \wedge \text{critical}_2)$

- ▶ **Fairness.** Ex: $\Box (\text{customer} = \text{student} \rightarrow \Diamond \text{customer} = \text{prof})$

- ▶ **Responsiveness:** every request will be eventually acknowledged

Ex: $\Box (\text{request} \rightarrow (\text{request} \text{ U } \text{ack}))$

- ▶ **Alternation.** Ex: $A \wedge \Box (A \leftrightarrow \neg \bigcirc A)$

Some useful properties

- ▶ **Reachability and safety properties.**

Let **unsafe** describe states which are **unsafe**.

Then $\Box \neg \text{unsafe}$ express a safety requirement.

Ex: $\Box \neg (\text{disp} = \text{beer} \wedge \text{customer} = \text{prof})$

- ▶ **Mutual exclusion.** Two processes are not in the critical section.

Ex: $\Box \neg (\text{critical}_1 \wedge \text{critical}_2)$

- ▶ **Fairness.** Ex: $\Box (\text{customer} = \text{student} \rightarrow \Diamond \text{customer} = \text{prof})$

- ▶ **Responsiveness:** every request will be eventually acknowledged

Ex: $\Box (\text{request} \rightarrow (\text{request} \text{ U } \text{ack}))$

- ▶ **Alternation.** Ex: $A \wedge \Box (A \leftrightarrow \neg \bigcirc A)$

Some useful properties

- ▶ **Reachability and safety properties.**

Let **unsafe** describe states which are **unsafe**.

Then $\Box \neg \text{unsafe}$ express a safety requirement.

Ex: $\Box \neg (\text{disp} = \text{beer} \wedge \text{customer} = \text{prof})$

- ▶ **Mutual exclusion.** Two processes are not in the critical section.

Ex: $\Box \neg (\text{critical}_1 \wedge \text{critical}_2)$

- ▶ **Fairness.** Ex: $\Box (\text{customer} = \text{student} \rightarrow \Diamond \text{customer} = \text{prof})$

- ▶ **Responsiveness:** every request will be eventually acknowledged

Ex: $\Box (\text{request} \rightarrow (\text{request} \text{ U } \text{ack}))$

- ▶ **Alternation.** Ex: $A \wedge \Box (A \leftrightarrow \neg \bigcirc A)$

Some Equivalences

Two LTL formulas F and G are called **equivalent**, denoted $F \equiv G$, if for every path π we have $\pi \models F$ if and only if $\pi \models G$.

Negation:

$$\begin{aligned}\neg \bigcirc A &\equiv \\ \neg \Diamond A &\equiv \\ \neg \Box A &\equiv \\ \neg(A \cup B) &\equiv\end{aligned}$$

Some Equivalences

Two LTL formulas F and G are called **equivalent**, denoted $F \equiv G$, if for every path π we have $\pi \models F$ if and only if $\pi \models G$.

Negation:

$$\begin{aligned}\neg \bigcirc A &\equiv \bigcirc \neg A \\ \neg \Diamond A &\equiv \\ \neg \Box A &\equiv \\ \neg(A \cup B) &\equiv\end{aligned}$$

Some Equivalences

Two LTL formulas F and G are called **equivalent**, denoted $F \equiv G$, if for every path π we have $\pi \models F$ if and only if $\pi \models G$.

Negation:

$$\begin{aligned}\neg \bigcirc A &\equiv \bigcirc \neg A \\ \neg \Diamond A &\equiv \Box \neg A \\ \neg \Box A &\equiv \Diamond \neg A \\ \neg(A \cup B) &\equiv \neg A \cap \neg B\end{aligned}$$

Some Equivalences

Two LTL formulas F and G are called **equivalent**, denoted $F \equiv G$, if for every path π we have $\pi \models F$ if and only if $\pi \models G$.

Negation:

$$\begin{aligned}\neg \bigcirc A &\equiv \bigcirc \neg A \\ \neg \Diamond A &\equiv \Box \neg A \\ \neg \Box A &\equiv \Diamond \neg A \\ \neg(A \cup B) &\equiv\end{aligned}$$

Some Equivalences

Two LTL formulas F and G are called **equivalent**, denoted $F \equiv G$, if for every path π we have $\pi \models F$ if and only if $\pi \models G$.

Negation:

$$\begin{aligned}\neg \bigcirc A &\equiv \bigcirc \neg A \\ \neg \Diamond A &\equiv \Box \neg A \\ \neg \Box A &\equiv \Diamond \neg A \\ \neg(A \cup B) &\equiv \neg A \mathbin{\Box} \neg B\end{aligned}$$

Expressing operators through \mathbf{U} .

Expressing operators through \mathbf{U} .

$$\begin{aligned}\Diamond A &\equiv \\ \Box A &\equiv \\ A R B &\equiv\end{aligned}$$

LTL **with only** temporal operators \mathbf{U} , \bigcirc has the same expressive power as LTL.

Expressing operators through \mathbf{U} .

Expressing operators through \mathbf{U} .

$$\begin{aligned}\Diamond A &\equiv \top \mathbf{U} A \\ \Box A &\equiv \\ A \mathbf{R} B &\equiv\end{aligned}$$

LTL **with only** temporal operators \mathbf{U} , \bigcirc has the same expressive power as LTL.

Expressing operators through \mathbf{U} .

Expressing operators through \mathbf{U} .

$$\begin{aligned}\Diamond A &\equiv \top \mathbf{U} A \\ \Box A &\equiv \neg(\top \mathbf{U} \neg A) \\ A \mathbf{R} B &\equiv\end{aligned}$$

LTL **with only** temporal operators \mathbf{U} , \bigcirc has the same expressive power as LTL.

Expressing operators through \mathbf{U} .

Expressing operators through \mathbf{U} .

$$\begin{aligned}\Diamond A &\equiv \top \mathbf{U} A \\ \Box A &\equiv \neg(\top \mathbf{U} \neg A) \\ A \mathbf{R} B &\equiv \neg(\neg A \mathbf{U} \neg B)\end{aligned}$$

LTL **with only** temporal operators \mathbf{U} , \bigcirc has the same expressive power as LTL.

Equivalences: Unwinding Properties

$$\begin{aligned}\Diamond F &\equiv F \vee \bigcirc \Diamond F \\ \Box F &\equiv F \wedge \bigcirc \Box F \\ F \mathbf{U} G &\equiv G \vee (F \wedge \bigcirc (F \mathbf{U} G)) \\ F \mathbf{R} G &\equiv G \wedge (F \vee \bigcirc (F \mathbf{R} G))\end{aligned}$$

Other Equivalences

$$\begin{aligned}\Diamond(F \vee G) &\equiv \Diamond F \vee \Diamond G \\ \Box(F \wedge G) &\equiv \Box F \wedge \Box G\end{aligned}$$

Other Equivalences

$$\begin{aligned}\Diamond(F \vee G) &\equiv \Diamond F \vee \Diamond G \\ \Box(F \wedge G) &\equiv \Box F \wedge \Box G\end{aligned}$$

But

$$\begin{aligned}\Box(F \vee G) &\not\equiv \Box F \vee \Box G \\ \Diamond(F \wedge G) &\not\equiv \Diamond F \wedge \Diamond G\end{aligned}$$

How to Show that Two Formulas are **not** Equivalent?

Find a path that satisfies one of the formulas but not the other. For example for $\Box(F \vee G)$ and $\Box F \vee \Box G$.

How to Show that Two Formulas are **not** Equivalent?

Find a path that satisfies one of the formulas but not the other. For example for $\Box(F \vee G)$ and $\Box F \vee \Box G$.



Standard properties

Consider a transition system \mathbb{S} . We are interested in checking the following properties of LTL formulas

For an LTL formula F we can consider two kinds of properties of \mathbb{S} :

1. does F hold on **some** computation path for \mathbb{S} from an initial state?
2. does F hold on **all** computation paths for \mathbb{S} from an initial state?

Standard properties


Consider a transition system \mathbb{S} . We are interested in checking the following properties of LTL formulas

For an LTL formula F we can consider two kinds of properties of \mathbb{S} :

1. does F hold on some computation path for \mathbb{S} from an initial state?
2. does F hold on all computation paths for \mathbb{S} from an initial state?

Example

Consider a transition system with the following state transition graph.



Are the following formulas true **on all/some paths** (from the initial state)?

$$\begin{array}{l} \Box (x = a \leftrightarrow y = a) \\ \Box (x = b \rightarrow \Diamond y = a) \end{array}$$

$$\begin{array}{l} \Box \Diamond y = b \\ \Box \Diamond y \neq b \end{array}$$

Summary LTL

Linear temporal logic (LTL) – expressing properties of computations.

- ▶ Computation tree, path
- ▶ LTL Syntax \bigcirc , \Box , \Diamond , **U**, **R**
- ▶ LTL Semantics
- ▶ Equivalences of temporal formulas
- ▶ expressing properties of state-changing systems