



SmartVista Solution

DEV2 environment description for Bancoppel

DESCRIPTION INSTALLATION

VERSION 1.0

12 January 2024



bpcbt.com

Confidential © 2024 BPC Banking Technologies

Notice

All information contained in this documentation, as well as the software described in it, is proprietary to BPC Group and its affiliates. BPC Group reserves any and all intellectual property rights in respect of this document.

The Customer is granted the right to use this document in accordance with the relevant agreement entered into with authorized SmartVista distributors within BPC Group. Except as permitted by the relevant license agreement, no part of this documentation may be reproduced, stored in a retrieval system, or transmitted in any form or by electronic, mechanical, recording, or any other means, without the prior written permission of BPC Group.

The limited warranties provided in respect of this document are described in the relevant legal agreement entered into with BPC Group. BPC Group provides no other warranties, explicit or implied.

This document is confidential and proprietary and is not intended for use by any person other than a named Customer.

SmartVista is the registered trademark of BPC Group entities. Other company, product or service names mentioned herein may be trademarks or service marks of their respective owners.

For information regarding permissions, write to:

BPC Group HQ
Neuhofstrasse 5a
6340 Baar
Switzerland

Phone: +41 43 508 4024

Email: info@bpcbt.com

Web: www.bpcbt.com

Permitted distribution: Under NDA only

Contents

THE LIST OF AUTHORS AND DATES OF UPDATE.....	5
1 Introduction	6
2 Abbreviations.....	6
3 Specification.....	6
3.1 Software.....	6
3.2 Servers\VM specification	6
3.3 System users	7
3.4 Kernel parameters	8
3.5 /etc/hosts configuration.....	9
4 FE-APP Configuration	9
4.1 Application Parameters	9
4.2 FE-Adapter	9
4.3 Oracle Client applied patches.....	10
4.4 Wallet Configuration.....	10
4.4 Start/Stop Commands.....	10
5 SV-UI Configuration.....	11
5.1 WebLogic Instances	11
5.2 Applied patches.....	11
5.3 Managed Servers.....	11
5.4 Datasources.....	11
5.6 Deployments	12
5.7 Start/Stop Commands.....	12
6 SV-BUS Configuration	12
6.1 ActiveMQ Instances.....	12
6.2 Start/Stop Commands.....	13
7 SVIP-APP Configuration	13
7.1 Application Parameters	13
7.2 SVIP Frontend (UI console)	13
7.3 nginx instances.....	14
7.4 Keycloak	14
7.5 Logstash.....	15
7.6 Elasticsearch.....	15
7.7 Kibana.....	15
8 Oracle Database Configuration	16
8.1 Instances.....	16

8.2	Applied patches.....	16
8.3	Parameters.....	16
8.4	LISTENER configuration	17
8.5	TNSNAMES configuration.....	17
8.6	SQLNET configuration	17
8.7	TDE configuration	18
8.8	Schemas	18
8.9	Start/Stop Commands.....	18

THE LIST OF AUTHORS AND DATES OF UPDATE

Surname Name	Position	Ver	Comment	Date	Internal Number
Andrei Volokhonskyi	System Architect	1.0	Initial document	12.01.2024	BCS-10898

1 Introduction

This document provides the description of SmartVista installation in Bancoppel on DEV2 environment.

2 Abbreviations

Abbreviation	DESCRIPTION
SV	SmartVista
FE	Front End
SVIP	SmartVista Integration Platform
BO	BackOffice
CG	Card Generation
SVBUS	SV bus
APIGATE	SmartVista APIGate
WEB	FE WEB + BO WEB applications

3 Specification

The following elements are related to the specification:

- Software
- **Error! Reference source not found.**
- **Error! Reference source not found.**users
- Kernel parameters
- /etc/hosts configuration

6.1 Software

Component	Version
Virtualization	Amazon AWS EC2
OS	RHEL 8.9
Application Server	WebLogic 14c Standard Edition 14.1.1
Java for WLS	Oracle JDK 1.8.0_381
Java for SVIP	Eclipse Temurin JDK 17.0.9_9
Java for KCK	OpenJDK 11.0.2
SVIP Logging	ELK (Elasticsearch, Logstash, Kibana) 7.17.0
SVIP Authorization Service	Keycloak 18.0.2
SVIP WebServer	Nginx 1.24.0
Database	Oracle 19c Enterprise Edition 19.21
MQ software	Apache ActiveMQ 5.16.6

6.2 Servers\VM specification

VM/Hostname	CPU, cores	RAM, GB	HDD, GB	IP Address	SV Components	OS
-------------	------------	---------	---------	------------	---------------	----

bcplcmsappdev01	2	32	422	10.209.14.16	ALL APPs	RHEL 8.9
bcplcmsdbdev01	2	16	622	10.209.14.49	ALL DBs	RHEL 8.9

6.3 System users

VM/Hostname	User/Password	Profile settings
bcplcmsappdev01	root	
	svfe/svfe1	<pre># CONFIGURACION BPC export ORACLE_BASE=/oracle export ORACLE_HOME=\$ORACLE_BASE/19c export PATH=\$PATH:\$ORACLE_HOME/bin:\$ORACLE_HOME/lib/usr/ccs/bin:\$ORACLE_HOME/OPatch export LD_LIBRARY_PATH=\$LD_LIBRARY_PATH:\$ORACLE_HOME/lib export ORACLE_SID=svfe export PS1='\u@\h \W] <\$ORACLE_SID> \ \$ ' export DB_LOGIN=/@svfe export SV_HOME=/home/svfe export ADAPTER_HOME=\$SV_HOME/adapter SV_PROFILE=\$SV_HOME/etc/sv_profile if [-e \$SV_PROFILE] then . \$SV_PROFILE fi ulimit -c unlimited if ["x\$(env grep '^TZ=')" == "x"] then TZ=\$(ls -la /etc/localtime cut -d ' ' -f 2 sed -e 's/ ..usr/share/zoneinfo//'); export TZ fi</pre>
	oracle/oracle1	<pre># CONFIGURACION BPC export ORACLE_BASE=/oracle export ORACLE_HOME=\$ORACLE_BASE/19c export PATH=\$PATH:\$ORACLE_HOME/bin:\$ORACLE_HOME/lib/usr/ccs/bin:\$ORACLE_HOME/OPatch export LD_LIBRARY_PATH=\$LD_LIBRARY_PATH:\$ORACLE_HOME/lib export ORACLE_SID=svfe export PS1='\u@\h \W] <\$ORACLE_SID> \ \$ '</pre>
	weblogic/weblogic1	<pre># CONFIGURACION BPC export ORACLE_HOME=/home/weblogic/Oracle/Middleware/Oracle_Home export JAVA_HOME=/home/weblogic/java/jdk export PATH=\$ORACLE_HOME/OPatch:\$JAVA_HOME/bin:\$PATH export ORACLE_BASE=/home/weblogic/Oracle</pre>
	svip/svip1	<pre>#CONFIGURACION BPC export LANGUAGE="en_US" export LANG="en_US.UTF-8" export JAVA_HOME=/home/svip/java/jdk export PATH=\$JAVA_HOME/bin:\$PATH</pre>
bcplcmsdbdev01	root	
	oracle/oracle1	<pre>####CONFIGURACION BPC #### export ORACLE_BASE=/oracle export ORACLE_HOME=\$ORACLE_BASE/19c</pre>

		export PATH=\$PATH:\$ORACLE_HOME/bin:\$ORACLE_HOME/lib:/usr/ccs/bin:\$ORACLE_HOME/OPatch: \$ORACLE_HOME/jdk export LD_LIBRARY_PATH=\$LD_LIBRARY_PATH:\$ORACLE_HOME/lib export ORACLE_SID=svdb export PS1='\u@\h \W] <\$ORACLE_SID> \\$_ '
--	--	--

6.4 Kernel parameters

Hostname	Parameters
bcplcmsappdev01	<pre> /etc/resolv.conf options timeout:2 options attempts:2 /etc/sysctl.d/50-SmartVista.conf net.ipv4.tcp_keepalive_intvl = 10 net.ipv4.tcp_keepalive_probes = 2 net.ipv4.tcp_keepalive_time = 120 kernel.msgmmax = 65536 kernel.msgmnb = 16777216 kernel.sem = 250 32000 100 128 kernel.shmall = 2251799813685247 fs.file-max = 6815744 net.core.rmem_default = 262144 net.core.rmem_max = 4194304 net.core.wmem_default = 262144 net.core.wmem_max = 1048576 fs.aio-max-nr = 1048576 vm.max_map_count = 262144 net.ipv4.ip_local_port_range = 1024 65500 /etc/security/limits.d/50-svfe.conf svfe hard nproc 16384 svfe hard nofile 16384 svfe soft nproc 16384 svfe soft nofile 16384 /etc/security/limits.d/51-weblogic.conf weblogic hard nproc 16384 weblogic hard nofile 16384 weblogic soft nproc 16384 weblogic soft nofile 16384 /etc/security/limits.d/60-svip.conf svip hard nofile 65535 svip soft nofile 65535 /etc/systemd/logind.conf RemoveIPC=no </pre>
bcplcmsdbdev01	<pre> /etc/resolv.conf options timeout:2 options attempts:2 /etc/sysctl.d/50-SmartVista.conf kernel.sem = 250 32000 100 128 kernel.shmall = 2251799813685247 fs.file-max = 6815744 net.core.rmem_default = 262144 net.core.rmem_max = 4194304 net.core.wmem_default = 262144 net.core.wmem_max = 1048576 fs.aio-max-nr = 1048576 vm.max_map_count=200000 net.ipv4.ip_local_port_range = 9000 65500 /etc/security/limits.d/50-oracle.conf oracle hard stack 32768 oracle soft stack 10240 oracle hard nofile 65536 oracle soft memlock unlimited </pre>

	<pre>oracle hard memlock unlimited [oracle@bcplcmsdbdev01 ~] <svfe> \$ df -h grep shm tmpfs 7.6G 0 7.6G 0% /dev/shm [oracle@bcplcmsdbdev01 ~] <svfe> \$ /etc/systemd/logind.conf RemoveIPC=no</pre>
--	---

6.5 /etc/hosts configuration

```
10.209.14.16  bcplcmsappdev01.bcpl.net bcplcmsappdev01 fe-app sv-ui sv-bus cg-app svip-app svip-elk
10.209.14.49  bcplcmsdbdev01.bcpl.net bcplcmsdbdev01  fe-db bo-db cg-db svip-db
```

4 FE-APP Configuration

4.1 Application Parameters

Parameter	Value
System User	svfe
Home Directory	/home/svfe
ORACLE_HOME	/oracle/19c
DB_LOGIN	/@svfe
tnsnames.ora	<pre>svfe = (DESCRIPTION = (ADDRESS = (PROTOCOL = TCP)(HOST = fe-db)(PORT = 1521)) (CONNECT_DATA = (SERVER = DEDICATED) (SERVICE_NAME = dev2db)))</pre>

4.2 FE-Adapter

Parameter	Value
System User	svfe
Home Directory	/home/svfe/adapter

4.3 Oracle Client applied patches

Patch	Unique ID	Description
35643107	25405995	Database Release Update : 19.21.0.0.231017 (35643107)

4.4 Wallet Configuration

Parameter	Value
Wallet Location	/oracle/19c/owm/wallets/svfe
sqlnet.ora	NAMES.DIRECTORY_PATH= (TNSNAMES, EZCONNECT) WALLET_LOCATION = (SOURCE = (METHOD = FILE) (METHOD_DATA = (DIRECTORY = /oracle/19c/owm/wallets/\${ORACLE_SID}))) SQLNET.EXPIRE_TIME = 1 SQLNET.INBOUND_CONNECT_TIMEOUT = 120 SQLNET.WALLET_OVERRIDE = TRUE
Wallet Password	Jds7ahb23h8sWsd
Connection Strings	svfe -> SVISTA/SVISTA1

4.4 Start/Stop Commands

Script Location	Description
systemctl {start,stop,status} svfe systemctl {start,stop,status} svfe-adapter	Starting by systemctl (root user)
/etc/init.d/svfe {start,stop,status} /etc/init.d/svfe-adapter {start,stop,status}	Starting by script
startpro_forced all \ shutpro all atndnt_srv start \ atndnt_srv stop /home/svfe/adapter/bin/svfe_adapter {start,stop,status}	Manual starting

5 SV-UI Configuration

5.1 WebLogic Instances

SV Component	Parameter	Value
SV-UI, CG App	Admin URL	https://10.209.14.16:7002/console
	Admin login\pass	weblogic\weblogic1
	OS User	weblogic
	DM_NAME	base_domain
	DM_HOME	/home/weblogic/Oracle/Middleware/Oracle_Home/user_projects/domains/base_domain

5.2 Applied patches

Patch	Unique ID	Description
35908381	25419080	WLS STACK PATCH BUNDLE 14.1.1.0.231013 (Patch 35908319)
35904051	25417625	WLS PATCH SET UPDATE 14.1.1.0.231012
35778872	25381850	Coherence Cumulative Patch 14.1.1.0.15
35671007	25347998	RDA release 23.4-20231017 for OFM 14.1.1 SPB
35476075	25370614	ADR FOR WEBLOGIC SERVER 14.1.1.0 CPU OCT 2023
32720458	24558359	JDBC 19.3.0.0 FOR CPUJAN2022 (WLS 12.2.1.4, WLS 14.1.1)

5.3 Managed Servers

Server Name	Port	SSL Port	Arguments
AdminServer	7001	7002	
BO	7007	7703	-Xms1024m -Xmx4096m -XX:PermSize=512m
BUS	7009	7903	-Xms512m -Xmx1024m
FE	7005	7503	-Xms1024m -Xmx2048m -XX:PermSize=512m
CG	8080	8443	-Xms1024m -Xmx2048m -XX:MaxMetaspaceSize=512m -Dspring.profiles.active=security-disabled,audit-jms-disabled,audit-file-disabled,audit-logging-disabled -Dauth.sso.enabled=false
APIGATE	7031	7313	-Xms768m -Xmx1536m -XX:MaxMetaspaceSize=512m -DAPIGATE_HOME=/home/weblogic/apigate_home -javaagent:/home/weblogic/apigate_home/agent/jaxrs-integration-agent-1.0.0.jar

5.4 Datasources

DS Name	Type	Target	JNDI	URL	User/Password
BO-DS	Generic	BO	jdbc/SVWeb	jdbc:oracle:thin:@//bo-db:1521/DEV2DB	MAIN/MAIN1

WI-DS	Generic	FE	jdbc/svwi/WI	jdbc:oracle:thin:@//fe-db:1521/DEV2DB	SVWEB/SVWEB1
FE-DS	Generic	FE	jdbc/svwi/FE jdbc/svwi/FEAuthorized	jdbc:oracle:thin:@//fe-db:1521/DEV2DB	SVISTA/SVISTA1
CG-DS	Generic	CG	SettingsController	jdbc:oracle:thin:@//cg-db:1521/DEV2DB	SVCG/SVCG1
API-FE-DS	Generic	APIGATE	jdbc/apigate/fe jdbc/apigate/fero	jdbc:oracle:thin:@//fe-db:1521/DEV2DB	SVISTA/SVISTA1
API-BO-DS	Generic	APIGATE	jdbc/apigate/bo jdbc/apigate/boro	jdbc:oracle:thin:@//bo-db:1521/DEV2DB	MAIN/MAIN1

5.6 Deployments

File Name	Target	Type	URL	User/Password
com.bpcbt.sv.camel (v2.42.2.1621)	BUS	Application	https://10.209.14.16:7903/camel/services	
ru_bpc_svwi_common-v0.71.0-17-g8474c9af_fix712	FE	Application	https://10.209.14.16:7503/SVFE2	admin/admin1
sv2-ear (2.2.10.42.2.1623)	BO	Application	https://10.209.14.16:7703/sv	admin/admin
ru.bpcbt.cg.core	CG	Application		
ru.bpcbt.cg.gui	CG	Application	https://10.209.14.16:8443/svcl	admin/admin1
ru_bpc_apigate_master-rest-v1.1.58-549-g8bb447fa_bancoppel	APIGATE	Application	https://10.209.14.16:7313/apigate/buildinfo	

5.7 Start/Stop Commands

Script Location	Description
/etc/init.d/wls14j8 {start,stop,status}	Starting by script
systemctl {start,stop,status} wls14j8	Starting by systemctl (root user)
nohup /home/weblogic/Oracle/Middleware/Oracle_Home/user_projects/domains/base_domain/bin/startNodeManager.sh & nohup /home/weblogic/Oracle/Middleware/Oracle_Home/user_projects/domains/base_domain/startWebLogic.sh &	Manual starting

6 SV-BUS Configuration

6.1 ActiveMQ Instances

SV Component	Parameter	Value
SVBUS	Apache ActiveMQ version	5.16.6
	Admin URL	http://127.0.0.1:8161/admin
	Admin login\pass	admin\admin

	OS User	weblogic
	Home dir	/home/weblogic/apache-activemq
	ACTMQ PORT	61616

6.2 Start/Stop Commands

Script Location	Description
systemctl {start,stop,status} activemq	Starting by systemctl
/etc/init.d/activemq {start,stop,status}	Starting by script
/home/weblogic/apache-activemq/bin/activemq {start,stop,status}	Manual starting

7 SVIP-APP Configuration

7.1 Application Parameters

Parameter	Value
System User	svip
APP Directory	/home/svip/svip-backend/
JAVA_HOME	/home/svip/java/jdk
datasource.default.jdbcUrl	jdbc:oracle:thin:@//svip-db:1521/DEV2DB
Start\Stop	/etc/init.d/svip {start,stop,status}

7.2 SVIP Frontend (UI console)

URL	Login	Password
-----	-------	----------

https://10.209.14.16:9443	admin	admin1
---	-------	--------

7.3 nginx instances

SV Component	Parameter	Value
SVIP UI	System User	svip
	SVIP config	/home/svip/nginx/conf/nginx.conf
	SVIP UI frontend	/home/svip/svip-frontend/
	SSL cert directory	/home/svip/nginx/ssl
	Manual start\stop	/etc/init.d/nginx-svip {start, stop, status}
	Auto start\stop	systemctl {start, stop, status} nginx

7.4 Keycloak

Parameter	Value
Hostname	bcplcmsappdev01
System user	svip
JAVA_HOME	/home/svip/java/jdk-11
Installed dir	/home/svip/keycloak
Configuration file	/home/svip/keycloak/conf/keycloak.conf
db-url	jdbc:oracle:thin:@//svip-db:1521/DEVDB
Port	7443
URL	https://10.209.14.16:7443/
Login/Password	admin/admin1
Manual Start	nohup /home/svip/keycloak/bin/kc.sh start &
Auto Start\Stop	systemctl {start,stop,status} keycloak

7.5 Logstash

Parameter	Value
Hostname	bcplcmsappdev01
System user	svip
Installed dir	/home/svip/svip-elk/logstash/
config	/home/svip/svip-elk/logstash/config/logstash.yml
Manual start\stop	/home/svip/svip-elk/bin/start-logstash.sh /home/svip/svip-elk/bin/stop-logstash.sh
Auto start\stop	systemctl {start,stop} svip

7.6 Elasticsearch

Parameter	Value
Hostname	bcplcmsappdev01
Ports	9200, 9300
System user	svip
Installed dir	/home/svip/svip-elk/elasticsearch/
config	/home/svip/svip-elk/elasticsearch/config/elasticsearch.yml
Manual Start\Stop	/home/svip/svip-elk/bin/start-elasticsearch.sh /home/svip/svip-elk/bin/stop-elasticsearch.sh
Auto start\stop	systemctl {start,stop} svip

7.7 Kibana

Parameter	Value
Hostname	bcplcmsappdev01
URL	http://10.209.14.16:5601/

System user	svip
Installed dir	/home/svip/svip-elk/kibana/
config	/home/svip/svip-elk/kibana/config/kibana.yml
Manual Start	cd /home/svip/svip-elk/kibana/bin nohup ./kibana &

8 Oracle Database Configuration

8.1 Instances

SV Component	VM	DB Name	SID	PDB	SERVICE_NAME	ORACLE_HOME
FE, BO, CG, SVIP DBs	bcplcmsdbdev01	svdb	svdb	dev2db	dev2db	/oracle/19c

8.2 Applied patches

Patch	Unique ID	Description
35643107	25405995	Database Release Update : 19.21.0.0.231017 (35643107)
35655527	25393129	OCW RELEASE UPDATE 19.21.0.0.0 (35655527)

8.3 Parameters

DB Name	PDB NAME	NLS_CHARACTERSET	NLS_NCHAR_CHARACTERSET	NLS_SEMANTICS	SGA, GB	PGA AGGR, GB	Process	Sessions	Open cursor	DG Broker	ARCHIVE LOG	FLASHBACK
SVDB	CDB\$ROOT	AL32UTF8	AL16UTF16	BYTE	6	1	320	504	300	NO	NO	NO

	DEV2DB	AL32U TF8	AL16UT F16	BYTE	N/A	1	320	504	300	NO	NO	NO
--	--------	--------------	---------------	------	-----	---	-----	-----	-----	----	----	----

8.4 LISTENER configuration

```
$ cat $ORACLE_HOME/network/admin/listener.ora
# listener.ora Network Configuration File: /oracle/19c/network/admin/listener.ora
# Generated by Oracle configuration tools.

LISTENER =
  (DESCRIPTION_LIST =
    (DESCRIPTION =
      (ADDRESS = (PROTOCOL = TCP)(HOST = bcplcmsdbdev01.bcpl.net)(PORT = 1521))
      (ADDRESS = (PROTOCOL = IPC)(KEY = EXTPROC1521))
    )
  )
```

8.5 TNSNAMES configuration

```
$ cat $ORACLE_HOME/network/admin/tnsnames.ora
# tnsnames.ora Network Configuration File: /oracle/19c/network/admin/tnsnames.ora
# Generated by Oracle configuration tools.

LISTENER_SVDB =
  (ADDRESS = (PROTOCOL = TCP)(HOST = bcplcmsdbdev01.bcpl.net)(PORT = 1521))

SVDB =
  (DESCRIPTION =
    (ADDRESS = (PROTOCOL = TCP)(HOST = bcplcmsdbdev01.bcpl.net)(PORT = 1521))
    (CONNECT_DATA =
      (SERVER = DEDICATED)
      (SERVICE_NAME = svdb)
    )
  )
```

8.6 SQLNET configuration

```
$ cat $ORACLE_HOME/network/admin/sqlnet.ora
# sqlnet.ora Network Configuration File: /oracle/19c/network/admin/sqlnet.ora
# Generated by Oracle configuration tools.
```

NAMES.DIRECTORY_PATH= (TNSNAMES, ONAMES, HOSTNAME)

WALLET_LOCATION =

(SOURCE =

(METHOD = FILE)

(METHOD_DATA =

(DIRECTORY = /oracle/19c/owm/wallets/\${ORACLE_SID})

)

)

SQLNET.EXPIRE_TIME = 1

SQLNET.INBOUND_CONNECT_TIMEOUT = 120

8.7 TDE configuration

DB Name	SID	PDB	WALLET_LOCATION	AUTO_LOGIN	PASSWORD
svdb	svdb	dev2db	/oracle/19c/owm/wallets/svdb	YES	Jds7ahb23h8sWsd

8.8 Schemas

PDB Name	Schemas	Description
dev2db	SVISTA/SVISTA1	FE APP schema
	SVWEB/SVWEB1	FE UI schema
	MAIN/MAIN1	BO schema
	SVCG/SVCG1	CG schema
	SVIP/SVIP1	SVIP schema
	KEYCLOAK/KEYCLOAK1	KEYCLOAK schema
	SYS/SYS1	DBA schema
	SYSTEM/SYSTEM1	SYSTEM schema
	PDBADMIN/PDBADMIN1	PDBADMIN schema

8.9 Start/Stop Commands

Database	Description	Commands
ALL	Starting by systemctl (root user)	systemctl {start,stop,status} sv_db
	Starting by script	/etc/init.d/sv_db {start,stop,status}
	Starting by srvctl	srvctl start database -d <DB_NAME> srvctl stop database -d <DB_NAME>
	Manual starting	sqlplus / as sysdba

		SQL> startup SQL> shutdown immediate lsnrctl {start,stop,status}
--	--	--