



SmartVista Solution

Pre-Production environment description for
Bancoppel

DESCRIPTION INSTALLATION

VERSION 1.0

17 June 2024



bpcbt.com

Confidential © 2024 BPC Banking Technologies

Notice

All information contained in this documentation, as well as the software described in it, is proprietary to BPC Group and its affiliates. BPC Group reserves any and all intellectual property rights in respect of this document.

The Customer is granted the right to use this document in accordance with the relevant agreement entered into with authorized SmartVista distributors within BPC Group. Except as permitted by the relevant license agreement, no part of this documentation may be reproduced, stored in a retrieval system, or transmitted in any form or by electronic, mechanical, recording, or any other means, without the prior written permission of BPC Group.

The limited warranties provided in respect of this document are described in the relevant legal agreement entered into with BPC Group. BPC Group provides no other warranties, explicit or implied.

This document is confidential and proprietary and is not intended for use by any person other than a named Customer.

SmartVista is the registered trademark of BPC Group entities. Other company, product or service names mentioned herein may be trademarks or service marks of their respective owners.

For information regarding permissions, write to:

BPC Group HQ
Neuhofstrasse 5a
6340 Baar
Switzerland

Phone: +41 43 508 4024

Email: info@bpcbt.com

Web: www.bpcbt.com

Permitted distribution: Under NDA only

Contents

THE LIST OF AUTHORS AND DATES OF UPDATE.....	5
1 Introduction	6
2 Abbreviations.....	6
3 Specification.....	6
3.1 Software.....	6
3.2 Servers\VM specification	6
3.3 System users	7
3.4 Kernel parameters	8
3.5 /etc/hosts configuration.....	10
4 FE-APP Configuration	10
4.1 Application Parameters	10
4.2 FE-Adapter	11
4.3 Oracle Client applied patches.....	11
4.4 Wallet Configuration.....	11
4.4 Start/Stop Commands.....	12
5 SV-UI Configuration.....	13
5.1 WebLogic Instances	13
5.3 Managed Servers.....	13
5.4 Datasources.....	13
5.6 Deployments	14
5.7 Start/Stop Commands.....	14
6 CG-App Configuration	14
6.1 WebLogic Instances	14
6.2 Managed Servers.....	15
6.3 Datasources.....	15
6.4 Deployments	15
6.5 Start/Stop Commands.....	15
7 SV-BUS Configuration	15
6.1 ActiveMQ Instances.....	15
6.2 Start/Stop Commands.....	16
8 SVIP-APP Configuration.....	16
7.1 Application Parameters	16
7.2 SVIP Frontend (UI console)	16
7.3 nginx instances.....	16
7.4 Keycloak	17

7.5	Logstash.....	17
7.6	Elasticsearch.....	18
7.7	Kibana.....	18
9	Oracle Database Configuration	19
8.1	Instances.....	19
8.2	Applied patches.....	19
8.3	Parameters.....	19
8.4	LISTENER configuration	20
8.5	TNSNAMES configuration.....	22
8.6	SQLNET configuration (all instances).....	23
8.7	TDE configuration	23
8.8	Schemas	24
8.9	Start/Stop Commands.....	24

THE LIST OF AUTHORS AND DATES OF UPDATE

Surname Name	Position	Ver	Comment	Date	Internal Number
Derby Simon	System Administrator	1.0	Initial document	17.06.2024	BCS-11660

1 Introduction

This document provides the description of SmartVista installation for Bancoppel in the Pre-Production environment.

2 Abbreviations

Abbreviation	DESCRIPTION
SV	SmartVista
FE	Front End
SVIP	SmartVista Integration Platform
BO	BackOffice
CG	Card Generation
SVBUS	SV bus
APIGATE	SmartVista APIGate
WEB	FE WEB + BO WEB applications

3 Specification

The following elements are related to the specification:

- Software
- **Error! Reference source not found.**
- **Error! Reference source not found.**users
- Kernel parameters
- /etc/hosts configuration

6.1 Software

Component	Version
Virtualization	Amazon AWS EC2
OS	RHEL 8.9
Application Server	WebLogic 14c Standard Edition 14.1.1
Java for WLS	Oracle JDK 1.8.0_401
Java for SVIP, ELK	Eclipse Temurin JDK 17.0.9_9
Java for KCK	OpenJDK 11.0.2
SVIP Logging	ELK (Elasticsearch, Logstash, Kibana) 7.17.0
SVIP Authorization Service	Keycloak 18.0.2
SVIP WebServer	Nginx 1.24.0
Database	Oracle 19c Enterprise Edition 19.23
MQ software	Apache ActiveMQ 5.16.6

6.2 Servers\VM specification

VM/Hostname	CPU, cores	RAM, GB	HDD, GB	IP Address	SV Components	OS
-------------	------------	---------	---------	------------	---------------	----

bcpfeappcmsoraqa01.bcpl.net	2	8	222	10.209.32.212	FE App	RHEL 8.9
bcpfeappcmsbusqa01.bcpl.net	2	8	192	10.209.32.214	FE GUI, BO GUI, BUS App, API Gate App	RHEL 8.9
bcpfeappcmscgqa01.bcpl.net	2	8	192	10.209.32.196	CG App	RHEL 8.9
bcpfeappcmssvkckqa01.bcpl.net	2	8	192	10.209.32.217	SVIP, Logstash	RHEL 8.9
bcpfeappcmssvelkqa01.bcpl.net	2	8	292	10.209.32.219	Elastic Search, Kibana	RHEL 8.9
bcpfedbcmsoraqa01.bcpl.net	2	8	472	10.209.33.51	FE DB	RHEL 8.9
bcpbodbcmsoraqa01.bcpl.net	2	8	472	10.209.33.50	BO DB	RHEL 8.9
bcpcgdbcmsoraqa01.bcpl.net	2	8	472	10.209.33.45	CG DB	RHEL 8.9
bcpsvdbcmsoraqa01.bcpl.net	2	8	472	10.209.33.38	SVIP DB	RHEL 8.9

6.3 System users

VM/Hostname	User/Password	Profile settings
	svfe	<pre> export ORACLE_BASE=/oracle export ORACLE_HOME=\$ORACLE_BASE/19c export PATH=\$PATH:\$ORACLE_HOME/bin:\$ORACLE_HOME/lib:/usr/ccs/bin:\$ORACLE_HOME/OPat export LD_LIBRARY_PATH=\$LD_LIBRARY_PATH:\$ORACLE_HOME/lib export ORACLE_SID=svfe export PS1='\u@\h \W] <\$ORACLE_SID> \ \$ ' ulimit -n 4096 ulimit -u 4096 export DB_LOGIN=/@svfe export SV_HOME=/home/svfe export ADAPTER_HOME=\$SV_HOME/adapter export PATH=\$PATH:\$ADAPTER_HOME/bin SV_PROFILE=\$SV_HOME/etc/sv_profile if [-e \$SV_PROFILE] then . \$SV_PROFILE fi ulimit -c unlimited if ["x\$(env grep '^TZ=') " == "x"] then TZ='ls -la /etc/localtime cut -d ' ' -f 2 sed -e 's/ ..usr\share\zoneinfo\/' ; export TZ fi </pre>
	oracle/oracle1	<pre> ORACLE_BASE=/oracle export ORACLE_BASE ORACLE_HOME=\$ORACLE_BASE/19c export ORACLE_HOME PATH=\$PATH:\$ORACLE_HOME/bin:\$ORACLE_HOME/lib:/usr/ccs/bin:\$ORACLE_HOME/OPat export PATH export LD_LIBRARY_PATH=\$LD_LIBRARY_PATH:\$ORACLE_HOME/lib ORACLE_SID=svfe export ORACLE_SID export PS1='\u@\h \W] <\$ORACLE_SID> \ \$ ' </pre>

bcpfeappcmsbusqa01.bcpl.net	weblogic	export ORACLE_HOME=/home/weblogic/Oracle/Middleware/Oracle_Home export JAVA_HOME=/home/weblogic/java/jdk export PATH=\$ORACLE_HOME/OPatch:\$JAVA_HOME/bin:\$PATH export APIGATE_HOME=/home/weblogic/apigate_home
bcpfeappcmscgqa01.bcpl.net	weblogic	export ORACLE_HOME=/home/weblogic/Oracle/Middleware/Oracle_Home export JAVA_HOME=/home/weblogic/java/jdk export PATH=\$ORACLE_HOME/OPatch:\$JAVA_HOME/bin:\$PATH
bcpfeappcmssvkckqa01.bcpl.net	svip	export LANGUAGE="en_US" export LANG="en_US.UTF-8" export JAVA_HOME=/home/svip/java/jdk export PATH=\$PATH:\$JAVA_HOME/bin export KEYCLOAK_ADMIN=keycloak export KEYCLOAK_ADMIN_PASSWORD=keycloak1
bcpfeappcmssvelkqa01.bcpl.net	svip	export LANGUAGE="en_US" export LANG="en_US.UTF-8" export JAVA_HOME=/home/svip/java/jdk export PATH=\$PATH:\$JAVA_HOME/bin
bcpfedbcmsoraqa01.bcpl.net	oracle	export ORACLE_BASE=/u01/oracle export ORACLE_HOME=\$ORACLE_BASE/19c export PATH=\$PATH:\$ORACLE_HOME/bin:\$ORACLE_HOME/lib:/usr/ccs/bin:\$ORACLE_HOME/OPatch export LD_LIBRARY_PATH=\$LD_LIBRARY_PATH:\$ORACLE_HOME/lib export ORACLE_SID=svfecdb export PS1='\u@\h \W] <\$ORACLE_SID> \\$ '
bcpbodbcmsoraqa01.bcpl.net	oracle	export ORACLE_BASE=/u01/oracle export ORACLE_HOME=\$ORACLE_BASE/19c export PATH=\$PATH:\$ORACLE_HOME/bin:\$ORACLE_HOME/lib:/usr/ccs/bin:\$ORACLE_HOME/OPatch export LD_LIBRARY_PATH=\$LD_LIBRARY_PATH:\$ORACLE_HOME/lib export ORACLE_SID=svcdb export PS1='\u@\h \W] <\$ORACLE_SID> \\$ '
bcpcgdbcmsoraqa01.bcpl.net	oracle	export ORACLE_BASE=/u01/oracle export ORACLE_HOME=\$ORACLE_BASE/19c export PATH=\$PATH:\$ORACLE_HOME/bin:\$ORACLE_HOME/lib:/usr/ccs/bin:\$ORACLE_HOME/OPatch export LD_LIBRARY_PATH=\$LD_LIBRARY_PATH:\$ORACLE_HOME/lib export ORACLE_SID=svcgcdb export PS1='\u@\h \W] <\$ORACLE_SID> \\$ '
bcpsvdbcmsoraqa01.bcpl.net	oracle	export ORACLE_BASE=/u01/oracle export ORACLE_HOME=\$ORACLE_BASE/19c export PATH=\$PATH:\$ORACLE_HOME/bin:\$ORACLE_HOME/lib:/usr/ccs/bin:\$ORACLE_HOME/OPatch export LD_LIBRARY_PATH=\$LD_LIBRARY_PATH:\$ORACLE_HOME/lib export ORACLE_SID=svipcdb export PS1='\u@\h \W] <\$ORACLE_SID> \\$ '

6.4 Kernel parameters

Hostname	Parameters
bcpfeappcmsoraqa01.bcpl.net	/etc/resolv.conf options timeout:2 options attempts:2 /etc/sysctl.d/50-SmartVista.conf net.ipv4.tcp_keepalive_intvl = 10 net.ipv4.tcp_keepalive_probes = 2 net.ipv4.tcp_keepalive_time = 120 net.ipv4.ip_local_port_range = 9000 30000 kernel.msgmax 65536 kernel.msgmnb = 16777216 /etc/security/limits.d/50-svfe.conf svfe hard nproc 16384 svfe hard nofile 16384

	<pre>svfe soft nproc 16384 svfe soft nofile 16384 /etc/systemd/logind.conf RemoveIPC=no</pre>
bcpfeappcmsbusqa01.bcpl.net	<pre>/etc/resolv.conf options timeout:2 options attempts:2 /etc/security/limits.d/50-weblogic.conf weblogic hard nproc 16384 weblogic hard nofile 16384 weblogic soft nproc 16384 weblogic soft nofile 16384 /etc/systemd/logind.conf RemoveIPC=no</pre>
bcpfeappcmscgqa01.bcpl.net	<pre>/etc/resolv.conf options timeout:2 options attempts:2 /etc/sysctl.d/50-SmartVista.conf net.ipv4.tcp_keepalive_intvl = 10 net.ipv4.tcp_keepalive_probes = 2 net.ipv4.tcp_keepalive_time = 120 net.ipv4.ip_local_port_range = 9000 30000 kernel.msgmax 65536 kernel.msgmnb = 16777216 /etc/security/limits.d/50-weblogic.conf weblogic hard nproc 16384 weblogic hard nofile 16384 weblogic soft nproc 16384 weblogic soft nofile 16384 /etc/systemd/logind.conf RemoveIPC=no</pre>
bcpfeappcmssvkckqa01.bcpl.net	<pre>/etc/resolv.conf options timeout:2 options attempts:2 /etc/sysctl.d/50-SmartVista.conf net.ipv4.tcp_keepalive_intvl = 10 net.ipv4.tcp_keepalive_probes = 2 net.ipv4.tcp_keepalive_time = 120 net.ipv4.ip_local_port_range = 9000 30000 kernel.msgmax 65536 kernel.msgmnb = 16777216 /etc/security/limits.d/60-svip.conf svip hard nofile 65535 svip soft nofile 65535 /etc/systemd/logind.conf RemoveIPC=no</pre>
bcpfeappcmssvelkqa01.bcpl.net	<pre>/etc/resolv.conf options timeout:2 options attempts:2 /etc/sysctl.d/50-SmartVista.conf net.ipv4.tcp_keepalive_intvl = 10 net.ipv4.tcp_keepalive_probes = 2 net.ipv4.tcp_keepalive_time = 120 net.ipv4.ip_local_port_range = 9000 30000 kernel.msgmax 65536 kernel.msgmnb = 16777216 /etc/security/limits.d/60-svip.conf svip hard nofile 65535 svip soft nofile 65535 /etc/systemd/logind.conf</pre>

	RemoveIPC=no
bcpfedbcmsoraqa01.bcpl.net/ bcpbodbcmsoraqa01.bcpl.net/ bcpcgdbcmsoraqa01.bcpl.net/ bcpsvdbcmsoraqa01.bcpl.net	<pre> /etc/resolv.conf options timeout:2 options attempts:2 /etc/sysctl.d/50-SmartVista.conf kernel.sem = 250 32000 100 128 kernel.shmall = 2251799813685247 fs.file-max = 6815744 net.core.rmem_default = 262144 net.core.rmem_max = 4194304 net.core.wmem_default = 262144 net.core.wmem_max = 1048576 fs.aio-max-nr = 1048576 vm.max_map_count=200000 net.ipv4.ip_local_port_range = 9000 65500 /etc/security/limits.d/50-oracle.conf oracle hard stack 32768 oracle soft stack 10240 oracle hard nofile 65536 oracle soft memlock unlimited oracle hard memlock unlimited [oracle@bcpfedbcmsoraqa01 ~] <svfecdb> \$ df -h grep shm tmpfs 3.7G 2.0G 1.8G 54% /dev/shm [oracle@bcpbodbcmsoraqa01 ~] <svfdb> \$ df -h grep shm tmpfs 3.7G 2.0G 1.8G 54% /dev/shm [oracle@bcpcgdbcmsoraqa01 ~] <svcgcdb> \$ df -h grep shm tmpfs 3.7G 608M 3.1G 17% /dev/shm [oracle@bcpsvdbcmsoraqa01 ~] <svipcdb> \$ df -h grep shm tmpfs 3.7G 1.8G 1.9G 49% /dev/shm /etc/systemd/logind.conf RemoveIPC=no </pre>

6.5 /etc/hosts configuration

```

10.209.32.212 bcpfeappcmsoraqa01.bcpl.net bcpfeappcmsoraqa01
10.209.32.214 bcpfeappcmsbusqa01.bcpl.net bcpfeappcmsbusqa01
10.209.32.196 bcpfeappcmscgqa01.bcpl.net bcpfeappcmscgqa01
10.209.32.217 bcpfeappcmssvkckqa01.bcpl.net bcpfeappcmssvkckqa01
10.209.32.219 bcpfeappcmssvelkqa01.bcpl.net bcpfeappcmssvelkqa01
10.209.33.51 bcpfedbcmsoraqa01.bcpl.net bcpfedbcmsoraqa01
10.209.33.50 bcpbodbcmsoraqa01.bcpl.net bcpbodbcmsoraqa01
10.209.33.45 bcpcgdbcmsoraqa01.bcpl.net bcpcgdbcmsoraqa01
10.209.33.38 bcpsvdbcmsoraqa01.bcpl.net bcpsvdbcmsoraqa01

```

4 FE-APP Configuration

4.1 Application Parameters

Parameter	Value
System User	svfe
Home Directory	/home/svfe

ORACLE_HOME	/oracle/19c
DB_LOGIN	/@svfe
tnsnames.ora	svfe = (DESCRIPTION = (AADDRESS = (PROTOCOL = TCP)(HOST = 10.209.33.51)(PORT = 1521)) (CONNECT_DATA = (SERVER = DEDICATED) (SERVICE_NAME = svfepdb)))

4.2 FE-Adapter

Parameter	Value
System User	svfe
Home Directory	/home/svfe/adapter

4.3 Oracle Client applied patches

Patch	Unique ID	Description
35643107	25405995	Database Release Update : 19.21.0.0.231017 (35643107)

4.4 Wallet Configuration

Parameter	Value
Wallet Location	/oracle/19c/owm/wallets/svfe
sqlnet.ora	NAMES.DIRECTORY_PATH= (TNSNAMES, EZCONNECT) WALLET_LOCATION = (SOURCE = (METHOD = FILE) (METHOD_DATA = (DIRECTORY = /oracle/19c/owm/wallets/\${ORACLE_SID}))) SQLNET.EXPIRE_TIME=2 SQLNET.WALLET_OVERRIDE = TRUE
Wallet Password	Gvne05nxjFnmz
Connection Strings	svfe -> SVISTA/svista1

4.4 Start/Stop Commands

Script Location	Description
systemctl {start,stop,status} svfe systemctl {start,stop,status} svfe-adapter	Starting by systemctl (root user)
/etc/init.d/svfe {start,stop,status} /etc/init.d/svfe-adapter {start,stop,status}	Starting by script
startpro_forced all \ shutpro all atndnt_srv start \ atndnt_srv stop svfe_adapter {start,stop,status}	Manual starting

5 SV-UI Configuration

5.1 WebLogic Instances

SV Component	Parameter	Value
SV-UI	Admin URL	https://10.209.32.214:7002/console
	Admin login\pass	weblogic\weblogic1
	OS User	weblogic
	DM_NAME	base_domain
	DM_HOME	/home/weblogic/Oracle/Middleware/Oracle_Home/user_projects/domains/base_domain

5.3 Managed Servers

Server Name	Port	SSL Port	Arguments
AdminServer	7001	7002	
BO	7007	7703	-Xms1024m -Xmx2048m -XX:MaxMetaspaceSize=512m
BUS	7009	7903	-Xms512m -Xmx1024m -XX:MaxMetaspaceSize=512m - Dcamel_config_file=/home/weblogic/camel/config/camel.properties - Dcamel_logs_path=/home/weblogic/camel/logs
FE	7005	7503	-Xms768m -Xmx1536m -verbose:gc -server -Duser.language=en - Dsv.home=/home/weblogic/svwi/ - Dlog4j.configuration=file:///home/weblogic/svwi/conf/log4j.properties - Djava.awt.headless=true - Dcom.sun.xml.ws.fault.SOAPFaultBuilder.disableCaptureStackTrace=false - Dcom.sun.xml.ws.transport.http.client.HttpTransportPipe.dump=true
IG	7031	7313	-Xms768m -Xmx1536m -XX:MaxMetaspaceSize=512m - DAPIGATE_HOME=/home/weblogic/apigate_home - javaagent:/home/weblogic/apigate_home/agent/jaxrs-integration-agent-1.0.0.jar

5.4 Datasources

DS Name	Type	Target	JNDI	URL	User/Password
BO	Generic	BO	jdbc/SVWeb	jdbc:oracle:thin:@//10.209.33.50:1521/svpdb	MAIN/main1
BOSQLAuth	Generic	BO	BOSQLAuth	jdbc:oracle:thin:@//10.209.33.50:1521/svpdb	MAIN/main1
FE	Generic	FE	jdbc/svwi/FE	jdbc:oracle:thin:@//10.209.33.51:1521/svfepdb	SVISTA/svista1
FE Authorized	Generic	FE	jdbc/svwi/FEAuthorized jdbc/svwi/BO jdbc/svwi/BOAuthorized	jdbc:oracle:thin:@//10.209.33.51:1521/svfepdb	SVISTA/svista1
WI	Generic	FE	jdbc/svwi/WI jdbc/svwi/WF jdbc/svwi/wf	jdbc:oracle:thin:@//10.209.33.51:1521/svfepdb	SVWEB/svweb1
API-FE-DS	Generic	IG	jdbc/apigate/fe jdbc/apigate/fero	jdbc:oracle:thin:@//10.209.33.51:1521/svfepdb	SVISTA/svista1

API-BO-DS	Generic	IG	jdbc/apigate/bo jdbc/apigate/boro	jdbc:oracle:thin:@//10.209.33.50:1521/svpdb	MAIN/main1
-----------	---------	----	--------------------------------------	---	------------

5.6 Deployments

File Name	Target	Type	URL	User/Password
com.bpcbt.sv.camel (v2.42.2.1621)	BUS	Application	http://10.209.32.214:7009/camel/services	
ru_bpc_svwi_common-v0.71.0-17-g8474c9af_fix712	FE	Application	http://10.209.32.214:7005/SVFE2	admin/admin1
sv2-ear (2.2.10.42.2.1665)	BO	Application	http://10.209.32.214:7007/sv	admin/admin
ru_bpc_apigate_master-rest-v1.2.4-709-g0a1808b8_bancoppel	IG	Application	http://10.209.32.214:7031/apigate/buildinfo	

5.7 Start/Stop Commands

Script Location	Description
/etc/init.d/wls14j8 {start,stop,status}	Starting by script
systemctl {start,stop,status} wls14j8	Starting by systemctl (root user)
nohup /home/weblogic/Oracle/Middleware/Oracle_Home/user_projects/domains/base_domain/bin/startNodeManager.sh & nohup /home/weblogic/Oracle/Middleware/Oracle_Home/user_projects/domains/base_domain/startWebLogic.sh &	Manual starting

6 CG-App Configuration

6.1 WebLogic Instances

SV Component	Parameter	Value
CG App	Admin URL	https://10.209.32.196:7002/console
	Admin login\pass	weblogic\weblogic1
	OS User	weblogic
	DM_NAME	base_domain
	DM_HOME	/home/weblogic/Oracle/Middleware/Oracle_Home/user_projects/domains/base_domain

6.2 Managed Servers

Server Name	Port	SSL Port	Arguments
AdminServer	7001	7002	
CG	8080	8443	-Xms512m -Xmx1024m -XX:MaxMetaspaceSize=512m -Dspring.profiles.active=security-disabled,audit-jms-disabled,audit-logging-disabled,audit-file-disabled -Dauth.sso.enabled=false

6.3 Datasources

DS Name	Type	Target	JNDI	URL	User/Password
CG	Generic	CG	SettingsController SettingsControllerDS	jdbc:oracle:thin:@//10.209.33.45:1521/svcgpdb	SVCG/svcg1

6.4 Deployments

File Name	Target	Type	URL	User/Password
com.bpcbt.cg.core	CG	Application		
com.bpcbt.cg.gui	CG	Application	http://10.209.32.196:8080/svcl	admin/admin1

6.5 Start/Stop Commands

Script Location	Description
/etc/init.d/wls14j8 {start,stop,status}	Starting by script
systemctl {start,stop,status} wls14j8	Starting by systemctl (root user)
nohup /home/weblogic/Oracle/Middleware/Oracle_Home/user_projects/domains/base_domain/bin/startNodeManager.sh & nohup /home/weblogic/Oracle/Middleware/Oracle_Home/user_projects/domains/base_domain/startWebLogic.sh &	Manual starting

7 SV-BUS Configuration

6.1 ActiveMQ Instances

SV Component	Parameter	Value
SVBUS	Apache ActiveMQ version	5.16.6
	Admin URL	http://127.0.0.1:8161/admin

	Admin login\pass	admin\admin
	OS User	weblogic
	Home dir	/home/weblogic/apache-activemq
	ACTMQ PORT	61616

6.2 Start/Stop Commands

Script Location	Description
systemctl {start,stop,status} activemq	Starting by systemctl
/etc/init.d/activemq {start,stop,status}	Starting by script
/home/weblogic/apache-activemq/bin/activemq {start,stop,status}	Manual starting

8 SVIP-APP Configuration

7.1 Application Parameters

Parameter	Value
System User	svip
APP Directory	/home/svip/svip-backend/
JAVA_HOME	/home/svip/java/jdk
datasource.default.jdbcUrl	jdbc:oracle:thin:@//10.209.33.38:1521/svippdb
Start\Stop	/etc/init.d/svip {start,stop,status}

7.2 SVIP Frontend (UI console)

URL	Login	Password
https://10.209.32.217:9443	Credentials are as configured in Keycloak by BPC Implementation Engineer	

7.3 nginx instances

SV Component	Parameter	Value
SVIP UI	System User	svip

	SVIP config	/home/svip/nginx/conf/nginx.conf
	SVIP UI frontend	/home/svip/svip-frontend/
	SSL cert directory	/home/svip/nginx/ssl
	Manual start\stop	/etc/init.d/nginx-svip {start, stop, status}
	Auto start\stop	systemctl {start, stop, status} nginx-svip

7.4 Keycloak

Parameter	Value
Hostname	bcpfeappcmssvkckqa01
System user	svip
JAVA_HOME	/home/svip/java/jdk-11
Installed dir	/home/svip/keycloak
Configuration file	/home/svip/keycloak/conf/keycloak.conf
db-url	jdbc:oracle:thin:@//10.209.33.38:1521/svippdb
Port	7443
URL	https://10.209.32.217:7443
Login/Password	keycloak/keycloak1
Manual Start	nohup /home/svip/keycloak/bin/kc.sh start &
Auto Start\Stop	systemctl {start,stop,status} keycloak

7.5 Logstash

Parameter	Value
Hostname	bcpfeappcmssvkckqa01
System user	svip
Installed dir	/home/svip/svip-elk/logstash/
config	/home/svip/svip-elk/logstash/config/logstash.yml

Manual start\stop	/home/svip/svip-elk/bin/start-logstash.sh /home/svip/svip-elk/bin/stop-logstash.sh
Auto start\stop	systemctl {start,stop} svip

7.6 Elasticsearch

Parameter	Value
Hostname	bcpfeappcmssvelkqa01
Ports	9200, 9300
System user	svip
Installed dir	/home/svip/svip-elk/elasticsearch/
config	/home/svip/svip-elk/elasticsearch/config/elasticsearch.yml
Manual Start\Stop	/home/svip/svip-elk/bin/start-elasticsearch.sh /home/svip/svip-elk/bin/stop-elasticsearch.sh
Auto start\stop	systemctl {start,stop} svip

7.7 Kibana

Parameter	Value
Hostname	bcpfeappcmssvelkqa01
URL	http://10.209.32.219:5601
System user	svip
Installed dir	/home/svip/svip-elk/kibana/
config	/home/svip/svip-elk/kibana/config/kibana.yml
Manual Start	cd /home/svip/svip-elk/kibana/bin nohup ./kibana &

9 Oracle Database Configuration

8.1 Instances

SV Component	VM	DB Name	SID	PDB	SERVICE_NAME	ORACLE_HOME
FE DB	bcpfedbcmsoraqa01	svfecdb	svfecdb	SVFEPDB	svfepdb	/u01/oracle/19c
BO DB	bcpbodbcmsoraqa01	svcdb	svcdb	SVPDB	svpdb	/u01/oracle/19c
CG DB	bcpcgdbcmsoraqa01	svcgcdb	svcgcdb	SVCGPDB	svcgpdb	/u01/oracle/19c
SVIP DB	bcpsvdbcmsoraqa01	svipcdb	svipcdb	SVIPPDB	svippdb	/u01/oracle/19c

8.2 Applied patches

Patch	Unique ID	Description
36233263	25638263	Database Release Update : 19.23.0.0.240416 (36233263)
29585399	22840393	OCW RELEASE UPDATE 19.3.0.0.0 (29585399)

8.3 Parameters

DB Name	PDB NAME	NLS_CHARACTERSET	NLS_NCHAR_CHARACTERSET	NLS_SEMANTICS	SGA, GB	PGA AGGR, GB	Process	Sessions	Open cursor	DG Broker	ARCHIVE LOG	FLASHBACK
svfecdb	CDB\$ROOT	AL32UTF8	AL16UTF16	BYTE	0	0	1500	2272	600	NO	YES	YES
	SVFEPDB	AL32UTF8	AL16UTF16	BYTE	0	0	1500	2272	600	NO	YES	YES
svcdb	CDB\$ROOT	AL32UTF8	AL16UTF16	CHAR	0	0	3000	4522	600	NO	YES	YES

	SVPD B	AL32U TF8	AL16UT F16	CHAR	0	0	3000	4522	600	NO	YES	YES
svcgcdb	CDB\$ ROOT	AL32U TF8	AL16UT F16	BYTE	0	0	140	232	300	NO	YES	YES
	SVCG PDB	AL32U TF8	AL16UT F16	BYTE	0	0	140	232	300	NO	YES	YES
svipcdb	CDB\$ ROOT	AL32U TF8	AL16UT F16	BYTE	0	0	1500	2272	600	NO	YES	YES
	SVIPP DB	AL32U TF8	AL16UT F16	BYTE	0	0	1500	2272	600	NO	YES	YES

8.4 LISTENER configuration

```
[oracle@bcpfedbcmsoraqa01 ~] <svfecdb> $ cat $ORACLE_HOME/network/admin/listener.ora
```

```
LISTENER =
```

```
(DESCRIPTION_LIST =
```

```
(DESCRIPTION =
```

```
(ADDRESS = (PROTOCOL = TCP)(HOST = 0.0.0.0)(PORT = 1521))
```

```
)
```

```
)
```

```
SID_LIST_LISTENER =
```

```
(SID_LIST =
```

```
(SID_DESC =
```

```
# (GLOBAL_DBNAME = svfepdb_DGMGRL)
```

```
(GLOBAL_DBNAME = svfepdb)
```

```
(ORACLE_HOME = /u01/oracle/19c)
```

```
(SID_NAME = svfecdb)
```

```
(SERVICE_NAME = svfepdb)
```

```
)
```

```
)
```

```
INBOUND_CONNECT_TIMEOUT_LISTENER = 110
```

```
[oracle@bcpbodbcmsoraqa01 ~] <svcdb> $ cat $ORACLE_HOME/network/admin/listener.ora
```

```
LISTENER =
```

```
(DESCRIPTION_LIST =
```

```
(DESCRIPTION =
```

```
(ADDRESS = (PROTOCOL = TCP)(HOST = 0.0.0.0)(PORT = 1521))
```

```
)
```

```
)
```

```
SID_LIST_LISTENER =  
(SID_LIST =  
  (SID_DESC =  
#    (GLOBAL_DBNAME = svpdb_DGMGRL)  
    (GLOBAL_DBNAME = svpdb)  
    (ORACLE_HOME = /u01/oracle/19c)  
    (SID_NAME = svcdb)  
    (SERVICE_NAME = svpdb)  
  )  
)
```

```
INBOUND_CONNECT_TIMEOUT_LISTENER = 110
```

```
[oracle@bcpcgdbcmsoraqa01 ~] <svcgcdb> $ cat $ORACLE_HOME/network/admin/listener.ora
```

```
LISTENER =  
(DESCRIPTION_LIST =  
  (DESCRIPTION =  
    (ADDRESS = (PROTOCOL = TCP)(HOST = 0.0.0.0)(PORT = 1521))  
  )  
)
```

```
SID_LIST_LISTENER =  
(SID_LIST =  
  (SID_DESC =  
#    (GLOBAL_DBNAME = svcgpdb_DGMGRL)  
    (GLOBAL_DBNAME = svcgpdb)  
    (ORACLE_HOME = /u01/oracle/19c)  
    (SID_NAME = svcgcdb)  
    (SERVICE_NAME = svcgpdb)  
  )  
)
```

```
INBOUND_CONNECT_TIMEOUT_LISTENER = 110
```

```
[oracle@bcpsvdbcmsoraqa01 ~] <svipcdb> $ cat $ORACLE_HOME/network/admin/listener.ora
```

```
LISTENER =  
(DESCRIPTION_LIST =  
  (DESCRIPTION =  
    (ADDRESS = (PROTOCOL = TCP)(HOST = 0.0.0.0)(PORT = 1521))  
  )  
)
```

```
)

SID_LIST_LISTENER =
(SID_LIST =
(SID_DESC =
# (GLOBAL_DBNAME = svippdb_DGMGRL)
(GLOBAL_DBNAME = svippdb)
(ORACLE_HOME = /u01/oracle/19c)
(SID_NAME = svipcdb)
(SERVICE_NAME = svippdb)
)
)

INBOUND_CONNECT_TIMEOUT_LISTENER = 110
```

8.5 TNSNAMES configuration

```
[oracle@bcpfedbcmsoraqa01 ~] <svfecdb> $ cat $ORACLE_HOME/network/admin/tnsnames.ora
svfecdb =
```

```
(DESCRIPTION =
  (ADDRESS = (PROTOCOL = TCP)(HOST = 10.209.33.51)(PORT = 1521))
  (CONNECT_DATA =
    (SERVER = DEDICATED)
    (SID = svfecdb)
    (SERVICE_NAME = svfecdb)
  )
)
```

```
[oracle@bcpbodbcmsoraqa01 ~] <svcdb> $ cat $ORACLE_HOME/network/admin/tnsnames.ora
svpdb =
```

```
(DESCRIPTION =
  (ADDRESS = (PROTOCOL = TCP)(HOST = 10.209.33.50)(PORT = 1521))
  (CONNECT_DATA =
    (SERVER = DEDICATED)
    (SID = svcdb)
    (SERVICE_NAME = svpdb)
  )
)
```

```
[oracle@bcpcgdbcmsoraqa01 ~] <svcgcdb> $ cat $ORACLE_HOME/network/admin/tnsnames.ora
svcgpdb =
```

```
(DESCRIPTION =
```

```
(ADDRESS = (PROTOCOL = TCP)(HOST = 10.209.33.45)(PORT = 1521))
(CONNECT_DATA =
  (SERVER = DEDICATED)
  (SID = svcgcdb)
  (SERVICE_NAME = svcgpdb)
)
)
[oracle@bcpsvdbcmsoraqa01 ~] <svipcdb> $ cat $ORACLE_HOME/network/admin/tnsnames.ora
svippdb =
  (DESCRIPTION =
    (ADDRESS = (PROTOCOL = TCP)(HOST = 10.209.33.38)(PORT = 1521))
    (CONNECT_DATA =
      (SERVER = DEDICATED)
      (SID = svipcdb)
      (SERVICE_NAME = svippdb)
    )
  )
)
```

8.6 SQLNET configuration (all instances)

```
$ cat $ORACLE_HOME/network/admin/sqlnet.ora
WALLET_LOCATION =
  (SOURCE =
    (METHOD = FILE)
    (METHOD_DATA =
      (DIRECTORY = /u01/oracle/19c/owm/wallets/${ORACLE_SID})
    )
  )
SQLNET.EXPIRE_TIME=2
SQLNET.INBOUND_CONNECT_TIMEOUT = 120
SQLNET.EXPIRE_TIME = 1
SQLNET.INBOUND_CONNECT_TIMEOUT = 120
```

8.7 TDE configuration

DB Name	SID	PDB	WALLET_LOCATION	AUTO_LOGIN	PASSWORD
svfecdb	svfecdb	SVFEPDB	/u01/oracle/19c/owm/wallets/\${ORACLE_SID}	YES	Gvne05nxjFnmz
svcdb	svcdb	SVPDB	/u01/oracle/19c/owm/wallets/\${ORACLE_SID}	YES	Gvne05nxjFnmz
svcgcdb	svcgcdb	SVCGPDB	/u01/oracle/19c/owm/wallets/\${ORACLE_SID}	YES	Gvne05nxjFnmz
svipcdb	svipcdb	SVIPPDB	/u01/oracle/19c/owm/wallets/\${ORACLE_SID}	YES	Gvne05nxjFnmz

8.8 Schemas

PDB Name	Schemas	Description
SVFEPDB	SVISTA/svista1	FE APP schema
SVFEPDB	SVWEB/svweb1	FE UI schema
SVPDB	MAIN/main1	BO schema
SVCGPDB	SVCG/svcg1	CG schema
SVIPPDB	SVIP/svip1	SVIP schema
SVIPPDB	KEYCLOAK/keycloak1	KEYCLOAK schema
ALL	SYS/sys1	DBA schema
ALL	SYSTEM/system1	SYSTEM schema
SVFEPDB	SVFEADM/svfeadm1	FE PDBADMIN schema
SVPDB	SVADM/svadm1	BO PDBADMIN schema
SVCGPDB	SVCGADM/svcgadm1	CG PDBADMIN schema
SVIPPDB	SVIPADM/svipadm1	SVIP PDBADMIN schema

8.9 Start/Stop Commands

Database	Description	Commands
ALL	Starting by systemctl (root user)	systemctl {start,stop,status} sv_db
	Starting by script	/etc/init.d/sv_db {start,stop,status}
	Starting by srvctl	srvctl start database -d <DB_NAME> srvctl stop database -d <DB_NAME>
	Manual starting	sqlplus / as sysdba SQL> startup SQL> shutdown immediate lsnrctl {start,stop,status}