

Assignment 2

Sreemanti Dey

September 2022

1 Introduction

Note : All accuracies have been calculated in decimal, i.e. out of 1.

2 Q1

2.1 Qa

Laplace smoothing has been used here, with zero preprocessing.

Accuracy of train data : 0.94984

Accuracy of test data : 0.8070666666666667



| | | |
|---|------------------|------------------|
| Negative (predicted) | 2274 | 4380 |
| Confusion matrix for random model | | |
| | Positive(actual) | Negative(actual) |
| ----- | ----- | ----- |
| Positive (predicted) | 4971 | 2511 |
| Negative (predicted) | 5029 | 2489 |
| Confusion matrix for all positive model | | |
| | Positive(actual) | Negative(actual) |
| ----- | ----- | ----- |
| Positive (predicted) | 10000 | 5000 |
| Negative (predicted) | 0 | 0 |

For the first confusion matrix (Naive Bayes Model), the number of diagonal entries = $7726 + 4380 = 12106$, while for second confusion matrix (Random model), it is $4971 + 2489 = 7460$, and for third one (all positive model), it is 10000.

Thus for the Naive Bayes model, we have highest diagonal values which means that this model is the best, it has trained well, and is able to perform well on test data. The diagonal values actually tell us how many positives have been labelled correctly and how many negatives have been labelled correctly.

Pattern observed is that there have been more than twice the number of examples classified as negative (despite actually being positive) than the opposite. Maybe this is because we tend to use negative words too a lot to show positive sentiment/review. In english, lots of words have double meanings too and are used in different context, despite having same spelling.

2.4 Qd

Accuracy of test data : 0.8172666666666667



Positive wordcloud

Negative wordcloud

overfitting of data, since number of training examples is kept constant here but we keep increasing number of features. However, I feel that the main cause for slight decrease in accuracy when trigram model is introduced is that trigram sees 3 words context so if that 3 words together don't occur later then, probability decreases, hence in test examples they might not occur together so that could also add to the decrease in accuracy.

Accuracy of test data : 0.8391333333333333

2.6 Qf

Bigram model is the best performing model so far.

$$\text{Recall} = \frac{TP}{TP+FN} = 0.8074$$

$$\text{Precision} = \frac{TP}{TP+FP} = 0.9470967741935484$$

$$\text{F1 score} = \frac{2}{\frac{1}{\text{precision}} + \frac{1}{\text{recall}}} = 0.8716869095816463$$

I believe that F1 score is more suited for this type of dataset since we have to not only consider the correctly classified examples but also minimize false positives and false negatives. In case of such binary classification problems, (positive class or negative class), i.e. here, if we classify a positive as negative and if positives matter more, then this is to be considered with a higher penalty. Thus, F1 score takes into account more metrics (hence considers extreme values) than accuracy, thus is a better measure.

3 Q2

3.1 Qa

The number of support vectors are : 2159

Fraction of support vectors : 0.53975

accuracy of test data : 0.6745

Weight vector :

```


[[-0.5112897 ]
 [-0.36868977]
 [-0.05279729]
 ...
 [ 0.44036701]
 [ 0.13636418]
 [-1.1679294 ]]

```

Bias :

$b = -0.3878895740991633$

Plot of weight vs features (after reshaping):



The following are the 5 images having the highest coefficients of alpha.



3.2 Qb

The number of support vectors are : 2643

Fraction of support vectors : 0.66075

accuracy of test data : 0.7785

The following are the 5 images having the highest coefficients of alpha.



Test accuracy with gaussian kernel is much higher than that with linear kernel, that is because the data is not linearly separable and might possibly have a gaussian nature in higher dimension. And since the gaussian kernel is of infinite dimension, it performs better than any other model and often is best in cases we don't have any prior information about the data.

3.3 Qc

Using LIBSVM,

Accuracy of test data in linear sklearn : 0.674

Number of support vectors that match in linear kernel case: 2140

Accuracy of test data in gaussian sklearn : 0.778

Number of support vectors that match in gaussian kernel case: 2631

Weights in case of linear sklearn model :

```
[[ -0.51065518
  -0.36886153
  -0.05346012
   ...
   0.44094125
   0.13648895
  -1.16855984]]
```

Bias in case of linear sklearn model :

```
-0.3883493
```

Both are quite similar to the ones obtained using cvxopt model.

Training time comparisons:

1. Linear kernel (CVXOPT) = 34 sec
2. Gaussian kernel (CVXOPT) = 37 sec
3. Linear Kernel (Sklearn) = 42 sec
4. Gaussian kernel (Sklearn) = 34 sec

The training times are very close since I have vectorised my code using cvxopt completely hence the computation has become as fast as that in sklearn.

4 Q3

4.1 Qa

This takes around 13 min.
accuracy of test data : 0.5926

4.2 Qb

This takes 15 min.
Accuracy of test data : 0.593

Test set accuracy is slightly greater than part a and time taken also is almost same for both parts (sklearn being slightly greater).

4.3 Qc

Actual labels are on Y-axis (rows) and predicted labels are on X-axis (columns).

confusion matrix for the one using cvxopt function:


| | | | | |
|-----|-----|-----|-----|-----|
| 724 | 77 | 83 | 65 | 51 |
| 102 | 722 | 46 | 93 | 37 |
| 142 | 55 | 412 | 136 | 255 |
| 79 | 94 | 125 | 578 | 124 |
| 93 | 38 | 221 | 121 | 527 |

confusion matrix for the one using sklearn svm function:

| | | | | |
|-----|-----|-----|-----|-----|
| 729 | 83 | 78 | 61 | 49 |
| 100 | 731 | 42 | 92 | 35 |
| 145 | 61 | 409 | 133 | 252 |
| 82 | 97 | 123 | 572 | 126 |
| 98 | 48 | 212 | 118 | 524 |

1. class 2 gets mis - classified as 4 (252-255 times)
2. class 4 gets mis - classified as 2 (212-221 times).
3. class 2 gets miss-classified as 0 (142-145 times).

Top-10 images that get miss-classified are :



They all belong to class label 0 actually but get mis classified as other classes.



This is a training example from class label 0, as we can see the structure of the pose given by the cat does not exactly match with the images above.





This is an example of label 2, and since the second and third images above get classified as 2, we can see a lot of similarities (for example in the second image above, we can see 2 protrusions (wings of the plane) which can also be seen in this example). Hence the mis -classification is justified.

4.4 Qd

This takes approx 1 hour.

Plots are as follows:





$C = 10$ gives the highest validation accuracy (80.14%) and the same value of C also gives highest test accuracy (52.82%). This is correct and acceptable since the model that gives the highest validation accuracy can be said to be the best model, hence is supposed to work best on the test data too.