

05 - Inicio do login com Google

Laboratorio OAuth2 + PKCE em Cloudflare Pages - Alexandre e Laerto

URL_BASE: <https://oauth-pages-lab-57s.pages.dev>

Capturado em 21/09/2026 no painel Network do navegador, com "Preserve log" ativo.

Valores de state, nonce, code_challenge e o valor do cookie __Host-oauth-tx foram substituídos por [REMOVED], conforme a seção 6 do roteiro. O client_id é público e foi mantido.

General

Request URL <https://oauth-pages-lab-57s.pages.dev/oauth/login/google>
Request method GET
Status code 302 Found
Remote address [2606:4700:310c::ac42:2f17]:443
Referrer policy strict-origin-when-cross-origin

Request headers

:authority: oauth-pages-lab-57s.pages.dev
:method: GET
:path: /oauth/login/google
:scheme: https
accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
accept-encoding: gzip, deflate, br, zstd
accept-language: pt-BR,pt;q=0.9,en-US;q=0.8,en;q=0.7
priority: u=0, i
referer: https://oauth-pages-lab-57s.pages.dev/
sec-ch-ua: "Google Chrome";v="153", "Not_A Brand";v="8", "Chromium";v="153"
sec-ch-ua-mobile: ?0
sec-ch-ua-platform: "Linux"
sec-fetch-dest: document
sec-fetch-mode: navigate
sec-fetch-site: same-origin
sec-fetch-user: ?1
upgrade-insecure-requests: 1
user-agent: Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/153.0.0.0 Safari/537.36

Response headers (saneado)

HTTP/3 302
date: Mon, 21 Sep 2026 22:34:22 GMT
content-length: 0
location: [https://accounts.google.com/o/oauth2/v2/auth?client_id=59724989932-is3q0cto9mbjooop2pb07bom819on7id7.ap&ps.googleusercontent.com&redirect_uri=https%3A%2F%2Foauth-pages-lab-57s.pages.dev%2Foauth%2Fcallback%2Fgoogle&response_type=code&state=\[REMOVED\]&code_challenge=\[REMOVED\]&code_challenge_method=S256&scope=openid+email+profile&nonce=\[REMOVED\]](https://accounts.google.com/o/oauth2/v2/auth?client_id=59724989932-is3q0cto9mbjooop2pb07bom819on7id7.ap&ps.googleusercontent.com&redirect_uri=https%3A%2F%2Foauth-pages-lab-57s.pages.dev%2Foauth%2Fcallback%2Fgoogle&response_type=code&state=[REMOVED]&code_challenge=[REMOVED]&code_challenge_method=S256&scope=openid+email+profile&nonce=[REMOVED])
cache-control: no-store
set-cookie: __Host-oauth-tx=[REMOVED]; Path=/; HttpOnly; Secure; SameSite=Lax; Max-Age=600
report-to: [REMOVED - token de relatório da Cloudflare]
nel: {"report_to":"cf-nel","success_fraction":0.0,"max_age":604800}
priority: u=0,i
server: cloudflare
alt-svc: h3=":443"; ma=86400
server-timing: cfExtPri

Conferencia da seção 15.2

[x] o estado HTTP é 302
[x] a resposta cria __Host-oauth-tx
[x] Location aponta para accounts.google.com
[x] response_type=code está presente
[x] code_challenge_method=S256 está presente
[x] a URL de retorno é a URL pages.dev exata
(redirect_uri = <https://oauth-pages-lab-57s.pages.dev/oauth/callback/google>)
[x] Client Secret e code_verifier estão ausentes

Observação sobre o SameSite do cookie de transação: __Host-oauth-tx usa SameSite=Lax de propósito, porque precisa acompanhar a navegação de volta vinda do domínio do Google. Com SameSite=Strict o navegador não o enviaria no retorno e a transação seria perdida. O cookie de sessão (__Host-session), que nunca atravessa outro site, é emitido com SameSite=Strict.