

## CS4342 Assignment #3

Total points: 70

### Conceptual and Theoretical Questions

1. We now examine the differences between LDA and QDA.

(a) If the Bayes decision boundary is linear, do we expect LDA or QDA to perform better on the training set? On the test set?

(b) If the Bayes decision boundary is non-linear, do we expect LDA or QDA to perform better on the training set? On the test set?

(c) In general, as the sample size  $n$  increases, do we expect the test prediction accuracy of QDA relative to LDA to improve, decline, or be unchanged? Why?

(d) True or False: Even if the Bayes decision boundary for a given problem is linear, we will probably achieve a superior test error rate using QDA rather than LDA because QDA is flexible enough to model a linear decision boundary. Justify your answer.

Points: 5

2. Suppose we collect data for a group of students in a statistics class with variables  $X_1$  =hours studied,  $X_2$  =undergrad GPA, and  $Y$  = receive an A. We fit a logistic regression and produce estimated coefficient,  $\hat{\beta}_0 = -6$ ,  $\hat{\beta}_1 = 0.05$ ,  $\hat{\beta}_2 = 1$ .

(a) Estimate the probability that a student who studies for 40 h and has an undergrad GPA of 3.5 gets an A in the class.

(b) How many hours would the student in part (a) need to study to have a 50% chance of getting an A in the class?

Points: 5

3. Suppose that we wish to predict whether a given stock will issue a dividend this year ("Yes" or "No") based on  $X$ , last year's percent profit. We examine a large number of companies and discover that the mean value of  $X$  for companies that issued a dividend was  $\bar{X} = 10$ , while the mean for those that didn't was  $\bar{X} = 0$ . In addition, the variance of  $X$  for these two sets of companies was  $\hat{\sigma}^2 = 36$ . Finally, 80% of companies issued dividends. Assuming that  $X$  follows a normal distribution, predict the probability that a company will issue a dividend this year given that its percentage profit was  $X = 4$  last year.

Hint: You will need to use Bayes' theorem.

Points: 5

4. Suppose that we take a data set, divide it into equally-sized training and test sets, and then try out two different classification procedures. First we use logistic regression and get an error rate of 20% on the training data and 30% on the test data. Next we use 1-nearest neighbors (i.e.  $K = 1$ ) and get an average error rate (averaged over both test and training data sets) of 18%. Based on these results, which method should we prefer to use for classification of new observations? Why?

Points: 5

## Applied Questions

1. This question should be answered using the **Weekly** data set.

- (a) Produce some numerical and graphical summaries of the **Weekly** data. Do there appear to be any patterns?
- (b) Use the full data set to perform a logistic regression with **Direction** as the response and the five lag variables plus **Volume** as predictors. Do any of the predictors appear to be statistically significant? If so, which ones?
- (c) Compute the confusion matrix and overall fraction of correct predictions. Explain what the confusion matrix is telling you about the types of mistakes made by logistic regression.
- (d) Now fit the logistic regression model using a training data period from 1990 to 2008, with **Lag2** as the only predictor. Compute the confusion matrix and the overall fraction of correct predictions for the held out data (that is, the data from 2009 and 2010).
- (e) Repeat (d) using LDA.
- (f) Repeat (d) using QDA.
- (g) Repeat (d) using KNN with  $K = 1$ .
- (h) Which of these methods appears to provide the best results on this data?
- (i) Experiment with different combinations of predictors, including possible transformations and interactions, for each of the methods. Report the variables, method, and associated confusion matrix that appears to provide the best results on the held out data. Note that you should also experiment with values for  $K$  in the KNN classifier.

### Hints:

- The dataset explanation can be found here: <https://rdrr.io/cran/ISLR/man/Smarket.html>
- Check [https://scikit-learn.org/stable/modules/generated/sklearn.linear\\_model.LogisticRegression.html](https://scikit-learn.org/stable/modules/generated/sklearn.linear_model.LogisticRegression.html) for logistic regression
- Check [https://scikit-learn.org/stable/modules/generated/sklearn.discriminant\\_analysis.QuadraticDiscriminantAnalysis.html](https://scikit-learn.org/stable/modules/generated/sklearn.discriminant_analysis.QuadraticDiscriminantAnalysis.html) for QDA
- Check [https://scikit-learn.org/stable/modules/generated/sklearn.discriminant\\_analysis.LinearDiscriminantAnalysis.html](https://scikit-learn.org/stable/modules/generated/sklearn.discriminant_analysis.LinearDiscriminantAnalysis.html) for LDA
- Check [https://scikit-learn.org/stable/modules/generated/sklearn.metrics.confusion\\_matrix.html](https://scikit-learn.org/stable/modules/generated/sklearn.metrics.confusion_matrix.html) for confusion matrix
- Check <https://scikit-learn.org/stable/modules/generated/sklearn.neighbors.KNeighborsClassifier.html> for KNN

### Points: 25

2. In this problem, you will develop a model to predict whether a given car gets high or low gas mileage based on the **Auto** data set.

- (a) Create a binary variable, **mpg01**, that contains a 1 if **mpg** contains a value above its median, and a 0 if **mpg** contains a value below its median. Create a single data set containing both **mpg01** and the other **Auto** variables.
- (b) Explore the data graphically in order to investigate the association between **mpg01** and the other features. Which of the other features seem most likely to be useful in predicting **mpg01**? Scatterplots and boxplots may be useful tools to answer this question. Describe your findings.
- (c) Split the data into a training set and a test set.
- (d) Perform LDA on the training data in order to predict **mpg01** using the variables that seemed most associated with **mpg01** in (b). What is the test error of the model obtained?
- (e) Perform QDA on the training data in order to predict **mpg01** using the variables that seemed most associated with **mpg01** in (b). What is the test error of the model obtained?

- (f) Perform logistic regression on the training data in order to predict **mpg01** using the variables that seemed most associated with **mpg01** in (b). What is the test error of the model obtained?
- (g) Perform KNN on the training data, with several values of K, in order to predict **mpg01**. Use only the variables that seemed most associated with **mpg01** in (b). What test errors do you obtain? Which value of K seems to perform the best on this data set?

**Hint:**

- Check this link for boxplots <https://seaborn.pydata.org/generated/seaborn.boxplot.html>

**Points: 25**