Dynamics-Aware Gradient Clipping: Separating Feedback from Threshold Scheduling

Yuxin Li [1] **Zisong Yuan** [1]

Abstract

An adaptive clipping rule can protect training even when its feedback signals provide little benefit beyond the resulting threshold schedule. We study this distinction in Dynamics-Aware Gradient Clipping (DAGC), a bounded controller using clipping exposure and consecutive-gradient alignment. A stationary mean-field analysis shows that its excess-exposure response reinforces clipping rather than stabilizing a target rate. We evaluate the frozen V2 rule against validation-tuned clipping, an alignment ablation, and calibration-trace replay on FashionMNIST and CIFAR-10, with twelve paired seeds per condition. Across 405 audited calibration and confirmation outcomes, DAGC falls below tuned fixed clipping by 0.18, 1.17, and 0.29 percentage points in the three confirmation conditions; all three paired deficits survive Holm correction. Replay meets the prespecified per-comparison ± 0.5 point equivalence criterion. The controller occupies its moving lower bound on 97.2–99.1% of updates, and removing alignment leaves all logged CIFAR-10 trajectories unchanged. The results identify a concrete regime in which projection masks feedback and predetermined thresholds reproduce its accuracy within a stated tolerance. They motivate separating protection, threshold scheduling, and feedback value when evaluating adaptive clipping, without claiming universal superiority or convergence of the coupled training dynamics.

1. Introduction

Gradient clipping limits the contribution of a large gradient to an optimizer update (Pascanu et al., 2013). A fixed threshold is simple but introduces a scale-sensitive hyperparameter. Adaptive rules can instead derive a threshold from gradient history or parameter magnitude (Seetharaman et al., 2020; Brock et al., 2021). When an adaptive method succeeds, however, its accuracy alone does not establish why: a useful threshold profile, a smaller effective step size, and informative feedback can produce similar outcomes.

We examine that ambiguity in Dynamics-Aware Gradient Clipping (DAGC). The controller uses the recent frequency of clipping and the alignment of consecutive raw gradients. Its first version, V1, allowed exposure alone to increase the threshold but not decrease it. V2 replaces that one-sided term with a term that becomes negative above a reference exposure. This makes sustained clipping more restrictive. It also gives the feedback the opposite sign to a clipping-rate tracker: lowering a threshold makes further clipping more likely.

This distinction changes both the interpretation and the experiment needed to support the method. A comparison with an arbitrary fixed threshold cannot establish that exposure or alignment provides useful information beyond the gradient scale. Removing the alignment term tests its necessity. A lagged median rule tests whether magnitude information is sufficient. Replaying a threshold trace constructed on separate calibration runs tests the incremental value of adapting that threshold to the new training trajectory. Replay still uses the current norm to apply clipping; only its threshold is predetermined.

We ask three distinct questions: does clipping protect training, does the chosen threshold profile improve accuracy, and does feedback add value beyond that profile? Our contribution is a controlled study of these questions for one concrete controller. A local analysis identifies positive exposure feedback; paired confirmation separates its effect from tuned fixed clipping, magnitude-only adaptation, and replay; complete-trace diagnostics show when projection masks the direction term. The combined evidence explains how promising small-subset results can coexist with limited feedback value under a longer, validation-calibrated protocol. It does not establish that feedback is unhelpful in general. Our scope is small image classifiers and momentum SGD, with no claim of architecture-independent or language-model transfer.

[1]Beihang University. Correspondence to: Yuxin Li <taolee16@outlook.com>, Zisong Yuan <alexsongyzs@gmail.com>.

Preprint. October 11, 2026.

2. Related Work

Adaptive gradient and update clipping. Fixed norm clipping was popularized for recurrent-network optimization (Pascanu et al., 2013). AutoClip derives a global threshold from historical norm percentiles (Seetharaman et al., 2020); AGC instead uses unit-wise parameter magnitude (Brock et al., 2021). ACClip uses coordinate-wise adaptation in attention models (Zhang et al., 2020c). ZClip detects norm spikes through running statistics (Kumar et al., 2025), whereas the revised AdaGC bounds tensor gradients relative to historical clipped-norm estimates (Wang et al., 2025). Group-level historical control also appears in AGGC (Li et al., 2026). These rules differ in granularity, reference scale, and treatment of anomalous gradients. DAGC uses one global threshold with exposure and consecutive-gradient alignment; its distinction must be tested against these simpler information sources, not inferred from the general novelty of an adaptive threshold.

Clippy constrains optimizer updates in multitask ranking (Tang et al., 2023). This distinction matters because raw-gradient clipping does not directly bound the parameter step after momentum or preconditioning. StableAdamW addresses underestimated second-moment states in vision-language training (Wortsman et al., 2023). Such optimizer-specific protections motivate our explicit clipping order, but their large-scale results are not experimental evidence for DAGC.

Rate feedback, quantiles, and robust estimation. Adaptive private federated clipping estimates a desired norm quantile online (Andrew et al., 2021). Quantile clipping has also been studied through robust stochastic optimization (Merad & Gaïffas, 2024) and adaptive DP-SGD convergence analysis (Shulgin & Richtárik, 2024). These analyses highlight clipping bias and the joint role of threshold and stepsize schedules. The geometric treatment of private SGD likewise shows that clipping can bias an update (Chen et al., 2020). DAGC is neither a privacy mechanism nor a quantile estimator: its excess-exposure response has the opposite sign to rate tracking. Median-gradient estimators connect some clipping methods to robust location estimation (Schaipp et al., 2025), but estimating a median gradient vector is distinct from our scalar rolling-median norm control.

Optimization theory and heavy-tailed noise. Relaxed-smoothness analyses explain why clipping can accelerate optimization (Zhang et al., 2020b;a). Stability and convergence results also cover rapidly growing subgradients and clipped momentum (Mai & Johansson, 2021). Stochastic bias can limit convergence even when clipping prevents large updates (Koloskova et al., 2023). Empirical tail-index studies (Şimşekli et al., 2019) and attention-model analysis (Zhang et al., 2020c) motivate considering non-Gaussian gradient noise. Accelerated clipping and normalized clipped momentum provide heavy-tail guarantees under stated assumptions (Gorbunov et al., 2020; Cutkosky & Mehta, 2021); newer work separates the roles of normalization and clipping (Sun et al., 2025). We neither estimate a tail index nor verify these assumptions for our networks. These results supply context, not a convergence theorem for the DAGC controller coupled to neural-network training.

Adaptation, architecture, and training scale. AdaGrad (Duchi et al., 2011) and AdaGrad-Norm (Ward et al., 2019) adapt step scales using past gradients; Adam (Kingma & Ba, 2015) adds coordinate-wise moment estimates. AdamW separates weight decay from its adaptive update (Loshchilov & Hutter, 2019), while LAMB uses layer-wise update scaling (You et al., 2020). These are alternative ways to change update magnitude rather than evidence that a specific clipping feedback signal is informative. Initialization and momentum also materially affect optimization (Glorot & Bengio, 2010; Sutskever et al., 2013). Batch normalization (Ioffe & Szegedy, 2015; Santurkar et al., 2018) and residual connections (He et al., 2016) change the training setting, so gains on a small CNN cannot automatically transfer to a residual model. Small-scale Transformer proxies reproduce selected instabilities under explicit conditions (Wortsman et al., 2024); our image experiments do not establish a corresponding language-model transfer claim.

Evidence for a mechanism. Benchmark variance (Bouthillier et al., 2021), selection bias (Cawley & Talbot, 2010), and finite hyperparameter-search budgets (Bergstra & Bengio, 2012) motivate paired seeds and validation-only selection. Freshly collected benchmark tests can change absolute scores (Recht et al., 2019); withholding a test set during the new campaign does not erase earlier exposure to it. Statistical comparisons must respect the replication unit and test assumptions (Dror et al., 2018). We distinguish descriptive legacy evidence, multiplicity-corrected confirmation (Holm, 1979), and equivalence within a stated practical margin (Lakens, 2017). This prevents a null replay comparison from being presented either as proof of superiority or as proof of equivalence.

3. Controller and Competing Explanations

Let $g_t = \nabla_\theta \ell_t(\theta_t)$ be the raw minibatch gradient, and let $n_t = \|g_t\|_2$. A positive threshold c_t gives

$$\widetilde{g}_t = \alpha_t g_t, \qquad \alpha_t = \min\{1, c_t / \max(n_t, \epsilon)\}. \tag{1}$$

We log exposure $e_t = \mathbf{1}[n_t > c_t]$, intensity $I_t = 1 - \alpha_t$, and alignment $a_t = \langle g_t, g_{t-1} \rangle / \max(n_t n_{t-1}, \epsilon)$. The first

Algorithm 1 One DAGC-V2 training step

1: Compute raw g_t, n_t, and a_t.
2: Save raw g_t for the next alignment calculation.
3: Apply clipping at the current c_t using Eq. (1).
4: Update exposure E_t, alignment A_t, and norm history.
5: Compute c_{t+1} using Eqs. (4)–(5).
6: Update momentum and parameters using $\widetilde{g}_t$.

alignment is one. The exposure and alignment states are

$$E_t = \beta E_{t-1} + (1-\beta)e_t, \tag{2}$$
$$A_t = \beta_a A_{t-1} + (1-\beta_a)a_t, \tag{3}$$

initialized at $E_{-1} = 0$ and $A_{-1} = 1$. DAGC-V2 updates

$$u_t = r(\tau - E_t) - w\max(0, -A_t), \tag{4}$$
$$c_{t+1} = \Pi_{[L_t,U_t]}(c_t \exp[\gamma \tanh(u_t)])\,. \tag{5}$$

Here $L_t = \max(0.1m_t, 10^{-12})$ and $U_t = \max(10m_t, 10^{-9})$, where m_t is the lower median of the last 200 raw gradient norms, including n_t. Thus these bounds affect the next step. The frozen settings are $(c_0, \gamma, \beta, \beta_a, r, w, \tau) = (0.5, 0.05, 0.9, 0.9, 0.3, 3, 0.1)$. V1 replaces $r(\tau - E_t)$ with $r(1 - E_t)$; since $E_t \in [0, 1]$, its exposure term cannot itself tighten clipping. V2 can tighten, but this change alone does not imply useful regulation.

The ordering prevents the current norm from selecting its own DAGC threshold. Clipping precedes SGD's coupled weight decay and momentum accumulation. Hence c_t bounds the clipped data gradient, not the final parameter displacement. The method stores a previous full gradient, requiring $O(d)$ additional memory, and a 200-element norm window. Its diagnostic alignment requires an $O(d)$ dot product. We do not describe it as constant-memory control.

3.1. The reference exposure is not a stable target

For a stationary, exogenous gradient-norm distribution, with alignment disabled and inactive bounds, the exposure-EMA mean-field system has a linearly unstable interior reference-exposure fixed point whenever the density at that threshold is positive. Appendix F gives the assumptions, Jacobian and complete proof, together with conditional results on alignment masking and replay.

The result includes exposure smoothing; an EMA does not reverse the feedback sign. It does not prove instability of neural-network training: the gradient norm distribution changes with the parameters, the bounds move, and the alignment signal can activate. It does explain why the reference τ should not be interpreted as a regulated clipping frequency. Persistent clipping can instead drive the threshold to its lower bound, where historical norm scale may dominate the resulting behavior.

3.2. What clipping can protect

For momentum SGD without weight decay, $v_t = \mu v_{t-1} + \widetilde{g}_t$. If $c_j \le C$ over k updates and $0 \le \mu < 1$, then

$$\|v_t\| \le \mu^k \|v_{t-k}\| + C\frac{1-\mu^k}{1-\mu}. \tag{6}$$

A smaller sustained threshold bounds new momentum contributions but does not remove an existing buffer. Coupled weight decay adds parameter-dependent terms. This elementary bound motivates a protection hypothesis without establishing convergence, explaining a test-accuracy improvement, or requiring exposure and alignment to be the best threshold signals.

4. Experimental Design

4.1. Questions, conditions, and data separation

The new study asks whether the frozen controller outperforms tuned fixed clipping, a tuned median-scale rule, and calibration-trace replay. Its secondary question is whether removing alignment changes the outcome. The three conditions are FashionMNIST with the existing small CNN at initial learning rate 0.8, and CIFAR-10 with ResNet-20 at 0.1 or 0.4. The latter two are designated lower and higher learning rates; we do not assume either one diverges without clipping.

FashionMNIST (Xiao et al., 2017) uses 55,000 training images and a fixed 5,000-image validation split. CIFAR-10 (Krizhevsky, 2009) uses 45,000 training and 5,000 validation images. Both splits hold out 500 images per class using seed 1729. All methods train on the same remaining examples; validation images never enter training. Only calibration runs evaluate the validation set. Confirmation runs evaluate the complete official 10,000-image test set once, after the last training epoch. They retain the same training partition, preserving the number of steps used to construct replay schedules. No test score is used to choose a new-campaign hyperparameter or checkpoint.

FashionMNIST uses two convolutional layers (32 and 64 channels), max pooling, and a 128-unit hidden classifier, with 421,642 parameters. CIFAR-10 uses the $6n$+2 residual architecture of He et al. (2016), $n = 3$, widths 16/32/64, option-A shortcuts, and batch normalization, with 269,722 parameters. The RGB model is deeper, not larger in parameter count. This is an architectural transfer test, not a reproduction of the original ResNet training recipe.

4.2. Training and calibration budget

Training uses FP32 SGD with momentum 0.9, batch size 256, and no dropped last batch. FashionMNIST runs for 30 epochs with weight decay 10^{-4}; CIFAR-10 runs for 60

Table 1. Final test accuracy (percent), mean ± Student-t 95% interval half-width over twelve paired training seeds. Hyperparameters are selected using the validation set. Failures are retained at zero accuracy.

Policy	FashionMNIST, LR 0.8	CIFAR-10, LR 0.1	CIFAR-10, LR 0.4
No clipping	3.33 ± 3.13	90.67 ± 0.09	90.35 ± 0.28
Tuned fixed	92.60 ± 0.07	90.67 ± 0.09	91.16 ± 0.12
Tuned AGC	92.40 ± 0.05	90.66 ± 0.14	91.20 ± 0.16
Tuned AutoClip	90.46 ± 0.15	90.63 ± 0.12	90.78 ± 0.27
Tuned median scale	92.56 ± 0.12	90.58 ± 0.16	91.08 ± 0.15
DAGC-V2	92.41 ± 0.09	89.50 ± 0.10	90.87 ± 0.11
No alignment	92.26 ± 0.18	89.50 ± 0.10	90.87 ± 0.11
Trace replay	92.39 ± 0.09	89.40 ± 0.15	90.94 ± 0.09

Table 2. Primary paired comparisons in percentage points: DAGC minus the comparator. Intervals are unadjusted 95% paired t intervals; p_H is the exact two-sided sign-flip p-value after Holm adjustment over all nine tests. Win counts exclude ties.

Condition / initial LR	Comparator	Difference	95% interval	Wins	p_H
FashionMNIST / 0.8	Tuned fixed	-0.184	[-0.291, -0.078]	1/12	0.0176
FashionMNIST / 0.8	Tuned median scale	-0.148	[-0.251, -0.044]	2/12	0.0635
FashionMNIST / 0.8	Trace replay	+0.023	[-0.081, +0.126]	5/12	0.7236
CIFAR-10 / 0.1	Tuned fixed	-1.172	[-1.325, -1.019]	0/12	0.0044
CIFAR-10 / 0.1	Tuned median scale	-1.080	[-1.257, -0.903]	0/12	0.0044
CIFAR-10 / 0.1	Trace replay	+0.102	[-0.076, +0.280]	8/12	0.7236
CIFAR-10 / 0.4	Tuned fixed	-0.292	[-0.409, -0.175]	1/12	0.0103
CIFAR-10 / 0.4	Tuned median scale	-0.205	[-0.405, -0.005]	3/12	0.1914
CIFAR-10 / 0.4	Trace replay	-0.068	[-0.200, +0.065]	4/12	0.7236

epochs with weight decay 5×10^{-4}. A cosine schedule decreases the learning rate to 1% of its initial value. CIFAR-10 uses random padded crops and horizontal flips; FashionMNIST uses normalization only. All settings are fixed across clipping policies within a condition.

Fixed clipping, AGC, AutoClip, and the median rule each receive three candidates and three calibration seeds (2100–2102): nine runs per policy per condition. Their grids are, respectively, $\{0.05, 0.5, 5\}$, $\{0.005, 0.03, 0.18\}$, percentiles $\{1, 10, 50\}$, and $\{0.025, 0.1, 0.4\}$. The winner maximizes mean final validation accuracy, with grid order breaking exact ties. These equal finite budgets do not constitute exhaustive tuning. DAGC retains the setting selected during earlier development, so its total historical tuning budget is not matched to the new baselines.

AGC clips every parameter, grouping matrix and convolution weights by output unit and treating vectors as a single unit, with parameter-norm floor 10^{-3}. AutoClip takes the stated percentile of all raw norms through the current step, following its authors' convention. The median rule clips at $\lambda \operatorname{median}(n_{t-200}, \ldots, n_{t-1})$, using available history and initial threshold 0.5. It is causal and uses the same lower-median convention as DAGC. The no-alignment variant sets $w = 0$ without retuning. Replay averages the thresholds actually applied in three full DAGC calibration runs and applies this fixed, step-indexed schedule in confirmation. All eight policies, including no clipping, share a complete training budget.

4.3. Pairing, failures, and inference

Confirmation uses twelve seeds, 3100–3111. Within a seed, initial weights, minibatch order, and augmentations are identical across policies. Private random generators isolate the input stream from diagnostics and controller state. Deterministic CUDA operations are enabled and TF32 is disabled. Epoch checkpoints include model, optimizer, controller, previous raw gradient, and logs; a test verifies that resumed and uninterrupted runs agree exactly. Configuration and source checksums reject stale results.

A run stops on nonfinite loss or gradient norm, or loss above 10^6. A nonfinite final evaluation also fails. Failed runs receive accuracy zero and remain in all aggregates; finite chance-level runs retain their observed score. We do not choose the best epoch, discard failures, or rerun unfavorable seeds. The final audit checks all 117 calibration and 288 confirmation outcomes.

We report Student-t 95% intervals over seeds, including paired intervals for accuracy differences. The primary family comprises DAGC versus fixed, median, and replay in all three conditions: nine two-sided exact sign-flip tests with Holm correction. Sign flipping assumes exchangeability under the null; the t intervals assume the seed-level mean is adequately approximated by that model. Neither addresses uncertainty from sampling a new dataset. A broad superiority claim requires a positive effect and corrected significance in all nine comparisons. Secondary comparisons

are descriptive.

A prespecified ± 0.5 percentage-point margin supplies an additional within-comparison equivalence check: the paired 90% interval must lie entirely inside that range. This is not a familywise equivalence claim. Nonsignificance alone is not evidence of equivalence. The original eight-seed plan was amended to twelve during calibration, before any confirmation runs: with eight seeds, the minimum two-sided sign-flip $p = 2/256$ cannot pass the first nine-test Holm threshold $0.05/9$. The audit preserves this amendment and all identical calibration results carried forward from the first execution.

5. Results

5.1. Completeness, failures, and accuracy

All 405 planned outcomes pass the source/configuration, split, seed-coverage, epoch-continuity, calibration-selection, and replay-construction audits. There are 397 full-budget completions and eight predefined scientific failures, with no process errors. All eight failures occur without clipping on FashionMNIST. Its four remaining unclipped runs finish at 10% accuracy; retaining failures at zero gives a mean of 3.33%. Every clipped confirmation run and every CIFAR-10 run completes its budget.

Table 1 reports the full comparison. On FashionMNIST, DAGC reaches 92.41%, versus 92.60% for tuned fixed clipping and 92.56% for the tuned median rule. On CIFAR-10 at LR 0.1, DAGC reaches 89.50%, versus 90.67% for fixed clipping. At LR 0.4, the corresponding scores are 90.87% and 91.16%. AGC attains the highest observed mean at the higher CIFAR rate, 91.20%; differences among non-DAGC baselines are not a prespecified hypothesis family.

The paired DAGC-minus-fixed effects are -0.18, -1.17, and -0.29 points, with Holm-adjusted p-values 0.0176, 0.0044, and 0.0103, respectively (Table 2). Thus the new study reverses the earlier exploratory fixed-baseline advantage. These are different data sizes, schedules, and calibration budgets, so this is a failure of transfer under the new protocol, not a claim that the earlier measurements were numerically false. The prespecified broad-superiority criterion is not met.

At CIFAR-10 LR 0.1, calibration selects fixed threshold 5.0, and this threshold never binds in confirmation. Its norm traces and coefficients exactly match no clipping. Accordingly, the 1.17-point deficit is also a deficit to the unmodified optimizer. At LR 0.4, DAGC exceeds no clipping by 0.52 points [0.25, 0.79], but stronger performance is achieved by the tuned fixed rule. Avoiding divergence or improving on no clipping is therefore insufficient evidence for the particular DAGC controller.

5.2. Replay and alignment controls

DAGC-minus-replay differences are $+0.02$, $+0.10$, and -0.07 points. Their paired 90% intervals are $[-0.06, 0.11]$, $[-0.04, 0.25]$, and $[-0.18, 0.04]$. Each lies inside the prespecified ± 0.5 point margin. This supports equivalence within each tested condition at that tolerance; it is not a multiplicity-adjusted familywise equivalence result, nor a claim that the methods coincide outside these settings. The corresponding 95% intervals appear in Table 2 and Figure 1.

Removing alignment changes FashionMNIST accuracy by $+0.15$ points in DAGC's favor, with a paired 95% interval $[-0.04, 0.33]$. On both CIFAR-10 conditions, all twelve paired raw-gradient norms, applied thresholds, coefficients, alignment traces, and lower-bound indicators are exactly equal between DAGC and the no-alignment variant. The complete-trace audit shows that negative smoothed alignments do occur; the direction term is therefore not intrinsically inactive. All 3,860 negative-alignment-EMA updates across the two CIFAR conditions are projected to the lower bound. Its effect on the applied threshold is masked by lower-bound projection in these runs. This identifies a limit of the implemented controller, rather than demonstrating that gradient direction never matters.

5.3. The lower bound dominates the controller

DAGC's next-step threshold equals its moving lower bound on 97.18%, 99.07%, and 99.00% of updates, respectively. Its mean clipping intensities are 0.893, 0.900, and 0.899. Figure 2 shows the resulting profiles. These measurements are consistent with the positive-feedback calculation: clipping stays active and the projection frequently determines the threshold.

The validation-selected median coefficient is 0.1 on FashionMNIST, matching DAGC's lower-bound scale, and 0.4 on both CIFAR conditions. The CIFAR median rule therefore retains larger gradients, with intensities near 0.60. DAGC falls below it by 1.08 points at LR 0.1 (Holm $p = 0.0044$) and 0.21 points at LR 0.4 (Holm $p = 0.1914$). The latter comparison does not pass the primary multiplicity criterion. Bound occupancy describes which part of the rule is active; by itself it does not prove that changing only the bound would produce a particular accuracy gain.

5.4. Earlier exploratory evidence and corrected interpretation

The corresponding audited historical plots are retained in Appendix C.1; they are distinct from the confirmation evidence in Figures 1 and 2.

The earlier 15-epoch, 5,000-training/2,000-test experiments used different training seeds for development and evaluation,




Figure 1. Paired effects of DAGC versus the main controls and the no-alignment variant. Bars show 95% intervals; the shaded region is the prespecified ± 0.5 point margin. Equivalence requires a separate 90% interval check.

but sampled from the same official test set for both stages. We therefore classify them as exploratory, not independent data-held-out confirmation. Their positive comparisons to fixed clipping motivated the present study; they cannot substitute for it.

The most discriminating legacy experiment already limited the mechanism claim. Over eight paired seeds, DAGC exceeded an intensity-matched fixed rule by 1.18 points (recomputed 95% paired interval [0.62, 1.74]), but its advantage over replay was 0.21 points $[-0.43, 0.86]$. Removing alignment changed accuracy by 0.16 points $[-0.33, 0.66]$, whereas removing exposure cost 5.47 points [4.04, 6.90]. These results identify the effect of specified ablations on the whole training trajectory. They do not show that reversal predicts future loss deterioration or that online feedback adds value beyond replay.

Independent-seed learning-rate perturbations did not resolve the ambiguity: the DAGC-minus-replay difference was -0.06 $[-0.71, 0.59]$ for a temporary learning-rate doubling and $+0.01$ $[-0.51, 0.52]$ for a sustained decrease. The uncertainty spans effects beyond the new equivalence margin, so these legacy null results are not equivalence claims. Appendix C reports all controls and corrected intervals.

A development sweep over the reference exposure had previously pooled two gains and three seeds into six apparent replicates. We instead report each gain separately with three seeds. Realized exposure remains at least 0.999 across the grid, while intensity changes. The sweep is consistent with the positive-feedback interpretation, but its small sample and development role preclude precise claims of performance insensitivity.

6. Discussion and Limitations

The central distinction is between protection from unstable updates and the incremental value of a controller's information. On FashionMNIST, every clipped confirmation policy completes its budget, while eight unclipped runs fail. Protection is therefore a shared benefit of clipping in this condition, not evidence unique to DAGC. Replay removes threshold adaptation to the new run; the median control retains online magnitude information; the alignment ablation removes direction alone. Their agreement or disagreement answers different questions and must not be collapsed into a single mechanism claim.

The combined evidence identifies a regime of projection-dominated control. DAGC spends nearly all threshold updates at its moving lower bound. Negative alignment EMAs occur on CIFAR-10, but every such update is projected to that bound, and the paired no-alignment trajectories are identical. This supports masking by projection in these runs, rather than the stronger claim that direction is intrinsically uninformative. Calibration replay attains equivalent accuracy within the prespecified per-condition tolerance; this empirical result is distinct from the exact same-run replay theorem in the appendix.

The controller loses to tuned fixed clipping in all three conditions. Two accuracy gaps, on FashionMNIST and higher-rate CIFAR-10, are statistically resolved yet satisfy the stated ± 0.5 point equivalence criterion; the low-rate CIFAR-10 gap does not. Practical tolerance and statistical difference answer distinct questions. Neither supplies a benefit-cost argument without measuring the corresponding costs. Earlier small-subset gains remain valid observations,




Figure 2. Applied thresholds and clipping intensities averaged over twelve confirmation seeds and 100 bins of training progress. DAGC and no-alignment curves overlap on CIFAR-10. These observational trajectories describe behavior; they do not establish the causal value of an individual feedback signal.

but do not establish transfer across the changed data sizes, schedules, architectures, and baseline selection rules.

Accuracy, calibration, and implementation cost. A useful method need not maximize accuracy if it offers a verified advantage in calibration effort, latency, memory, or reliability. The current study does not establish such a trade-off for DAGC. Its parameters are frozen from earlier development, whereas the four tuned baselines receive equal new search budgets; the historical optimization effort is unequal and was not measured as a comparable total cost. Full-gradient alignment adds an $O(d)$ stored vector and a dot product. Campaign timings are not isolated measurements of controller overhead. Accordingly, we neither infer efficiency from small accuracy gaps nor claim that replay is computationally superior. Those claims require matched timing, memory, and calibration-cost measurements.

The study remains limited to two image datasets, two small architectures, one optimizer, and fixed learning-rate schedules. Sixty CIFAR epochs are longer than the legacy diagnostics but do not establish asymptotic performance or large-scale training stability. Fixed grids can miss better baseline settings. Historical FashionMNIST test exposure and unequal earlier method development remain limitations despite validation-only selection in the new campaign. Seed intervals are conditional on a fixed data split. Our analytic model freezes the norm distribution; its unstable controller equilibrium is not a theorem about the nonlinear coupled training system. Likewise, lower-bound occupancy and accuracy correlation cannot identify a causal mechanism alone.

Appendix F proves conditional results on projection masking, exact same-run replay, and the value of causal information. These results do not establish that DAGC realizes an optimal feedback policy or outperforms independent-calibration replay; the confirmation results do not support either claim.

7. Conclusion

Adaptive clipping should be evaluated at three levels: protection, threshold selection, and the value of feedback beyond the selected profile. For the frozen DAGC-V2 rule, the stationary analysis identifies positive exposure feedback and the confirmation study reveals strong lower-bound control. Tuned fixed clipping is more accurate in all three

tested conditions, while calibration replay meets the stated per-condition equivalence criterion. The CIFAR alignment ablation and full-trace audit identify projection masking as a concrete limit of the implemented direction feedback. These results separate a useful clipping intervention from evidence that its proposed feedback signals add value; they do not rule out feedback gains elsewhere. A productive next step is to identify a measurable condition in which an informative signal changes the applied threshold and improves a specified accuracy, stability, or cost objective. The present experiments provide a reproducible reference for that question, not evidence that the current rule already achieves it.

Impact Statement

This work examines optimization behavior in small image classifiers. It does not deploy a model or introduce a new dataset. Better-controlled evaluation can reduce wasted experiments and unsupported claims about training stability. A clipping rule is not a guarantee of reliable or safe behavior in downstream applications; broader deployment consequences depend on the model and use.

References

Andrew, G., Thakkar, O., McMahan, H. B., and Ramaswamy, S. Differentially private learning with adaptive clipping. In *Advances in Neural Information Processing Systems*, volume 34, 2021. URL https://arxiv.org/abs/1905.03871.

Bergstra, J. and Bengio, Y. Random search for hyper-parameter optimization. *Journal of Machine Learning Research*, 2012. URL https://jmlr.org/papers/v13/bergstra12a.html.

Bouthillier, X., Delaunay, P., Bronzi, M., Trofimov, A., Nichyporuk, B., Szeto, J., Sepah, N., Raff, E., Madan, K., Voleti, V., Kahou, S. E., Michalski, V., Serdyuk, D., Arbel, T., Pal, C., Varoquaux, G., and Vincent, P. Accounting for variance in machine learning benchmarks. In *Proceedings of Machine Learning and Systems*, volume 3, pp. 730–743, 2021.

Brock, A., De, S., Smith, S. L., and Simonyan, K. High-performance large-scale image recognition without normalization. In *International Conference on Machine Learning*, 2021.

Cawley, G. C. and Talbot, N. L. C. On over-fitting in model selection and subsequent selection bias in performance evaluation. *Journal of Machine Learning Research*, 2010. URL https://jmlr.org/papers/v11/cawley10a.html.

Chen, X., Wu, Z. S., and Hong, M. Understanding gradient clipping in private sgd: A geometric perspective. In *Advances in Neural Information Processing Systems*, 2020. URL https://arxiv.org/abs/2006.15429.

Cutkosky, A. and Mehta, H. High-probability bounds for non-convex stochastic optimization with heavy tails. *arXiv preprint arXiv:2106.14343*, 2021. URL https://arxiv.org/abs/2106.14343.

Dror, R., Baumer, G., Shlomov, S., and Reichart, R. The hitchhiker's guide to testing statistical significance in natural language processing. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics*, 2018. URL https://aclanthology.org/P18-1128/.

Duchi, J., Hazan, E., and Singer, Y. Adaptive subgradient methods for online learning and stochastic optimization. *Journal of Machine Learning Research*, 2011. URL https://jmlr.org/papers/v12/duchi11a.html.

Glorot, X. and Bengio, Y. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, pp. 249–256, 2010.

Gorbunov, E., Danilova, M., and Gasnikov, A. Stochastic optimization with heavy-tailed noise via accelerated gradient clipping. In *Advances in Neural Information Processing Systems*, 2020. URL https://arxiv.org/abs/2005.10785.

He, K., Zhang, X., Ren, S., and Sun, J. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 770–778, 2016. URL https://www.cv-foundation.org/openaccess/content_cvpr_2016/html/He_Deep_Residual_Learning_CVPR_2016_paper.html.

Holm, S. A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics*, 1979. URL https://www.jstor.org/stable/4615733.

Ioffe, S. and Szegedy, C. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International Conference on Machine Learning*, pp. 448–456, 2015.

Kingma, D. P. and Ba, J. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2015.

Koloskova, A., Hendrikx, H., and Stich, S. U. Revisiting gradient clipping: Stochastic bias and tight convergence guarantees. In *International Conference on Machine Learning*, 2023.

Krizhevsky, A. Learning multiple layers of features from tiny images. Technical report, University of Toronto, 2009. URL https://www.cs.toronto.edu/~kriz/learning-features-2009-TR.pdf.

Kumar, A., Owen, L., Roy Chowdhury, N., and Güra, F. ZClip: Adaptive spike mitigation for LLM pre-training. *arXiv preprint arXiv:2504.02507*, 2025.

Lakens, D. Equivalence tests: A practical primer for t tests, correlations, and meta-analyses. *Social Psychological and Personality Science*, 2017. URL https://doi.org/10.1177/1948550617697177.

Li, Z., Wu, Y., and Chang, Y. Aggc: Adaptive group gradient clipping for stabilizing large language model training. *arXiv preprint arXiv:2601.11864*, 2026. URL https://arxiv.org/abs/2601.11864.

Loshchilov, I. and Hutter, F. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019.

Mai, V. V. and Johansson, M. Stability and convergence of stochastic gradient clipping: Beyond lipschitz continuity

and smoothness. In *International Conference on Machine Learning*, 2021. URL https://proceedings.mlr.press/v139/mai21a.html.

Merad, I. and Gaïffas, S. Robust stochastic optimization via gradient quantile clipping. *Transactions on Machine Learning Research*, 2024. URL https://arxiv.org/abs/2309.17316.

Pascanu, R., Mikolov, T., and Bengio, Y. On the difficulty of training recurrent neural networks. In *International Conference on Machine Learning*, pp. 1310–1318, 2013.

Recht, B., Roelofs, R., Schmidt, L., and Shankar, V. Do imagenet classifiers generalize to imagenet? In *International Conference on Machine Learning*, 2019. URL https://proceedings.mlr.press/v97/recht19a.html.

Santurkar, S., Tsipras, D., Ilyas, A., and Madry, A. How does batch normalization help optimization? In *Advances in Neural Information Processing Systems*, 2018.

Schaipp, F., Garrigos, G., Simsekli, U., and Gower, R. Tracking the median of gradients with a stochastic proximal point method. *Transactions on Machine Learning Research*, 2025. URL https://arxiv.org/abs/2402.12828v2.

Seetharaman, P., Wichern, G., Pardo, B., and Le Roux, J. Autoclip: Adaptive gradient clipping for source separation networks. In *IEEE Workshop on Machine Learning for Signal Processing*, 2020.

Shulgin, E. and Richtárik, P. On the convergence of DP-SGD with adaptive clipping. *arXiv preprint arXiv:2412.19916*, 2024. URL https://arxiv.org/abs/2412.19916.

Şimşekli, U., Sagun, L., and Gürbüzbalaban, M. A tail-index analysis of stochastic gradient noise in deep neural networks. In *International Conference on Machine Learning*, 2019.

Sun, T., Liu, X., and Yuan, K. Revisiting gradient normalization and clipping for nonconvex sgd under heavy-tailed noise: Necessity, sufficiency, and acceleration. *Journal of Machine Learning Research*, 2025. URL https://jmlr.org/papers/v26/24-1991.html.

Sutskever, I., Martens, J., Dahl, G., and Hinton, G. On the importance of initialization and momentum in deep learning. In *International Conference on Machine Learning*, pp. 1139–1147, 2013.

Tang, J., Drori, Y., Chang, D., Sathiamoorthy, M., Gilmer, J., Wei, L., Yi, X., Hong, L., and Chi, E. H. Improving training stability for multitask ranking models in recommender systems. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, 2023.

Wang, G., Li, S., Chen, C., Zeng, J., Yang, J., Sun, T., Ma, Y., Yu, D., and Shen, L. AdaGC: Improving training stability for large language model pretraining. *arXiv preprint arXiv:2502.11034*, 2025.

Ward, R., Wu, X., and Bottou, L. Adagrad stepsizes: Sharp convergence over nonconvex landscapes. In *International Conference on Machine Learning*, 2019. URL https://proceedings.mlr.press/v97/ward19a.html.

Wortsman, M., Dettmers, T., Zettlemoyer, L., Morcos, A., Farhadi, A., and Schmidt, L. Stable and low-precision training for large-scale vision-language models. In *Advances in Neural Information Processing Systems*, 2023.

Wortsman, M., Liu, P. J., Xiao, L., Everett, K., Alemi, A., Adlam, B., Co-Reyes, J. D., Gur, I., Kumar, A., Novak, R., Pennington, J., Sohl-Dickstein, J., Xu, K., Lee, J., Gilmer, J., and Kornblith, S. Small-scale proxies for large-scale transformer training instabilities. In *International Conference on Learning Representations*, 2024.

Xiao, H., Rasul, K., and Vollgraf, R. Fashion-MNIST: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017. URL https://arxiv.org/abs/1708.07747.

You, Y., Li, J., Reddi, S., Hseu, J., Kumar, S., Bhojanapalli, S., Song, X., Demmel, J., Keutzer, K., and Hsieh, C.-J. Large batch optimization for deep learning: Training BERT in 76 minutes. In *International Conference on Learning Representations*, 2020.

Zhang, B., Jin, J., Fang, C., and Wang, L. Improved analysis of clipping algorithms for non-convex optimization. In *Advances in Neural Information Processing Systems*, 2020a. URL https://arxiv.org/abs/2010.02519.

Zhang, J., He, T., Sra, S., and Jadbabaie, A. Why gradient clipping accelerates training: A theoretical justification for adaptivity. In *International Conference on Learning Representations*, 2020b.

Zhang, J., Karimireddy, S. P., Veit, A., Kim, S., Reddi, S., Kumar, S., and Sra, S. Gradient clipping and normalization for nonconvex optimization. In *International Conference on Machine Learning*, 2020c.

A. Reproducibility and Complete Calibration

The complete code, compact evidence, and manuscript are available at https://github.com/alexsongyzs-dotcom/Dynamics_Aware_Gradient_Clipping/tree/develop/yzs. The completed confirmation protocol is in `docs/lyx1_protocol.md`; seed-level records and audit hashes are in `results/lyx1/evidence/`. The original full-resolution server archive is required to rerun exact trace equality checks; binned exports alone cannot establish those equalities.

The machine-readable protocol fixes conditions, hyperparameter grids, calibration and confirmation seeds, and comparison families before confirmation. The source/configuration digest is checked when a run is resumed or reused. The evidence export verifies every run identity, exact confirmation seed sets, completed epoch continuity, and failure accounting. It retains per-epoch training metrics, final evaluation scores, 100-bin diagnostic traces, full replay schedules, and checksums for the full-resolution traces archived with the raw experiment. Tables and figures are generated from the exported seed-level records; summary values are not entered by hand.

Training inputs are cached on the GPU. CIFAR crop offsets and flips use a private generator keyed by training seed and epoch; a separate generator controls the permutation of training examples. No dropout or other random model operation is used. Model initialization uses the training seed. Exact resume tests cover optimizer state, controller state, prior gradient, metrics, and diagnostic traces. The numerical epsilon in scalar clipping is 10^{-12}; AGC's parameter floor is 10^{-3}. CUDA determinism is requested explicitly.

Table 3. Shared implementation details.

Item	FashionMNIST	CIFAR-10
Training / validation / test	55,000 / 5,000 / 10,000	45,000 / 5,000 / 10,000
Epochs / updates	30 / 6,450	60 / 10,560
Model / parameters	SmallCNN / 421,642	ResNet-20 / 269,722
Batch / SGD momentum	256 / 0.9	256 / 0.9
Weight decay	10^{-4}	5×10^{-4}
Mean	0.286	(0.4914, 0.4822, 0.4465)
Standard deviation	0.353	(0.2470, 0.2435, 0.2616)
Augmentation	None	Padded crop and horizontal flip
Evaluation frequency	Final epoch only	Final epoch only

Table 4. Complete calibration grid. Each candidate uses the same three seeds. Entries list candidate: mean validation accuracy (percent). The final column is selected before confirmation.

Condition / initial LR	Policy	Candidate scores	Selected
FashionMNIST / 0.8	Tuned fixed	0.05: 93.04, 0.5: 90.32, 5: 10.00	0.05
FashionMNIST / 0.8	Tuned AGC	0.005: 93.10, 0.03: 63.57, 0.18: 10.00	0.005
FashionMNIST / 0.8	Tuned AutoClip	1: 90.89, 10: 90.33, 50: 36.63	1
FashionMNIST / 0.8	Tuned median scale	0.025: 91.94, 0.1: 93.06, 0.4: 91.17	0.1
CIFAR-10 / 0.1	Tuned fixed	0.05: 77.25, 0.5: 91.16, 5: 91.64	5
CIFAR-10 / 0.1	Tuned AGC	0.005: 84.25, 0.03: 90.31, 0.18: 91.51	0.18
CIFAR-10 / 0.1	Tuned AutoClip	1: 91.34, 10: 91.51, 50: 91.48	10
CIFAR-10 / 0.1	Tuned median scale	0.025: 87.73, 0.1: 90.61, 0.4: 91.17	0.4
CIFAR-10 / 0.4	Tuned fixed	0.05: 88.76, 0.5: 92.01, 5: 91.26	0.5
CIFAR-10 / 0.4	Tuned AGC	0.005: 83.66, 0.03: 91.57, 0.18: 91.45	0.03
CIFAR-10 / 0.4	Tuned AutoClip	1: 91.44, 10: 91.63, 50: 91.44	10
CIFAR-10 / 0.4	Tuned median scale	0.025: 89.85, 0.1: 91.91, 0.4: 92.03	0.4

B. Failures and Clipping Diagnostics

For global clipping, the logged coefficient is the scalar multiplier. AGC instead logs the ratio of the whole clipped-gradient norm to the raw norm; its value does not imply a global scalar intervention, since individual units receive different multipliers. Frequency counts ratios below $1 - 10^{-7}$. Intensity is one minus that ratio. Bound occupancy counts whether the newly computed DAGC threshold equals its lower bound to relative tolerance 10^{-6}. For other policies this diagnostic is zero by construction and does not imply that their thresholds are unconstrained.

Table 5. Failures and mean diagnostics across twelve seeds. f is clipping frequency, I is intensity, and b is lower-bound occupancy.

Condition / initial LR	Policy	Failed	f	I	b
FashionMNIST / 0.8	No clipping	8/12	0.000	0.000	0.000
FashionMNIST / 0.8	Tuned fixed	0/12	1.000	0.947	0.000
FashionMNIST / 0.8	Tuned AGC	0/12	1.000	0.941	0.000
FashionMNIST / 0.8	Tuned AutoClip	0/12	0.954	0.297	0.000
FashionMNIST / 0.8	Tuned median scale	0/12	1.000	0.896	0.000
FashionMNIST / 0.8	DAGC-V2	0/12	1.000	0.893	0.972
FashionMNIST / 0.8	No alignment	0/12	1.000	0.893	0.970
FashionMNIST / 0.8	Trace replay	0/12	1.000	0.894	0.000
CIFAR-10 / 0.1	No clipping	0/12	0.000	0.000	0.000
CIFAR-10 / 0.1	Tuned fixed	0/12	0.000	0.000	0.000
CIFAR-10 / 0.1	Tuned AGC	0/12	0.763	0.008	0.000
CIFAR-10 / 0.1	Tuned AutoClip	0/12	0.960	0.262	0.000
CIFAR-10 / 0.1	Tuned median scale	0/12	1.000	0.598	0.000
CIFAR-10 / 0.1	DAGC-V2	0/12	1.000	0.900	0.991
CIFAR-10 / 0.1	No alignment	0/12	1.000	0.900	0.991
CIFAR-10 / 0.1	Trace replay	0/12	1.000	0.900	0.000
CIFAR-10 / 0.4	No clipping	0/12	0.000	0.000	0.000
CIFAR-10 / 0.4	Tuned fixed	0/12	1.000	0.585	0.000
CIFAR-10 / 0.4	Tuned AGC	0/12	1.000	0.232	0.000
CIFAR-10 / 0.4	Tuned AutoClip	0/12	0.987	0.355	0.000
CIFAR-10 / 0.4	Tuned median scale	0/12	0.999	0.599	0.000
CIFAR-10 / 0.4	DAGC-V2	0/12	1.000	0.899	0.990
CIFAR-10 / 0.4	No alignment	0/12	1.000	0.899	0.990
CIFAR-10 / 0.4	Trace replay	0/12	1.000	0.900	0.000

C. Legacy Exploratory Experiments

These experiments precede the new validation-isolated protocol. Each training seed selects 5,000 official training images and 2,000 official test images; test scores were available during earlier method selection. The CNN is the same SmallCNN. Training uses 15 epochs, 300 updates, constant LR 0.8, batch 256, SGD momentum 0.9, and weight decay 10^{-4}. Calibration seeds 800–802 construct the mean replay trace and select a fixed threshold from $\{0.05, 0.1, 0.2, 0.3, 0.5\}$ by matching mean clipping intensity, not accuracy. That criterion chooses 0.2. Evaluation seeds are 900–907. The new campaign instead tunes fixed clipping for validation accuracy.

Table 6. Legacy mechanism controls, eight paired seeds. All intervals are recomputed Student-t 95% intervals, replacing the original normal approximation. Δ is DAGC minus the listed control, in percentage points.

Policy	Accuracy (%)	Δ	Paired 95% interval
DAGC-V2	86.79 ± 0.66	+0.00	[+0.00, +0.00]
No alignment	86.63 ± 0.93	+0.16	[-0.33, +0.66]
No exposure	81.33 ± 1.24	+5.47	[+4.04, +6.90]
Zero controller gain	80.74 ± 1.04	+6.05	[+4.92, +7.18]
Intensity-matched fixed	85.61 ± 0.93	+1.18	[+0.62, +1.74]
Trace replay	86.58 ± 0.56	+0.21	[-0.43, +0.86]
AutoClip (10th percentile)	79.88 ± 1.74	+6.92	[+5.39, +8.45]
Rate tracking	75.21 ± 1.89	+11.59	[+9.62, +13.56]

"Zero controller gain" sets $\gamma = 0$ but retains projection onto moving norm-dependent bounds. It therefore does not implement a truly fixed threshold. The older label "frozen threshold" obscured that distinction. "No exposure" sets $r = 0$; no alignment sets $w = 0$. AutoClip uses its tenth percentile, without a tuning search. The rate-tracking control reverses the exposure sign and removes the direction term, giving $c^+ = c \exp\{0.05 \tanh[0.3(E - 0.1)]\}$ without rolling-median bounds and with the same initial threshold. It is an isolated sign-control experiment, not a replication of a private federated algorithm. These untuned configurations do not establish method-wide superiority over those algorithm families.

Table 7. Legacy learning-rate perturbations, eight paired seeds 1000–1007. DAGC-minus-control accuracy differences in percentage points.

Perturbation	Comparator	Difference	Paired 95% interval
Drop	No alignment	+0.21	[-0.21, +0.64]
Drop	Trace replay	+0.01	[-0.51, +0.52]
Pulse	No alignment	-0.02	[-0.54, +0.50]
Pulse	Trace replay	-0.06	[-0.71, +0.59]

The pulse changes LR from 0.8 to 1.6 at zero-based step 100 and back to 0.8 at step 160. The drop changes LR from 0.8 to 0.2 at step 100 and keeps it there. The replay remains the unperturbed calibration trace. Neither condition recalibrates or resets the optimizer.

Legacy comparisons labeled ZClip or AdaGC are not used as evidence here: the correspondence of their local implementations and modified warmup to the authors' algorithms has not been established. Their raw artifacts remain in the project history, but calling those settings "published defaults" would not be justified. The present baseline claims are limited to the explicitly defined, calibrated clipping rules in the new protocol.

Table 8. Legacy development sweep, three seeds (200–202) per gain/reference combination. Gains are not pooled as independent replicates. Intervals reflect only within-setting seed variation and are descriptive, not selection-adjusted.

Gain γ	Reference τ	Accuracy (%), 95% interval	Exposure	Intensity
0.05	0.10	86.83 ± 3.50	1.000	0.799
0.05	0.20	86.20 ± 2.69	1.000	0.779
0.05	0.35	86.08 ± 2.59	1.000	0.749
0.05	0.50	85.87 ± 3.39	1.000	0.716
0.05	0.70	85.85 ± 4.00	0.999	0.633
0.10	0.10	86.52 ± 3.73	1.000	0.850
0.10	0.20	86.47 ± 5.54	1.000	0.840
0.10	0.35	86.53 ± 2.76	1.000	0.827
0.10	0.50	86.12 ± 2.87	1.000	0.801
0.10	0.70	86.62 ± 2.08	1.000	0.762

C.1. Audited plots of the earlier V2 experiments

The following plots preserve the earlier evidence without mixing it with the completed confirmation study. The benchmark campaigns used 5,000 training and 2,000 test images, 15 epochs, and eight evaluation seeds per condition. Method development had already consulted the official test distribution; fresh seeds do not remove that historical selection limitation. Figures below use audited records and seed-level Student-t intervals. Their values must not be pooled with the full-data, validation-calibrated confirmation outcomes.




Figure 3. Earlier exploratory V2 benchmarks on four dataset/model/LR conditions. The panels preserve recorded local gains and no-clipping failures; they are not independent confirmation of an advantage over tuned baselines. The new study uses different data sizes, schedules and calibration budgets and finds DAGC inferior to tuned fixed clipping in all three conditions.




Figure 4. Earlier mechanism controls, eight paired seeds. The intensity-matched fixed comparator was selected by calibration clipping intensity, whereas the new fixed baseline was selected by validation accuracy. The earlier paired intervals do not establish an incremental alignment or online-feedback benefit over replay. Zero gain retains moving bounds.




Figure 5. Earlier V2 mechanism trajectories: applied threshold, clipping intensity and gradient alignment, aggregated over eight paired seeds. Bands show across-seed standard deviation, not confidence intervals. The curves illustrate threshold profiles and controller activity; similarity or apparent reversal alone does not establish predictive information or causal accuracy benefit. Compare with the completed confirmation trajectories in Figure 2, where lower-bound occupancy and alignment masking are supported by a separate full-trace audit.

Together, these historical plots explain the progression from promising small-subset observations to a stronger comparison with tuned clipping and calibration replay. The confirmation results constrain the original mechanism interpretation rather than invalidate the recorded exploratory measurements. Neither campaign proves that modifying only the lower bound would improve accuracy; that intervention has not been tested here.

D. Completed Screening Protocol and Negative Gate

This separate screening campaign must not be pooled with the ResNet-20 confirmation study. It used ResNet-18 for CIFAR-10, two screening seeds, 20 epochs, and validation evaluation. Training/validation sizes were 55,000/5,000 for FashionMNIST and 45,000/5,000 for CIFAR-10, split seed 1729. The SGD learning-rate grids were $\{0.05, 0.2, 0.4, 0.8\}$ for FashionMNIST and $\{0.05, 0.1, 0.2, 0.4, 0.8\}$ for CIFAR-10; the AdamW grid was $\{0.0003, 0.001, 0.003, 0.01\}$. Each learning rate included no clipping and fixed thresholds $\{0.1, 0.3, 1, 3, 10\}$.

Table 9. Completed screening outcomes. These are validation screening runs, not independent confirmation of DAGC. Adverse events are counts across runs.

Family	Runs	Full budget	Early stops	Adverse events
FashionMNIST / SmallCNN / SGD	48	46	2	14
CIFAR-10 / ResNet-18 / SGD	60	60	0	0
CIFAR-10 / ResNet-18 / AdamW	48	48	0	0

The frozen adverse-event label included a loss spike after step 50 above $\max(5, 2.5 \,\text{previous loss EMA})$, nonfinite loss/gradient/update, or loss above 100. Future labels covered steps 1–20; unknown negative tails were censored and observed terminal positives were retained. Labels were constructed before every-fifth-step subsampling. Base predictors included progress, learning rate, loss and its slope, gradient/update norms, alignment, and optimizer-state proxies. Added history features were exposure EMA, duty cycle, switching rate, burst age, time since transition, and intensity. Grouped evaluation held out seeds, complete configurations, or families; individual steps were never randomly split across training and evaluation.

G1 required at least ten informative runs in every grouped analysis, a mean AUPRC increment of at least 0.01, a bootstrap lower bound above zero, and positive mean increments in all three families. Only two runs were evaluable: FashionMNIST, LR 0.8, fixed threshold 3, seeds 0 and 1. The exploratory seed-held-out interval was $[-0.002269, 0.002196]$; the configuration-held-out interval was $[-0.061966, -0.001883]$. Neither can justify population-wide inference with two screening seeds. Withholding FashionMNIST left no positive training labels; withholding either CIFAR family left no positive evaluation labels, preventing the required family-held-out comparison.

Event-count robustness used on/off margins $\{0.02, 0.05, 0.1\}$ and dwell values $\{1, 3, 5\}$. For runs with median count at least two, the relative range $(\max - \min)/\text{median}$ had to be at most 0.5. Only 27/63 met this criterion; the campaign required at least 75%. Thresholds and labels were not revised retrospectively to make the gate pass.

The two early stops were FashionMNIST at LR 0.8, seed 0: no clipping stopped after 10 steps (loss 2605.40), and threshold 10 after 12 steps (loss 160.40). Their outcomes remain in the screening map at zero accuracy. Runs with finite chance-level accuracy retain their observed values. There were no process errors; maintenance interruptions were not counted as scientific failures.




Figure 6. Complete validation screening map, averaged over two seeds per configuration; instability stops contribute zero accuracy. The map describes screening behavior and does not replace paired confirmation.

The accompanying `evidence/` directory contains all 156 run summaries, the G1 report, the verification record, and the frozen screening protocol. The screening source is `develop/lyx` commit `bbc9214`. The separate confirmation study was completed in `develop/lyx1` commit `ede9c4d`: all 117 calibration and 288 confirmation outcomes are included in the compact audited export at `results/lyx1/evidence/`. The completed confirmation results and historical screening are integrated on `develop/yzs`. The screening G1 failure remains a result of that separate campaign and does not imply that confirmation is still pending. Code and public records are available at `https://github.com/alexsongyzs-dotcom/Dynamics_Aware_Gradient_Clipping/tree/develop/yzs`.

E. Original V1 Benchmarks and Additional Exploratory Figures

The initial A3 and A4 studies used V1 with initial threshold 1.0; they must not be presented as V2 evaluations. A3 has five seeds per variant and A4 has five seeds per policy in each of eight dataset/model/optimizer settings. V1 does not uniformly outperform the no-clipping baseline. Their raw tables lack explicit failure flags, so the figures report the recorded scores rather than asserting that all runs were failure-free. Historical normal-approximation error bars are replaced here with Student-t intervals. Complete audit records and source hashes accompany this manuscript in `audit_20261010/`.




Figure 7. Original V1 ablations, five seeds per variant. Zero gain retains moving bounds; it is distinct from fixed global clipping.




Figure 8. All eight original A4 settings, five seeds per policy. Error bars are Student-t 95% intervals and scores are exploratory.




Figure 9. Development reference sweep stratified by controller gain. Each point has three seeds; gains are not pooled. Realized exposure differs from the reference and cannot be interpreted as target-rate tracking.




Figure 10. Exploratory learning-rate perturbations, eight paired seeds. V2-minus-replay intervals span zero; nonsignificance is not equivalence.

Single-seed smoke runs and high-learning-rate pilot selection are retained as development artifacts, not replication evidence. The unstable-band tables include legacy comparator implementations whose fidelity has not been verified; they are not used to establish superiority over published ZClip or AdaGC.

F. Mathematical Mechanism: Exact Results and Their Limits

This appendix separates implementation-level facts from conditional statements about the value of feedback. None establishes unconditional test-accuracy superiority of DAGC or its alignment term. In particular, a theorem about an optimal feedback policy is not a theorem that DAGC realizes that policy.

F.1. Exposure feedback with exponential smoothing

Use the stationary, exogenous norm distribution of Section 3, with inactive bounds and no alignment term. Define $x_t = \log c_t$ and $q(x) = 1 - F(e^x)$. The deterministic mean-field recursion is

$$E_t = \beta E_{t-1} + (1-\beta)q(x_t), \tag{7}$$

$$x_{t+1} = x_t + \gamma \tanh[r(\tau - E_t)]. \tag{8}$$

Proposition 1. *Suppose $0 \le \beta < 1$, $\gamma r > 0$, and an interior fixed point $c_* > 0$ satisfies $1 - F(c_*) = \tau$ and $f(c_*) > 0$. The mean-field fixed point is linearly unstable.*

Proof. Write $s = c_* f(c_*) > 0$ and $k = \gamma r(1-\beta)s > 0$. For the state (x_t, E_{t-1}), the Jacobian at the fixed point is

$$J = \begin{pmatrix} 1+k & -\gamma r \beta \\ -(1-\beta)s & \beta \end{pmatrix}. \tag{9}$$

Its characteristic polynomial is $p(\lambda) = \lambda^2 - (1+\beta+k)\lambda + \beta$. Since $p(1) = -k < 0$ and $p(\lambda) \to +\infty$ as $\lambda \to +\infty$, it has a real root greater than one. □

The positive eigenvalue exceeding one proves local instability of this mean-field equilibrium only. Moving bounds, alignment, and the evolving training distribution are excluded assumptions, not small perturbations whose effects have been proved negligible.

F.2. What the direction penalty provably changes

Proposition 2 (One-step monotonicity and saturation)**.** *Compare two controller updates from the same state c, E, A, with the same positive bounds $L \le U$, gains $\gamma \ge 0$, $w \ge 0$, and reference signal $b = r(\tau - E)$. Let*

$$c^{(0)} = \Pi_{[L,U]}\big(c \exp[\gamma \tanh b]\big), \tag{10}$$

$$c^{(A)} = \Pi_{[L,U]}\big(c \exp[\gamma \tanh(b - wz)]\big), \quad z = \max(0, -A). \tag{11}$$

Then

$$0 \le \log c^{(0)} - \log c^{(A)} \le \gamma w z. \tag{12}$$

They are equal when $z = 0$, or when both proposals saturate at the same bound. If $\gamma w z > 0$ and both proposals lie strictly inside the bounds, $c^{(A)} < c^{(0)}$.

Proof. In log coordinates, projection is the monotone, 1-Lipschitz map $P(x) = \min(\log U, \max(\log L, x))$. The unprojected difference is $\gamma[\tanh b - \tanh(b - wz)]$. Monotonicity and the derivative bound $0 < \tanh'(x) \le 1$ place it in $[0, \gamma w z]$; applying P preserves order and cannot increase the difference. Strictness holds without projection saturation because $\tanh$ is strictly increasing. □

This result concerns the next threshold at a shared state. It does not order the full trajectories after the two policies change their gradients, exposures, and bounds. A negative instantaneous alignment is also not sufficient for activation: the implemented penalty uses the smoothed state A.

Proposition 3 (Inactive direction term gives identical training)**.** *Start full DAGC and its no-alignment variant with identical model, optimizer, controller, and random-stream states. If the full run has $A_t \ge 0$ at every controller update, their thresholds, model states, and losses are identical at every step.*

Proof. At the initial shared state the direction penalty is zero. Both policies use the same current threshold and sample, hence the same raw and clipped gradients. Their exposure, norm history, moving bounds, and optimizer updates are identical, giving the same next state. Induction repeats this argument; the hypothesis makes the full policy's direction penalty zero at each step. □

Thus no strictly positive directional benefit can hold uniformly over all training problems. Merely observing a nonzero penalty establishes intervention, not improved loss or generalization.

F.3. Exact replay equivalence and its scope

Proposition 4 (Replay of a run's own applied thresholds)**.** *Consider any deterministic execution conditional on its initial state and complete random stream, including minibatches and augmentation. Save the thresholds actually applied by a feedback run. A replay run using that exact step-indexed trace, the same initial model/optimizer state, and the same random stream has identical raw gradients, clipped gradients, optimizer states, parameters, and evaluations at all steps.*

Proof. At step zero both executions have the same parameters and training sample, so their raw gradients agree. The replayed applied threshold makes clipping identical. The deterministic optimizer update, including coupled weight decay and momentum, then produces identical next states. Repeat by induction. The replay need not reconstruct controller states; it only reproduces its applied thresholds, and its diagnostics must not alter the training random stream. □

This oracle trace comes from the very run being reproduced and is not our independent-calibration comparator. The proposition therefore neither proves nor disproves a benefit over calibration-trace replay. It does prove that a successful feedback trajectory can be reproduced by a schedule when the schedule contains the same realized decisions. In a problem where feedback produces the same trace for every seed, independent replay is also identical; universal strict dominance of feedback over replay is consequently impossible. Replay still responds to the current gradient norm through its clipping coefficient; it is not a fixed learning-rate multiplier.

F.4. When pre-gradient information can strictly help

We now give a sufficient-condition analysis that respects causal threshold selection. It compares policies at a common random checkpoint, not policies whose earlier training has already produced different states. Let the objective be $f(\theta) = \kappa\|\theta\|^2/2$, $\kappa > 0$. Let v denote the previous momentum buffer, $\mu \in [0, 1)$, and $\eta > 0$ the shared step size. Set weight decay to zero in this model. A policy chooses a threshold c from $[l, u]$, $0 < l < u$, using information $\mathcal{F}$ available before the next stochastic gradient G is drawn. Assume $\|G\| > u$ almost surely, so every admissible policy actively clips. Write $U = G/\|G\|$, and suppose all second moments needed below are finite. Then the actual momentum update is

$$\theta^+ = \theta - \eta(\mu v + cU), \qquad \|U\| = 1. \tag{13}$$

Define the scalar conditional prediction

$$H_{\mathcal{F}} = \mathbb{E}[\langle \theta/\eta - \mu v, U\rangle \mid \mathcal{F}]. \tag{14}$$

The random state and the future gradient have the same joint distribution for every policy in this one-step comparison. Policies may change c, but may not change that checkpoint distribution or use the future G to choose it.

Proposition 5 (Optimal causal threshold and approximation cost)**.** *In this model the optimal $\mathcal{F}$-measurable threshold is $c^*_{\mathcal{F}} = \Pi_{[l,u]} H_{\mathcal{F}}$. If $l < H_{\mathcal{F}} < u$ almost surely, any admissible feedback rule c_D satisfies*

$$\mathbb{E}f(\theta^+_D) - \mathbb{E}f(\theta^+_*) = \frac{\kappa\eta^2}{2}\mathbb{E}(c_D - H_{\mathcal{F}})^2. \tag{15}$$

Without the interior assumption, the difference is at least $\kappa\eta^2\mathbb{E}(c_D - c^*_{\mathcal{F}})^2/2$.

Proof. Expanding the squared norm gives

$$f(\theta^+) = \frac{\kappa}{2}\|\theta - \eta\mu v\|^2 + \frac{\kappa\eta^2}{2}c^2 - \kappa\eta^2 c\langle \theta/\eta - \mu v, U\rangle. \tag{16}$$

Take conditional expectations and use measurability of c. The terms depending on the chosen threshold become $\kappa\eta^2[(c - H_{\mathcal{F}})^2 - H_{\mathcal{F}}^2]/2$. Pointwise minimization over $[l, u]$ yields projection. In the interior the optimal squared term vanishes, proving Eq. (15). For a projected optimum, the projection inequality $(c_D - c^*)(c^* - H_{\mathcal{F}}) \geq 0$ yields the stated lower bound after expanding the difference of squares. □

Proposition 6 (Exact benefit over a predetermined threshold)**.** *Under the interior assumptions above, the best constant threshold at that step is $\bar{c} = \mathbb{E}H_{\mathcal{F}}$. Its advantage relative to any admissible causal rule c_D is exactly*

$$\mathbb{E}f(\theta_{\bar{c}}^+) - \mathbb{E}f(\theta_D^+) = \frac{\kappa\eta^2}{2}\left[\mathrm{Var}(H_{\mathcal{F}}) - \mathbb{E}(c_D - H_{\mathcal{F}})^2\right]. \tag{17}$$

Hence the feedback rule strictly improves expected one-step loss if and only if its squared approximation error is smaller than $\mathrm{Var}(H_{\mathcal{F}})$.

Proof. A constant policy minimizes $\mathbb{E}(c - H_{\mathcal{F}})^2$ at $c = \mathbb{E}H_{\mathcal{F}}$, which is admissible because $H_{\mathcal{F}} \in (l, u)$ almost surely. Its minimum value is $\mathrm{Var}(H_{\mathcal{F}})$. Subtract the two risks using Eq. (15). □

A calibration-generated replay value is constant across new runs at a fixed step, conditional on the independent calibration archive. The result applies to such a common-state, one-step comparison if its other assumptions hold. It does not apply directly to complete DAGC/replay runs with different states, moving bounds, or intermittently inactive clipping.

F.5. Exact value of additional directional information

Proposition 7 (Information gain versus policy error)**.** *Let $\mathcal{F}_0 \subseteq \mathcal{F}_1$ be two pre-gradient information sets; the latter may add stored alignment history. Define H_j by Eq. (14) using $\mathcal{F}_j$, and assume $l < H_j < u$ almost surely for $j = 0, 1$. The difference between the optimal policies is*

$$\mathbb{E}f(\theta_{H_0}^+) - \mathbb{E}f(\theta_{H_1}^+) = \frac{\kappa\eta^2}{2}\mathbb{E}(H_1 - H_0)^2. \tag{18}$$

For actual policies c_0, c_1 measurable with respect to their respective information sets, the exact difference is

$$\mathbb{E}f(\theta_{c_0}^+) - \mathbb{E}f(\theta_{c_1}^+) \tag{19}$$

$$= \frac{\kappa\eta^2}{2}\left[\mathbb{E}(H_1 - H_0)^2 + \mathbb{E}(c_0 - H_0)^2 - \mathbb{E}(c_1 - H_1)^2\right]. \tag{20}$$

Proof. The tower property gives $\mathbb{E}(H_1 \mid \mathcal{F}_0) = H_0$. Since H_0 and c_0 are $\mathcal{F}_0$-measurable, $\mathbb{E}[(c_0 - H_0)(H_1 - H_0)] = 0$. Thus $\mathbb{E}(c_0 - H_1)^2 = \mathbb{E}(c_0 - H_0)^2 + \mathbb{E}(H_1 - H_0)^2$. Use the expanded risk conditional on $\mathcal{F}_1$ and subtract the two policies. Taking $c_j = H_j$ proves Eq. (18). □

Additional alignment information helps the ideal policy strictly only if it changes the conditional prediction on a set of positive probability. Even then a particular direction penalty can lose that benefit through policy approximation error. Its sign and coefficient cannot be justified by the mere availability of directional information.

F.6. Why threshold tightening alone is not a proof of improvement

Set $f(\theta) = \theta^2/2$, $\theta = 1$, $v = 0$, $U = G = 1$. Both $c_h = 0.8$ and $c_l = 0.4$ actively clip. At $\eta = 0.1$, their next losses are 0.4232 and 0.4608: tightening increases loss by 0.0376. At $\eta = 3$, losses are 0.98 and 0.02: tightening decreases loss by 0.96. A negative stored alignment does not identify which step-size regime holds. These one-step examples refute universal benefit from tightening; they are not complete DAGC training trajectories.

What remains unproved for DAGC. DAGC has not been shown to predict $H_{\mathcal{F}}$ accurately enough, to obtain incremental information from alignment, or to satisfy this model's assumptions throughout training. G1 estimates a different risk target. Consequently, these conditional proofs explain when feedback can help; they do not establish DAGC's empirical incremental benefit or generalization. Paired replay, median, no-alignment, and bound-only controls remain needed.