Dynamics-Aware Gradient Clipping: Separating Feedback from Threshold Scheduling

Anonymous Author(s) [1]

Abstract

Adaptive gradient clipping can improve a training run without demonstrating that its particular feedback signals are useful. We study this distinction for Dynamics-Aware Gradient Clipping (DAGC), a bounded global-threshold controller driven by clipping exposure and consecutive-gradient alignment. Its exposure term tightens clipping when clipping is already frequent. We show that an interior target-exposure equilibrium is unstable in a stationary mean-field model, even with exponential smoothing: the rule reinforces clipping rather than tracking a target rate. This motivates controls that separate exposure and alignment feedback from historical gradient scale and a predetermined threshold schedule. We retain earlier small-subset experiments as exploratory evidence, correct their data-split and uncertainty reporting, and specify an ongoing validation-isolated study on FashionMNIST and CIFAR-10 with three conditions, four equally budgeted baseline searches, and twelve paired confirmation seeds per policy. A separate 156-run validation screening did not pass its prespecified risk-prediction gate: only two runs supported within-run predictive comparison and event-definition robustness was 42.86%. The confirmation analysis is pending completion of the frozen experiment. The study distinguishes useful threshold adaptation from evidence for the specific information that drives it, without claiming convergence of the coupled neural-network training dynamics.

1. Introduction

Gradient clipping limits the contribution of a large gradient to an optimizer update (Pascanu et al., 2013). A fixed threshold is simple but introduces a scale-sensitive hyperparameter. Adaptive rules can instead derive a threshold from gradient history or parameter magnitude (Seetharaman et al., 2020; Brock et al., 2021). When an adaptive method succeeds, however, its accuracy alone does not establish why: a useful threshold profile, a smaller effective step size, and informative feedback can produce similar outcomes.

We examine that ambiguity in Dynamics-Aware Gradient Clipping (DAGC). The controller uses the recent frequency of clipping and the alignment of consecutive raw gradients. Its first version, V1, allowed exposure alone to increase the threshold but not decrease it. V2 replaces that one-sided term with a term that becomes negative above a reference exposure. This makes sustained clipping more restrictive. It also gives the feedback the opposite sign to a clipping-rate tracker: lowering a threshold makes further clipping more likely.

This distinction changes both the interpretation and the experiment needed to support the method. A comparison with an arbitrary fixed threshold cannot establish that exposure or alignment provides useful information beyond the gradient scale. Removing the alignment term tests its necessity. A lagged median rule tests whether magnitude information is sufficient. Replaying a threshold trace constructed on separate calibration runs tests the incremental value of adapting that threshold to the new training trajectory. Replay still uses the current norm to apply clipping; only its threshold is predetermined.

Our contribution is an analysis and controlled evaluation of this concrete controller. First, we derive its local positive-feedback behavior with the exposure EMA included. Second, we define a reproducible comparison with validation-only parameter selection, identical paired training streams, and explicit failure accounting. Third, we preserve the earlier negative mechanism controls and report a completed, separate validation screening; transfer to longer training and a residual network on RGB images remains under evaluation. The scope is small image classifiers trained with momentum SGD; there is no claim of broad optimizer, architecture, or language-model transfer.

[1]Anonymous Institution. Correspondence to: Anonymous Author(s) <anonymous@example.com>.

Preprint. October 10, 2026.

2. Related Work

Adaptive gradient and update clipping. Fixed norm clipping was popularized for recurrent-network optimization (Pascanu et al., 2013). AutoClip derives a global threshold from historical norm percentiles (Seetharaman et al., 2020); AGC instead uses unit-wise parameter magnitude (Brock et al., 2021). ACClip uses coordinate-wise adaptation in attention models (Zhang et al., 2020c). ZClip detects norm spikes through running statistics (Kumar et al., 2025), whereas the revised AdaGC bounds tensor gradients relative to historical clipped-norm estimates (Wang et al., 2026). Group-level historical control also appears in AGGC (Li et al., 2026). These rules differ in granularity, reference scale, and treatment of anomalous gradients. DAGC uses one global threshold with exposure and consecutive-gradient alignment; its distinction must be tested against these simpler information sources, not inferred from the general novelty of an adaptive threshold.

Clippy constrains optimizer updates in multitask ranking (Tang et al., 2023). This distinction matters because raw-gradient clipping does not directly bound the parameter step after momentum or preconditioning. StableAdamW addresses underestimated second-moment states in vision-language training (Wortsman et al., 2023). Such optimizer-specific protections motivate our explicit clipping order, but their large-scale results are not experimental evidence for DAGC.

Rate feedback, quantiles, and robust estimation. Adaptive private federated clipping estimates a desired norm quantile online (Andrew et al., 2021). Quantile clipping has also been studied through robust stochastic optimization (Merad & Gaïffas, 2024) and adaptive DP-SGD convergence analysis (Shulgin & Richtárik, 2024). These analyses highlight clipping bias and the joint role of threshold and stepsize schedules. The geometric treatment of private SGD likewise shows that clipping can bias an update (Chen et al., 2020). DAGC is neither a privacy mechanism nor a quantile estimator: its excess-exposure response has the opposite sign to rate tracking. Median-gradient estimators connect some clipping methods to robust location estimation (Schaipp et al., 2025), but estimating a median gradient vector is distinct from our scalar rolling-median norm control.

Optimization theory and heavy-tailed noise. Relaxed-smoothness analyses explain why clipping can accelerate optimization (Zhang et al., 2020b;a). Stability and convergence results also cover rapidly growing subgradients and clipped momentum (Mai & Johansson, 2021). Stochastic bias can limit convergence even when clipping prevents large updates (Koloskova et al., 2023). Empirical tail-index studies (Şimşekli et al., 2019) and attention-model analysis (Zhang et al., 2020c) motivate considering non-Gaussian gradient noise. Accelerated clipping and normalized clipped momentum provide heavy-tail guarantees under stated assumptions (Gorbunov et al., 2020; Cutkosky & Mehta, 2021); newer work separates the roles of normalization and clipping (Sun et al., 2025). We neither estimate a tail index nor verify these assumptions for our networks. These results supply context, not a convergence theorem for the DAGC controller coupled to neural-network training.

Adaptation, architecture, and training scale. AdaGrad (Duchi et al., 2011) and AdaGrad-Norm (Ward et al., 2019) adapt step scales using past gradients; Adam (Kingma & Ba, 2015) adds coordinate-wise moment estimates. AdamW separates weight decay from its adaptive update (Loshchilov & Hutter, 2019), while LAMB uses layer-wise update scaling (You et al., 2020). These are alternative ways to change update magnitude rather than evidence that a specific clipping feedback signal is informative. Initialization and momentum also materially affect optimization (Glorot & Bengio, 2010; Sutskever et al., 2013). Batch normalization (Ioffe & Szegedy, 2015; Santurkar et al., 2018) and residual connections (He et al., 2016) change the training setting, so gains on a small CNN cannot automatically transfer to a residual model. Small-scale Transformer proxies reproduce selected instabilities under explicit conditions (Wortsman et al., 2024); our image experiments do not establish a corresponding language-model transfer claim.

Evidence for a mechanism. Benchmark variance (Bouthillier et al., 2021), selection bias (Cawley & Talbot, 2010), and finite hyperparameter-search budgets (Bergstra & Bengio, 2012) motivate paired seeds and validation-only selection. Freshly collected benchmark tests can change absolute scores (Recht et al., 2019); withholding a test set during the new campaign does not erase earlier exposure to it. Statistical comparisons must respect the replication unit and test assumptions (Dror et al., 2018). We distinguish descriptive legacy evidence, multiplicity-corrected confirmation (Holm, 1979), and equivalence within a stated practical margin (Lakens, 2017). This prevents a null replay comparison from being presented either as proof of superiority or as proof of equivalence.

3. Controller and Competing Explanations

Let $g_t = \nabla_\theta \ell_t(\theta_t)$ be the raw minibatch gradient, and let $n_t = \|g_t\|_2$. A positive threshold c_t gives

$$\widetilde{g}_t = \alpha_t g_t, \qquad \alpha_t = \min\{1, c_t / \max(n_t, \epsilon)\}. \tag{1}$$

We log exposure $e_t = \mathbb{1}[n_t > c_t]$, intensity $I_t = 1 - \alpha_t$, and alignment $a_t = \langle g_t, g_{t-1} \rangle / \max(n_t n_{t-1}, \epsilon)$. The first

Algorithm 1 One DAGC-V2 training step

1: Compute raw g_t, n_t, and a_t.
2: Save raw g_t for the next alignment calculation.
3: Apply clipping at the current c_t using Eq. (1).
4: Update exposure E_t, alignment A_t, and norm history.
5: Compute c_{t+1} using Eqs. (4)–(5).
6: Update momentum and parameters using $\widetilde{g}_t$.

alignment is one. The exposure and alignment states are

$$E_t = \beta E_{t-1} + (1-\beta)e_t, \tag{2}$$
$$A_t = \beta_a A_{t-1} + (1-\beta_a)a_t, \tag{3}$$

initialized at $E_{-1} = 0$ and $A_{-1} = 1$. DAGC-V2 updates

$$u_t = r(\tau - E_t) - w\max(0, -A_t), \tag{4}$$
$$c_{t+1} = \Pi_{[L_t,U_t]}(c_t \exp[\gamma \tanh(u_t)]). \tag{5}$$

Here $L_t = \max(0.1m_t, 10^{-12})$ and $U_t = \max(10m_t, 10^{-9})$, where m_t is the lower median of the last 200 raw gradient norms, including n_t. Thus these bounds affect the next step. The frozen settings are $(c_0, \gamma, \beta, \beta_a, r, w, \tau) = (0.5, 0.05, 0.9, 0.9, 0.3, 3, 0.1)$. V1 replaces $r(\tau - E_t)$ with $r(1 - E_t)$; since $E_t \in [0, 1]$, its exposure term cannot itself tighten clipping. V2 can tighten, but this change alone does not imply useful regulation.

The ordering prevents the current norm from selecting its own DAGC threshold. Clipping precedes SGD's coupled weight decay and momentum accumulation. Hence c_t bounds the clipped data gradient, not the final parameter displacement. The method stores a previous full gradient, requiring $O(d)$ additional memory, and a 200-element norm window. Its diagnostic alignment requires an $O(d)$ dot product. We do not describe it as constant-memory control.

3.1. The reference exposure is not a stable target

Consider a stationary, exogenous norm distribution with differentiable CDF F and density f. Remove the alignment term and assume the bounds are inactive. With $x_t = \log c_t$, replace the binary exposure by its conditional mean $q(x_t) = 1 - F(e^{x_t})$. The deterministic mean-field system is

$$E_t = \beta E_{t-1} + (1-\beta)q(x_t), \tag{6}$$
$$x_{t+1} = x_t + \gamma \tanh[r(\tau - E_t)]. \tag{7}$$

Proposition 1. *Suppose $0 \le \beta < 1$, $\gamma r > 0$, and an interior fixed point $c_* > 0$ satisfies $1 - F(c_*) = \tau$ and $f(c_*) > 0$. The mean-field fixed point is linearly unstable.*

Proof. Write $s = c_* f(c_*) > 0$ and $k = \gamma r(1-\beta)s > 0$. For the state (x_t, E_{t-1}), the Jacobian at the fixed point is

$$J = \begin{pmatrix} 1+k & -\gamma r\beta \\ -(1-\beta)s & \beta \end{pmatrix}. \tag{8}$$

Its characteristic polynomial is $p(\lambda) = \lambda^2 - (1+\beta+k)\lambda + \beta$. Since $p(1) = -k < 0$ and $p(\lambda) \to +\infty$ as $\lambda \to +\infty$, it has a real root greater than one. □

The result includes exposure smoothing; an EMA does not reverse the feedback sign. It does not prove instability of neural-network training: the gradient norm distribution changes with the parameters, the bounds move, and the alignment signal can activate. It does explain why the reference τ should not be interpreted as a regulated clipping frequency. Persistent clipping can instead drive the threshold to its lower bound, where historical norm scale may dominate the resulting behavior.

3.2. What clipping can protect

For momentum SGD without weight decay, $v_t = \mu v_{t-1} + \widetilde{g}_t$. If $c_j \le C$ over k updates and $0 \le \mu < 1$, then

$$\|v_t\| \le \mu^k \|v_{t-k}\| + C\frac{1-\mu^k}{1-\mu}. \tag{9}$$

A smaller sustained threshold bounds new momentum contributions but does not remove an existing buffer. Coupled weight decay adds parameter-dependent terms. This elementary bound motivates a protection hypothesis without establishing convergence, explaining a test-accuracy improvement, or requiring exposure and alignment to be the best threshold signals.

4. Experimental Design

4.1. Questions, conditions, and data separation

The new study asks whether the frozen controller outperforms tuned fixed clipping, a tuned median-scale rule, and calibration-trace replay. Its secondary question is whether removing alignment changes the outcome. The three conditions are FashionMNIST with the existing small CNN at initial learning rate 0.8, and CIFAR-10 with ResNet-20 at 0.1 or 0.4. The latter two are designated lower and higher learning rates; we do not assume either one diverges without clipping.

FashionMNIST (Xiao et al., 2017) uses 55,000 training images and a fixed 5,000-image validation split. CIFAR-10 (Krizhevsky, 2009) uses 45,000 training and 5,000 validation images. Both splits hold out 500 images per class using seed 1729. All methods train on the same remaining examples; validation images never enter training. Only calibration runs evaluate the validation set. Confirmation runs evaluate the complete official 10,000-image test set once, after the last training epoch. They retain the same training partition, preserving the number of steps used to construct replay schedules. No test score is used to choose a new-campaign hyperparameter or checkpoint.

FashionMNIST uses two convolutional layers (32 and 64 channels), max pooling, and a 128-unit hidden classifier, with 421,642 parameters. CIFAR-10 uses the $6n$+2 residual architecture of He et al. (2016), $n = 3$, widths 16/32/64, option-A shortcuts, and batch normalization, with 269,722 parameters. The RGB model is deeper, not larger in parameter count. This is an architectural transfer test, not a reproduction of the original ResNet training recipe.

4.2. Training and calibration budget

Training uses FP32 SGD with momentum 0.9, batch size 256, and no dropped last batch. FashionMNIST runs for 30 epochs with weight decay 10^{-4}; CIFAR-10 runs for 60 epochs with weight decay 5×10^{-4}. A cosine schedule decreases the learning rate to 1% of its initial value. CIFAR-10 uses random padded crops and horizontal flips; FashionMNIST uses normalization only. All settings are fixed across clipping policies within a condition.

Fixed clipping, AGC, AutoClip, and the median rule each receive three candidates and three calibration seeds (2100–2102): nine runs per policy per condition. Their grids are, respectively, $\{0.05, 0.5, 5\}$, $\{0.005, 0.03, 0.18\}$, percentiles $\{1, 10, 50\}$, and $\{0.025, 0.1, 0.4\}$. The winner maximizes mean final validation accuracy, with grid order breaking exact ties. These equal finite budgets do not constitute exhaustive tuning. DAGC retains the setting selected during earlier development, so its total historical tuning budget is not matched to the new baselines.

AGC clips every parameter, grouping matrix and convolution weights by output unit and treating vectors as a single unit, with parameter-norm floor 10^{-3}. AutoClip takes the stated percentile of all raw norms through the current step, following its authors' convention. The median rule clips at $\lambda \operatorname{median}(n_{t-200}, \ldots, n_{t-1})$, using available history and initial threshold 0.5. It is causal and uses the same lower-median convention as DAGC. The no-alignment variant sets $w = 0$ without retuning. Replay averages the thresholds actually applied in three full DAGC calibration runs and applies this fixed, step-indexed schedule in confirmation. All eight policies, including no clipping, share a complete training budget.

4.3. Pairing, failures, and inference

Confirmation uses twelve seeds, 3100–3111. Within a seed, initial weights, minibatch order, and augmentations are identical across policies. Private random generators isolate the input stream from diagnostics and controller state. Deterministic CUDA operations are enabled and TF32 is disabled. Epoch checkpoints include model, optimizer, controller, previous raw gradient, and logs; a test verifies that resumed and uninterrupted runs agree exactly. Configuration and source checksums reject stale results.

A run stops on nonfinite loss or gradient norm, or loss above 10^6. A nonfinite final evaluation also fails. Failed runs receive accuracy zero and remain in all aggregates; finite chance-level runs retain their observed score. We do not choose the best epoch, discard failures, or rerun unfavorable seeds. The final audit checks all 117 calibration and 288 confirmation outcomes.

We report Student-t 95% intervals over seeds, including paired intervals for accuracy differences. The primary family comprises DAGC versus fixed, median, and replay in all three conditions: nine two-sided exact sign-flip tests with Holm correction. Sign flipping assumes exchangeability under the null; the t intervals assume the seed-level mean is adequately approximated by that model. Neither addresses uncertainty from sampling a new dataset. A broad superiority claim requires a positive effect and corrected significance in all nine comparisons. Secondary comparisons are descriptive.

A prespecified ± 0.5 percentage-point margin supplies an additional within-comparison equivalence check: the paired 90% interval must lie entirely inside that range. This is not a familywise equivalence claim. Nonsignificance alone is not evidence of equivalence. The original eight-seed plan was amended to twelve during calibration, before any confirmation runs: with eight seeds, the minimum two-sided sign-flip $p = 2/256$ cannot pass the first nine-test Holm threshold $0.05/9$. The audit preserves this amendment and all identical calibration results carried forward from the first execution.

5. Results

The fixed campaign is running. Numerical confirmation results will be inserted only after its completeness and identity audits pass.

5.1. Earlier exploratory evidence and corrected interpretation

The earlier 15-epoch, 5,000-training/2,000-test experiments used different training seeds for development and evaluation, but sampled from the same official test set for both stages. We therefore classify them as exploratory, not independent data-held-out confirmation. Their positive comparisons to fixed clipping motivated the present study; they cannot substitute for it.

Figure 1 retains all exploratory benchmark conditions, including no-clipping and failed outcomes. Figures 2 and 3 show paired mechanism effects and observed behavior. The most discriminating legacy experiment already limited the mechanism claim. Over eight paired seeds, DAGC exceeded an intensity-matched fixed rule by 1.18 points (recomputed 95% paired interval [0.62, 1.74]), but its advantage over




Figure 1. Complete exploratory V2 evaluations over eight seeds per policy. Bars are Student-t 95% intervals. Failed runs contribute zero accuracy. All four conditions and no-clipping outcomes are retained; historical test-data reuse prevents calling these clean held-out confirmation. AGC and fixed settings follow the historical protocol, not the new equally budgeted tuning.




Figure 3. Mean threshold, clipping intensity, and raw-gradient alignment over eight exploratory seeds; bands show one between-seed standard deviation. These traces describe behavior and do not identify causal signal value.

replay was 0.21 points [−0.43, 0.86]. Removing alignment changed accuracy by 0.16 points [−0.33, 0.66], whereas removing exposure cost 5.47 points [4.04, 6.90]. These results identify the effect of specified ablations on the whole training trajectory. They do not show that reversal predicts future loss deterioration or that online feedback adds value beyond replay.




Figure 2. Exploratory paired mechanism effects, eight seeds. Positive differences favor V2. Replay and no-alignment intervals include zero; the zero-gain control still retains moving bounds. Intervals are descriptive, without multiplicity correction.

Independent-seed learning-rate perturbations did not resolve the ambiguity: the DAGC-minus-replay difference was −0.06 [−0.71, 0.59] for a temporary learning-rate doubling and +0.01 [−0.51, 0.52] for a sustained decrease. The uncertainty spans effects beyond the new equivalence margin, so these legacy null results are not equivalence claims. Appendix B reports all controls and corrected intervals.

A development sweep over the reference exposure had previously pooled two gains and three seeds into six apparent replicates. We instead report each gain separately with three seeds. Realized exposure remains at least 0.999 across the grid, while intensity changes. The sweep is consistent with the positive-feedback interpretation, but its small sample and development role preclude precise claims of performance insensitivity.

5.2. Completed validation screening: the predictive gate did not pass

A separate frozen screening campaign completed 156 runs across FashionMNIST with SmallCNN/SGD (48), CIFAR-10 with ResNet-18/SGD (60), and CIFAR-10 with ResNet-18/AdamW (48). Each configuration used seeds 0 and 1, constant learning rate, batch size 128, and a 20-epoch budget. This campaign used validation scores only and compared no clipping with fixed thresholds; it did not test DAGC-V2 against the eight policies of the ongoing confirmation campaign. Of 156 outcomes, 154 completed the budget and two FashionMNIST runs met the prespecified instability stop. All failures were retained.

The predictive gate asked whether clipping-history features added future-risk information beyond a base model that already included gradient alignment. After constructing future 1–20-step event labels and sampling every fifth step, 230,573 rows remained, with only 35 positive labels from four FashionMNIST runs. Only two runs contained both classes for a within-run AUPRC comparison. Seed-held-out and configuration-held-out mean AUPRC increments were −0.000037 and −0.031925, respectively. Neither met the

required increment of 0.01 or the minimum of ten informative runs; family-held-out comparison was not evaluable. Precision–recall evaluation is appropriate to discuss class skew (Davis & Goadrich, 2006), but cannot compensate for having only two informative replication units. The two-run bootstrap intervals are exploratory and do not supply confirmatory evidence. In addition, only 27 of 63 eligible runs (42.86%) passed the frozen event-definition robustness check, below the required 75%.

The campaign therefore stopped at G1; causal branching, event-controller confirmation, and subsequent transfer stages were not executed. This is a negative result for the tested predictive gate, not a direct comparison of DAGC accuracy or an isolated test of alignment. Absence of a labeled event also did not ensure successful training: two no-clipping FashionMNIST runs at LR 0.4 finished with validation accuracy 9.54% and 10.42%, despite zero adverse-event counts. Thus the risk label failed to cover some severe finite performance degradation. Appendix C provides the frozen labels, gate thresholds, and complete run-level evidence location.

6. Discussion and Limitations

A controller can influence an optimization trajectory without the proposed feedback signal being necessary for its gains. The replay comparison removes threshold adaptation to the confirmation trajectory; the median comparison retains online magnitude information but removes exposure and alignment; and the no-alignment comparison removes only direction. Their scopes differ, so no single one is a complete mechanistic explanation. The completed risk screening additionally supplies no validated predictive or causal mechanism; its rare positive labels and sensitive event counts limit what can be inferred.

The study remains limited to two image datasets, two small architectures, one optimizer, and fixed learning-rate schedules. Sixty CIFAR epochs are longer than the legacy diagnostics but do not establish asymptotic performance or large-scale training stability. Fixed grids can miss better baseline settings. Historical FashionMNIST test exposure and unequal earlier method development remain limitations despite validation-only selection in the new campaign. Seed intervals are conditional on a fixed data split. Our analytic model freezes the norm distribution; its unstable controller equilibrium is not a theorem about the nonlinear coupled training system. Likewise, lower-bound occupancy and accuracy correlation cannot identify a causal mechanism alone.

7. Conclusion

DAGC-V2 implements positive exposure feedback, not stable target-rate tracking in the stationary mean-field model. A useful empirical claim must therefore survive comparisons with magnitude-only adaptation and a predetermined threshold schedule, in addition to tuned fixed clipping. Our protocol makes those comparisons explicit, preserves failure outcomes, and separates legacy exploration from current validation-only selection.

Impact Statement

This work examines optimization behavior in small image classifiers. It does not deploy a model or introduce a new dataset. Better-controlled evaluation can reduce wasted experiments and unsupported claims about training stability. A clipping rule is not a guarantee of reliable or safe behavior in downstream applications; broader deployment consequences depend on the model and use.

References

Andrew, G., Thakkar, O., McMahan, H. B., and Ramaswamy, S. Differentially private learning with adaptive clipping. In *Advances in Neural Information Processing Systems*, volume 34, 2021. URL https://arxiv.org/abs/1905.03871.

Bergstra, J. and Bengio, Y. Random search for hyper-parameter optimization. *Journal of Machine Learning Research*, 2012. URL https://jmlr.org/papers/v13/bergstra12a.html.

Bouthillier, X., Delaunay, P., Bronzi, M., Trofimov, A., Nichyporuk, B., Szeto, J., Sepah, N., Raff, E., Madan, K., Voleti, V., Kahou, S. E., Michalski, V., Serdyuk, D., Arbel, T., Pal, C., Varoquaux, G., and Vincent, P. Accounting for variance in machine learning benchmarks. In *Proceedings of Machine Learning and Systems*, volume 3, pp. 730–743, 2021.

Brock, A., De, S., Smith, S. L., and Simonyan, K. High-performance large-scale image recognition without normalization. In *International Conference on Machine Learning*, 2021.

Cawley, G. C. and Talbot, N. L. C. On over-fitting in model selection and subsequent selection bias in performance evaluation. *Journal of Machine Learning Research*, 2010. URL https://jmlr.org/papers/v11/cawley10a.html.

Chen, X., Wu, Z. S., and Hong, M. Understanding gradient clipping in private sgd: A geometric perspective. In *Advances in Neural Information Processing Systems*, 2020. URL https://arxiv.org/abs/2006.15429.

Cutkosky, A. and Mehta, H. High-probability bounds for non-convex stochastic optimization with heavy tails. *arXiv preprint arXiv:2106.14343*, 2021. URL https://arxiv.org/abs/2106.14343.

Davis, J. and Goadrich, M. The relationship between precision-recall and roc curves. In *International Conference on Machine Learning*, 2006. URL https://ftp.cs.wisc.edu/machine-learning/shavlik-group/davis.icml06.pdf.

Dror, R., Baumer, G., Shlomov, S., and Reichart, R. The hitchhiker's guide to testing statistical significance in natural language processing. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics*, 2018. URL https://aclanthology.org/P18-1128/.

Duchi, J., Hazan, E., and Singer, Y. Adaptive subgradient methods for online learning and stochastic optimization. *Journal of Machine Learning Research*, 2011. URL https://jmlr.org/papers/v12/duchi11a.html.

Glorot, X. and Bengio, Y. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, pp. 249–256, 2010.

Gorbunov, E., Danilova, M., and Gasnikov, A. Stochastic optimization with heavy-tailed noise via accelerated gradient clipping. In *Advances in Neural Information Processing Systems*, 2020. URL https://arxiv.org/abs/2005.10785.

He, K., Zhang, X., Ren, S., and Sun, J. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 770–778, 2016. URL https://www.cv-foundation.org/openaccess/content_cvpr_2016/html/He_Deep_Residual_Learning_CVPR_2016_paper.html.

Holm, S. A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics*, 1979. URL https://www.jstor.org/stable/4615733.

Ioffe, S. and Szegedy, C. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International Conference on Machine Learning*, pp. 448–456, 2015.

Kingma, D. P. and Ba, J. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2015.

Koloskova, A., Hendrikx, H., and Stich, S. U. Revisiting gradient clipping: Stochastic bias and tight convergence guarantees. In *International Conference on Machine Learning*, 2023.

Krizhevsky, A. Learning multiple layers of features from tiny images. Technical report, University of Toronto, 2009. URL https://www.cs.toronto.edu/~kriz/learning-features-2009-TR.pdf.

Kumar, A., Owen, L., Roy Chowdhury, N., and Güra, F. ZClip: Adaptive spike mitigation for LLM pre-training. *arXiv preprint arXiv:2504.02507*, 2025.

Lakens, D. Equivalence tests: A practical primer for t tests, correlations, and meta-analyses. *Social Psychological and Personality Science*, 2017. URL https://doi.org/10.1177/1948550617697177.

Li, Z., Wu, Y., and Chang, Y. Aggc: Adaptive group gradient clipping for stabilizing large language model training. *arXiv preprint arXiv:2601.11864*, 2026. URL https://arxiv.org/abs/2601.11864.

Loshchilov, I. and Hutter, F. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019.

Mai, V. V. and Johansson, M. Stability and convergence of stochastic gradient clipping: Beyond lipschitz continuity and smoothness. In *International Conference on Machine Learning*, 2021. URL https://proceedings.mlr.press/v139/mai21a.html.

Merad, I. and Gaïffas, S. Robust stochastic optimization via gradient quantile clipping. *Transactions on Machine Learning Research*, 2024. URL https://arxiv.org/abs/2309.17316.

Pascanu, R., Mikolov, T., and Bengio, Y. On the difficulty of training recurrent neural networks. In *International Conference on Machine Learning*, pp. 1310–1318, 2013.

Recht, B., Roelofs, R., Schmidt, L., and Shankar, V. Do imagenet classifiers generalize to imagenet? In *International Conference on Machine Learning*, 2019. URL https://proceedings.mlr.press/v97/recht19a.html.

Santurkar, S., Tsipras, D., Ilyas, A., and Madry, A. How does batch normalization help optimization? In *Advances in Neural Information Processing Systems*, 2018.

Schaipp, F., Garrigos, G., Simsekli, U., and Gower, R. Tracking the median of gradients with a stochastic proximal point method. *Transactions on Machine Learning Research*, 2025. URL https://arxiv.org/abs/2402.12828v2.

Seetharaman, P., Wichern, G., Pardo, B., and Le Roux, J. Autoclip: Adaptive gradient clipping for source separation networks. In *IEEE Workshop on Machine Learning for Signal Processing*, 2020.

Shulgin, E. and Richtárik, P. On the convergence of DP-SGD with adaptive clipping. *arXiv preprint arXiv:2412.19916*, 2024. URL https://arxiv.org/abs/2412.19916.

Şimşekli, U., Sagun, L., and Gürbüzbalaban, M. A tail-index analysis of stochastic gradient noise in deep neural networks. In *International Conference on Machine Learning*, 2019.

Sun, T., Liu, X., and Yuan, K. Revisiting gradient normalization and clipping for nonconvex sgd under heavy-tailed noise: Necessity, sufficiency, and acceleration. *Journal of Machine Learning Research*, 2025. URL https://jmlr.org/papers/v26/24-1991.html.

Sutskever, I., Martens, J., Dahl, G., and Hinton, G. On the importance of initialization and momentum in deep learning. In *International Conference on Machine Learning*, pp. 1139–1147, 2013.

Tang, J., Drori, Y., Chang, D., Sathiamoorthy, M., Gilmer, J., Wei, L., Yi, X., Hong, L., and Chi, E. H. Improving training stability for multitask ranking models in recommender systems. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, 2023.

Wang, G., Li, S., Chen, C., Zeng, J., Yang, J., Yu, D., Ma, Y., and Shen, L. AdaGC: Enhancing LLM pretraining stability via adaptive gradient clipping. *arXiv preprint arXiv:2502.11034*, 2026. URL https://arxiv.org/abs/2502.11034v4. Revised version v4; accepted at ICML 2026.

Ward, R., Wu, X., and Bottou, L. Adagrad stepsizes: Sharp convergence over nonconvex landscapes. In *International Conference on Machine Learning*, 2019. URL https://proceedings.mlr.press/v97/ward19a.html.

Wortsman, M., Dettmers, T., Zettlemoyer, L., Morcos, A., Farhadi, A., and Schmidt, L. Stable and low-precision training for large-scale vision-language models. In *Advances in Neural Information Processing Systems*, 2023.

Wortsman, M., Liu, P. J., Xiao, L., Everett, K., Alemi, A., Adlam, B., Co-Reyes, J. D., Gur, I., Kumar, A., Novak, R., Pennington, J., Sohl-Dickstein, J., Xu, K., Lee, J., Gilmer, J., and Kornblith, S. Small-scale proxies for large-scale transformer training instabilities. In *International Conference on Learning Representations*, 2024.

Xiao, H., Rasul, K., and Vollgraf, R. Fashion-MNIST: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017. URL https://arxiv.org/abs/1708.07747.

You, Y., Li, J., Reddi, S., Hseu, J., Kumar, S., Bhojanapalli, S., Song, X., Demmel, J., Keutzer, K., and Hsieh, C.-J. Large batch optimization for deep learning: Training BERT in 76 minutes. In *International Conference on Learning Representations*, 2020.

Zhang, B., Jin, J., Fang, C., and Wang, L. Improved analysis of clipping algorithms for non-convex optimization. In *Advances in Neural Information Processing Systems*, 2020a. URL https://arxiv.org/abs/2010.02519.

Zhang, J., He, T., Sra, S., and Jadbabaie, A. Why gradient clipping accelerates training: A theoretical justification for adaptivity. In *International Conference on Learning Representations*, 2020b.

Zhang, J., Karimireddy, S. P., Veit, A., Kim, S., Reddi, S., Kumar, S., and Sra, S. Why are adaptive methods good for attention models? In *Advances in Neural Information Processing Systems*, 2020c. URL https://arxiv.org/abs/1912.03194.

A. Reproducibility and Complete Calibration

The machine-readable protocol fixes conditions, hyperparameter grids, calibration and confirmation seeds, and comparison families before confirmation. The source/configuration digest is checked when a run is resumed or reused. The evidence export verifies every run identity, exact confirmation seed sets, completed epoch continuity, and failure accounting. It retains per-epoch training metrics, final evaluation scores, 100-bin diagnostic traces, full replay schedules, and checksums for the full-resolution traces archived with the raw experiment. Tables and figures are generated from the exported seed-level records; summary values are not entered by hand.

Training inputs are cached on the GPU. CIFAR crop offsets and flips use a private generator keyed by training seed and epoch; a separate generator controls the permutation of training examples. No dropout or other random model operation is used. Model initialization uses the training seed. Exact resume tests cover optimizer state, controller state, prior gradient, metrics, and diagnostic traces. The numerical epsilon in scalar clipping is 10^{-12}; AGC's parameter floor is 10^{-3}. CUDA determinism is requested explicitly.

Table 1. Shared implementation details.

Item	FashionMNIST	CIFAR-10
Training / validation / test	55,000 / 5,000 / 10,000	45,000 / 5,000 / 10,000
Epochs / updates	30 / 6,450	60 / 10,560
Model / parameters	SmallCNN / 421,642	ResNet-20 / 269,722
Batch / SGD momentum	256 / 0.9	256 / 0.9
Weight decay	10^{-4}	5×10^{-4}
Mean	0.286	(0.4914, 0.4822, 0.4465)
Standard deviation	0.353	(0.2470, 0.2435, 0.2616)
Augmentation	None	Padded crop and horizontal flip
Evaluation frequency	Final epoch only	Final epoch only

B. Legacy Exploratory Experiments

These experiments precede the new validation-isolated protocol. Each training seed selects 5,000 official training images and 2,000 official test images; test scores were available during earlier method selection. The CNN is the same SmallCNN. Training uses 15 epochs, 300 updates, constant LR 0.8, batch 256, SGD momentum 0.9, and weight decay 10^{-4}. Calibration seeds 800–802 construct the mean replay trace and select a fixed threshold from $\{0.05, 0.1, 0.2, 0.3, 0.5\}$ by matching mean clipping intensity, not accuracy. That criterion chooses 0.2. Evaluation seeds are 900–907. The new campaign instead tunes fixed clipping for validation accuracy.

Table 2. Legacy mechanism controls, eight paired seeds. All intervals are recomputed Student-t 95% intervals, replacing the original normal approximation. Δ is DAGC minus the listed control, in percentage points.

Policy	Accuracy (%)	Δ	Paired 95% interval
DAGC-V2	86.79 ± 0.66	+0.00	[+0.00, +0.00]
No alignment	86.63 ± 0.93	+0.16	[-0.33, +0.66]
No exposure	81.33 ± 1.24	+5.47	[+4.04, +6.90]
Zero controller gain	80.74 ± 1.04	+6.05	[+4.92, +7.18]
Intensity-matched fixed	85.61 ± 0.93	+1.18	[+0.62, +1.74]
Trace replay	86.58 ± 0.56	+0.21	[-0.43, +0.86]
AutoClip (10th percentile)	79.88 ± 1.74	+6.92	[+5.39, +8.45]
Rate tracking	75.21 ± 1.89	+11.59	[+9.62, +13.56]

"Zero controller gain" sets $\gamma = 0$ but retains projection onto moving norm-dependent bounds. It therefore does not implement a truly fixed threshold. The older label "frozen threshold" obscured that distinction. "No exposure" sets $r = 0$; no alignment sets $w = 0$. AutoClip uses its tenth percentile, without a tuning search. The rate-tracking control reverses the exposure sign and removes the direction term, giving $c^+ = c \exp\{0.05 \tanh[0.3(E - 0.1)]\}$ without rolling-median bounds and with the same initial threshold. It is an isolated sign-control experiment, not a replication of a private federated algorithm. These untuned configurations do not establish method-wide superiority over those algorithm families.

Table 3. Legacy learning-rate perturbations, eight paired seeds 1000–1007. DAGC-minus-control accuracy differences in percentage points.

Perturbation	Comparator	Difference	Paired 95% interval
Drop	No alignment	+0.21	[-0.21, +0.64]
Drop	Trace replay	+0.01	[-0.51, +0.52]
Pulse	No alignment	-0.02	[-0.54, +0.50]
Pulse	Trace replay	-0.06	[-0.71, +0.59]

The pulse changes LR from 0.8 to 1.6 at zero-based step 100 and back to 0.8 at step 160. The drop changes LR from 0.8 to 0.2 at step 100 and keeps it there. The replay remains the unperturbed calibration trace. Neither condition recalibrates or resets the optimizer.

Table 4. Legacy development sweep, three seeds (200–202) per gain/reference combination. Gains are not pooled as independent replicates. Intervals reflect only within-setting seed variation and are descriptive, not selection-adjusted.

Gain γ	Reference τ	Accuracy (%), 95% interval	Exposure	Intensity
0.05	0.10	86.83 ± 3.50	1.000	0.799
0.05	0.20	86.20 ± 2.69	1.000	0.779
0.05	0.35	86.08 ± 2.59	1.000	0.749
0.05	0.50	85.87 ± 3.39	1.000	0.716
0.05	0.70	85.85 ± 4.00	0.999	0.633
0.10	0.10	86.52 ± 3.73	1.000	0.850
0.10	0.20	86.47 ± 5.54	1.000	0.840
0.10	0.35	86.53 ± 2.76	1.000	0.827
0.10	0.50	86.12 ± 2.87	1.000	0.801
0.10	0.70	86.62 ± 2.08	1.000	0.762

Legacy comparisons labeled ZClip or AdaGC are not used as evidence here: the correspondence of their local implementations and modified warmup to the authors' algorithms has not been established. Their raw artifacts remain in the project history, but calling those settings "published defaults" would not be justified. The present baseline claims are limited to the

explicitly defined, calibrated clipping rules in the new protocol.

C. Completed Screening Protocol and Negative Gate

This separate screening campaign must not be pooled with the ResNet-20 confirmation study. It used ResNet-18 for CIFAR-10, two screening seeds, 20 epochs, and validation evaluation. Training/validation sizes were 55,000/5,000 for FashionMNIST and 45,000/5,000 for CIFAR-10, split seed 1729. The SGD learning-rate grids were $\{0.05, 0.2, 0.4, 0.8\}$ for FashionMNIST and $\{0.05, 0.1, 0.2, 0.4, 0.8\}$ for CIFAR-10; the AdamW grid was $\{0.0003, 0.001, 0.003, 0.01\}$. Each learning rate included no clipping and fixed thresholds $\{0.1, 0.3, 1, 3, 10\}$.

Table 5. Completed screening outcomes. These are validation screening runs, not independent confirmation of DAGC. Adverse events are counts across runs.

Family	Runs	Full budget	Early stops	Adverse events
FashionMNIST / SmallCNN / SGD	48	46	2	14
CIFAR-10 / ResNet-18 / SGD	60	60	0	0
CIFAR-10 / ResNet-18 / AdamW	48	48	0	0

The frozen adverse-event label included a loss spike after step 50 above $\max(5, 2.5 \,\text{previous loss EMA})$, nonfinite loss/gradient/update, or loss above 100. Future labels covered steps 1–20; unknown negative tails were censored and observed terminal positives were retained. Labels were constructed before every-fifth-step subsampling. Base predictors included progress, learning rate, loss and its slope, gradient/update norms, alignment, and optimizer-state proxies. Added history features were exposure EMA, duty cycle, switching rate, burst age, time since transition, and intensity. Grouped evaluation held out seeds, complete configurations, or families; individual steps were never randomly split across training and evaluation.

G1 required at least ten informative runs in every grouped analysis, a mean AUPRC increment of at least 0.01, a bootstrap lower bound above zero, and positive mean increments in all three families. Only two runs were evaluable: FashionMNIST, LR 0.8, fixed threshold 3, seeds 0 and 1. The exploratory seed-held-out interval was $[-0.002269, 0.002196]$; the configuration-held-out interval was $[-0.061966, -0.001883]$. Neither can justify population-wide inference with two screening seeds. Withholding FashionMNIST left no positive training labels; withholding either CIFAR family left no positive evaluation labels, preventing the required family-held-out comparison.

Event-count robustness used on/off margins $\{0.02, 0.05, 0.1\}$ and dwell values $\{1, 3, 5\}$. For runs with median count at least two, the relative range $(\max - \min)/\text{median}$ had to be at most 0.5. Only 27/63 met this criterion; the campaign required at least 75%. Thresholds and labels were not revised retrospectively to make the gate pass.

The two early stops were FashionMNIST at LR 0.8, seed 0: no clipping stopped after 10 steps (loss 2605.40), and threshold 10 after 12 steps (loss 160.40). Their outcomes remain in the screening map at zero accuracy. Runs with finite chance-level accuracy retain their observed values. There were no process errors; maintenance interruptions were not counted as scientific failures.




Figure 4. Complete validation screening map, averaged over two seeds per configuration; instability stops contribute zero accuracy. The map describes screening behavior and does not replace paired confirmation.

The accompanying `evidence/` directory contains all 156 run summaries, the G1 report, the verification record, and the frozen screening protocol. The source is `develop/lyx` commit `bbc9214`; the ongoing confirmation draft is based on `develop/lyx1` commit `050beca`. Code and public screening records are available at https://github.com/alexsongyzs-dotcom/Dynamics_Aware_Gradient_Clipping. At this revision, no complete audited confirmation export was committed. Pending-result text is deliberately retained and is not a final study finding.

D. Original V1 Benchmarks and Additional Exploratory Figures

The initial A3 and A4 studies used V1 with initial threshold 1.0; they must not be presented as V2 evaluations. A3 has five seeds per variant and A4 has five seeds per policy in each of eight dataset/model/optimizer settings. V1 does not uniformly outperform the no-clipping baseline. Their raw tables lack explicit failure flags, so the figures report the recorded scores rather than asserting that all runs were failure-free. Historical normal-approximation error bars are replaced here with Student-t intervals. Complete audit records and source hashes accompany this manuscript in `audit_20261010/`.




Figure 5. Original V1 ablations, five seeds per variant. Zero gain retains moving bounds; it is distinct from fixed global clipping.




Figure 6. All eight original A4 settings, five seeds per policy. Error bars are Student-t 95% intervals and scores are exploratory.




Figure 7. Development reference sweep stratified by controller gain. Each point has three seeds; gains are not pooled. Realized exposure differs from the reference and cannot be interpreted as target-rate tracking.




Figure 8. Exploratory learning-rate perturbations, eight paired seeds. V2-minus-replay intervals span zero; nonsignificance is not equivalence.

Single-seed smoke runs and high-learning-rate pilot selection are retained as development artifacts, not replication evidence. The unstable-band tables include legacy comparator implementations whose fidelity has not been verified; they are not used to establish superiority over published ZClip or AdaGC.