

6-3. Heating capacity

NOTE: Values mentioned in the table are calculated based on the maximum capacity.

■ Model: AOUH18KWAH2

- TC: Total Capacity
- IP: Input Power
- Values mentioned in the table are based on the following conditions:
 - Power source of specifications: 230 V
 - Pipe length: 25 ft (7.5 m), Height difference: 0 ft (0 m). (Between outdoor unit and indoor unit.)
- 2 indoor units should be connected.
- The total ability of connected indoor unit is from 14,000 Btu/h up to 24,000 Btu/h.
- Input in the table are calculated based on the maximum indoor unit input combinations.

AOUH18KWAH2, Heating capacity												
Indoor unit connecting capacity	Outdoor temperature		Indoor temperature (°FDB)									
			60		65		70		75		78	
			TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
kBtu/h	°FDB	°FWB	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW
24	-15	-17	12.66	1.64	12.36	1.77	12.06	1.90	11.76	2.02	11.46	2.15
	-5	-7	18.32	2.30	17.88	2.48	17.45	2.67	17.01	2.85	16.58	3.03
	5	3	23.10	2.76	22.55	2.99	22.00	3.22	21.45	3.45	20.90	3.68
	14	12	23.78	2.53	23.21	2.74	22.64	2.95	22.08	3.16	21.51	3.37
	23	19	24.45	2.33	23.87	2.50	23.29	2.68	22.70	2.85	22.12	3.03
	32	28	25.13	2.08	24.53	2.24	23.93	2.40	23.33	2.57	22.73	2.73
	41	37	25.80	1.84	25.19	1.98	24.57	2.13	23.96	2.28	23.34	2.42
	47	43	26.25	1.68	25.63	1.81	25.00	1.95	24.38	2.09	23.75	2.22
	50	47	26.25	1.62	25.63	1.75	25.00	1.88	24.38	2.01	23.75	2.14
	59	50	26.25	1.41	25.63	1.52	25.00	1.64	24.38	1.75	23.75	1.86
	68	59	26.25	1.19	25.63	1.28	25.00	1.38	24.38	1.47	23.75	1.57
75	65	26.25	1.08	25.63	1.16	25.00	1.25	24.38	1.34	23.75	1.42	
22	-15	-17	12.66	1.38	12.36	1.50	12.06	1.62	11.76	1.75	11.46	1.87
	-5	-7	18.32	1.93	17.88	2.11	17.45	2.28	17.01	2.46	16.58	2.64
	5	3	23.10	2.31	22.55	2.54	22.00	2.76	21.45	2.98	20.90	3.20
	14	12	23.78	2.12	23.21	2.32	22.64	2.52	22.08	2.73	21.51	2.93
	23	19	24.45	1.96	23.87	2.12	23.29	2.29	22.70	2.46	22.12	2.63
	32	28	25.13	1.75	24.53	1.90	23.93	2.06	23.33	2.22	22.73	2.37
	41	37	25.80	1.55	25.19	1.69	24.57	1.83	23.96	1.97	23.34	2.11
	47	43	26.25	1.41	25.63	1.54	25.00	1.67	24.38	1.80	23.75	1.93
	50	47	26.25	1.36	25.63	1.48	25.00	1.61	24.38	1.73	23.75	1.86
	59	50	26.25	1.18	25.63	1.29	25.00	1.40	24.38	1.51	23.75	1.62
	68	59	26.25	1.00	25.63	1.09	25.00	1.18	24.38	1.27	23.75	1.36
75	65	26.25	0.90	25.63	0.99	25.00	1.07	24.38	1.15	23.75	1.24	
21	-15	-17	12.66	1.64	12.36	1.77	12.06	1.90	11.76	2.02	11.46	2.15
	-5	-7	18.32	2.30	17.88	2.48	17.45	2.67	17.01	2.85	16.58	3.03
	5	3	23.10	2.76	22.55	2.99	22.00	3.22	21.45	3.45	20.90	3.68
	14	12	23.78	2.53	23.21	2.74	22.64	2.95	22.08	3.16	21.51	3.37
	23	19	24.45	2.33	23.87	2.50	23.29	2.68	22.70	2.85	22.12	3.03
	32	28	25.13	2.08	24.53	2.24	23.93	2.40	23.33	2.57	22.73	2.73
	41	37	25.80	1.84	25.19	1.98	24.57	2.13	23.96	2.28	23.34	2.42
	47	43	26.25	1.68	25.63	1.81	25.00	1.95	24.38	2.09	23.75	2.22
	50	47	26.25	1.62	25.63	1.75	25.00	1.88	24.38	2.01	23.75	2.14
	59	50	26.25	1.41	25.63	1.52	25.00	1.64	24.38	1.75	23.75	1.86
	68	59	26.25	1.19	25.63	1.28	25.00	1.38	24.38	1.47	23.75	1.57
75	65	26.25	1.08	25.63	1.16	25.00	1.25	24.38	1.34	23.75	1.42	
19	-15	-17	12.66	1.64	12.36	1.77	12.06	1.90	11.76	2.02	11.46	2.15
	-5	-7	18.32	2.30	17.88	2.48	17.45	2.67	17.01	2.85	16.58	3.03
	5	3	23.10	2.76	22.55	2.99	22.00	3.22	21.45	3.45	20.90	3.68
	14	12	23.78	2.53	23.21	2.74	22.64	2.95	22.08	3.16	21.51	3.37
	23	19	24.45	2.33	23.87	2.50	23.29	2.68	22.70	2.85	22.12	3.03
	32	28	25.13	2.08	24.53	2.24	23.93	2.40	23.33	2.57	22.73	2.73
	41	37	25.80	1.84	25.19	1.98	24.57	2.13	23.96	2.28	23.34	2.42
	47	43	26.25	1.68	25.63	1.81	25.00	1.95	24.38	2.09	23.75	2.22
	50	47	26.25	1.62	25.63	1.75	25.00	1.88	24.38	2.01	23.75	2.14
	59	50	26.25	1.41	25.63	1.52	25.00	1.64	24.38	1.75	23.75	1.86
	68	59	26.25	1.19	25.63	1.28	25.00	1.38	24.38	1.47	23.75	1.57
75	65	26.25	1.08	25.63	1.16	25.00	1.25	24.38	1.34	23.75	1.42	
18	-15	-17	12.66	1.64	12.36	1.77	12.06	1.90	11.76	2.02	11.46	2.15
	-5	-7	18.32	2.30	17.88	2.48	17.45	2.67	17.01	2.85	16.58	3.03
	5	3	23.10	2.76	22.55	2.99	22.00	3.22	21.45	3.45	20.90	3.68
	14	12	23.78	2.53	23.21	2.74	22.64	2.95	22.08	3.16	21.51	3.37
	23	19	24.45	2.33	23.87	2.50	23.29	2.68	22.70	2.85	22.12	3.03
	32	28	25.13	2.08	24.53	2.24	23.93	2.40	23.33	2.57	22.73	2.73
	41	37	25.80	1.84	25.19	1.98	24.57	2.13	23.96	2.28	23.34	2.42
	47	43	26.25	1.68	25.63	1.81	25.00	1.95	24.38	2.09	23.75	2.22
	50	47	26.25	1.62	25.63	1.75	25.00	1.88	24.38	2.01	23.75	2.14
	59	50	26.25	1.41	25.63	1.52	25.00	1.64	24.38	1.75	23.75	1.86
	68	59	26.25	1.19	25.63	1.28	25.00	1.38	24.38	1.47	23.75	1.57
75	65	26.25	1.08	25.63	1.16	25.00	1.25	24.38	1.34	23.75	1.42	

FUJITSU GENERAL LIMITED

AOUH18KWAH2, Heating capacity												
Indoor unit connecting capacity	Outdoor temperature		Indoor temperature (°FDB)									
			60		65		70		75		78	
			TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
kBtu/h	°FDB	°FWB	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW
16	-15	-17	11.40	1.49	11.13	1.60	10.85	1.71	10.58	1.82	10.56	1.83
	-5	-7	16.49	2.09	16.10	2.25	15.70	2.41	15.31	2.57	15.28	2.58
	5	3	20.79	2.51	20.30	2.71	19.80	2.91	19.31	3.11	19.41	3.06
	14	12	21.40	2.30	20.89	2.48	20.38	2.66	19.87	2.84	20.29	2.69
	23	19	22.01	2.11	21.48	2.26	20.96	2.42	20.43	2.57	21.48	2.26
	32	28	22.61	1.89	22.07	2.03	21.54	2.17	21.00	2.31	21.01	2.31
	41	37	23.22	1.67	22.67	1.80	22.11	1.92	21.56	2.05	21.24	2.12
	47	43	23.63	1.53	23.06	1.64	22.50	1.76	21.94	1.88	21.38	1.99
	50	47	23.63	1.47	23.06	1.58	22.50	1.69	21.94	1.81	21.38	1.92
	59	50	23.63	1.28	23.06	1.38	22.50	1.48	21.94	1.58	21.38	1.67
	68	59	23.63	1.08	23.06	1.16	22.50	1.24	21.94	1.33	21.38	1.41
	75	65	23.63	0.98	23.06	1.05	22.50	1.13	21.94	1.20	21.38	1.28
14	-15	-17	10.74	1.26	10.49	1.36	9.99	1.57	9.98	1.57	9.72	1.67
	-5	-7	15.54	1.76	15.17	1.91	14.45	2.20	14.43	2.21	14.06	2.36
	5	3	19.73	2.05	19.26	2.24	18.22	2.66	18.32	2.62	17.85	2.80
	14	12	20.64	1.76	20.14	1.94	18.75	2.43	19.16	2.29	18.67	2.46
	23	19	21.84	1.47	21.32	1.62	19.28	2.21	20.28	1.92	19.76	2.07
	32	28	21.36	1.58	20.85	1.71	19.81	1.98	19.84	1.98	19.33	2.11
	41	37	21.60	1.47	21.08	1.59	20.35	1.76	20.05	1.83	19.54	1.94
	47	43	21.74	1.40	21.22	1.50	20.70	1.61	20.18	1.72	19.67	1.82
	50	47	21.74	1.34	21.22	1.45	20.70	1.55	20.18	1.65	19.67	1.76
	59	50	21.74	1.17	21.22	1.26	20.70	1.35	20.18	1.44	19.67	1.53
	68	59	21.74	0.99	21.22	1.06	20.70	1.14	20.18	1.21	19.67	1.29
	75	65	21.74	0.89	21.22	0.96	20.70	1.03	20.18	1.10	19.67	1.17

OUTDOOR UNIT
AOUH18-36KWAHOUTDOOR UNIT
AOUH18-36KWAH