

Model: AOUH24KWAH3

- TC: Total Capacity
- IP: Input Power
- Values mentioned in the table are based on the following conditions:
 - Power source of specifications: 230 V
 - Pipe length: 25 ft (7.5 m), Height difference: 0 ft (0 m). (Between outdoor unit and indoor unit.)
- 2 or more indoor units should be connected.
- The total ability of connected indoor unit is from 14,000 Btu/h up to 31,000 Btu/h.
- Input in the table are calculated based on the maximum indoor unit input combinations.

OUTDOOR UNIT
AOUH18-36KWAHOUTDOOR UNIT
AOUH18-36KWAH

AOUH24KWAH3, Heating capacity												
Indoor unit connecting capacity	Outdoor temperature		Indoor temperature (°FDB)									
			60		65		70		75		78	
	°FDB	°FWB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
kBtu/h			kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW
31	-15	-17	14.70	2.16	14.35	2.31	14.00	2.46	13.65	2.61	13.30	2.75
	-5	-7	20.80	2.61	20.30	2.82	19.81	3.02	19.31	3.23	18.82	3.44
	5	3	26.46	3.02	25.83	3.28	25.20	3.55	24.57	3.82	23.94	4.08
	14	12	27.77	2.77	27.10	3.01	26.44	3.26	25.78	3.51	25.12	3.75
	23	19	29.07	2.62	28.38	2.83	27.69	3.03	26.99	3.24	26.30	3.45
	32	28	30.38	2.35	29.65	2.55	28.93	2.74	28.21	2.94	27.48	3.14
	41	37	31.68	2.09	30.93	2.27	30.17	2.45	29.42	2.63	28.66	2.81
	47	43	32.55	1.92	31.78	2.09	31.00	2.26	30.23	2.43	29.45	2.60
	50	47	32.55	1.85	31.78	2.01	31.00	2.18	30.23	2.34	29.45	2.50
	59	50	32.55	1.62	31.78	1.76	31.00	1.90	30.23	2.04	29.45	2.18
30	-15	-17	14.70	2.16	14.35	2.31	14.00	2.46	13.65	2.61	13.30	2.75
	-5	-7	20.80	2.61	20.30	2.82	19.81	3.02	19.31	3.23	18.82	3.44
	5	3	26.46	3.02	25.83	3.28	25.20	3.55	24.57	3.82	23.94	4.08
	14	12	27.77	2.77	27.10	3.01	26.44	3.26	25.78	3.51	25.12	3.75
	23	19	29.07	2.62	28.38	2.83	27.69	3.03	26.99	3.24	26.30	3.45
	32	28	30.38	2.35	29.65	2.55	28.93	2.74	28.21	2.94	27.48	3.14
	41	37	31.68	2.09	30.93	2.27	30.17	2.45	29.42	2.63	28.66	2.81
	47	43	32.55	1.92	31.78	2.09	31.00	2.26	30.23	2.43	29.45	2.60
	50	47	32.55	1.85	31.78	2.01	31.00	2.18	30.23	2.34	29.45	2.50
	59	50	32.55	1.62	31.78	1.76	31.00	1.90	30.23	2.04	29.45	2.18
29	-15	-17	14.70	1.95	14.35	2.09	14.00	2.24	13.65	2.39	13.30	2.54
	-5	-7	20.80	2.34	20.30	2.55	19.81	2.76	19.31	2.97	18.82	3.17
	5	3	26.46	2.71	25.83	2.97	25.20	3.24	24.57	3.50	23.94	3.77
	14	12	27.77	2.48	27.10	2.73	26.44	2.97	25.78	3.22	25.12	3.46
	23	19	29.07	2.35	28.38	2.56	27.69	2.77	26.99	2.97	26.30	3.18
	32	28	30.38	2.10	29.65	2.30	28.93	2.50	28.21	2.70	27.48	2.90
	41	37	31.68	1.88	30.93	2.06	30.17	2.24	29.42	2.42	28.66	2.60
	47	43	32.55	1.72	31.78	1.89	31.00	2.06	30.23	2.23	29.45	2.40
	50	47	32.55	1.66	31.78	1.82	31.00	1.98	30.23	2.14	29.45	2.31
	59	50	32.55	1.45	31.78	1.59	31.00	1.73	30.23	1.87	29.45	2.01
28	-15	-17	14.70	2.16	14.35	2.31	14.00	2.46	13.65	2.61	13.30	2.75
	-5	-7	20.80	2.61	20.30	2.82	19.81	3.02	19.31	3.23	18.82	3.44
	5	3	26.46	3.02	25.83	3.28	25.20	3.55	24.57	3.82	23.94	4.08
	14	12	27.77	2.77	27.10	3.01	26.44	3.26	25.78	3.51	25.12	3.75
	23	19	29.07	2.62	28.38	2.83	27.69	3.03	26.99	3.24	26.30	3.45
	32	28	30.38	2.35	29.65	2.55	28.93	2.74	28.21	2.94	27.48	3.14
	41	37	31.68	2.09	30.93	2.27	30.17	2.45	29.42	2.63	28.66	2.81
	47	43	32.55	1.92	31.78	2.09	31.00	2.26	30.23	2.43	29.45	2.60
	50	47	32.55	1.85	31.78	2.01	31.00	2.18	30.23	2.34	29.45	2.50
	59	50	32.55	1.62	31.78	1.76	31.00	1.90	30.23	2.04	29.45	2.18
27	-15	-17	14.70	2.16	14.35	2.31	14.00	2.46	13.65	2.61	13.30	2.75
	-5	-7	20.80	2.61	20.30	2.82	19.81	3.02	19.31	3.23	18.82	3.44
	5	3	26.46	3.02	25.83	3.28	25.20	3.55	24.57	3.82	23.94	4.08
	14	12	27.77	2.77	27.10	3.01	26.44	3.26	25.78	3.51	25.12	3.75
	23	19	29.07	2.62	28.38	2.83	27.69	3.03	26.99	3.24	26.30	3.45
	32	28	30.38	2.35	29.65	2.55	28.93	2.74	28.21	2.94	27.48	3.14
	41	37	31.68	2.09	30.93	2.27	30.17	2.45	29.42	2.63	28.66	2.81
	47	43	32.55	1.92	31.78	2.09	31.00	2.26	30.23	2.43	29.45	2.60
	50	47	32.55	1.85	31.78	2.01	31.00	2.18	30.23	2.34	29.45	2.50
	59	50	32.55	1.62	31.78	1.76	31.00	1.90	30.23	2.04	29.45	2.18

AOUH24KWAH3, Heating capacity												
Indoor unit connecting capacity	Outdoor temperature		Indoor temperature (°FDB)									
			60		65		70		75		78	
			TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
kBtu/h	°FDB	°FWB	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW
18	-15	-17	12.04	1.61	11.76	1.72	11.47	1.84	11.18	1.96	11.34	1.89
	-5	-7	17.04	1.93	16.63	2.10	16.23	2.26	15.82	2.43	16.04	2.34
	5	3	21.68	2.24	21.16	2.45	20.65	2.65	20.13	2.86	20.74	2.62
	14	12	22.75	2.05	22.21	2.24	21.67	2.44	21.12	2.63	21.12	2.63
	23	19	23.82	1.94	23.25	2.10	22.68	2.27	22.12	2.43	21.51	2.61
	32	28	24.89	1.74	24.30	1.90	23.70	2.05	23.11	2.21	22.56	2.35
	41	37	25.96	1.55	25.34	1.69	24.72	1.83	24.10	1.98	23.35	2.15
	47	43	26.67	1.43	26.04	1.56	25.40	1.69	24.77	1.82	24.13	1.95
	50	47	26.67	1.37	26.04	1.50	25.40	1.63	24.77	1.75	24.13	1.88
	59	50	26.67	1.20	26.04	1.31	25.40	1.42	24.77	1.53	24.13	1.64
	68	59	26.67	1.01	26.04	1.10	25.40	1.19	24.77	1.29	24.13	1.38
	75	65	26.67	0.91	26.04	1.00	25.40	1.08	24.77	1.17	24.13	1.25
16	-15	-17	11.62	1.53	11.34	1.64	11.06	1.75	10.79	1.86	10.93	1.80
	-5	-7	16.44	1.84	16.05	2.00	15.65	2.15	15.26	2.31	15.47	2.23
	5	3	20.91	2.13	20.41	2.33	19.92	2.53	19.42	2.73	20.01	2.49
	14	12	21.94	1.95	21.42	2.14	20.90	2.32	20.38	2.51	20.38	2.51
	23	19	22.98	1.85	22.43	2.00	21.88	2.16	21.33	2.32	20.75	2.49
	32	28	24.01	1.66	23.44	1.80	22.86	1.95	22.29	2.10	21.76	2.24
	41	37	25.04	1.48	24.44	1.61	23.85	1.75	23.25	1.88	22.52	2.05
	47	43	25.73	1.36	25.11	1.48	24.50	1.61	23.89	1.74	23.28	1.86
	50	47	25.73	1.31	25.11	1.43	24.50	1.55	23.89	1.67	23.28	1.79
	59	50	25.73	1.14	25.11	1.25	24.50	1.35	23.89	1.46	23.28	1.56
	68	59	25.73	0.96	25.11	1.05	24.50	1.14	23.89	1.23	23.28	1.32
	75	65	25.73	0.87	25.11	0.95	24.50	1.03	23.89	1.11	23.28	1.19
14	-15	-17	10.95	1.15	10.69	1.26	10.03	1.52	10.17	1.47	9.91	1.57
	-5	-7	15.49	1.35	15.12	1.50	14.18	1.87	14.39	1.79	14.02	1.94
	5	3	20.04	1.40	19.56	1.59	18.05	2.20	18.60	1.97	18.13	2.17
	14	12	20.41	1.50	19.92	1.67	18.94	2.02	18.95	2.02	18.46	2.19
	23	19	20.78	1.61	20.28	1.75	19.83	1.88	19.29	2.03	18.80	2.18
	32	28	21.80	1.42	21.28	1.55	20.72	1.70	20.24	1.82	19.72	1.96
	41	37	22.55	1.30	22.02	1.43	21.61	1.52	20.94	1.67	20.41	1.79
	47	43	23.31	1.17	22.76	1.29	22.20	1.40	21.65	1.51	21.09	1.63
	50	47	23.31	1.13	22.76	1.24	22.20	1.35	21.65	1.46	21.09	1.57
	59	50	23.31	0.98	22.76	1.08	22.20	1.18	21.65	1.27	21.09	1.37
	68	59	23.31	0.83	22.76	0.91	22.20	0.99	21.65	1.07	21.09	1.15
	75	65	23.31	0.75	22.76	0.82	22.20	0.90	21.65	0.97	21.09	1.04

OUTDOOR UNIT
AOUH18-36KWAH

OUTDOOR UNIT
AOUH18-36KWAH