

Model: AOUH36KWAH4

- TC: Total Capacity
- IP: Input Power
- Values mentioned in the table are based on the following conditions:
 - Power source of specifications: 230 V
 - Pipe length: 25 ft (7.5 m), Height difference: 0 ft (0 m). (Between outdoor unit and indoor unit.)
- 2 or more indoor units should be connected.
- The total ability of connected indoor unit is from 26,000 Btu/h up to 46,000 Btu/h.
- Input in the table are calculated based on the maximum indoor unit input combinations.

OUTDOOR UNIT
AOUH18-36KWAHOUTDOOR UNIT
AOUH18-36KWAH

AOUH36KWAH4, Heating capacity												
Indoor unit connecting capacity	Outdoor temperature		Indoor temperature (°FDB)									
			60		65		70		75		78	
	°FDB	°FWB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
kBtu/h			kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW
46	-15	-17	23.25	3.78	22.70	3.85	22.14	3.92	21.59	3.99	21.04	4.06
	-5	-7	26.38	3.97	25.75	4.04	25.12	4.12	24.49	4.19	23.87	4.27
	5	3	38.22	5.40	37.31	5.50	36.40	5.61	35.49	5.72	34.58	5.82
	14	12	40.18	4.91	39.22	5.01	38.27	5.11	37.31	5.22	36.35	5.32
	23	19	42.14	4.42	41.14	4.52	40.13	4.62	39.13	4.71	38.13	4.81
	32	28	44.10	3.93	43.05	4.02	42.00	4.12	40.95	4.21	39.90	4.31
	41	37	44.10	3.46	43.05	3.54	42.00	3.62	40.95	3.70	39.90	3.79
	47	43	44.10	3.16	43.05	3.22	42.00	3.29	40.95	3.36	39.90	3.42
	50	47	44.10	3.15	43.05	3.22	42.00	3.28	40.95	3.35	39.90	3.42
	59	50	44.10	3.12	43.05	3.19	42.00	3.26	40.95	3.32	39.90	3.39
45	68	59	44.10	3.00	43.05	3.06	42.00	3.12	40.95	3.19	39.90	3.25
	75	65	44.10	2.90	43.05	2.96	42.00	3.02	40.95	3.08	39.90	3.14
	-15	-17	23.25	3.78	22.70	3.85	22.14	3.92	21.59	3.99	21.04	4.06
	-5	-7	26.38	3.97	25.75	4.04	25.12	4.12	24.49	4.19	23.87	4.27
	5	3	38.22	5.40	37.31	5.50	36.40	5.61	35.49	5.72	34.58	5.82
	14	12	40.18	4.91	39.22	5.01	38.27	5.11	37.31	5.22	36.35	5.32
	23	19	42.14	4.42	41.14	4.52	40.13	4.62	39.13	4.71	38.13	4.81
	32	28	44.10	3.93	43.05	4.02	42.00	4.12	40.95	4.21	39.90	4.31
	41	37	44.10	3.46	43.05	3.54	42.00	3.62	40.95	3.70	39.90	3.79
	47	43	44.10	3.16	43.05	3.22	42.00	3.29	40.95	3.36	39.90	3.42
44	50	47	44.10	3.15	43.05	3.22	42.00	3.28	40.95	3.35	39.90	3.42
	59	50	44.10	3.12	43.05	3.19	42.00	3.26	40.95	3.32	39.90	3.39
	68	59	44.10	3.00	43.05	3.06	42.00	3.12	40.95	3.19	39.90	3.25
	75	65	44.10	2.90	43.05	2.96	42.00	3.02	40.95	3.08	39.90	3.14
	-15	-17	23.25	3.78	22.70	3.85	22.14	3.92	21.59	3.99	21.04	4.06
	-5	-7	26.38	3.97	25.75	4.04	25.12	4.12	24.49	4.19	23.87	4.27
	5	3	38.22	5.40	37.31	5.50	36.40	5.61	35.49	5.72	34.58	5.82
	14	12	40.18	4.91	39.22	5.01	38.27	5.11	37.31	5.22	36.35	5.32
	23	19	42.14	4.42	41.14	4.52	40.13	4.62	39.13	4.71	38.13	4.81
	32	28	44.10	3.93	43.05	4.02	42.00	4.12	40.95	4.21	39.90	4.31
43	41	37	44.10	3.46	43.05	3.54	42.00	3.62	40.95	3.70	39.90	3.79
	47	43	44.10	3.16	43.05	3.22	42.00	3.29	40.95	3.36	39.90	3.42
	50	47	44.10	3.15	43.05	3.22	42.00	3.28	40.95	3.35	39.90	3.42
	59	50	44.10	3.12	43.05	3.19	42.00	3.26	40.95	3.32	39.90	3.39
	68	59	44.10	3.00	43.05	3.06	42.00	3.12	40.95	3.19	39.90	3.25
	75	65	44.10	2.90	43.05	2.96	42.00	3.02	40.95	3.08	39.90	3.14
	-15	-17	23.25	3.78	22.70	3.85	22.14	3.92	21.59	3.99	21.04	4.06
	-5	-7	26.38	3.97	25.75	4.04	25.12	4.12	24.49	4.19	23.87	4.27
	5	3	38.22	5.40	37.31	5.50	36.40	5.61	35.49	5.72	34.58	5.82
	14	12	40.18	4.91	39.22	5.01	38.27	5.11	37.31	5.22	36.35	5.32
42	23	19	42.14	4.42	41.14	4.52	40.13	4.62	39.13	4.71	38.13	4.81
	32	28	44.10	3.93	43.05	4.02	42.00	4.12	40.95	4.21	39.90	4.31
	41	37	44.10	3.46	43.05	3.54	42.00	3.62	40.95	3.70	39.90	3.79
	47	43	44.10	3.16	43.05	3.22	42.00	3.29	40.95	3.36	39.90	3.42
	50	47	44.10	3.15	43.05	3.22	42.00	3.28	40.95	3.35	39.90	3.42
	59	50	44.10	3.12	43.05	3.19	42.00	3.26	40.95	3.32	39.90	3.39
	68	59	44.10	3.00	43.05	3.06	42.00	3.12	40.95	3.19	39.90	3.25
	75	65	44.10	2.90	43.05	2.96	42.00	3.02	40.95	3.08	39.90	3.14
	-15	-17	23.25	3.78	22.70	3.85	22.14	3.92	21.59	3.99	21.04	4.06
	-5	-7	26.38	3.97	25.75	4.04	25.12	4.12	24.49	4.19	23.87	4.27

AOUH36KWAH4, Heating capacity												
Indoor unit connecting capacity	Outdoor temperature		Indoor temperature (°FDB)									
			60		65		70		75		78	
			TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
kBtu/h	°FDB	°FWB	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW
41	-15	-17	23.25	3.78	22.70	3.85	22.14	3.92	21.59	3.99	21.04	4.06
	-5	-7	26.38	3.97	25.75	4.04	25.12	4.12	24.49	4.19	23.87	4.27
	5	3	38.22	5.40	37.31	5.50	36.40	5.61	35.49	5.72	34.58	5.82
	14	12	40.18	4.91	39.22	5.01	38.27	5.11	37.31	5.22	36.35	5.32
	23	19	42.14	4.42	41.14	4.52	40.13	4.62	39.13	4.71	38.13	4.81
	32	28	44.10	3.93	43.05	4.02	42.00	4.12	40.95	4.21	39.90	4.31
	41	37	44.10	3.46	43.05	3.54	42.00	3.62	40.95	3.70	39.90	3.79
	47	43	44.10	3.16	43.05	3.22	42.00	3.29	40.95	3.36	39.90	3.42
	50	47	44.10	3.15	43.05	3.22	42.00	3.28	40.95	3.35	39.90	3.42
	59	50	44.10	3.12	43.05	3.19	42.00	3.26	40.95	3.32	39.90	3.39
	68	59	44.10	3.00	43.05	3.06	42.00	3.12	40.95	3.19	39.90	3.25
	75	65	44.10	2.90	43.05	2.96	42.00	3.02	40.95	3.08	39.90	3.14
40	-15	-17	23.25	3.78	22.70	3.85	22.14	3.92	21.59	3.99	21.04	4.06
	-5	-7	26.38	3.97	25.75	4.04	25.12	4.12	24.49	4.19	23.87	4.27
	5	3	38.22	5.40	37.31	5.50	36.40	5.61	35.49	5.72	34.58	5.82
	14	12	40.18	4.91	39.22	5.01	38.27	5.11	37.31	5.22	36.35	5.32
	23	19	42.14	4.42	41.14	4.52	40.13	4.62	39.13	4.71	38.13	4.81
	32	28	44.10	3.93	43.05	4.02	42.00	4.12	40.95	4.21	39.90	4.31
	41	37	44.10	3.46	43.05	3.54	42.00	3.62	40.95	3.70	39.90	3.79
	47	43	44.10	3.16	43.05	3.22	42.00	3.29	40.95	3.36	39.90	3.42
	50	47	44.10	3.15	43.05	3.22	42.00	3.28	40.95	3.35	39.90	3.42
	59	50	44.10	3.12	43.05	3.19	42.00	3.26	40.95	3.32	39.90	3.39
	68	59	44.10	3.00	43.05	3.06	42.00	3.12	40.95	3.19	39.90	3.25
	75	65	44.10	2.90	43.05	2.96	42.00	3.02	40.95	3.08	39.90	3.14
39	-15	-17	23.25	3.78	22.70	3.85	22.14	3.92	21.59	3.99	21.04	4.06
	-5	-7	26.38	3.97	25.75	4.04	25.12	4.12	24.49	4.19	23.87	4.27
	5	3	38.22	5.40	37.31	5.50	36.40	5.61	35.49	5.72	34.58	5.82
	14	12	40.18	4.91	39.22	5.01	38.27	5.11	37.31	5.22	36.35	5.32
	23	19	42.14	4.42	41.14	4.52	40.13	4.62	39.13	4.71	38.13	4.81
	32	28	44.10	3.93	43.05	4.02	42.00	4.12	40.95	4.21	39.90	4.31
	41	37	44.10	3.46	43.05	3.54	42.00	3.62	40.95	3.70	39.90	3.79
	47	43	44.10	3.16	43.05	3.22	42.00	3.29	40.95	3.36	39.90	3.42
	50	47	44.10	3.15	43.05	3.22	42.00	3.28	40.95	3.35	39.90	3.42
	59	50	44.10	3.12	43.05	3.19	42.00	3.26	40.95	3.32	39.90	3.39
	68	59	44.10	3.00	43.05	3.06	42.00	3.12	40.95	3.19	39.90	3.25
	75	65	44.10	2.90	43.05	2.96	42.00	3.02	40.95	3.08	39.90	3.14
38	-15	-17	23.25	3.78	22.70	3.85	22.14	3.92	21.59	3.99	21.04	4.06
	-5	-7	26.38	3.97	25.75	4.04	25.12	4.12	24.49	4.19	23.87	4.27
	5	3	38.22	5.40	37.31	5.50	36.40	5.61	35.49	5.72	34.58	5.82
	14	12	40.18	4.91	39.22	5.01	38.27	5.11	37.31	5.22	36.35	5.32
	23	19	42.14	4.42	41.14	4.52	40.13	4.62	39.13	4.71	38.13	4.81
	32	28	44.10	3.93	43.05	4.02	42.00	4.12	40.95	4.21	39.90	4.31
	41	37	44.10	3.46	43.05	3.54	42.00	3.62	40.95	3.70	39.90	3.79
	47	43	44.10	3.16	43.05	3.22	42.00	3.29	40.95	3.36	39.90	3.42
	50	47	44.10	3.15	43.05	3.22	42.00	3.28	40.95	3.35	39.90	3.42
	59	50	44.10	3.12	43.05	3.19	42.00	3.26	40.95	3.32	39.90	3.39
	68	59	44.10	3.00	43.05	3.06	42.00	3.12	40.95	3.19	39.90	3.25
	75	65	44.10	2.90	43.05	2.96	42.00	3.02	40.95	3.08	39.90	3.14
37	-15	-17	23.25	3.78	22.70	3.85	22.14	3.92	21.59	3.99	21.04	4.06
	-5	-7	26.38	3.97	25.75	4.04	25.12	4.12	24.49	4.19	23.87	4.27
	5	3	38.22	5.40	37.31	5.50	36.40	5.61	35.49	5.72	34.58	5.82
	14	12	40.18	4.91	39.22	5.01	38.27	5.11	37.31	5.22	36.35	5.32
	23	19	42.14	4.42	41.14	4.52	40.13	4.62	39.13	4.71	38.13	4.81
	32	28	44.10	3.93	43.05	4.02	42.00	4.12	40.95	4.21	39.90	4.31
	41	37	44.10	3.46	43.05	3.54	42.00	3.62	40.95	3.70	39.90	3.79
	47	43	44.10	3.16	43.05	3.22	42.00	3.29	40.95	3.36	39.90	3.42
	50	47	44.10	3.15	43.05	3.22	42.00	3.28	40.95	3.35	39.90	3.42
	59	50	44.10	3.12	43.05	3.19	42.00	3.26	40.95	3.32	39.90	3.39
	68	59	44.10	3.00	43.05	3.06	42.00	3.12	40.95	3.19	39.90	3.25
	75	65	44.10	2.90	43.05	2.96	42.00	3.02	40.95	3.08	39.90	3.14
36	-15	-17	23.25	3.78	22.70	3.85	22.14	3.92	21.59	3.99	21.04	4.06
	-5	-7	26.38	3.97	25.75	4.04	25.12	4.12	24.49	4.19	23.87	4.27
	5	3	38.22	5.40	37.31	5.50	36.40	5.61	35.49	5.72	34.58	5.82
	14	12	40.18	4.91	39.22	5.01	38.27	5.11	37.31	5.22	36.35	5.32
	23	19	42.14	4.42	41.14	4.52	40.13	4.62	39.13	4.71	38.13	4.81
	32	28	44.10	3.93	43.05	4.02	42.00	4.12	40.95	4.21	39.90	4.31
	41	37	44.10	3.46	43.05	3.54	42.00	3.62	40.95	3.70	39.90	3.79
	47	43	44.10	3.16	43.05	3.22	42.00	3.29	40.95	3.36	39.90	3.42
	50	47	44.10	3.15	43.05	3.22	42.00	3.28	40.95	3.35	39.90	3.42
	59	50	44.10	3.12	43.05	3.19	42.00	3.26	40.95	3.32	39.90	3.39
	68	59	44.10	3.00	43.05	3.06	42.00	3.12	40.95	3.19	39.90	3.25
	75	65	44.10	2.90	43.05	2.96	42.00	3.02	40.95	3.08	39.90	3.14
35	-15	-17	22.59	3.62	22.05	3.69	21.51	3.76	20.97	3.83	20.44	3.90
	-5	-7	25.62	3.81	25.01	3.88	24.40	3.96	23.79	4.03	23.18	4.10
	5	3	37.13	5.18	36.24	5.29	35.36	5.39	34.48	5.49	33.59	5.59
	14	12	39.03	4.71	38.10	4.81	37.17	4.91	36.24	5.01	35.31	5.11
	23	19	40.94	4.24	39.96	4.34	38.99	4.43	38.01	4.53	37.04	4.62
	32	28	42.84	3.77	41.82	3.86	40.80	3.96	39.78	4.05	38.76	4.14
	41	37	42.84	3.32	41.82	3.40	40.80	3.48	39.78	3.56	38.76	3.64
	47	43	42.84	3.03	41.82	3.10	40.80	3.16	39.78	3.22	38.76	3.29
	50	47	42.84	3.02	41.82	3.09	40.80	3.15	39.78	3.22	38.76	3.28
	59	50	42.84	3.00	41.82	3.06	40.80	3.13	39.78	3.19	38.76	3.26
	68	59	42.84	2.88	41.82	2.94	40.80	3.00	39.78	3.06	38.76	3.12
	75	65	42.84	2.78	41.82	2.84	40.80	2.90	39.78	2.96	38.76	3.02

FUJITSU GENERAL LIMITED

AOUH36KWAH4, Heating capacity												
Indoor unit connecting capacity	Outdoor temperature		Indoor temperature (°FDB)									
			60		65		70		75		78	
			TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
kBtu/h	°FDB	°FWB	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW
34	-15	-17	21.92	3.47	21.40	3.54	20.88	3.61	20.36	3.68	19.84	3.74
	-5	-7	24.87	3.65	24.28	3.72	23.69	3.79	23.09	3.86	22.50	3.94
	5	3	36.04	4.97	35.18	5.07	34.32	5.17	33.46	5.27	32.60	5.37
	14	12	37.88	4.51	36.98	4.61	36.08	4.71	35.18	4.81	34.28	4.90
	23	19	39.73	4.07	38.79	4.16	37.84	4.25	36.89	4.34	35.95	4.43
	32	28	41.58	3.61	40.59	3.70	39.60	3.79	38.61	3.88	37.62	3.97
	41	37	41.58	3.18	40.59	3.26	39.60	3.34	38.61	3.41	37.62	3.49
	47	43	41.58	2.90	40.59	2.97	39.60	3.03	38.61	3.09	37.62	3.16
	50	47	41.58	2.90	40.59	2.96	39.60	3.02	38.61	3.09	37.62	3.15
	59	50	41.58	2.88	40.59	2.94	39.60	3.00	38.61	3.06	37.62	3.12
	68	59	41.58	2.76	40.59	2.82	39.60	2.88	38.61	2.94	37.62	3.00
	75	65	41.58	2.67	40.59	2.72	39.60	2.78	38.61	2.84	37.62	2.90
33	-15	-17	21.31	3.35	20.81	3.41	20.30	3.48	19.79	3.54	19.28	3.61
	-5	-7	24.18	3.52	23.60	3.59	23.03	3.66	22.45	3.72	21.88	3.79
	5	3	35.04	4.79	34.20	4.88	33.37	4.98	32.53	5.08	31.70	5.17
	14	12	36.83	4.35	35.95	4.44	35.08	4.54	34.20	4.63	33.32	4.73
	23	19	38.63	3.92	37.71	4.01	36.79	4.10	35.87	4.19	34.95	4.27
	32	28	40.43	3.48	39.46	3.57	38.50	3.66	37.54	3.74	36.58	3.83
	41	37	40.43	3.06	39.46	3.14	38.50	3.21	37.54	3.29	36.58	3.36
	47	43	40.43	2.80	39.46	2.86	38.50	2.92	37.54	2.98	36.58	3.04
	50	47	40.43	2.79	39.46	2.85	38.50	2.91	37.54	2.97	36.58	3.03
	59	50	40.43	2.77	39.46	2.83	38.50	2.89	37.54	2.95	36.58	3.01
	68	59	40.43	2.66	39.46	2.71	38.50	2.77	37.54	2.83	36.58	2.89
	75	65	40.43	2.57	39.46	2.62	38.50	2.68	37.54	2.74	36.58	2.79
32	-15	-17	20.65	3.21	20.16	3.27	19.67	3.34	19.18	3.40	18.68	3.46
	-5	-7	23.43	3.37	22.87	3.44	22.31	3.51	21.75	3.57	21.20	3.64
	5	3	33.94	4.59	33.13	4.68	32.33	4.77	31.52	4.87	30.71	4.96
	14	12	35.68	4.17	34.83	4.26	33.98	4.35	33.13	4.44	32.29	4.53
	23	19	37.42	3.76	36.53	3.84	35.64	3.93	34.75	4.01	33.86	4.10
	32	28	39.17	3.34	38.23	3.42	37.30	3.51	36.37	3.59	35.44	3.67
	41	37	39.17	2.94	38.23	3.01	37.30	3.08	36.37	3.15	35.44	3.23
	47	43	39.17	2.68	38.23	2.74	37.30	2.80	36.37	2.86	35.44	2.92
	50	47	39.17	2.68	38.23	2.73	37.30	2.79	36.37	2.85	35.44	2.91
	59	50	39.17	2.66	38.23	2.71	37.30	2.77	36.37	2.83	35.44	2.89
	68	59	39.17	2.55	38.23	2.60	37.30	2.66	36.37	2.71	35.44	2.77
	75	65	39.17	2.46	38.23	2.52	37.30	2.57	36.37	2.62	35.44	2.68
31	-15	-17	19.99	3.33	19.51	3.39	19.03	3.45	18.56	3.52	18.08	3.58
	-5	-7	22.67	3.50	22.13	3.57	21.59	3.63	21.05	3.69	20.51	3.76
	5	3	32.85	4.77	32.07	4.86	31.29	4.94	30.50	5.03	29.72	5.12
	14	12	34.54	4.33	33.71	4.42	32.89	4.51	32.07	4.59	31.25	4.68
	23	19	36.22	3.90	35.36	3.99	34.50	4.07	33.63	4.15	32.77	4.23
	32	28	37.91	3.47	37.00	3.55	36.10	3.63	35.20	3.71	34.30	3.79
	41	37	37.91	3.05	37.00	3.12	36.10	3.19	35.20	3.26	34.30	3.33
	47	43	37.91	2.79	37.00	2.84	36.10	2.90	35.20	2.96	34.30	3.01
	50	47	37.91	2.78	37.00	2.84	36.10	2.89	35.20	2.95	34.30	3.01
	59	50	37.91	2.76	37.00	2.81	36.10	2.87	35.20	2.93	34.30	2.98
	68	59	37.91	2.65	37.00	2.70	36.10	2.75	35.20	2.81	34.30	2.86
	75	65	37.91	2.56	37.00	2.61	36.10	2.66	35.20	2.71	34.30	2.77
30	-15	-17	19.38	2.94	18.92	3.00	18.45	3.06	17.99	3.12	17.53	3.18
	-5	-7	21.98	3.09	21.46	3.16	20.94	3.22	20.41	3.28	19.89	3.34
	5	3	31.85	4.21	31.09	4.30	30.33	4.38	29.58	4.47	28.82	4.56
	14	12	33.48	3.82	32.69	3.91	31.89	3.99	31.09	4.08	30.29	4.16
	23	19	35.12	3.45	34.28	3.53	33.44	3.61	32.61	3.69	31.77	3.77
	32	28	36.75	3.06	35.88	3.14	35.00	3.22	34.13	3.30	33.25	3.37
	41	37	36.75	2.69	35.88	2.76	35.00	2.83	34.13	2.90	33.25	2.96
	47	43	36.75	2.46	35.88	2.52	35.00	2.57	34.13	2.62	33.25	2.68
	50	47	36.75	2.45	35.88	2.51	35.00	2.56	34.13	2.62	33.25	2.67
	59	50	36.75	2.44	35.88	2.49	35.00	2.54	34.13	2.60	33.25	2.65
	68	59	36.75	2.34	35.88	2.39	35.00	2.44	34.13	2.49	33.25	2.54
	75	65	36.75	2.26	35.88	2.31	35.00	2.36	34.13	2.41	33.25	2.46
29	-15	-17	18.71	2.78	18.27	2.84	17.82	2.89	17.38	2.95	16.93	3.01
	-5	-7	21.23	2.92	20.72	2.98	20.22	3.04	19.71	3.10	19.21	3.16
	5	3	30.76	3.98	30.03	4.06	29.29	4.14	28.56	4.23	27.83	4.31
	14	12	32.34	3.61	31.57	3.70	30.80	3.78	30.03	3.86	29.26	3.94
	23	19	33.91	3.26	33.11	3.33	32.30	3.41	31.49	3.49	30.68	3.56
	32	28	35.49	2.89	34.65	2.97	33.80	3.04	32.96	3.12	32.11	3.19
	41	37	35.49	2.55	34.65	2.61	33.80	2.67	32.96	2.74	32.11	2.80
	47	43	35.49	2.32	34.65	2.38	33.80	2.43	32.96	2.48	32.11	2.54
	50	47	35.49	2.32	34.65	2.37	33.80	2.42	32.96	2.48	32.11	2.53
	59	50	35.49	2.30	34.65	2.35	33.80	2.41	32.96	2.46	32.11	2.51
	68	59	35.49	2.21	34.65	2.26	33.80	2.31	32.96	2.36	32.11	2.41
	75	65	35.49	2.13	34.65	2.18	33.80	2.23	32.96	2.28	32.11	2.33
28	-15	-17	18.05	2.68	17.62	2.73	17.19	2.79	16.76	2.84	16.33	2.90
	-5	-7	20.47	2.81	19.99	2.87	19.50	2.93	19.01	2.99	18.52	3.04
	5	3	29.67	3.83	28.96	3.91	28.25	3.99	27.55	4.07	26.84	4.15
	14	12	31.19	3.48	30.44	3.56	29.70	3.64	28.96	3.71	28.22	3.79
	23	19	32.71	3.14	31.93	3.21	31.15	3.28	30.37	3.36	29.59	3.43
	32	28	34.23	2.79	33.42	2.86	32.60	2.93	31.79	3.00	30.97	3.07
	41	37	34.23	2.45	33.42	2.51	32.60	2.58	31.79	2.64	30.97	2.70
	47	43	34.23	2.24	33.42	2.29	32.60	2.34	31.79	2.39	30.97	2.44
	50	47	34.23	2.23	33.42	2.28	32.60	2.33	31.79	2.38	30.97	2.44
	59	50	34.23	2.22	33.42	2.27	32.60	2.32	31.79	2.37	30.97	2.42
	68	59	34.23	2.13	33.42	2.17	32.60	2.22	31.79	2.27	30.97	2.32
	75	65	34.23	2.05	33.42	2.10	32.60	2.15	31.79	2.19	30.97	2.24

OUTDOOR UNIT
AOUH18-36KWAHOUTDOOR UNIT
AOUH18-36KWAH

FUJITSU GENERAL LIMITED

AOUH36KWAH4, Heating capacity												
Indoor unit connecting capacity	Outdoor temperature		Indoor temperature (°FDB)									
			60		65		70		75		78	
			TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
kBtu/h	°FDB	°FWB	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW	kBtu/h	kW
27	-15	-17	17.44	2.78	17.02	2.83	16.61	2.88	16.19	2.94	15.78	2.99
	-5	-7	19.78	2.92	19.31	2.97	18.84	3.03	18.37	3.08	17.90	3.14
	5	3	28.67	3.97	27.98	4.05	27.30	4.13	26.62	4.20	25.94	4.28
	14	12	30.14	3.61	29.42	3.69	28.70	3.76	27.98	3.84	27.27	3.91
	23	19	31.61	3.25	30.85	3.32	30.10	3.40	29.35	3.47	28.60	3.54
	32	28	33.08	2.89	32.29	2.96	31.50	3.03	30.71	3.10	29.93	3.17
	41	37	33.08	2.54	32.29	2.60	31.50	2.66	30.71	2.72	29.93	2.78
	47	43	33.08	2.32	32.29	2.37	31.50	2.42	30.71	2.47	29.93	2.52
	50	47	33.08	2.32	32.29	2.37	31.50	2.41	30.71	2.46	29.93	2.51
	59	50	33.08	2.30	32.29	2.35	31.50	2.40	30.71	2.44	29.93	2.49
	68	59	33.08	2.20	32.29	2.25	31.50	2.30	30.71	2.34	29.93	2.39
	75	65	33.08	2.13	32.29	2.18	31.50	2.22	30.71	2.27	29.93	2.31
26	-15	-17	16.77	2.64	16.38	2.69	15.98	2.74	15.58	2.79	15.18	2.84
	-5	-7	19.03	2.77	18.58	2.83	18.12	2.88	17.67	2.93	17.22	2.99
	5	3	27.57	3.77	26.92	3.85	26.26	3.92	25.60	4.00	24.95	4.07
	14	12	28.99	3.43	28.30	3.50	27.61	3.57	26.92	3.65	26.23	3.72
	23	19	30.40	3.09	29.68	3.16	28.95	3.23	28.23	3.29	27.51	3.36
	32	28	31.82	2.75	31.06	2.81	30.30	2.88	29.54	2.95	28.79	3.01
	41	37	31.82	2.42	31.06	2.47	30.30	2.53	29.54	2.59	28.79	2.65
	47	43	31.82	2.21	31.06	2.25	30.30	2.30	29.54	2.35	28.79	2.39
	50	47	31.82	2.20	31.06	2.25	30.30	2.29	29.54	2.34	28.79	2.39
	59	50	31.82	2.18	31.06	2.23	30.30	2.28	29.54	2.32	28.79	2.37
	68	59	31.82	2.09	31.06	2.14	30.30	2.18	29.54	2.23	28.79	2.27
	75	65	31.82	2.02	31.06	2.07	30.30	2.11	29.54	2.15	28.79	2.20
25	-15	-17	16.11	2.51	15.73	2.56	15.34	2.61	14.96	2.66	14.58	2.71
	-5	-7	18.28	2.64	17.84	2.69	17.41	2.74	16.97	2.79	16.54	2.84
	5	3	26.48	3.59	25.85	3.66	25.22	3.73	24.59	3.81	23.96	3.88
	14	12	27.84	3.26	27.18	3.33	26.51	3.40	25.85	3.47	25.19	3.54
	23	19	29.20	2.94	28.50	3.01	27.81	3.07	27.11	3.14	26.42	3.20
	32	28	30.56	2.61	29.83	2.68	29.10	2.74	28.37	2.81	27.65	2.87
	41	37	30.56	2.30	29.83	2.36	29.10	2.41	28.37	2.47	27.65	2.52
	47	43	30.56	2.10	29.83	2.15	29.10	2.19	28.37	2.23	27.65	2.28
	50	47	30.56	2.09	29.83	2.14	29.10	2.18	28.37	2.23	27.65	2.27
	59	50	30.56	2.08	29.83	2.12	29.10	2.17	28.37	2.21	27.65	2.26
	68	59	30.56	1.99	29.83	2.04	29.10	2.08	28.37	2.12	27.65	2.16
	75	65	30.56	1.93	29.83	1.97	29.10	2.01	28.37	2.05	27.65	2.09

OUTDOOR UNIT
AOUH18-36KWAHOUTDOOR UNIT
AOUH18-36KWAH