

Grust

covers grust (0.4.0)

A Rust Property Graph Architecture

Alexy Khrabrov

&

Codex with ChatGPT 5.5

Preface

Grust is a small Rust property graph API with a large architectural promise: application code should be able to build, validate, traverse, and persist graph data without committing itself to a database query language too early.

That goal matters because many graph-shaped Rust applications live between worlds. A crawler wants a local graph while it extracts facts. An indexing pipeline wants deterministic target state. A data product may begin with tests and an in-memory backend, then later need SurrealDB, FalkorDB, PostgreSQL, LanceDB, Sail, or another backend. Grust gives those applications one model to program against:

```
Graph = nodes + edges
Node  = id + label + properties
Edge  = optional id + from + to + label + properties
```

This book is a guided tour of that model. It covers the workspace architecture, the Rust concepts the code leans on, the core graph types, traversal IR, backend contracts, implemented backends, proposed backends, and practical examples.

1. The Shape of Grust

Grust is not trying to be every graph library for Rust. It is not an algorithm crate like `petgraph`, and it is not a thin wrapper around a single database. It is a property graph layer: a compact model of labeled nodes, labeled edges, and typed properties that can be carried across storage engines.

The current workspace is arranged around one core crate, one public facade, and backend or integration crates:




Figure 1: Diagram 1

The `grust-core` crate owns the durable concepts. It defines identifiers, labels, property values, graph builders, schemas, traversals, error types, load reports, and backend traits. The `grust` crate re-exports those pieces and gates backend crates behind Cargo features.

That split is important. Core model code stays light, deterministic, and mostly dependency-free. Backends are allowed to depend on Redis, SurrealDB, LanceDB, PostgreSQL, Spark Connect, HTTP clients, gRPC clients, or SDKs without dragging those dependencies into every Grust user.

2. The Core Property Graph

At the center of Grust are three public data structures:

```
pub struct Graph {
    pub nodes: Vec<Node>,
    pub edges: Vec<Edge>,
}
```

```
pub struct Node {
    pub id: NodeId,
    pub label: Label,
    pub props: Props,
}

pub struct Edge {
    pub id: Option<EdgeId>,
    pub from: NodeId,
    pub to: NodeId,
    pub label: Label,
    pub props: Props,
}
```

NodeId, EdgeId, and Label are newtypes over String. They are small wrappers, but they carry meaning through Rust's type system. A function that expects a Label cannot accidentally receive an EdgeId without an explicit conversion. The wrappers implement common conversion traits such as From<&str> and From<String>, so the public API remains ergonomic.

Properties are stored in a BTreeMap<String, Value>:

```
pub enum Value {
    Null,
    Bool(bool),
    Int(i64),
    Float(f64),
    String(String),
    StringArray(Vec<String>),
    Json(serde_json::Value),
}
```

The use of BTreeMap is a quiet but useful choice. Iteration order is stable, which makes generated JSON, tests, and backend query generation more predictable. That is especially helpful in a project whose backends turn one graph into SQL, Cypher-like queries, Arrow batches, JSON target state, or SDK calls.

Node::new also inserts an id property if one is not already present. That means a Grust node has a first-class typed identity and an ordinary property view of that identity, which helps backends that identify records through property maps.

3. Building Graphs

Most application code should not construct every Node and Edge by hand. It should use GraphBuilder:

```
use grust::prelude::*;

let mut builder = GraphBuilder::new();

let talk = builder
    .node("Talk", "talk:rust-graph-api")
    .prop("title", "A Modern Graph API for Rust")
    .prop("year", 2026_i64)
    .finish();

let speaker = builder
    .node("Person", "person:ada")
```

```
.prop("name", "Ada Example")
.finish();
```

builder

```
.edge("PRESENTED_BY", &talk, &speaker)
.prop("source", "conference-schedule")
.finish();
```

```
let graph = builder.build();
```

The builder deduplicates nodes by `NodeId`. If an existing node has the same label, additional properties are merged into it. Edges default to `EdgePolicy::DedupeByFromLabelTo`, so the tuple (from, label, to) is treated as the relationship identity. Domains that need true multi-edges can opt into `EdgePolicy::AllowDuplicates`.

```
let mut builder = GraphBuilder::new()
    .edge_policy(EdgePolicy::AllowDuplicates);
```

This is an example of Grust's overall style: put the common property-graph case on the simple path, but leave an explicit escape hatch for graph models with different identity rules.

Loading and Saving Graph Documents

A Graph can also move through textual document formats without touching a backend. The core crate exposes paired constructors and serializers for YAML, JSON, and XML:

```
let graph = Graph::from_yaml(yaml_text)?;
let yaml_text = graph.to_yaml()?;
```

```
let graph = Graph::from_json(json_text)?;
let json_text = graph.to_json()?;
```

```
let graph = Graph::from_xml(xml_text)?;
let xml_text = graph.to_xml()?;
```

These methods are useful for fixtures, migration inputs, examples, audits, and small graph interchange files. They all feed the same validation path, so a document with duplicate node ids or an edge that points at a missing node fails before it reaches a store.

YAML and JSON share the same document shape. A property value can be written as a plain JSON-like scalar when the type is obvious, or as the tagged Grust Value representation when the exact variant matters:

```
{
  "nodes": [
    {
      "id": "talk:rust-graph-api",
      "label": "Talk",
      "props": {
        "title": "A Modern Graph API for Rust",
        "year": 2026,
        "tracks": {
          "type": "string_array",
          "value": ["rust", "graphs"]
        }
      }
    }
  ],
  {
```

```

    "id": "person:ada",
    "label": "Person",
    "props": {
      "name": "Ada Example"
    }
  },
  "edges": [
    {
      "label": "PRESENTED_BY",
      "from": "talk:rust-graph-api",
      "to": "person:ada",
      "props": {
        "source": "conference-schedule"
      }
    }
  ]
}

```

The XML form is more explicit because XML has no native object or array type. Properties are represented as repeated prop entries with a key and a tagged value:

```

<graph>
  <nodes>
    <node>
      <id>talk:rust-graph-api</id>
      <label>Talk</label>
      <props>
        <prop>
          <key>title</key>
          <value>
            <type>string</type>
            <value>A Modern Graph API for Rust</value>
          </value>
        </prop>
      </props>
    </node>
    <node>
      <id>person:ada</id>
      <label>Person</label>
    </node>
  </nodes>
  <edges>
    <edge>
      <label>PRESENTED_BY</label>
      <from>talk:rust-graph-api</from>
      <to>person:ada</to>
    </edge>
  </edges>
</graph>

```

Serialization removes the generated `id` property from node property maps when it only mirrors the node's `NodeId`. That keeps exported documents readable without changing what `Node::new` guarantees after loading.

4. Typed Graph Ingestion with garde and zod-rs

The core Graph, Node, and Edge types are intentionally dynamic. A node has a label and a property map; an edge has a label, endpoints, and a property map. That dynamic shape is the right interchange format for backends, graph documents, audits, and cross-system movement. Application code, however, often starts with typed Rust structs: a Person, a Project, a WorksOn relationship, or some domain-specific event. Grust's typed ingestion layer connects those two worlds.

The typed layer is optional. It is enabled through Cargo features:

```
[dependencies]
grust = { package = "grust-graph", version = "0.4", features = ["typed-garde"] }
```

typed-garde adds Rust-struct validation and typed lowering. A second feature, typed-zod-rs, layers raw JSON shape validation on top:

```
[dependencies]
grust = { package = "grust-graph", version = "0.4", features = ["typed-zod-rs"] }
```

typed-zod-rs implies typed-garde. That relationship matters: zod-rs checks untrusted JSON shape first, Serde turns the JSON into Rust values, and garde checks typed domain invariants before Grust lowers the value into a normal Node or Edge.




Figure 2: Diagram 2

The important promise is that typed ingestion does not create a second graph model. Once validation succeeds, everything becomes the ordinary Grust graph shape. Backends do not need to know whether a node came from GraphBuilder, a YAML document, a typed Rust struct, or a zod-rs-validated JSON payload.

garde: Typed Rust Validation

garde is a Rust validation library built around a derive macro. You attach validation rules to fields, derive `garde::Validate`, and then call `validate()` or `validate_with(...)`. The rules live near the Rust type, so they travel with the domain model instead of being hidden in a loader function.

Common garde rules include:

- `length(min = 1)` for nonempty strings and collections.
- `range(min = 1, max = 100)` for numeric bounds.
- `inner(...)` for validating items inside a collection.
- `custom(...)` for domain-specific validation functions.
- `dive` for validating nested values that also implement `Validate`.

In Grust, a typed node implements `TypedNode`. It supplies a graph label and a stable node id. The default property conversion serializes the struct through Serde and converts the resulting object fields into Grust properties:

```
use grust::prelude::*;
use grust::typed::garde;
use serde::Serialize;

#[derive(Debug, Serialize, garde::Validate)]
#[garde(allow_unvalidated)]
struct Person {
```

```

    #[garde(length(min = 1))]
    id: String,
    #[garde(length(min = 1))]
    name: String,
    #[garde(length(min = 1), inner(length(min = 1)))]
    skills: Vec<String>,
}

```

```

impl TypedNode for Person {
    const LABEL: &'static str = "Person";

    fn node_id(&self) -> NodeId {
        format!("person:{}", self.id).into()
    }
}

```

Typed edges implement TypedEdge. They provide a label and endpoint ids:

```

#[derive(Debug, Serialize, garde::Validate)]
#[garde(allow_unvalidated)]
struct WorksOn {
    #[garde(length(min = 1))]
    person_id: String,
    #[garde(length(min = 1))]
    project_id: String,
    #[garde(range(min = 1, max = 100))]
    allocation_percent: u8,
}

impl TypedEdge for WorksOn {
    const LABEL: &'static str = "WORKS_ON";

    fn from_node_id(&self) -> NodeId {
        format!("person:{}", self.person_id).into()
    }

    fn to_node_id(&self) -> NodeId {
        format!("project:{}", self.project_id).into()
    }
}

```

TypedGraphBuilder validates and lowers these values:

```

let mut builder = TypedGraphBuilder::new();

builder.add_node(&Person {
    id: "nia".to_string(),
    name: "Nia".to_string(),
    skills: vec!["rust".to_string(), "graphs".to_string()],
})?;

builder.add_edge(&WorksOn {
    person_id: "nia".to_string(),
    project_id: "grust".to_string(),
    allocation_percent: 80,
})?;

let graph = builder.build();

```

Validation fails before graph construction. If `allocation_percent` is 0, the `range(min = 1, max = 100)` rule produces a Grust schema error and the edge is not added. This keeps invalid domain facts out of the graph rather than relying on a backend to reject them later.

Typed and Untyped Graphs Coexist

The typed layer is an ingestion layer over the ordinary `GraphBuilder`. It does not force an all-or-nothing choice. A graph can start as a document, accept raw nodes and edges, and then be extended with typed values:

```
let existing = Graph::new(
  vec![Node::new("Document", "doc:garde-proposal", Props::new()),
    Vec::new(),
];

let mut builder = TypedGraphBuilder::from_graph(existing);

builder.add_node(&Person {
  id: "nia".to_string(),
  name: "Nia".to_string(),
  skills: vec!["rust".to_string(), "graphs".to_string()],
})?;

builder.add_raw_edge(Edge::new(
  "AUTHORED",
  "person:nia",
  "doc:garde-proposal",
  Props::new(),
));

let graph = builder.build();
```

The coexistence API is explicit:

- `TypedGraphBuilder::from_graph(graph)` starts from an existing `Graph`.
- `TypedGraphBuilder::from_builder(builder)` starts from an existing `GraphBuilder`.
- `add_raw_node(node)` and `add_raw_edge(edge)` add ordinary Grust values.
- `into_builder()` returns the inner `GraphBuilder` when lower-level builder operations are needed.




Figure 3: Diagram 3

This is useful during migrations. A project can keep loading existing graph documents while adding typed definitions for the domain facts that benefit most from Rust validation. Over time, more labels can move to typed constructors without breaking the storage or document formats.

What Zod Means Here

Zod is best known from TypeScript. It lets developers define a runtime schema and validate untrusted input before treating it as application data. In TypeScript, this closes an important gap: static types disappear at runtime, so a value received from JSON, an HTTP request, a form, or a message queue still needs runtime validation.

Rust has a different type system, but the boundary problem still exists. External data arrives as bytes or JSON. Serde can deserialize those bytes into a Rust struct, but it is often useful to separate two questions:

1. Does this JSON have the expected shape?
2. Does the resulting Rust value satisfy my domain rules?

zod-rs answers the first question. garde answers the second. Grust's typed-zod-rs feature wires those stages together:

```

use grust::prelude::*;
use serde::{Deserialize, Serialize};
use serde_json::json;
use zod_rs::prelude::{Schema, number, object, string};

#[derive(Debug, Deserialize, Serialize, garde::Validate)]
#[garde(allow_unvalidated)]
struct Person {
    #[garde(length(min = 1))]
    id: String,
    #[garde(length(min = 1))]

```

```

    name: String,
    #[garde(length(min = 1), inner(length(min = 1)))]
    skills: Vec<String>,
}

impl TypedNode for Person {
    const LABEL: &'static str = "Person";

    fn node_id(&self) -> NodeId {
        format!("person:{}", self.id).into()
    }
}

let person_schema = object()
    .field("id", string().min(1))
    .field("name", string().min(1))
    .field("skills", string().min(1).array())
    .strict();

let json = json!({
    "id": "nia",
    "name": "Nia",
    "skills": ["rust", "graphs"]
});

let person: Person = parse_typed_json(&person_schema, &json)?;

```

The same schema can feed the graph builder directly:

```

let mut builder = TypedGraphBuilder::new();
builder.add_node_from_json::<Person, _>(&person_schema, &json)?;

```

For edges, the pattern is the same:

```

#[derive(Debug, Deserialize, Serialize, garde::Validate)]
#[garde(allow_unvalidated)]
struct WorksOn {
    #[garde(length(min = 1))]
    person_id: String,
    #[garde(length(min = 1))]
    project_id: String,
    #[garde(range(min = 1, max = 100))]
    allocation_percent: u8,
}

impl TypedEdge for WorksOn {
    const LABEL: &'static str = "WORKS_ON";

    fn from_node_id(&self) -> NodeId {
        format!("person:{}", self.person_id).into()
    }

    fn to_node_id(&self) -> NodeId {
        format!("project:{}", self.project_id).into()
    }
}

let works_on_schema = object()

```

```

        .field("person_id", string().min(1))
        .field("project_id", string().min(1))
        .field("allocation_percent", number().int().min(1.0).max(100.0))
        .strict();

builder.add_edge_from_json::<WorksOn, _>(
    &works_on_schema,
    &json!({
        "person_id": "nia",
        "project_id": "grust",
        "allocation_percent": 80
    })),
)?;

```

The adapter intentionally deserializes the original JSON after zod-rs accepts it. This preserves Rust integer types. For example, zod-rs validates numbers through a floating-point schema, but Serde should still be allowed to decode the original JSON integer 80 into a Rust u8.

How the Options Interact

There are four common construction paths:

Raw GraphBuilder:

trusted Rust code -> Node/Edge -> Graph

Graph documents:

YAML/JSON/XML -> Graph::from_* validation -> Graph

typed-garde:

Rust struct -> garde validation -> TypedNode/TypedEdge lowering -> Graph

typed-zod-rs:

raw JSON -> zod-rs shape validation -> Serde -> garde validation -> Graph

Choose GraphBuilder when the data is already trusted Rust code and the dynamic graph model is enough. Choose graph documents when you need readable fixtures, interchange files, or migration inputs. Choose typed-garde when the domain model lives in Rust structs and should enforce Rust-level invariants. Choose typed-zod-rs when the input is untrusted JSON and you want a separate shape gate before Serde and garde.

These options compose. A single graph can contain nodes loaded from YAML, raw edges added by GraphBuilder, typed nodes validated by garde, and request payloads validated first by zod-rs. The result is still just Graph.

The distinction between zod-rs and garde is worth keeping crisp:

- zod-rs sees `serde_json::Value`.
- Serde converts JSON into Rust types.
- garde sees Rust fields with Rust types.
- TypedNode and TypedEdge convert validated Rust values into Grust labels, ids, endpoints, and properties.

For example, this JSON fails at the zod-rs stage because `skills` is not an array:

```

{
  "id": "nia",
  "name": "Nia",

```

```
"skills": "rust"
}
```

This JSON can pass a loose zod-rs shape check but fail at the garde stage if the Rust type requires at least two skills:

```
{
  "id": "nia",
  "name": "Nia",
  "skills": ["rust"]
}
```

That separation gives application authors precise error boundaries. Shape errors usually belong near the API or file-ingest boundary. Domain errors belong near the typed model.

Relationship to GraphSchema

GraphSchema and typed ingestion solve different problems. GraphSchema describes graph labels, fields, uniqueness, and backend-facing metadata. It can drive indexes, migrations, table layouts, or validation inside a store. Typed ingestion validates values before they become graph data.

In practice they can reinforce each other:

- TypedNode and TypedEdge keep application construction honest.
- zod-rs schemas protect JSON ingress points.
- GraphSchema tells storage backends what structure to expect.
- GraphStore remains the common persistence contract.

This layered design keeps Grust from becoming either too loose or too rigid. Projects can start with raw graph construction, add typed Rust validation for important labels, add zod-rs for JSON ingress, and later add GraphSchema for backend optimization.

The same schema can also validate and write in one step:

```
let report = store.put_typed_graph(&schema, &graph).await?;
```

That call validates labels, required fields, field value types, and edge endpoint labels before delegating to the backend. Schema-capable stores then use `apply_schema` to lower the portable model into their native storage surfaces.

5. Traversal as an Intermediate Representation

Grust traversal is not Cypher, SQL, GQL, SurrealQL, Spark SQL, or a graph database dialect. It is a small Rust intermediate representation:

```
let traversal = Traversal::from_node("talk:rust-graph-api")
  .out("PRESENTED_BY")
  .to("Person")
  .limit(10);
```

A traversal has a start expression, a sequence of steps, and an optional limit. The start can be a single node, all nodes with a label, or nodes with a property value. Each step has a direction, an optional edge label, and an optional target node label.




Figure 4: Diagram 4

The IR is deliberately modest. That makes it implementable across a wide range of backends. The memory backend can scan maps. LanceDB can query tables by hop. pgGraph can lower to SQL over universal graph tables. Sail can lower to Spark SQL through Spark Connect. Backends that do not yet support reads can return `GrustError::Unsupported`.

This design also protects application code. A caller asks for a graph-shaped operation; the backend decides whether that operation becomes a map scan, a SQL join, a DataFrame query, a Redis graph command, or a future native graph query.

6. The Store Contract

The central backend trait is `GraphStore`:

```
#[async_trait::async_trait]
pub trait GraphStore: Send + Sync {
    async fn apply_schema(&self, schema: &GraphSchema) -> Result<()>;
    async fn put_node(&self, node: &Node) -> Result<NodeId>;
    async fn put_edge(&self, edge: &Edge) -> Result<Option<EdgeId>>;
    async fn put_graph(&self, graph: &Graph) -> Result<LoadReport>;
    async fn put_typed_graph(&self, schema: &GraphSchema, graph: &Graph) ->
Result<LoadReport>;
    async fn get_node(&self, id: &NodeId) -> Result<Option<Node>>;
    async fn get_edges(&self, query: EdgeQuery) -> Result<Vec<Edge>>;
    async fn traverse(&self, traversal: Traversal) -> Result<Vec<Node>>;
}
```

The trait is `async` because real graph stores usually cross a process, network, database, or object-store boundary. The `async_trait` crate hides the current limitations around `async` functions in object-safe traits and lets backend implementations present one uniform interface.

`put_graph` takes `&Graph` instead of consuming `Graph`. That keeps retry, audit, comparison, and multi-backend loading workflows straightforward:

```
let report = store.put_graph(&graph).await?;
backup_store.put_graph(&graph).await?;
println!("loaded {} nodes and {} edges", report.nodes, report.edges);
```

Administrative operations are split into `GraphAdminStore`:

```
#[async_trait::async_trait]
pub trait GraphAdminStore: GraphStore {
    async fn bootstrap(&self) -> Result<()> { Ok(()) }
    async fn clear(&self) -> Result<()>;
}
```

This separation keeps ordinary application persistence apart from setup and destructive workflows. A production service may receive a `GraphStore`, while a test harness or migration tool can require `GraphAdminStore`.

7. Rust Concepts Used

Grust is a good example of idiomatic Rust applied to a storage abstraction.

Newtypes give semantic weight to strings. `NodeId`, `EdgeId`, and `Label` are cheap wrappers, but they prevent accidental parameter swaps and produce clearer APIs.

Trait-based polymorphism defines the backend boundary. Application code can be generic over `impl GraphStore`, while each backend owns its own connection, configuration, batching, serialization, and query strategy.

Feature flags keep the facade crate light. The public `grust` crate re-exports backend crates only when features such as `memory`, `lancedb`, `pggraph`, `sail`, `falkor`, `helix`, `surreal`, or `cocoindex` are enabled.

Serde makes the graph model portable. Core types derive `Serialize` and `Deserialize`, and backends can turn properties into JSON strings, JSONB, Arrow string columns, or target-state maps.

Interior mutability appears where it is appropriate. The memory backend stores its graph behind `Arc<RwLock<...>>`, making cloned stores share state while keeping mutation synchronized.

Error typing is explicit. `GrustError` distinguishes backend, schema, unsupported-feature, and serialization failures. That lets a caller tell the difference between “the database rejected this” and “this backend does not yet support traversal.”

8. Backend Architecture

Backends share the same input model but not the same execution model:




Figure 5: Diagram 5

Some backends are full read/write/traversal stores today. Others currently focus on writes and administrative loading. That is normal for an early multi-backend project, and the trait makes the maturity boundary explicit.

Memory

`grust-memory` is the deterministic local backend. It stores nodes in a `BTreeMap<NodeId, Node>` and edges in a `BTreeMap<(NodeId, Label, NodeId), Edge>`. Reads and traversals scan those maps. It is the best backend for tests, examples, and local workflows that need no external service. When a `GraphSchema` is applied, the memory backend validates writes against it, which makes it a useful conformance harness for typed storage behavior before a database enters the picture.

```

use grust::prelude::*;

# async fn demo(graph: Graph) -> grust::Result<()> {
let store = MemoryGraphStore::new();
store.put_graph(&graph).await?;

let people = store
    .traverse(
        Traversal::from_node("talk:rust-graph-api")
            .out("PRESENTED_BY")
            .to("Person"),
    )
    .await?;
# Ok(())
# }
  
```

LanceDB

grust-lancedb treats LanceDB first as a durable Arrow-native table store. It uses two tables, one for nodes and one for edges. Nodes are keyed by id. Edges are keyed by an explicit edge id when present, or by a deterministic from + label + to key otherwise. Writes use LanceDB merge_insert, and traversal performs hop-by-hop table queries.

This backend is a natural home for later vector-search extensions. The core GraphStore trait should stay graph-focused; LanceDB-specific nearest-neighbor search can live in an extension trait without leaking into every backend.

With GraphSchema, LanceDB also creates typed Arrow tables per node and edge label. The universal grust_nodes and grust_edges tables remain the portable read/traversal surface, while schema-labeled rows are mirrored into tables such as grust_node_person or grust_edge_presents with typed columns for declared fields. That gives analytical consumers and future vector extensions a native columnar surface without giving up the backend-neutral graph model.

pgGraph

grust-pggraph stores the source of truth in ordinary PostgreSQL tables:

```
grust_nodes(id text primary key, label text not null, props jsonb not null)
grust_edges(id text, from_id text not null, to_id text not null,
            label text not null, props jsonb not null)
```

The backend can bootstrap the graph extension, create tables and indexes, register graph tables, and optionally build the pgGraph projection. Reads use SQL against the universal tables. Traversal is lowered to SQL joins over those tables, with pgGraph projection support available as the backend matures.

Schema application adds typed label views and expression indexes. For example, a Person node schema with name: String and age: Int can produce a grust_node_person view over the universal node table, with age exposed as a bigint expression. This is a deliberately incremental typed-storage path: PostgreSQL keeps the flexible JSONB source of truth while callers that know the schema get typed SQL surfaces.

Sail

grust-sail connects to a Sail Spark Connect server over gRPC. It stores graph data in Spark DataFrames backed by Delta tables. Commands such as table creation and MERGE INTO are sent as Spark Connect command plans; reads are sent as SQL relation plans and decoded from Arrow IPC streams.

The implementation has an important practical detail: edge rows carry source and destination labels as well as IDs. That allows traversal joins to match node labels without an extra lookup during each edge hop.

When a schema is applied, Sail creates typed Delta tables per node and edge label and mirrors writes into them with MERGE INTO. The universal Spark tables keep traversal simple and portable; the typed tables make declared graph labels available as ordinary Spark columns.

FalkorDB, HelixDB, and SurrealDB

The FalkorDB backend writes through Redis GRAPH.QUERY using Cypher-like MERGE statements. It batches nodes by label path and edges by relationship type. Schema application creates label/property indexes for declared node types.

The HelixDB backend has HTTP and SDK stores. Both support batched writes; reads and traversal currently report unsupported operations. The current schema hook validates that labels, relationships, and fields can be safely lowered through the dynamic-query path; backend-native schema-file generation can build on that same GraphSchema contract later.

The SurrealDB backend also has HTTP and SDK stores. It can bootstrap, clear, upsert nodes, and relate edges. Like Helix today, read and traversal support is not yet implemented. Applying a schema lowers node and edge declarations to Surreal `DEFINE TABLE` and `DEFINE FIELD` statements so the backend can run in schemafull mode where the schema calls for it.

CocoIndex

grust-cocoindex is intentionally not an ordinary GraphStore. CocoIndex is an incremental target-state system, so the Grust integration exports a graph as serializable node and relationship state:

```
let export = graph.to_cocoindex_export()?;
```

The export uses Grust node IDs as target keys, converts properties to JSON, and requires edge endpoints to exist in the graph so relationship source and target labels can be emitted.

9. Example: A Conference Graph

Here is a complete graph-building example:

```
use grust::prelude::*;

fn conference_graph() -> Graph {
    let mut g = Graph::builder();

    let rust = g
        .node("Conference", "conf:rust-graph-day")
        .prop("name", "Rust Graph Day")
        .prop("city", "San Francisco")
        .finish();

    let talk = g
        .node("Talk", "talk:backend-neutral-graphs")
        .prop("title", "Backend-Neutral Graphs in Rust")
        .prop("track", "systems")
        .finish();

    let ada = g
        .node("Person", "person:ada")
        .prop("name", "Ada Example")
        .prop("role", "speaker")
        .finish();

    g.edge("HAS_TALK", &rust, &talk).finish();
    g.edge("PRESENTED_BY", &talk, &ada)
        .prop("confirmed", true)
        .finish();

    g.build()
}
```

The resulting graph can be loaded into memory, exported to CocoIndex target state, or sent to a configured backend:


```
# use grust::prelude::*;
# async fn load<S: GraphStore>(store: &S, graph: Graph) -> grust::Result<()> {
let report = store.put_graph(&graph).await?;
assert_eq!(report.nodes, 3);
assert_eq!(report.edges, 2);
# Ok(())
# }
```

The same graph can be loaded through the typed backend path by declaring the schema and using `put_typed_graph`:

```
# use grust::prelude::*;
# async fn typed_load<S: GraphStore>(store: &S, graph: Graph) -> grust::Result<()> {
let schema = GraphSchema::builder()
    .node(
        "Conference",
        vec![
            Field::required("name", FieldType::String),
            Field::required("city", FieldType::String),
        ],
    )
    .node(
        "Talk",
        vec![
            Field::required("title", FieldType::String),
            Field::required("track", FieldType::String),
        ],
    )
    .node(
        "Person",
        vec![
            Field::required("name", FieldType::String),
            Field::required("role", FieldType::String),
        ],
    )
    .edge(
        "HAS_TALK",
        vec![Label::new("Conference")],
        vec![Label::new("Talk")],
        Vec::<Field>::new(),
    )
    .edge(
        "PRESENTED_BY",
        vec![Label::new("Talk")],
        vec![Label::new("Person")],
        vec![Field::required("confirmed", FieldType::Bool)],
    )
    .build();

let report = store.put_typed_graph(&schema, &graph).await?;
assert_eq!(report.nodes, 3);
assert_eq!(report.edges, 2);
# Ok(())
# }
```

That call checks node labels, edge labels, required fields, field types, and edge endpoint labels before writing. Backends then use the same schema in their own way: memory validates, LanceDB mirrors

into typed Arrow tables, Sail mirrors into typed Delta tables, pgGraph exposes typed SQL views and indexes, SurrealDB defines schemafull tables and fields, and FalkorDB creates useful indexes.

Traversing from a conference to speakers becomes a backend-neutral expression:

```
let speakers = store
  .traverse(
    Traversal::from_node("conf:rust-graph-day")
      .out("HAS_TALK")
      .to("Talk")
      .out("PRESENTED_BY")
      .to("Person"),
  )
  .await?;
```




Figure 6: Diagram 6

10. Schema and Validation Direction

Grust has schema types: `GraphSchema`, `NodeType`, `EdgeType`, `Field`, `FieldType`, and `EdgeUniqueness`. `GraphSchema` validates labels, required fields, field value types, and edge endpoint labels. The default `GraphStore::apply_schema` implementation remains a no-op, which lets schemaless or schema-later backends work without ceremony.

Schema becomes more important for backends that want typed tables, indexes, or label-partitioned layouts. The current schema-capable backends use it in different ways:

- Memory stores the schema and validates local writes.
- FalkorDB creates label/property indexes for declared node types.
- Helix validates schema names that can be lowered through dynamic queries.
- LanceDB creates typed Arrow tables per node and edge label and mirrors writes into them.
- pgGraph/PostgreSQL exposes typed label views and expression indexes over the universal tables.
- Sail creates typed Delta tables per node and edge label and mirrors writes into them.
- SurrealDB lowers schema into `DEFINE TABLE` and `DEFINE FIELD` statements.

A flexible backend can keep universal node and edge tables as the portable interchange surface. A typed backend can add native tables, fields, indexes, or constraints behind the same `GraphStore` trait.

The key architectural point is that schema is metadata about a Grust graph, not a replacement for the graph. Application code can begin with plain graph construction, add schemas when operational needs demand it, and still speak the same store trait.

11. Design Tradeoffs

The universal node/edge layout appears in multiple backend plans because it is the easiest way to preserve arbitrary property graphs:




Figure 7: Diagram 7

The cost is that property typing and label-specific optimization require extra work. A label-partitioned backend can use stronger types and better indexes, but it needs schema, migrations, and more planning.

Grust’s current architecture keeps both paths open. Core stays universal. Backends choose their storage layout. Schema support can become richer without forcing every backend to look the same.

12. Where Grust Can Grow

The next natural step is to deepen read and traversal support across the write focused backends. FalkorDB, HelixDB, and SurrealDB already have enough write surface to load graphs; adding reads would make them more symmetric with memory, LanceDB, pgGraph, and Sail.

Traversal can also grow carefully. Property filters, bounded depth, path returns, shortest paths, and aggregation are all tempting. The important rule is to extend the IR only when several backends can implement the concept without smuggling database-specific query strings through the abstraction.

Incremental mutation is another likely addition. A dedicated mutation trait could express upsert and delete operations directly:

```

pub enum GraphMutation {
    UpsertNode(Node),
    DeleteNode(NodeId),
    UpsertEdge(Edge),
    DeleteEdge {
        id: Option<EdgeId>,
        from: NodeId,
        label: Label,
        to: NodeId,
    },
}

```

That would serve CocoIndex-style target-state systems, streaming pipelines, and ordinary applications that need to apply deltas instead of replacing whole graphs.

Conclusion

Grust is small by design. Its core model is easy to hold in your head, and its backend contract is narrow enough that very different systems can implement it. That is the source of its leverage.

The project says: build your graph once, keep the domain model in Rust, and let the backend translate. Sometimes that translation is a map scan. Sometimes it is Arrow and LanceDB. Sometimes

it is PostgreSQL, Spark SQL, Redis graph commands, SurrealQL, Helix SDK calls, or CocoIndex target state.

The more Grust grows, the more important that center becomes: a stable property graph model, a backend-neutral traversal IR, explicit errors, feature-gated integrations, and enough Rust type structure to make the right path feel natural.