

CSC301 HW1

Alex Zhang

Januray 2023

1 Question 1

1.1 (a)

Based on the formula, $g(n) = \sum_{k=0}^n r^k = \frac{1-r^{n+1}}{1-r}$, for $r < 1$. Then

$$g(n) = \frac{1-r^{n+1}}{1-r} \leq \frac{1}{1-r}$$

since $r^{n+1} \geq 0$ when $r \geq 0$. We can then assume that $\exists c$ which $c = \frac{1}{1-r}$ because r is a constant and $\exists N$ where $N = 1$. So,

$$g(n) \leq c \cdot 1$$

for all $n \geq N$, then

$$g(n) = O(1)$$

1.2 (b)

When $r = 1$, $g(n)$ will be $1 + 1 + 1^2 + \dots + 1^n$

$$g(n) = 1 \cdot n = n$$

So, there exists $c = 10$, $N = 1$ such that

$$g(n) \leq 10 \cdot n$$

for all $n \geq N$, then

$$g(n) = O(10n)$$

The time complexity for $g(n)$ when $r = 1$ will be $O(n)$.

1.3 (c)

When $r > 1$, the formula for finite geometric series sum will be $\frac{r^{n+1}-1}{r-1}$. Then,

$$g(n) = \frac{r^{n+1} - 1}{r - 1} \leq \frac{r^{n+1}}{r - 1}$$

We can assume that there exists a $c = \frac{1}{r-1}$, because r is a constant so $1/r - 1$ will also be a constant and exists $N = 1$. This satisfies that

$$g(n) \leq c \cdot r^{n+1}$$

for all $n \geq N$, then

$$g(n) = O(r^{n+1})$$

The time complexity for $g(n)$ when $r > 1$ will be $O(r^n)$.

2 Question 2

2.1 (a)

```
public static void main(String[] args) {
    int[] test = new int[2];
    test = divide(0b1011, 0b10);
    System.out.println("the quotient will be: " + test[0]);
    System.out.println("the remainder will be: " + test[1]);
}

static int[] divide(int x, int y){
    int[] ans = new int[2];
    if(x == 0)
        return ans;
    ans = divide(x / 2, y);
    ans[0] *= 2;
    ans[1] *= 2;

    if(x % 2 == 1)
        ans[1] += 1;
    if(ans[1] > y || ans[1] == y){
        ans[1] -= y;
        ans[0] += 1;
    }
    return ans;
}
```

My input for x is 1011 and y is 10 in binary. For line

```

    if(x == 0)
        return ans;

```

This happens in the last recursion call when $x = 0, y = 10$, and it will return the array. For lines

```

    ans = divide(x / 2, y);
    ans[0] *= 2;
    ans[1] *= 2;

```

The first line is doing the recursion and the rest will execute in every recursion. This condition

```

    if(x % 2 == 1)
        ans[1] += 1;

```

will be true when $x = 1, 101, 1011$ since they are all odd numbers. The last condition

```

    if(ans[1] > y || ans[1] == y){
        ans[1] -= y;
        ans[0] += 1;
    }

```

will execute when $x = 10, 1011$ which the remainder will be 10 and 100 respectively.

2.2 (b)

The base case will be $x = 0$ and y is an arbitrary number. Base case is true since the algorithm will return $q = 0, r = 0$, which satisfies

$$0 = 0 \cdot y + 0 \text{ with } 0 \leq r < y$$

For induction case, assume that $x = n$ is true for an arbitrary y , which satisfies

$$n = q \cdot y + r \text{ with } 0 \leq r < y$$

For $x = n + 1$,

$$n + 1 = q \cdot y + r + 1$$

If $r + 1$ still smaller than y , in this case, the division still holds true. If $r + 1 = y$, by algorithm, $q' = q + 1$, and $r + 1 - y = 0$. So

$$n + 1 = q' \cdot y + 0 \text{ with } 0 \leq r < y$$

which is also true.

Overall, the algorithm is correct proving by induction. ■

3 Question 3

By definition, $x \equiv y \pmod N$ if and only if N divides $x - y$. In question since $x \equiv x' \pmod N$, and $y \equiv y' \pmod N$, equivalently,

$$x - x' = N \cdot k$$

$$y - y' = N \cdot l$$

for $k, l \in \mathbb{Z}$

Then $x = N \cdot k + x'$, $y = N \cdot l + y'$, and

$$xy = (N \cdot k + x')(N \cdot l + y')$$

$$xy = N^2kl + Nky' + Nlx' + x'y'$$

$$xy = N(Nkl + ky' + lx') + x'y'$$

Take the mod N for both sides,

$$xy \equiv x'y' \pmod N$$

The substitution rule for modular multiplication is true. ■