

THE UNIVERSITY OF QUEENSLAND
AUSTRALIA

Privacy-Preserving Federated Learning for Distributed Skin Disease Classification

by
ALEX GU

under the supervision of
RUIHONG QIU
ZI (HELEN) HUANG

Use of AI Statement

I acknowledge the use of generative AI tools in completing this assessment. Details of which tools were used and how they were used are provided in the table below, along with appropriate in-text and full references. I take responsibility for critically evaluating and integrating the AI-generated content, and ensuring it adheres to academic integrity standards.

Have you used AI to

- Explore your topic? Yes – discussed federated learning and privacy concepts with Claude to build understanding
- Define your research question? No – research question was defined through meetings with supervisors
- Assist with your literature review? Yes – used Claude to generate notes, verified against originals
- Assist with formatting the answers presented here? Yes – used Claude for LaTeX troubleshooting
- Other aspects of your work? Yes – feedback on writing voice and tone

AI Model and date	Table 1. AI tool usage (tick all that apply)								
	Language Translation	Grammar / style / spelling	Topic exploration	Research question	Literature review	Content Creation visual (formatting)	Content Creation (e.g. code, text)	Feedback	Other (provide details)
Claude Opus 4.6 09/03/2026-17/03/2026			✓		✓	✓			
Claude Opus 4.6 17/03/2026-24/04/2026					✓	✓		✓	

Abstract

Skin disease classification using deep learning has shown strong potential but training accurate models requires large, diverse datasets often distributed across healthcare institutions. Privacy regulations such as the Health Insurance Portability and Accountability Act (HIPAA) and the General Data Protection Regulation (GDPR) prevent centralised data aggregation. Prior work has shown that even sharing model updates rather than raw data can leak sensitive patient information. Federated learning offers a framework for collaborative training across distributed nodes without centralising data, but standard federated averaging lacks convergence guarantees. This project evaluates federated learning approaches for multi-class skin disease classification in a simulated distributed healthcare environment. Skin disease image datasets totalling over 200,000 images across multiple diagnostic classes will be partitioned across multiple nodes. FedAvg and FedProx will be implemented and compared against a centralised training baseline, evaluating classification accuracy, communication efficiency, and model behaviour under data that is not independently and identically distributed (non-IID). The findings of this project will provide guidance for selecting and configuring federated learning for medical image classification tasks in privacy-constrained distributed settings.

Contents

Use of AI Statement ii

Abstract iv

List of Figures vi

List of Tables vii

1 Introduction 1

2 Background and Literature review 2

2.1 Skin Disease Classification with Deep Learning . . . 2
2.2 Federated Learning . . . 2
2.3 Handling Non-IID Data in Federated Learning . . . 4
2.4 Privacy in Federated Learning . . . 5
2.5 Federated Learning in Medical Imaging . . . 5
2.6 Summary and Knowledge Gap . . . 6

3 Project Plan 7

3.1 Project Aims . . . 7
3.2 Methodology . . . 7
3.2.1 Dataset . . . 7
3.2.2 Centralised Baseline . . . 8
3.2.3 Federated Learning . . . 8
3.2.4 Evaluation . . . 9
3.3 Milestones and Timeline . . . 10
3.3.1 Semester 1 . . . 10
3.3.2 Semester 2 . . . 10
3.3.3 High-risk Milestones . . . 11
3.4 Risk Assessment . . . 13
3.5 Ethics . . . 14

List of Figures

2.1 Overview of the federated learning pipeline 3

3.1 Project timeline showing major tasks across both semesters. 12

List of Tables

3.1 Summary statistics of the datasets used in this project. 8
3.2 Project risks and mitigation strategies. 13

1. Introduction

Skin diseases are among the most common health conditions worldwide [1] and deep learning has demonstrated strong performance in skin disease classification from images [2]. However, training models that generalise well requires diverse data across patient demographics and imaging setups. In practice this data sits in separate hospitals and research groups, each with a relatively small local dataset. Privacy regulations including the Health Insurance Portability and Accountability Act (HIPAA) and the General Data Protection Regulation (GDPR) restrict the centralisation of patient data [3], preventing the ability to build robust classifiers through conventional centralised training.

Federated learning addresses this by enabling multiple institutions to collaboratively train a shared model without exchanging raw data. Each participant trains on its local dataset and shares only model updates with a central server, which aggregates them into a global model. McMahan et al. introduced Federated Averaging (FedAvg), which reduces communication costs by performing multiple local training epochs before aggregation [4]. However, FedAvg lacks convergence guarantees when data across participants is not independently and identically distributed (non-IID), a condition that is common in healthcare settings where different institutions may see different patient demographics and disease distributions. FedProx extends FedAvg by introducing a proximal term that constrains local model updates, providing convergence guarantees under heterogeneous conditions [5]. Furthermore, federated learning alone does not fully resolve privacy concerns. Prior work has shown that shared model updates can leak sensitive information, and additional mechanisms may be needed [3].

This project evaluates federated learning for multi-class skin disease classification in a simulated distributed healthcare environment. Skin disease image datasets totalling over 200,000 images across multiple diagnostic classes will be partitioned across multiple nodes. FedAvg and FedProx will be implemented and compared against a centralised training baseline, evaluating classification accuracy and communication efficiency under non-IID data distributions.

The remainder of this proposal is organised as follows. Chapter 2 provides background on federated learning and associated heterogeneity and privacy considerations. Chapter 3 outlines the project plan including methodology and milestones.

2. Background and Literature review

2.1 Skin Disease Classification with Deep Learning

Skin diseases are among the most prevalent health conditions globally, affecting hundreds of millions of people and contributing significantly to the global burden of disease [1]. Accurate and timely diagnosis is critical for effective treatment, but access to dermatological expertise is limited in many regions. This has motivated research into automated classification systems that can assist clinicians by analysing images of skin conditions.

Deep learning, particularly convolutional neural networks (CNNs), has demonstrated strong performance in this domain. Esteva et al. [2] showed that a CNN trained on a large dataset of clinical images could classify skin cancer at a level comparable to board-certified dermatologists, establishing deep learning as a viable tool for skin disease diagnosis. Since then, the field has benefited from the availability of large public datasets such as HAM10000, a collection of 10,015 dermatoscopic images spanning seven diagnostic categories [6]. These datasets have enabled accelerated progress in automated skin disease classification.

The remaining bottleneck is data access. Generalisation across skin tones and imaging hardware requires broader datasets than any single institution holds. In practice, such data is distributed across hospitals and associated health and research institutions, and privacy regulations prevent its centralisation.

2.2 Federated Learning

Federated learning offers a solution for training machine learning models across distributed data sources without centralising the data itself. McMahan et al. [4] introduced Federated Averaging (FedAvg) which frames the learning problem as minimising a global objective function across K clients:

$$\min_{w} f(w) = \sum_{k=1}^{K} \frac{n_k}{n} F_k(w) \tag{2.1}$$

where w are the model parameters, $F_k(w)$ is the local objective function for client k, n_k is the number of data points held by client k, and n is the total number of

data points across all clients. Each client's contribution to the global objective is weighted by the proportion of data it holds. Figure 2.1 illustrates this process.




Figure 2.1: Overview of the federated learning pipeline

In each communication round, the server distributes the current global model w^t to a subset of clients. Each selected client initialises its local model with w^t and performs E epochs of stochastic gradient descent on its local data, producing updated parameters w_k^{t+1}. The server then aggregates these updates by computing a weighted average:

$$w^{t+1} = \sum_{k=1}^{K} \frac{n_k}{n} w_k^{t+1} \tag{2.2}$$

By performing multiple local training epochs before communication, FedAvg significantly reduces communication costs compared to approaches that require gradient updates after every training step.

Li et al. [7] surveyed the main challenges. 1) Communication costs are high when bandwidth is limited or models are large. 2) Participating devices vary in compute and connectivity. 3) Data across nodes is usually non-IID. 4) Shared updates can still leak information about training data.

2.3 Handling Non-IID Data in Federated Learning

Data distributions across participating nodes are rarely uniform. When each node holds data that is non-IID, local models trained on these subsets may diverge significantly from one another. Averaging such divergent models can produce a global model that performs poorly compared to one trained on centralised data.

FedAvg is particularly susceptible to this problem as it provides no way to limit how far local models can deviate from the global model during local training. Li et al. [5] proposed FedProx to address this limitation. FedProx modifies the local objective function by adding a proximal term:

$$\min_w h_k(w; w^t) = F_k(w) + \frac{\mu}{2}|w - w^t|^2 \tag{2.3}$$

where $F_k(w)$ is the local loss, w^t is the current global model and μ controls the strength of the penalty. This term penalises large deviations from the current global model. This modification provides convergence guarantees under heterogeneous data distributions, which FedAvg lacks. FedProx also accommodates systems heterogeneity by allowing nodes to perform variable amounts of local computation.

Other approaches have been proposed to tackle non-IID issues. Karimireddy et al. [8] introduced SCAFFOLD, which uses control variates to correct for the drift in local updates. This reduces the variance caused by heterogeneous data. Wang et al. [9] proposed Federated Matched Averaging (FedMA), which aligns neurons across local models before averaging. This prevents neurons in different local models from learning equivalent features in different positions. Wang et al. [10] proposed FedNova, which normalises local updates to account for differences in the number of local training steps, correcting an inconsistency in FedAvg that is amplified under heterogeneous conditions. While this project focuses on FedAvg and FedProx, these alternative approaches provide context for understanding the breadth of strategies available for handling non-IID data in federated settings.

To evaluate federated learning methods under heterogeneous conditions, a consistent experimental method is required for simulating non-IID data splits. A widely adopted approach, introduced by Hsu et al. [11], is to partition data across clients using a Dirichlet distribution over class labels, parameterised by a concentration parameter α. Lower values of α produce more skewed label distributions across clients while higher values approach IID. This provides a controllable and reproducible way to study model behaviour across a wide range of heterogeneous conditions.

2.4 Privacy in Federated Learning

Federated learning avoids sharing raw data but this alone does not guarantee privacy. Kaissis et al. [3] noted that the model updates transmitted during training can be exploited to infer information about the underlying data. Model inversion attacks use model outputs or gradients to reconstruct approximations of training inputs [12]. Membership inference attacks determine whether a specific data point was in the training set by analysing the model's response to that input [13].

Several defence mechanisms have been proposed to strengthen privacy in federated learning. Bonawitz et al. [14] designed a practical secure aggregation protocol using pairwise masking to protect each participant's contribution. This enables the server to compute the sum of client updates without observing any individual update. This protocol is robust to client dropout, making it suitable for real-world deployments. Differential privacy provides a complementary approach by adding calibrated noise to the data or model updates to limit the information that can be inferred about any individual training example. Dwork et al. [15] established the formal foundations of differential privacy, while Abadi et al. [16] introduced DP-SGD, a training procedure that clips per-example gradients and adds noise during optimisation which enables deep learning models to be trained with formal privacy guarantees. These mechanisms can be combined with federated learning to provide stronger privacy protections, though they often introduce trade-offs with model accuracy.

2.5 Federated Learning in Medical Imaging

Federated learning has attracted significant interest in medical imaging, where data is inherently distributed across institutions and subject to strict privacy requirements. Rieke et al. [17] outlined the potential of federated learning to enable collaborative model development across hospitals without centralising patient data, identifying it as a key enabler for the future of digital health. They noted that the heterogeneity of clinical data, arising from differences in imaging equipment, protocols, and patient demographics makes the non-IID problem particularly important in this domain.

Sheller et al. [18] demonstrated that federated learning could be applied to brain tumour segmentation across multiple institutions. They achieved performance comparable to centralised training while keeping patient data local. Their work provided early evidence that federated learning is viable in medical imaging tasks with complex, heterogeneous data. More recently, Dayan et al. [19] conducted one of the

largest federated learning studies to date, training a model to predict clinical outcomes in COVID-19 patients across 20 institutions worldwide. Their model outperformed any single-institution model, which justifies federated learning in practice.

2.6 Summary and Knowledge Gap

The preceding sections have reviewed the relevant literature across skin disease classification, federated learning, non-IID data handling, privacy mechanisms, and federated learning in medical imaging. Several key gaps emerge from this review:

1. **Limited evaluation of federated learning for multi-class skin disease classification.** Federated learning has been applied successfully in medical imaging, but primarily in radiology and pathology tasks with binary or few-class classification. Its performance on fine-grained, multi-class skin disease tasks with 20 or more classes has not been systematically studied.

2. **Insufficient comparison of federated algorithms under realistic non-IID conditions.** While FedProx was designed to address the non-IID limitations of FedAvg, direct comparisons between the two on medical imaging tasks with realistic heterogeneity remain scarce. Most evaluations use standard benchmarks rather than domain-specific datasets where class imbalance and label skew occur.

3. **Lack of practical guidance on federated learning trade-offs for clinical imaging.** Existing studies report accuracy but often do not systematically evaluate communication efficiency or per-class performance alongside non-IID sensitivity. Understanding these trade-offs is essential for informing whether federated learning is practical for real-world deployment.

This project addresses these gaps by evaluating FedAvg and FedProx on 30-class skin disease datasets to simulate realistic data heterogeneity. By comparing these approaches against a centralised baseline on classification accuracy, communication efficiency, and behaviour under non-IID distributions, this project aims to provide practical insight into the suitability of federated learning for fine-grained medical image classification.

3. Project Plan

3.1 Project Aims

Based on the knowledge gaps identified in the preceding chapter, this project has the following aims:

- Train a centralised ResNet classifier on ∼20,000 images across 30 classes to establish an upper-bound benchmark
- Run FedAvg and FedProx on the same data, partitioned into IID and Dirichlet non-IID splits across simulated clients.
- Report how each federated method degrades from the centralised baseline as heterogeneity increases, and what it costs in communication rounds.

3.2 Methodology

This project follows a three-stage experimental pipeline: centralised baseline training, federated learning implementation, and comparative evaluation. All experiments will be implemented in Python using PyTorch.

3.2.1 Dataset

Two publicly available skin disease image datasets from Kaggle will be used. The first, the Skin Diseases and Cancer Comprehensive Dataset, contains approximately 13,000 images across 24 diagnostic classes [20]. The second, a larger balanced skin disease dataset, contains approximately 262,000 images across 34 classes [21]. Table 3.1 summarises the two datasets. The final dataset composition will be determined during implementation; options include using either dataset independently, merging them with a unified class mapping, or using a subsampled combination to manage compute requirements. Images will be resized to a uniform resolution and normalised to standardise input across all experiments. Standard data augmentation techniques such as random horizontal flipping, rotation, and colour jittering will be applied during training to improve generalisation. The dataset will be split into training, validation, and test sets, with the test set held centrally and kept consistent across all experiments to ensure fair comparison.

Table 3.1: Summary statistics of the datasets used in this project.

Property	**Dataset 1**	**Dataset 2**
Name	Skin Diseases + Cancer	Massive Skin Disease
Source	Kaggle	Kaggle
Total images	∼13,000	∼262,000
Number of classes	24	34
Image type	Clinical photographs	Clinical photographs
Class balance	Imbalanced	Balanced

3.2.2 Centralised Baseline

A ResNet-18 architecture pre-trained on ImageNet will be used as the primary classification model across all experiments, selected for its established performance in image classification tasks [22]. If compute resources permit, ResNet-50 will also be evaluated to assess the impact of model capacity on classification performance. The baseline will be trained on the full training set in a standard centralised setting, with all data aggregated on a single machine. This represents an upper bound on classification performance. Training will use stochastic gradient descent with momentum, with learning rate, batch size, and number of epochs tuned on the validation set. To account for variability, experiments will be repeated across multiple random seeds and results reported as mean and standard deviation.

3.2.3 Federated Learning

The training set will be partitioned across K simulated client nodes to replicate a distributed healthcare environment. Two partitioning strategies will be used. In the IID setting, data will be distributed uniformly at random across clients, ensuring each client holds a roughly representative subset. In the non-IID setting, a Dirichlet distribution with concentration parameter α will be used to create heterogeneous label distributions across clients, where lower values of α produce greater skew [11]. Multiple values of α (for example, $\alpha \in \{0.1, 0.5, 1.0\}$) will be tested to evaluate model behaviour under varying degrees of heterogeneity. The inherent class imbalance in the dataset will be considered when designing the partitioning, as it interacts with the label skew introduced by non-IID splits.

FedAvg and FedProx will each be implemented following the procedures described in Chapter 2. The same ResNet-18 architecture and preprocessing pipeline used in

the centralised baseline will be applied to ensure that differences in performance are attributable to the training method rather than the model.

In each communication round, a fraction $C = 0.5$ of $K = 10$ clients will be selected to participate. Each selected client will train on its local data for $E = 5$ local epochs with batch size $B = 32$, then send its updated model parameters to the central server for aggregation.

For FedProx, the proximal term weight μ will be tuned over $\mu \in \{0.001, 0.01, 0.1, 1.0\}$ using the validation set. This allows assessment of its impact under different levels of regularisation.

Training will run for up to $T = 100$ communication rounds. Early stopping will be applied based on validation performance.

3.2.4 Evaluation

All approaches will be evaluated on the same held-out test set using the following metrics.

Classification accuracy. Overall top-1 accuracy on the test set, defined as:

$$\text{Accuracy} = \frac{\text{Number of correct predictions}}{\text{Total number of predictions}} \tag{3.1}$$

Per-class performance. Precision, recall, and F1-score per class to assess behaviour on individual classes, which is particularly important given dataset imbalance. For each class c:

$$\text{Precision}_c = \frac{TP_c}{TP_c + FP_c} \tag{3.2}$$

$$\text{Recall}_c = \frac{TP_c}{TP_c + FN_c} \tag{3.3}$$

$$F_{1,c} = 2 \cdot \frac{\text{Precision}_c \cdot \text{Recall}_c}{\text{Precision}_c + \text{Recall}_c} \tag{3.4}$$

where TP_c, FP_c, and FN_c denote the number of true positives, false positives, and false negatives for class c respectively.

Communication efficiency. The number of communication rounds required to reach a target accuracy, and the total volume of parameter data transmitted between

clients and server. For a model with $|w|$ parameters and T communication rounds with K_t participating clients in round t, the total communication cost is:

$$\text{Communication cost} = \sum_{t=1}^{T} K_t \cdot |w| \tag{3.5}$$

measured in the number of parameters transmitted (accounting for both upload and download).

Non-IID sensitivity. Accuracy as a function of the Dirichlet concentration parameter α, measuring how each method degrades under increasing data heterogeneity.

Results from FedAvg and FedProx will be compared against each other and against the centralised baseline across all metrics. All experiments will be repeated over multiple random seeds to ensure reported differences are statistically meaningful.

3.3 Milestones and Timeline

The project follows a structured timeline across both semesters of 2026, summarised in Figure 3.1.

3.3.1 Semester 1

The first half of the year focuses on laying the research and implementation foundations. The topic definition and proposal occupy the first eight weeks. Following the proposal submission, work shifts to implementing the dataset and preprocessing. This includes designing the data partitioning for IID and non-IID splits, as well as training the centralised baseline. FedAvg and FedProx implementations begin toward the end of Semester 1, carrying into the mid-year break.

3.3.2 Semester 2

The mid-year break is reserved for the main experimental phase. Here, FedAvg and FedProx will be run under IID and non-IID configurations across varying degrees of heterogeneity. Experiments continue into early Semester 2, overlapping with thesis writing. Thesis writing proceeds through the middle of Semester 2, with the poster prepared ahead of its deadline in Week 12. Final thesis revision and submission complete the project.

3.3.3 High-risk Milestones

Two milestones carry the most risk. The centralised baseline must achieve reasonable classification performance before federated comparisons become meaningful. If the baseline performs poorly, the project will need to revisit model architecture or dataset choices. The non-IID partitioning is similarly critical. If the splits fail to produce meaningful heterogeneity, differences between FedAvg and FedProx may not be observable. Both risks are mitigated by allocating early time to the baseline and partitioning before committing to the full experimental block.




Figure 3.1: Project timeline showing major tasks across both semesters.

3.4 Risk Assessment

Table 3.2 summarises the main risks to the project and the mitigation strategies in place.

Table 3.2: Project risks and mitigation strategies.

Risk	**Likelihood**	**Impact**	**Mitigation**
Centralised baseline underperforms, making federated comparisons uninformative	Medium	High	Allocate early time to baseline tuning. Revisit architecture or dataset choice if initial results are poor
Non-IID partitioning fails to produce meaningful heterogeneity	Low	High	Test multiple Dirichlet α values. Visualise label distributions across clients before running full experiments
Compute limitations restrict dataset size or number of experiments	Medium	Medium	Use a subsampled dataset for initial runs. Prioritise core experiments over ablations
Hyperparameter tuning does not yield stable results	Medium	Medium	Sweep key hyperparameters (e.g. learning rate, FedProx μ, number of local epochs) over reasonable ranges; fall back to values reported in the original papers
Kaggle dataset quality issues (mislabelled or duplicate images)	Medium	Medium	Perform initial data inspection and cleaning; use both datasets as cross-validation if significant issues are found
Loss of work due to system failure	Low	High	Version control via Git with remote backup

3.5 Ethics

This project uses only publicly available skin disease image datasets obtained from Kaggle. Both datasets have been released by their authors for research and educational purposes, and contain no directly identifying patient information such as names or dates of birth. No new patient data will be collected, and no human or animal subjects will be involved in the research. For these reasons, formal ethics approval is not required for this project.

Several ethical considerations remain relevant. Publicly released medical image datasets may still carry risks of re-identification. This project will treat all data as sensitive and will not attempt to link images back to individuals or external sources.

Skin disease classifiers are known to exhibit performance disparities across skin tones, as publicly available datasets are often skewed toward lighter skin types. Any results produced by this project will be interpreted with this limitation in mind and per-class performance metrics will be reported to surface any systematic disparities that arise.

While this project is a simulation and does not involve real clinical deployment, the broader motivation carries downstream implications for patient privacy, model accountability, and the trustworthiness of clinical AI systems. This project is a methodological evaluation and no diagnostic claims follow from it.

All code, experimental configurations, and results will be managed with version control to support reproducibility, and the datasets used will be properly cited so that others can verify and build upon the work.

Bibliography

[1] R. J. Hay, N. E. Johns, H. C. Williams, I. W. Bolliger, R. P. Dellavalle, D. J. Margolis, R. Marks, L. Naldi, M. A. Weinstock, S. K. Wulf, C. Michaud, C. J L Murray, and M. Naghavi, "The global burden of skin disease in 2010: An analysis of the prevalence and impact of skin conditions," *The Journal of Investigative Dermatology*, vol. 134, pp. 1527–1534, June 2014.

[2] A. Esteva, B. Kuprel, R. A. Novoa, J. Ko, S. M. Swetter, H. M. Blau, and S. Thrun, "Dermatologist-level classification of skin cancer with deep neural networks," *Nature*, vol. 542, pp. 115–118, Feb. 2017.

[3] G. A. Kaissis, M. R. Makowski, D. Rückert, and R. F. Braren, "Secure, privacy-preserving and federated machine learning in medical imaging," *Nature Machine Intelligence*, vol. 2, pp. 305–311, June 2020.

[4] H. B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. A. y Arcas, "Communication-Efficient Learning of Deep Networks from Decentralized Data," Jan. 2023.

[5] T. Li, A. K. Sahu, M. Zaheer, M. Sanjabi, A. Talwalkar, and V. Smith, "Federated Optimization in Heterogeneous Networks," Apr. 2020.

[6] P. Tschandl, C. Rosendahl, and H. Kittler, "The HAM10000 dataset, a large collection of multi-source dermatoscopic images of common pigmented skin lesions," *Scientific Data*, vol. 5, p. 180161, Aug. 2018.

[7] T. Li, A. K. Sahu, A. Talwalkar, and V. Smith, "Federated Learning: Challenges, Methods, and Future Directions," *IEEE Signal Processing Magazine*, vol. 37, pp. 50–60, May 2020.

[8] S. P. Karimireddy, S. Kale, M. Mohri, S. J. Reddi, S. U. Stich, and A. T. Suresh, "SCAFFOLD: Stochastic Controlled Averaging for Federated Learning," Apr. 2021.

[9] H. Wang, M. Yurochkin, Y. Sun, D. Papailiopoulos, and Y. Khazaeni, "Federated Learning with Matched Averaging," Feb. 2020.

[10] J. Wang, Q. Liu, H. Liang, G. Joshi, and H. V. Poor, "Tackling the Objective Inconsistency Problem in Heterogeneous Federated Optimization," July 2020.

[11] T.-M. H. Hsu, H. Qi, and M. Brown, "Measuring the Effects of Non-Identical Data Distribution for Federated Visual Classification," Sept. 2019.

[12] M. Fredrikson, S. Jha, and T. Ristenpart, "Model Inversion Attacks that Exploit Confidence Information and Basic Countermeasures," in *Proceedings of the 22nd ACM SIGSAC Conference on Computer and Communications Security*, CCS '15, (New York, NY, USA), pp. 1322–1333, Association for Computing Machinery, Oct. 2015.

[13] R. Shokri, M. Stronati, C. Song, and V. Shmatikov, "Membership Inference Attacks Against Machine Learning Models," in *2017 IEEE Symposium on Security and Privacy (SP)*, pp. 3–18, May 2017.

[14] K. Bonawitz, V. Ivanov, B. Kreuter, A. Marcedone, H. B. McMahan, S. Patel, D. Ramage, A. Segal, and K. Seth, "Practical Secure Aggregation for Privacy-Preserving Machine Learning," in *Proceedings of the 2017 ACM SIGSAC Conference on Computer and Communications Security*, CCS '17, (New York, NY, USA), pp. 1175–1191, Association for Computing Machinery, Oct. 2017.

[15] C. Dwork, F. McSherry, K. Nissim, and A. Smith, "Calibrating Noise to Sensitivity in Private Data Analysis," in *Theory of Cryptography* (S. Halevi and T. Rabin, eds.), (Berlin, Heidelberg), pp. 265–284, Springer, 2006.

[16] M. Abadi, A. Chu, I. Goodfellow, H. B. McMahan, I. Mironov, K. Talwar, and L. Zhang, "Deep Learning with Differential Privacy," in *Proceedings of the 2016 ACM SIGSAC Conference on Computer and Communications Security*, pp. 308–318, Oct. 2016.

[17] N. Rieke, J. Hancox, W. Li, F. Milletarì, H. R. Roth, S. Albarqouni, S. Bakas, M. N. Galtier, B. A. Landman, K. Maier-Hein, S. Ourselin, M. Sheller, R. M. Summers, A. Trask, D. Xu, M. Baust, and M. J. Cardoso, "The future of digital health with federated learning," *npj Digital Medicine*, vol. 3, p. 119, Sept. 2020.

[18] M. J. Sheller, B. Edwards, G. A. Reina, J. Martin, S. Pati, A. Kotrotsou, M. Milchenko, W. Xu, D. Marcus, R. R. Colen, and S. Bakas, "Federated learning in medicine: Facilitating multi-institutional collaborations without sharing patient data," *Scientific Reports*, vol. 10, p. 12598, July 2020.

[19] I. Dayan, H. R. Roth, A. Zhong, A. Harouni, A. Gentili, A. Z. Abidin, A. Liu, A. B. Costa, B. J. Wood, C.-S. Tsai, C.-H. Wang, C.-N. Hsu, C. K. Lee, P. Ruan, D. Xu, D. Wu, E. Huang, F. C. Kitamura, G. Lacey, G. C. de Antônio Corradi, G. Nino, H.-H. Shin, H. Obinata, H. Ren, J. C. Crane, J. Tetreault, J. Guan, J. W. Garrett, J. D. Kaggie, J. G. Park, K. Dreyer, K. Juluru, K. Kersten, M. A. B. C. Rockenbach, M. G. Linguraru, M. A. Haider, M. AbdelMaseeh,

N. Rieke, P. F. Damasceno, P. M. C. e Silva, P. Wang, S. Xu, S. Kawano, S. Sriswasdi, S. Y. Park, T. M. Grist, V. Buch, W. Jantarabenjakul, W. Wang, W. Y. Tak, X. Li, X. Lin, Y. J. Kwon, A. Quraini, A. Feng, A. N. Priest, B. Turkbey, B. Glicksberg, B. Bizzo, B. S. Kim, C. Tor-Díez, C.-C. Lee, C.-J. Hsu, C. Lin, C.-L. Lai, C. P. Hess, C. Compas, D. Bhatia, E. K. Oermann, E. Leibovitz, H. Sasaki, H. Mori, I. Yang, J. H. Sohn, K. N. K. Murthy, L.-C. Fu, M. R. F. de Mendonça, M. Fralick, M. K. Kang, M. Adil, N. Gangai, P. Vateekul, P. Elnajjar, S. Hickman, S. Majumdar, S. L. McLeod, S. Reed, S. Gräf, S. Harmon, T. Kodama, T. Puthanakit, T. Mazzulli, V. L. de Lavor, Y. Rakvongthai, Y. R. Lee, Y. Wen, F. J. Gilbert, M. G. Flores, and Q. Li, "Federated learning for predicting clinical outcomes in patients with COVID-19," *Nature Medicine*, vol. 27, pp. 1735–1743, Oct. 2021.

[20] "Skin Diseases + Cancer Comprehensive Dataset." `https://www.kaggle.com/datasets/anieetorudofia/skin-diseases-cancer-comprehensive-dataset`.

[21] "Massive skin disease balanced dataset." `https://www.kaggle.com/datasets/muhammadabdulsami/massive-skin-disease-balanced-dataset`.

[22] K. He, X. Zhang, S. Ren, and J. Sun, "Deep Residual Learning for Image Recognition," Dec. 2015.