

MentorPi Introduction

1. Product Introduction

MentorPi is a ROS2 robot powered by the Raspberry Pi 5. It comes in two variants: MentorPi-M1, which features a Mecanum-wheel chassis, and MentorPi-A1, equipped with an Ackermann chassis. Both models are built with high-performance hardware, including a TOF Lidar and a 3D depth camera, enabling advanced functionalities such as mapping, navigation, path planning, image recognition, vision tracking, and human-robot interaction.



2. Packing List

Note: The following packing list uses the Mecanum wheel version (M1) as an example.

The listed accessories are also compatible with the Ackermann version (A1).

MentorPi M1 (Depth camera version)

 M1 (Mecanum) Chassis (Assembled; Battery included)	 Controller top cover	 Front cover	 Rear cover	 Raspberry Pi 5 (Optional)	 64GB SD card (Optional)	 Cooling fan
 Raspberry Pi power supply cable	 RRC data cable	 RRC Lite controller	 Battery cable	 Lidar+4PIN wire	 Lidar data cable	 8.4V 2A charger (DC5.5 *2.5 male connector)
 3D Depth camera	 Depth data cable	 Wireless handle Handle receiver	 EVA ball	 Card reader	 Accessory bag	 User manual

MentorPi M1 (Monocular camera version)

 M1 (Mecanum) Chassis (Assembled; Battery included)	 Controller top cover	 Front cover	 Rear cover	 Raspberry Pi 5 (Optional)	 64GB SD card (Optional)	 Cooling fan
 Raspberry Pi power supply cable	 RRC data cable	 RRC Lite controller	 Battery cable	 Lidar	 4PIN Lidar wire	 Lidar data cable
 8.4V 2A charger (DC5.5 *2.5 male connector)	 Monocular camera	 Wireless handle Handle receiver	 EVA ball	 Card reader	 Accessory bag	 User manual