

Recochem Cool-C18 Coolant

Traditional coolant superconcentrate meeting GE Transportation Systems engineering specification 84A231282.

COOL-C18 is a nitrite-based, multi-functional corrosion and scale inhibitor chemical program designed for industrial closed cooling systems and for engine cooling systems.

Applications

Recochem Cool-C18 is a traditional conventional inorganic chemistry superconcentrate cooling product which is designed to be used in a wide range of stationary and mobile plant equipment.

When diluted appropriately with water, the product is officially approved to be used in General Electric locomotive and other stationary and mobile GE engines with the primary function to reject heat from the engine and other key components via heat exchange devices, prevent corrosion of locomotive materials, and prevent the scaling and deposit formation in cooling system passages.

The COOL-C18 product is a concentrated product and further dilution with water is required. Initial treat rate of 4% is recommended. When diluting, demineralised or deionised water should always be used.

Recochem Cool-C18 can be used in a wide range of mobile and stationary plant equipment cooling systems and heat transfer systems.

Performance Features and Benefits

Used for the control of corrosion, scale and fouling in closed cooling systems, chilled water systems as well as hot water systems that operate under high heat transfer conditions.

- Provides infield protection against cavitation erosion-corrosion
- Prevents overheating by reducing the formation of scale and sludge deposits in cooling systems
- Extends the life of cooling systems
- Compatible with many MEG based coolant antifreeze products
- No deleterious effects on non-metallic cooling system components

- Will not cause dermatitis or other skin related conditions

Typical Replacement Cycle

Monitor coolant (nitrite level target range 1200 to 1670 ppm as NO₂), and change fluid as necessary every 3000 hours of service life.

Specifications and Approvals

Recochem Cool-C18 is fully approved to GE Transportation Systems engineering specification.

GE 84A231282
GEK Maintenance Instruction 114885
(GEK 80833)

Cool-C18 Coolant also meets the following engine coolant specifications:-

ASTM D 1384

COOL-C18 protects all metals in engine cooling system from corrosive attack, consider alternative products for engines that contain aluminum and its alloys.

Health & Safety

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your Recochem representative.

Protect the Environment

Take used coolant products to an authorised collection point. Do not discharge into drains, soil or water.

Extended Shelf Life

When kept sealed in the original shipping container and stored under cover, away from direct sunlight this product has a two year shelf life. Product should not be left in open unsealed containers due to possible water loss.

Typical Physical and Chemical Characteristics

Cool C18	Method	Units	Performance
Appearance	Visual		Sl. Hazy, Deep Red liquid
pH (as sold)	ASTM D 1287		11.3 – 11.8
Specific Gravity (15 DegC)	ASTM D 1122	kg/L	1.095 – 1.125

These characteristics are typical of current production. Whilst future production will conform to Recochem's specification, variations in these characteristics may occur.