
Diesel Exhaust Fluid

Urea based Diesel Exhaust Fluid meeting ISO 22241

Diesel Exhaust Fluid is a high purity Urea based solution meeting ISO22241 for use in modern SCR (Selective Catalytic Reduction) emission systems for NO_x reduction in diesel trucks, passenger cars, pickups, SUVs, tractors and construction equipments.

Applications

Diesel Exhaust Fluid can be used in all diesel powered engine systems requiring a Urea based fluid for the SCR emission systems.

SCR technology reduced emissions of the NO_x gases that are produced inside the engine during combustion. This process requires the correct injection of Diesel Exhaust Fluid; a non-toxic, highly purified urea-based solution. Diesel Exhaust Fluid is sprayed into the exhaust system, where it is subsequently hydrolysed before the catalytic converter breaks down NO_x gases into harmless Nitrogen (N₂) and Oxygen (O₂).

SCR Technology is already proven to enable Heavy Duty diesel powered engines to comply with strict mandatory EURO V legislation which came into effect in 2008.

Performance Features and Benefits

- Diesel Exhaust Fluid meets ISO 22241
- The use of Diesel Exhaust Fluid is the most efficient way to make use of SCR Technology and comply with EPA emission regulations
- Fully compliant with mandatory legislative requirements
- Suitable for light duty and heavy-duty engine types
- Non harmful, non explosive, non toxic and non combustible

Product Use

You will not need to replenish your Diesel Exhaust Fluid tank every time you refuel. Diesel Exhaust Fluid consumption will be approximately 3% of your fuel consumption (for every 300L of fuel consumed, you will require 9L of Diesel Exhaust Fluid).

Only fill Diesel Exhaust Fluid into the marked Diesel Exhaust Fluid DEF tank on the vehicle.

Do not use Diesel Exhaust Fluid which is mixed with other fluids, either diesel, other fuels or water.

Specifications and Approvals

Fully meets ISO 22241

Health & Safety

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from our representative.

Diesel Exhaust Fluid is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained

Avoid contact with skin, wash any affected areas thoroughly with water and soap after contact.

Protect the Environment

Take used products to an authorized collection point. Do not discharge into drains, soil or water.

Shelf Life

When stored undercover, away from moisture and direct sunlight, this product should be suitable for use for up to one year after the date of manufacture.

Typical Physical and Chemical Characteristics

Diesel Exhaust Fluid	Units	Typical
Urea content	%m	32.5 +/- 0.7
Density (SG) at 20C	kg/m3	1.087 – 1.093
Refractive Index 20C		1.3814 – 1.3843
Alkalinity (Ammonia)	%m	0.2 max
Biuret	%	0.3 max

These characteristics are typical of current production. Whilst future production will conform to manufacture's specification, variations in these characteristics may occur.

Prepared By: Esron Fernando Eliakim	Title: Technical	Supersedes: New	Revision: 0	Date: 1 st February 2023	Next Review:
---	----------------------------	---------------------------	-----------------------	---	---------------------