



DUNAMOSS Tyre Mounting Grease

Technical Data Sheet

GENERAL DESCRIPTION

Dunamoss Tyre Mounting Grease (DTMG) is an odorless paste material specially formulated to possess lubrication properties. It is a waterbased material used for Tire Mounting and Demounting. It is especially suitable for use as lubricant in any manual or automatic tire mounting operation.

PHYSICAL & CHEMICAL PROPERTIES

pH (1 % solution)	: 9 ± 0.5
Boiling Point	: 100°C
Dropping Point	: $> 140^{\circ}\text{C}$
Appearance	: Brown amber paste
Solubility in Water	: Soluble
Odor	: Odorless

ADVANTAGES

☐ **Contain Corrosion Inhibitor**

DTMG contains corrosion inhibitor which will protect metal corrosion. It is safe to all metals.

☐ **Good Lubricating Properties**

This product helps ease the introduction of the tire onto the wheel/rim by lubricating all contacting surfaces.

☐ **Environmental Friendly**

DTMG is waterbased material thus environmental friendly.

☐ **Minimize tire bead damage**

DTMG helps minimize the possibility of damage to the tire beads from the wheel or mounting tools.

APPLICATION

Demounting

- ☐ Ensure the tire is completely deflated before removing from the rim.
- ☐ Break the beads loose on both sides of the tire using a bead breaking tool.
- ☐ Lubricate both beads of the tire using DTMG.
- ☐ Progressively work the tire off the rim using the proper tools.

Mounting

- ☐ Clean and prepare the rim or wheel.
- ☐ Lubricate both tire and the rim flange by using DTMG.
- ☐ Mount the tire over the valve side.

STORAGE & PACKING

Store separate from strong acids and oxidizers. Keep away from heat, sparks and open flame.

Packaging

18 kgs/Pail