



RECO-COOL HD EXPERT EXTRA GLYCOL FREE Pre-Diluted Coolant

Ready-to-Use premium quality Pre-Diluted Coolant that has been tested to be compatible with all automotive and heavy duty antifreeze/coolant products available in the market today.

Reco-Cool HD Expert EXTRA GLYCOL FREE Pre-Diluted Coolant is based on Recochem's proprietary hybrid organic acid technology and has been specifically designed for complete mixed fleet use. It can be used in all makes and models passenger vehicles, light duty and heavy duty diesel applications. Reco-Cool HD Expert EXTRA GLYCOL FREE Pre-Diluted Coolant provides critical protection against corrosion and where freeze protection is not required.

Applications

Reco-Cool HD Expert EXTRA GLYCOL FREE Pre-Diluted Coolant is a low silicate, organic additive, glycol free, extended service product, which is free of phosphates, borates, nitrites and amines. It will provide extended protection against rust, corrosion and pitting caused by cavitation for all coolant system metals, including aluminium. It also provides protection against wet sleeve liner cavitation and is compatible with the flux found in controlled atmosphere brazed (CAB) radiators.

The performance and stability of Recochem's premium extended life corrosion inhibitors allows them to go on working well beyond the lifetime of traditional products. As sold it is ready to use - **do not add water.**

Performance Features and Benefits

When Reco-Cool HD Expert EXTRA GLYCOL FREE Pre-Diluted Coolant is added as an initial fill and properly maintained in accordance with engine manufacturer's maintenance recommendation, it will provide up to 250,000km (150,000 miles) or 5 years of service life protection in automotive application and up to 1,000,000km (600,000 miles) 12,000 hours of service life protection in heavy duty diesel use.

- Complete mixed fleet use; automotive, light and heavy duty diesel
- Borate, nitrite, amine and phosphate free
- Add as top-up to any colour antifreeze
- Protects coolant system metals such as brass, copper, solder, steel, cast iron and aluminium
- Protects against wet sleeve liner cavitation
- Excellent water pump performance
- Fully compatible with inorganic, hybrid and organic acid coolant technologies
- Compatible with CAB radiators
- Extended service life



MINING | CONSTRUCTION | AGRICULTURE | MARINE | TRUCK | EQUIPMENT

Recommended for use in

General Motors

Ford

Honda

Chrysler

Toyota

VW

Nissan

Hyundai

Cummins

Mercedes-Benz

Volvo

Scania

Suitable in mixtures with all major coolant types for service fill

Reco-Cool HD Expert EXTRA GLYCOL FREE
Pre-Diluted Coolant Meets the requirements of
ASTM D3306 (excluding glycol content
requirement)

Health & Safety

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Recochem representative.

Protect the Environment

Take used coolant products to an authorised collection point. Do not discharge into drains, soil or water.

Extended Shelf Life

When stored undercover, away from moisture and direct sunlight, this product should be suitable for use for up to five years after manufacture.

Reco-Cool HD Expert EXTRA GLYCOL FREE Pre-Diluted Antifreeze/Coolant	Performance	Test Method
Typical Physical & Chemical Characteristics		
Appearance, Visual colour	Green	Visual
Specific Gravity (15.6°C)	1.005-1.015	ASTM D 1122
Freeze Point	0°C	ASTM D 1177
pH	7.5-9.5	ASTM D 1287
Reserve Alkalinity (ml 0.1N HCL)	1.0 Min	ASTM D 1121
Foam volume (ml)	150 Max	ASTM D 1881
Foam break time (seconds)	5 Max	ASTM D 1881
Chloride (ppm)	25 Max	ASTM D 3634
Silicon as silicate (ppm)	90 Max	ASTM D 6130
Boron (ppm)	<10	
Phosphorus (ppm)	<10	

These characteristics are typical of current production. Whilst future production will conform to Recochem's specification, variations in these characteristics may occur.