



RECO-COOL HD EXPERT PREMIUM 25% Pre-Diluted Antifreeze/Coolant

Ready-To-Use Long Life Hybrid Nitrited and Silicated Organic Additive Technology Coolant 25% Pre-Diluted

Reco-Cool HD Expert PREMIUM 25% Pre-Diluted Antifreeze/Coolant is a low silicate, nitrited, fully formulated, hybrid organic additive technology automotive and heavy-duty diesel engine coolant. This product does not require a charge of supplemental coolant additive (SCA) during the initial fill. This product is free of phosphate and amine. Reco-Cool HD Expert PREMIUM 25% Pre-Diluted Antifreeze/Coolant is designed for use in both automotive and heavy-duty applications.

Applications

Reco-Cool HD Expert PREMIUM 25% Pre-Diluted Antifreeze/Coolant can be used in both automotive and heavy-duty applications, and is suitable for use in both petrol and diesel powered engines.

This product is particularly suited in applications which require a hybrid technology which is nitrited and low-silicated, and yet is free of amines and phosphates. This product is 'ready-to-use' and should not be diluted further with water.

- **Universal use**

Meets or exceeds standard industry requirements for automotive and heavy-duty diesel applications.

- **Widely compatible with other coolants**

This product is widely compatible with other engine coolants; although to get best performance (regarding issues such as long life and time between SCA addition), it is best to flush the old coolant and replace with Reco-Cool HD Expert PREMIUM 25% Pre-Diluted Antifreeze/Coolant.

Performance Features and Benefits

- **Long life hybrid organic acid technology**

In petrol engine applications, this product is suitable for 5 years or 250,000km, whichever comes first. In diesel applications, it is suitable for 960,000km or 12,000hr lifetime prior to first SCA addition requirement whichever comes first.

- **No initial charge SCA requirement**

When used in long haul or heavy-duty applications, there is no need to initially charge the fresh coolant with SCAs.



MINING | CONSTRUCTION | AGRICULTURE | MARINE | TRUCK | EQUIPMENT

Specifications and Approvals

Reco-Cool HD Expert PREMIUM 25% Pre-Diluted Antifreeze/Coolant has been formulated to meet the following coolant specifications:

OEM/Industry

Specification

OEM/Industry

Specification

ASTM	D3306, D4985, D6210
AS/NZS	2108:2004 "Type A"
Caterpillar	EC-1 (Sections 2.3 – 4.5 incl.)
Cummins	CES 14603
Komatsu	AFNAC
Chrysler	MS 12106
Ford	WSS-M97B44-D1/ WSS-M97B51-A
Detroit Diesel	7SE298
General Motors	1825M, 1899M, 6277M
John Deere	JDM HD24
MAN	MAN 324 TUC 1637/77
Mercedes-Benz	DBL 7700
MTU	(EVP 1 1827/MTL 5048) & NA
SAE	J1034/J1941
Saab/Scania	6901
Volvo	
TMC	RP 329

Health & Safety

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Recochem representative.

Protect the Environment

Take used coolant products to an authorised collection point. Do not discharge into drains, soil or water.

Extended Shelf Life

When stored undercover, away from moisture and direct sunlight, this product should be suitable for use for up to two years after manufacture.

Typical Physical & Chemical Characteristics

Reco-Cool HD Expert Premium 25% Pre-Diluted Antifreeze/Coolant	Performance	Test Method
Appearance, visual colour	Flourescent yellow, clear & bright fluid	Visual
Freeze Point (50% by vol)	-12°C	ASTM D 1177
pH (50% vol)	7.6-9.0	ASTM D 1287
Reserve Alkalinity (ml 0.1N HCL)	3.0 Min	ASTM D 1121
Specific Gravity (15°C)	1.040-1.070	ASTM D 1122
Chloride (ppm)	25 Max	ASTM D 3634

These characteristics are typical of current production. Whilst future production will conform to Recochem's specification, variations in these characteristics may occur.