



HD EXPERT PREMIUM 35% PREMIX COOLANT

HD Expert Premium 35% Premix Coolant is a luminescent green, superior, fully formulated Hybrid technology engine coolant. This Hybrid technology coolant has the advantage of being more robust than both conventional and organic acid technology (OAT) engine coolants. This low silicate, phosphate and amine free product is recommended for use in automotive (aluminium compatible), light duty and heavy-duty diesel applications namely on-road truck, off-road, farm and marine. It is formulated with the same corrosion additive used in the 50% version, therefore upholding OEM approval

Applications

- On road truck and bus fleets.
- Earth moving equipment.
- Stationary power generation engines.
- On board marine engines.
- Off road mining equipment.
- Underground mining.

Features

- Low silicate
- Phosphate and amine free
- OEM approved
- Hard water compatible
- No initial SCA requirement at initial fill.
- Provides freeze protection down to -18°C.
Boil over protection up to 126°C.

Benefits

- Universal use, meeting standard industry requirements for automotive, light duty, and heavy-duty diesel applications (for on and off-road applications).
- Ideal for Multi-fleet applications, providing the following service life:
 - Heavy duty extended life 6 years, 12,000 hours or 1,000,000 km whichever comes first.
 - Automotive 5 years or 250,000 Km.
- Compatible with both conventional and OAT coolants (although to get best performance [regarding issues such as extended life and time between SCA additions] it is best to flush the old coolant and replace with Recochem Heavy Duty Diesel Engine Coolant).
- Compatible with PG coolant.
- Compatible with standard SCAs and coolant extenders.
- Aluminium and light alloy compatible.
- Reduced combustibility, while enhancing heat transfer.
- Excellent wet sleeve liner protection.



MINING | CONSTRUCTION | AGRICULTURE | MARINE | TRUCK | EQUIPMENT

HD Expert Premium 35% Premix Coolant is recommended and suitable for use for the performance requirements of the following engine coolant specifications:

- ASTM D-3306, D-4985, D-6210
- Caterpillar EC1
- Cummins 14603
- Detroit Diesel 7SE 298
- DaimlerChrysler MS 7170, MS 9769
- Ford ESE-M97B44A, ESE-M97B18-C, Ford WSS-M97B51-A1
- Freightliner 48-2288D
- GM 1825M, 1899M, GM Heavy Truck
- Hyundai
- JIS K2234
- Kenworth RO26-170-97
- Landrover
- MACK Trucks
- MAN 324|
- Mercedes Benz DBL 325
- MTU MTL 5048
- New Holland WSN-M97B18-DPACCAR
- Peterbilt 8502.002
- Perkins
- Saab-Scania 6901
- SAE J1034, J1941
- TMC RP 329
- Volvo Heavy Truck
- White Star
- US Federal A-A-870-A

HD Expert Premium 35% Premix Coolant is approved by the following OEMs:

MTU

HD Expert Premium 35% Premix Coolant Performance Testing

Metal Type	ASTM D1384 Glassware Corrosion		ASTM D2570 Simulated Service	
	Test Results	Max. Spec.	Test Results	Max. Spec
Copper	1	10	9	20
Solder	5	30	4	60
Brass	0	10	5	20
Steel	1	10	4	20
Cast Iron	-1	10	2	20
Aluminium	-1	30	4	60

Test	Test Results	Specification
ASTM D4340 Heat Rejecting Aluminium Corrosion (mg/cm ² /week)	0.2	1.0 max.
ASTM D2809 Aluminium Water Pump Cavitation – Erosion Corrosion Rating	8	8 min.



MINING | CONSTRUCTION | AGRICULTURE | MARINE | TRUCK | EQUIPMENT

Characteristics	Performance	Test Method
Appearance	Clear and transparent fluid	
Colour	Luminescent Green	
pH	7.5 – 9.0	ASTM D1287
Reserve Alkalinity, ml	3.0 min.	ASTM D1121
Specific Gravity	1.045 – 1.065	ASTM D1122
Freeze point C/F	-18/0	ASTM D1177
Foam, Volume, ml	50 max.	ASTM D1881
Foam break time, seconds	5 max.	ASTM D1881
Chloride, ppm	< 25	ASTM D3634
Silicon, ppm	< 200	ASTM D6130
Phosphate, ppm	< 10	ASTM D5827
Nitrite, ppm	1200 min.	ASTM D5827
Shelf Life, (Unopened, original container)	5 years	

HD Expert Premium 35% Premix Coolant

The performance and physical property data described for this product is typical results not sale specifications except where maximum or minimum is indicated.

Notice: Because use conditions and applicable laws may differ from one location to another and may change with time, the customer is responsible for determining whether products and the information in this document is appropriate for their use and for ensuring that their workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Recochem's warranty is limited to the claims of product meeting stated specifications. It is the responsibility of the end user to determine product suitability as recommended in the Owner's Manual and to follow engine manufacturer's instructions.