

Reco-Cool OAT-10XSC Superconcentrate Green

Coolant Superconcentrate for predilution for gasoline and diesel engines. This product requires approved dilution prior to use.

Reco-Cool OAT-10XSC is proprietary water based “super concentrate” corrosion inhibitor package. This corrosion inhibitor package is based on a balanced mixture of organic corrosion inhibitors and is classified as an organic acid engine coolant technology (OAT). This product **DOES NOT** contain any amine, borate, nitrate, nitrite, phosphate or silicate corrosion inhibitor technology and is fully compatible with other similarly formulated engine coolants.

Recochem OAT-10XSC must be properly diluted prior to use.

Applications

This material is a fully formulated coolant superconcentrate, and must be blended in accordance with Recochem’s guidelines prior to product use. It is recommended to be used at 7%*m/m* in solution.

The product is to be blended with good quality demineralised water to generate a fully formulated water based coolant for use in Heavy Duty and Automotive applications.

The product can also be blended with a combination of demineralised water and good quality MEG, to generate a fully formulated coolant for use in Heavy Duty and Automotive applications that also exhibits freezing point performance characteristics.

The blending processes using RECO-COOL OAT-10XSC Superconcentrate must be done in accordance with approved and audited Recochem processes in order to guarantee that the product specifications are met.

Performance Features and Benefits

When blended in according to approved Recochem guidelines, this product provides the following advantages:

- Universal, recommended for both automotive and heavy duty diesel applications.
- Silicate free so no silicate gellation / fallout issues
- Environmentally friendly - Product contains no glycol and the organic components are readily biodegradable.
- Amine, borate, nitrate and nitrite free and as such meets some basic Asian OEM chemistry requirements

- Phosphate free which meets some basic European OEM chemistry requirements
- Compatible with nitrite and molybdate corrosion inhibitor chemistry
- Compatible with other similarly formulated engine coolant technology
- Provides appropriate corrosion protection to all coolant system metals including copper, solder, brass, steel cast iron and aluminium
- Excellent shelf stability
- When this superconcentrate makes water based cooling fluid, the premix product must not be used in temperature below 0 DegC
- Blended product is green in colour.

Specifications and Approvals

At 7%*m/m* concentration OAT-10XSC is able to blend a coolant product which is suitable for use in applications requiring the following specifications:-

ASTM	D3306 / D6210
AS/NZS	2108:2004 Type B
BS	6580
JIS	K2234
CAT	EC-1
Cummins	CES 14603
Chrysler	MS12106
Ford	WSS-M97B44-D1/WSS-M97B51-A
GM	1825M/1899M/6277M
Komatsu	AFNAC
MAN	324 NF
Mercedes	MB 325.3/326.3
MTU	MTL 5048
Renault	Type D
VW/Audi	TL-774 F
Nissan	NES 5059 LLC
Peugeot	B71 5110



Health & Safety

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your Recochem representative.

Protect the Environment

Take used coolant products to an authorised collection point. Do not discharge into drains, soil or water.

Extended Shelf Life

When kept sealed in the original shipping container and stored under cover, away from direct sunlight this product has a two year shelf life. Product should not be left in open unsealed containers due to possible water loss.

Typical Physical and Chemical Characteristics

Test	Performance	Test Method
As a Super Concentrate		
Appearance	Deep Green Solution	Visual
pH (5% solution)	7.6 – 9.0	
Alkalinity, ml 0.1N HCl	60.0 min	
Specific Gravity (25°C) g/ml	1.11 to 1.12	ASTM D 1122
Shelf Life	1 year	

These characteristics are typical of current production. Whilst future production will conform to Recochem's specification, variations in these characteristics may occur.

