

2e. Arrays (Vectors and Matrices)

Martin Alfaro

PhD in Economics

INTRODUCTION

So far, we've explored variables representing single-element objects. Now, we'll shift our focus to **collections**, defined as **variables comprising multiple elements**. Julia provides several forms of collections, including:

- Arrays (including vectors and matrices)
- Tuples and Named Tuples
- Dictionaries
- Sets

Arrays represent one of the most common data structures for collections. They are formally defined as objects with type `Array{T,d}`, where `d` is the array's dimension and `T` is its elements' type (e.g., `Int64` or `Float64`).

Two special categories of arrays are **vectors** (1-dimensional arrays) and **matrices** (2-dimensional arrays). Vectors are represented by the type `Vector{T}`, which is an alias for `Array{T,1}`. For its part, matrices use the type `Matrix{T}`, which is an alias for `Array{T,2}`. Although we provide a subsection about matrices at the end, this is labeled as optional. The reason is that vectors are sufficient for conveying the topics of this website.

Remark

Julia uses 1 as an array's first index. This contrasts with many other languages (e.g., Python), where 0 is the first index.

VECTORS

Vectors in Julia are defined as *column-vectors*, and their elements are separated by a comma or a semicolon.

```
x = [1, 2, 3]           #= column-vector (defined
                        Vector{Int64} (alias for
```

```
x = [1; 2; 3]          # equivalent notation to c
```

```
julia> x
3-element Vector{Int64}:
 1
 2
 3
```

Remark

Arrays can hold elements of various types, such as numbers and strings. For example, `[1, 2.5, "Hello"]` is a valid vector in Julia, identifying its elements as having type `Any` (recall that `Any` encompasses all the possible types supported by Julia). While arrays mixing types can be created, they're highly discouraged for several reasons, including performance.

ACCESSING VECTOR ELEMENTS

Given a vector `x`, we can access its i -th element with `x[i]` and retrieve all its elements with `x[:]`.

```
x = [4, 5, 6]
```

```
julia> x
```

```
3-element Vector{Int64}:
```

```
1  
2  
3
```

```
julia> x[2]
```

```
5
```

```
julia> x[:]
```

```
3-element Vector{Int64}:
```

```
4  
5  
6
```

It's also possible to access a subset of `x`'s elements. There are several approaches to achieve this, and we'll only present two basic ones at this point. The simplest method involves setting the indices **via a vector**, using the syntax `x[<vector>]`.

```
x = [4, 5, 6, 7, 8]
```

```
julia> x
```

```
3-element Vector{Int64}:
```

```
1
2
3
```

```
julia> x[[1,3]] # elements of 'x' with indices 1 and 3
```

```
2-element Vector{Int64}:
```

```
4
6
```

```
julia> x[1,3] # be careful! this is the notation used
for matrices, indicating 'x[row 1, column 3]'
```

```
ERROR: BoundsError: attempt to access 5-element
Vector{Int64} at index [1, 3]
```

The second approach sets the indices **via ranges**. These are denoted as `<first>:<steps>:<last>`, with Julia assuming increments of one if we omit `<steps>`. To respectively express the first and last index in a range, you can use the keywords `begin` and `end`.

```
x = [4, 5, 6, 7, 8]
```

```
julia> x
```

```
3-element Vector{Int64}:
```

```
1  
2  
3
```

```
julia> x[1:2] # steps with unit increments (assumed by default)
```

```
2-element Vector{Int64}:
```

```
4  
5
```

```
julia> x[1:2:5] # steps with increments of 2 (explicitly indicated)
```

```
3-element Vector{Int64}:
```

```
4  
6  
8
```

```
julia> x[begin:end] # all elements. Equivalent to 'x[:]' or 'x[1:end]'
```

```
5-element Vector{Int64}:
```

```
4  
5  
6  
7  
8
```

MATRICES (***OPTIONAL***)

Matrices can be defined as collections of row- or column-vectors. If they're created through multiple row vectors, each row has to be separated by a semicolon `;`. If we instead adopt multiple column vectors, their elements need to be separated by a space.

Note that row vectors are considered as special cases of matrices, with their elements separated by a space—they're matrices with multiple columns having one element.

```
X = [1 2 ; 3 4]           #= matrix as a collection of
                           Matrix{Int64} (alias for Vector{Int64})

X = [ [1,3] [2,4] ]      # identical to `C`, but defined as a matrix

Y = [1 2 3]              #= row-vector (defined with Matrix{Int64} (alias for Vector{Int64}))
```

```
julia> X
```

```
2×2 Matrix{Int64}:
```

```
1  2
3  4
```

```
julia> Y
```

```
1×3 Matrix{Int64}:
```

```
1  2  3
```

ACCESSING A MATRIX'S ELEMENTS

Given a matrix `X`, we can access its element at row `r` and column `c` by `X[r,c]`. Likewise, the *i*-th element of a row vector is accessed with `X[i]`.¹ Moreover, we can select all elements across the row `r` by `X[r,:]`, and all elements of column `c` by `X[:,c]`.

```
X = [5 6 ; 7 8] # matrix

Y = [4 5 6]      # row-vector
```

```
julia> X
2×2 Matrix{Int64}:
 5  6
 7  8

julia> X[2,1]
7

julia> X[1,:]
2-element Vector{Int64}:
 5
 6

julia> X[:,2]
2-element Vector{Int64}:
 6
 8

julia> Y[2]
5
```

To access a subset of elements, you must follow the same approaches as with vectors, but applied to either rows or columns.


```
X = [5 6 ; 7 8]
```

```
julia> X
```

```
2×2 Matrix{Int64}:
```

```
 5  6  
 7  8
```

```
julia> X[[1,2],1]
```

```
2-element Vector{Int64}:
```

```
 5  
 7
```

```
julia> X[1:2,1]
```

```
2-element Vector{Int64}:
```

```
 5  
 7
```

```
julia> X[begin:end,1]
```

```
2-element Vector{Int64}:
```

```
 5  
 7
```

FOOTNOTES

- ¹. We could also use this approach for any matrix, as Julia also accepts a linear index for matrices. For instance, a 3x3 matrix accepts indices between 1 and 9. However, unless you want to iterate over all elements of a matrix, the notation `X[r,c]` is easier to interpret.