

## 9b. Stack vs Heap

[Martin Alfaro](#)

PhD in Economics

### INTRODUCTION

Memory allocations occur every time a new object is created. It involves setting aside a portion of the computer's Random Access Memory (RAM) to store the object's data. Conceptually, RAM is divided into two main areas: the stack and the heap. These areas aren't physical locations, but rather logical models that govern how memory is managed.

When an object is created, its storage location is implicitly determined by its type. For example, collections defined as vectors are stored on the heap, whereas those defined as tuples are allocated on the stack.

The choice between stack and heap allocation has significant implications for performance. Allocating memory on the heap is a comparatively expensive operation. It requires a systematic search for an available block of memory, bookkeeping to track its status, and an eventual deallocation process to reclaim the space once it's no longer needed. Stack allocations, by contrast, are simpler and therefore faster.

The performance gap between stack and heap allocations can easily become a critical bottleneck when an operation is performed repeatedly. This disparity in performance explains the common convention in programming, including Julia, where **memory allocations exclusively refer to heap allocations**. In the following, we provide a brief overview of how the stack and heap operate.

### STACK ALLOCATIONS

the stack is typically reserved for primitive types (e.g., integers, floating-point numbers, and characters) and fixed-size collections like tuples. These objects are characterized by their fixed size, precluding the possibility of dynamically growing or shrinking. This constraint makes the allocation and deallocation of memory on the stack extremely efficient.

The primary limitation of the stack is its limited capacity, making it suitable only for objects with a few elements. Indeed, attempting to allocate more memory than the stack can accommodate will result in a "stack overflow" error, causing program termination. And, even if an object fits on the stack, allocating too many elements will significantly degrade performance.

### HEAP ALLOCATIONS

Common objects stored on the heap include arrays (such as vectors and matrices) and strings. Unlike the stack, the heap is designed to support more complex data structures. In particular, the heap enables us to handle objects as large as the available RAM permits, with the ability to grow or shrink dynamically.

While the heap offers greater flexibility than the stack, its more complex memory management comes at the cost of slower performance. Due to its overhead, the following sections will discuss strategies for reducing heap allocations. These include computational techniques that translate vectorized operations into scalar operations, as well as programming practices that favor mutation of existing objects over the creation of new ones.