

2d. Strings

Martin Alfaro

PhD in Economics

INTRODUCTION

This section presents types for text representation, distinguishing between characters and strings. The coverage will be concise, as the website won't focus on string analysis. However, a minimal coverage is necessary as string variables are important for tasks like specifying paths, saving files, and other core functionalities.

CHARACTERS

In Julia, the `Char` type is used to represent individual characters. A character `x` is defined by using single quotes, as in `'x'`. Given its support for Unicode characters, `Char` encompasses not only numbers and letters, but also a wide range of symbols. This is shown below.

```
# x equals the character 'a'
x = 'a'

# 'Char' allows for Unicode characters
x = 'β'
y = '🐒'
```

Notice that characters must be enclosed in single quotes `' '`, even for symbols like . Otherwise, Julia will interpret the expression as a variable.

```
# any character is allowed for defining a variable
🐒 = 2           # 🦒 represents a variable, just
y = 🦒           # y equals 2
z = '🐒'         # z equals the character 🦒
```

STRINGS

We'll rarely use the type `Char` directly. Instead, we'll work with the so-called type `String`. This is an ordered collection of characters, making it possible to represent text.

Strings can be defined through either double quotes `" "` or triple quotes `""" """`. The latter is particularly convenient for

handling newlines, such as when the text has to span multiple lines.¹

```
x = "Hello, beautiful world"  
  
x = """Hello, beautiful world"""
```

STRING INTERPOLATION

String interpolation allows you to embed Julia code within a string, which is then evaluated and replaced in the string with its value.

To interpolate an expression, you must simply prefix the string with the `$` symbol. If the expression contains spaces, you'll need to enclose it in curly braces, like `$(())`. Both cases are exemplified below.

```
number_students = 10  
  
output_text      = "There are $(number_students) :  
  
julia> x  
"There are 10 students in the course"
```

```
number_matches = 50
goals_per_match = 2

output_text      = "Last year, Messi scored $(numl
julia> x
"Last year, Messi scored 100 goals"
```

FOOTNOTES

1. For more on the differences between double and triple quotes, see [here](#)