7c. Benchmarking Execution Time

Martin Alfaro
PhD in Economics

INTRODUCTION

This section introduces standard tools for benchmarking code performance. Our book reports results based on the `BenchmarkTools` package, which is currently the most mature and reliable option in the Julia ecosystem. That said, the newer `Chairmarks` package has demonstrated notable improvements in execution speed compared with `BenchmarkTools`. I recommend adopting `Chairmarks` once it's achieved sufficient stability and adoption within the community.

To set the stage, we'll start by addressing some key points for interpreting benchmark results. We'll also look at Julia's built-in `@time` macro, whose limitations explain why `BenchmarkTools` and `Chairmarks` should be used instead.

TIME METRICS

Julia uses the same time metrics described below, regardless of whether you use `BenchmarkTools` or `Chairmarks`. For quick reference, these metrics can be accessed at any point **in the left bar** under "**Notation & Hotkeys**".

Unit	Acronym	Measure in Seconds
Seconds	`s`	1
Milliseconds	`ms`	10^{-3}
Microseconds	`µs`	10^{-6}
Nanoseconds	`ns`	10^{-9}

Alongside execution times, each package also reports the amount of **memory allocated on the heap**, typically referred to simply as **allocations**. These allocations can play a major role in overall performance, and usually indicate suboptimal coding practices. As we'll explore in later sections, monitoring allocations tends to be crucial for achieving high performance.

"TIME TO FIRST PLOT"

The expression "Time to First Plot" refers to a specific performance characteristic inherent in Julia's operation. It describes the delay experienced when running a function for the first time during a session. This latency is a side effect of how the language translates code into action. Specifically, the first execution triggers the generation of low-level machine instructions to carry out the function's operations. This translation from human-readable code into machine-executable instructions is known as **compilation**. Unlike many other languages that compile before running, Julia relies on a just-in-time (JIT) compiler. This means the code compiles on-the-fly when the function is first executed.

While this approach enables high performance, it introduces latency during the initial run. Fortunately, recent developments have significantly reduced the practical impact of this delay. Thanks to improvements in the precompilation system since Julia 1.9, a vast majority of package functions are now compiled before you even start writing code. Consequently, the compilation penalty in any new session mainly affects functions defined by the user or novel combinations of argument types that precompilation doesn't cover. Once a function is compiled, its machine code is cached. This caching ensures that all subsequent calls to that specific function execute much faster than the first time.

The latency incurred varies significantly across functions. While it may be imperceptible for simple operations, it can still be noticeable when triggering a chain of user-defined methods or write complex operations. This explains the origin of the term "Time to First Plot", since originally drawing the first plot during a session was taking several seconds.

> ⚠️ **Warning!**
> Precompilation hasn't changed the JIT compilation model. Understanding that Julia compiles specialized machine code for your specific types remains crucial for writing performant Julia code.

@TIME

Julia comes with a built-in macro called `@time`, allowing you to get a quick sense of an operation's execution time. The results provided by this macro, nonetheless, suffer from several limitations that make it unsuitable for rigorous benchmarking.

First, a measurement based on just a single execution is often unreliable, as runtimes can fluctuate significantly due to background processes on your computer. Second, if that run represents a function's first call, the measurement will include compilation overhead. The extra time Julia spends generating machine code inflates the reported runtime, making it unrepresentative of subsequent calls.

Moreover, while running `@time` multiple times can address these issues, the macro still has a major flaw when used for rigorous benchmarking: it evaluates code in the global scope. We'll show in upcoming sections that non-constant global variables have a marked detrimental effect on performance. Consequently, the time reported doesn't accurately reflect how the function would perform in practice.

The following example illustrates the use of `@time`, highlighting the difference in execution time between the first and subsequent runs.

@TIME

```
x = 1:100

@time sum(x)         # first run                      -> it incorporates compilation time
@time sum(x)         # time without compilation time -> relevant for each subsequent run
```

```
 0.002747 seconds (3.56 k allocations: 157.859 KiB, 99.36% compilation time)
 0.000003 seconds (1 allocation: 16 bytes)
```

PACKAGE "BENCHMARKTOOLS"

A more reliable alternative for measuring execution time is provided by `BenchmarkTools`. This addresses the shortcomings of `@time` in several ways.

First, it reduces result variability by running operations multiple times and providing summary statistics. It also measures the execution time of functions without compilation latency, since the package discards the first run for the reported timing. Additionally, the package allows users to explicitly control variable scope: by prefixing function arguments with the `$` symbol, these are treated as local variables during a function call.

The package offers two macros, depending on the level of detail required: `@btime`, which only reports the minimum time, and `@benchmark`, which provides detailed statistics. Below, we demonstrate their use.

@BTIME

```
using BenchmarkTools

x = 1:100
@btime sum($x)        # provides minimum time only
```

```
  2.314 ns (0 allocations: 0 bytes)
```

@BENCHMARK

```
using BenchmarkTools

x = 1:100
@benchmark sum($x)    # provides more statistics than `@btime`
```

In upcoming sections, we'll exclusively benchmark functions. This means that you should always prefix the function arguments with `$`. **Omitting `$` will lead to inaccurate results**, including incorrect reports of memory allocations.

The following example demonstrates the consequence of excluding `$`, where the runtimes reported are higher than the actual runtime.

NO '$'

```
using BenchmarkTools
x = rand(100)

@btime sum(x)
```

```
  14.465 ns (1 allocation: 16 bytes)
```

WITH '$'

```
using BenchmarkTools
x = rand(100)

@btime sum($x)
```

```
  6.546 ns (0 allocations: 0 bytes)
```

PACKAGE "CHAIRMARKS"

A new alternative for benchmarking code is given by the `Chairmarks` package. Its notation closely resembles that of `BenchmarkTools`, with the macros `@b` and `@be` respectively providing a similar functionality to `@btime` and `@benchmark`. The main benefit of `Chairmarks` is its speed, as it can be orders of magnitude faster than `BenchmarkTools`.

As with `BenchmarkTools`, measuring the execution time of functions appropriately requires prepending function arguments with `$`.

@B

```
using Chairmarks
x = rand(100)

display(@b sum($x))        # provides minimum time only
```

```
6.550 ns
```

@BE

```
using Chairmarks
x = rand(100)

display(@be sum($x))       # analogous to `@benchmark` in BenchmarkTools
```

```
Benchmark: 3856 samples with 3661 evaluations
 min    6.679 ns
 median 6.815 ns
 mean   6.785 ns
 max    14.539 ns
```

REMARK ON RANDOM NUMBERS FOR BENCHMARKING

When comparing the performance of different methods, we must ensure that our measurements aren't skewed by variations in the input data. To accomplish this, each approach must be tested using *the exact same set of values*. In this way, differences in execution time can be attributed solely to the efficiency of the method itself, rather than to a change in the inputs.

This consistency can be achieved by using random number generators. They rely on a **random seed**, which is an arbitrary starting point that dictates the entire sequence of values to be produced. By setting the same seed before each test, we can generate identical deterministic sequences of random numbers across multiple runs. **Any arbitrary number can be used for the seed**. The only requirement is that the same number is employed, so that you replicate the exact same set of random numbers.

Below, we demonstrate random number generation by using the package `Random`. We choose the seed `1234` before executing each operation. Note, though, that any other number could be used as long as it's the same across runs.

SAME VALUES

```
using Random

Random.seed!(1234)      # 1234 is an arbitrary number, use any number you want
x = rand(100)

Random.seed!(1234)
y = rand(100)           # identical to `x`
```

DIFFERENT VALUES

```
using Random

Random.seed!(1234)      # 1234 is an arbitrary number, use any number you want
x = rand(100)


y = rand(100)           # different from `x`
```

For presentation purposes, code snippets in this book will omit the lines dedicated to setting the random seed. While adding these code lines is essential for ensuring reproducibility, their inclusion in every example would create unnecessary clutter. Below, we illustrate the code that will be displayed throughout the book, along with the actual code executed.

SNIPPET EXECUTED

```
using Random
Random.seed!(123)

x = rand(100)

y = sum(x)
```

SNIPPET SHOWN

```
# We omit the lines that seet the seed


x = rand(100)

y = sum(x)
```

BENCHMARKS IN PERSPECTIVE

When evaluating approaches for performing a task, execution times are often negligible, typically on the order of nanoseconds. Yet, this doesn't mean that the choice of method has no practical consequence: **the relevance of benchmarks becomes apparent when these operations are performed repeatedly**. This includes cases where the operation is called in a for-loop or embedded in iterative computations (e.g., solving systems of equations or optimizing functions). In these situations, small differences in timing are amplified, as they are replicated hundreds, thousands, or even millions of times.

AN EXAMPLE

To illustrate this matter, let's consider a specific example. Suppose we want to double each element of a vector `x`, and then calculate their sum. In the following, we'll compare two different approaches to accomplish this task. Both methods produce the same result.

The first method will be based on `sum(2 .* x)`, with `x` treated as a global variable. As we'll discuss in later sections, this approach is inefficient. A more performant alternative is given by `sum(a -> 2 * a, x)`, where `x` is passed as a function argument. The measured runtimes of each approach are as follows.

IMPLEMENTATION 1

```
x      = rand(100_000)

foo()  = sum(2 .* x)
```

```
 35.519 μs (5 allocations: 781.37 KiB)
```

IMPLEMENTATION 2

```
x      = rand(100_000)

foo(x) = sum(a -> 2 * a, x)
```

```
 6.393 μs (0 allocations: 0 bytes)
```

The results reveal that the second approach achieves a significant speedup, requiring less than 15% of the time consumed by the slower method. However, even the "slow" approach is remarkably fast when interpreted in absolute terms, completing in under 0.0001 seconds.

This pattern will be recurring in our benchmarks, where execution times are often negligible. In such cases, the relevance of our conclusions depends heavily on context. If the operation is performed only once, readability should guide the choice of implementation. Instead, if the operation is executed repeatedly, small performance differences accumulate and might become meaningful, making the faster approach a more suitable choice.

To make this point concrete, let's place these functions inside a for-loop that runs 100,000 times. Since our sole goal is to repeat the operation, the iteration variable itself plays no role. In such cases, it's a common practice to employ a **throwaway variable**: a placeholder that exists only to satisfy syntax requirements, without ever being referenced. This convention signals to other programmers that the variable's value can be safely ignored. In our example, `_` serves this purpose within the for-loop. It reflects that each iteration performs exactly the same operation, without depending on the for-loop index.

IMPLEMENTATION 1 WITHIN A FOR-LOOP

```
x      = rand(100_000)
foo()  = sum(2 .* x)

function replicate()
   for _ in 1:100_000
      foo()
   end
end
```

```
 5.697 s (500000 allocations: 74.52 GiB)
```

IMPLEMENTATION 2 WITHIN A FOR-LOOP

```
x      = rand(100_000)
foo(x) = sum(a -> 2 * a, x)

function replicate(x)
   for _ in 1:100_000
      foo(x)
   end
end
```

```
 677.130 ms (0 allocations: 0 bytes)
```

The example starkly reveals the consequences of calling these functions within a for-loop. The execution time of the slow version now jumps to more than 5 seconds, while the fast version finishes in under one second. Such a stark contrast underscores the importance of optimizing functions that are executed repeatedly: even seemingly minor improvements can accumulate into pronounced performance gains.