5e. Slices: Copies vs Views

Martin Alfaro
PhD in Economics

Code Script

This section's scripts are available **here**, under the name `allCode.jl`. They've been tested under Julia 1.11.8.

INTRODUCTION

This section concludes the introduction of preliminary concepts for the study of mutations. The attention is now shifted to the concept of vector **slices**: subsets of elements drawn from a vector, written as `x[<indices>]`. In particular, the focus will be on the critical distinction between whether slices act as:

- **copies** of the original vector, thus creating a new object at a new memory address.
- **views** of the original vector, where the original object and the slice share the same memory address.

Whether one or the other arises depends on where the slice appears within an expression.

The difference is central to implementing mutations correctly, as such operations are only possible when working with a view. If a slice is instead a copy, the parent object and the slice become entirely independent entities. Therefore, modifications to the slice have no impact on the original object.

In Part II of this website, we'll also see that the distinction between copies and views has implications for performance. Essentially, creating a copy requires allocating new memory, which introduces computational overhead. Views, by contrast, avoid this cost by reusing the memory of the original vector.

Because of its broad significance, we'll examine the topic of copies and views independently of mutations. In particular, we'll identify how slices behave in different cases. Moreover, we'll explain how to instruct Julia to treat slices as views or copies.

SLICES AND THE ASSIGNMENT OPERATOR

Slices in assignments behave differently depending on their position within the expression. Specifically, **slices on the left-hand (LHS) side of `=` act as views**. In this role, slices directly reference the original elements, enabling mutation of the parent object. In contrast, **slices on the right-hand side (RHS) of `=` create a copy**. Since copies point to a new object in memory, any modification to the slice won't affect the original object.

The following code snippet demonstrates these contrasting behaviors.

A Slice on the LHS | A Slice on the RHS

A SLICE ON THE LHS

```
x    = [4,5]


x[1] = 0        # 'x[1]' is a view, line mutates 'x'
```

Output in REPL

```
julia> x
2-element Vector{Int64}:
 0
 5
```

Aliasing vs Copying

Objects on the RHS of `=` are only treated as copies when it comes to **slices**, such as in statements `y = x[<indices>]`. Instead, if we insert the whole object `x` on the RHS of `=`, as in `y = x`, the operation creates an alias. In that case, `y` and `x` will reference the same object, so that any modification made to `y` will also be reflected in `x`.

Object on the RHS (Aliasing) | All Elements on the RHS (Copy)

OBJECT ON THE RHS (ALIASING)

```
x    = [4,5]
y    = x        # the whole object (a view)

x[1] = 0        # it DOES modify 'y'
```

Output in REPL

```
julia> y
2-element Vector{Int64}:
 0
 5
```

THE FUNCTION 'VIEW'

Beyond assignments, we must also distinguish whether slices represent copies or views within other expressions. As a rule of thumb, **slices typically default to creating copies**. Such behavior arises when, for instance, a slice is passed as a function argument or incorporated into a computation. Several of the scenarios are illustrated below.

Slices as Copies

SLICES AS COPIES

```
x = [3,4,5]

#the following slices are all copies
log.(x[1:2])

x[1:2] .+ 2

[sum(x[:]) * a for a in 1:3]

(sum(x[1:2]) > 0) && true
```

In all these cases, if you instead want to work with views, you must indicate this explicitly. Several methods exist for achieving this, with the most straightforward being the function `view`. Its syntax is `view(x, <indices>)`, where `<indices>` specify the indices that define the slice. To demonstrate its usage, we revisit the previous examples.

Slices as Views | Slices as Copies

SLICES AS VIEWS

```
x = [3,4,5]

#we make explicit that we want views
log.(view(x,1:2))

view(x,1:2) .+ 2

[sum(view(x,:)) * a for a in 1:3]

(sum(view(x,:)) > 0) && true
```

The examples reveal the potential verbosity involved when `view` isn't used sparingly. To mitigate this issue, Julia provides the `@view` and `@views` macros.

The `@view` macro is equivalent to `view`, allowing you to write `@view x[1:2]` instead of `view(x, 1:2)`. Its benefits, however, are somewhat limited: it saves only a few characters and still requires parentheses when multiple slices appear in the same expression (e.g., `@view(x[1:2]) .+ @view(x[2:3])`). By contrast, the `@views` macro significantly streamlines notation, converting *every* slice within an expression into a view.

Macros for Views

MACROS FOR VIEWS

```
x = [4,5,6]

# the following are all equivalent
       y = view(x, 1:2)  .+ view(x, 2:3)
       y = @view(x[1:2]) .+ @view(x[2:3])
@views y = x[1:2] .+ x[2:3]
```

One of the most notable applications of `@views` arises in functions. When placed at the beginning of a function definition, `@views` ensures that every slice appearing in the function body or its arguments is treated as a view.

@views At A Function Definition | Equivalent With @view

@VIEWS AT A FUNCTION DEFINITION

```
@views function foo(x)
  y = x[1:2] .+ x[2:3]
  z = sum(x[:]) .+ sum(y)

  return z
end
```

copy

Previous Section

Next Section