[MIDWAY REPORT] IS THE GAP AN INTERFACE GAP? AGENT TOOL INTERFACES FOR DATA CATALOGS

Alex Feng

1 PROBLEM STATEMENT (PROBLEM SPECIFICATION)

Maintainers of lakehouses need trustworthy catalog metadata (ownership, grain, filters, lifecycle state). But this metadata drifts from the code: annotations "can become outdated or incorrect" as data models evolve (Lakafosis et al., 2025). The evidence needed to correct it is scattered across catalog metadata, SQL, lineage, tests, and the data. I am building a *catalog steward*, prototyped on dbt and DuckDB, with two triggers over one workflow: *remediation* of existing hygiene debt and *change review* of a proposed contribution. Our question: **does a specialized evidence-gathering, risk-aware action, and verification workflow produce more complete, grounded, and safe maintenance outcomes than a general-purpose coding agent with access to the same repository and warehouse?**

2 METHODOLOGY

2.1 ENVIRONMENT & DATA

Environment and data. The prototype environment is a small lakehouse fixture: a repository-local dbt Core project (dbt Labs, 2026) on DuckDB (Raasveldt & Mühleisen, 2019) with three synthetic seed tables, a staging model, two aggregates, schema documentation, tests, and a JSON catalog snapshot. A versioned hygiene contract (`design/hygiene_contract.yaml`) bounds the task to five issue types (missing required metadata, SQL/metadata drift, grain or join drift, unsupported reliability claims, lifecycle drift) and three action classes (patch, propose, report). The pilot suite (`data/episodes/manifest.yaml`) has ten hand-built examples: four *remediation* cases, four *flawed changes*, and two *clean controls*. Each records its expected `(issue_type, asset)` findings and its acceptable and unsafe actions.

Evaluation. Each condition runs once on an identical, freshly built copy of each example. Codex's answer is converted to the steward's plan form, and the harness then diffs its workspace and applies the steward's patch verification. Findings are matched exactly against the manifest as `(issue_type, asset)` pairs. Every trace is also audited, with AI assistance, for what the scorer cannot check: whether each claim is true of the fixture, whether each action suits the example, and whether each extra finding is a real gap the labels miss.

2.2 METHODS

What I built. The catalog steward (Figure 1) pairs a domain-specific evidence interface for catalog hygiene with an inspect–plan–act–verify workflow under a risk-aware action policy, and both triggers share it: remediation starts from existing hygiene debt, and change review adds the proposed diff. This pairing is the contribution. Rather than leaving a model to search a repository and edit files, the steward first gathers the facts that hygiene decisions rest on into an evidence bundle (catalog metadata, dbt schema and manifest, model SQL with facts parsed by SQLGlot (Mao, 2026), lineage, bounded data profiles), each item carrying a stable, content-hashed ID. Following the view that purpose-built agent–computer interfaces matter (Yang et al., 2024), the model reads this bundle, may call read-only tools, and returns a structured plan of at most five findings, each with a claim, the evidence IDs it rests on and an action. A deterministic validator rejects a plan that breaks the schema or the contract's scope, evidence or action rules, with one repair turn. It then routes each finding to a catalog patch, a review proposal or a report, and appends every outcome to a ledger. Only reversible technical metadata may be patched, and only in an example-local override file.

Limits. Verification is weak. A patch is kept only if the written field equals the value the model declared and `dbt parse` still succeeds. Neither check tests semantic correctness, and `dbt parse`

does not read `catalog/`. The contract's per-issue checks (dashed in the figure) are not implemented yet.




Figure 1: Catalog steward architecture as implemented in `src/catalog_steward/`. Both triggers feed one workflow. The model reads a bundle of content-hashed evidence, may call read-only tools, and returns a structured plan. A deterministic validator accepts the plan or returns it once for repair, and each accepted finding is then patched, proposed or reported, and logged. The only planned element is dashed: the contract's per-issue verification checks.

Conditions. The *steward* is the frozen pilot (config v1.2.0): `gpt-6-luna` at low reasoning effort, at most 12 turns, with the evidence bundle, read-only tools, validator and executor; two of its ten records replay an earlier identical run. *Codex, matched* is OpenAI Codex CLI 0.167.0 (OpenAI) on the same model and effort, so the harness is what differs; *Codex, frontier* uses `gpt-6.1-sol` at medium effort. Both get the steward's task specification, including the hygiene contract, and the same project, warehouse and diff, but general shell and file tools instead of the bundle, validator and executor: a sandbox writable only inside the workspace, no network, no turn limit within a 30-minute timeout, and a JSON output schema.

2.3 What Did Not Work, and Pivots

Reply format. In a preliminary run the model copied a wrapper key from the format example, so its replies were rejected; I fixed the example and added one shared repair turn (commit `d2a547b`).

Raw-tool exploration. On `change_daily_revenue_filter` our raw-tool agent batched tool calls; once rejected, it reported nothing and missed the regression. Another run cited unreceived output yet passed the ID-only evidence check (pilot `analysis.md`). Codex replaced it.

Label choice. On `rem_customer_orders_wrong_grain` the steward labelled a grain error SQL/metadata drift, a patchable type, and patched a correct value, but the example required a proposal with uniqueness evidence, so it failed. Next, issue type is checked apart from the label.

Unmatched baseline. A first Codex run matched the steward on two cases, but a different model, no contract rules in the prompt and hand-mapped labels confounded harness with model and wording (`codex_midway_two_case/README.md`). The new baseline removes all three.

3 Results (Summary of Progress)

What I compared. All of Figure 1 and the Codex adapter are implemented. Under the unchanged scorer the steward does not win (Table 1): it succeeds on 5 examples, against 6 for matched and 7 for frontier Codex, with the highest recall (0.90, against 0.70 and 0.80) and the most extra findings (6, against 5 and 3). No run used a forbidden action, failed verification or edited another file, and no isolation flag fired. The largest difference goes unscored: in change review the steward

Table 1: Per-example outcomes, one run each. TP: a finding whose (issue type, asset) pair matches an expected one exactly; FP: any other finding; FN: an expected finding left unmatched. An example *succeeds* if the run completes with no FP or FN, no forbidden action class and no failed verification. Micro precision and recall are $\sum$TP/ $\sum$(TP+FP) and $\sum$TP/ $\sum$(TP+FN). The last row counts forbidden action classes, failed patch verifications, and runs that edited a file other than the override file, which the steward cannot do (n/a).

	Steward		Codex, matched		Codex, frontier	
Example	TP/FP/FN	Success	TP/FP/FN	Success	TP/FP/FN	Success
Remediation						
Stale revenue-filter description	1/0/0	yes	1/0/0	yes	1/0/0	yes
Wrong customer-order grain	0/1/1	no	0/1/1	no	1/0/0	yes
Missing owner	1/0/0	yes	1/0/0	yes	1/0/0	yes
Legacy copy still active	1/1/0	no	0/1/1	no	0/0/1	no
Flawed change						
Revenue filter changed	1/0/0	yes	1/0/0	yes	1/0/0	yes
Grain changed, metadata not	2/2/0	no	1/2/1	no	1/2/1	no
New undocumented model	1/0/0	yes	1/0/0	yes	1/0/0	yes
Rename without lifecycle change	2/0/0	yes	2/0/0	yes	2/0/0	yes
Clean control						
Documented new model	0/1/0	no	0/1/0	no	0/1/0	no
Documented revenue metric	0/1/0	no	0/0/0	yes	0/0/0	yes
Example successes	5/10		6/10		7/10	
Micro precision / recall	0.60 / 0.90		0.58 / 0.70		0.73 / 0.80	
Forbidden / failed / other edits	0 / 0 / n/a		0 / 0 / 0		0 / 0 / 0	

only proposed, while Codex patched the catalog in 3 (matched) and 4 (frontier) of six runs (audit: `experiments/results/codex_baseline_v1/analysis.md`; records by example there and in the pilot folder).

Remediation: legacy copy still active (`rem_legacy_model_lifecycle`). A pass-through copy of `customer_orders` is still marked active and canonical. I expect lifecycle drift, proposed or reported, on catalog, manifest, lineage and repository-history evidence. From its bundle's catalog flags and lineage the steward rightly proposed a lifecycle review, but met the history requirement with the example's empty diff and added a grain report its own claim calls unestablished: 1/1/0, no success. Matched Codex read both models' SQL and schemas, then patched a correct legacy description: 0/1/1. Frontier Codex also profiled both models and saw the conflict, but filed nothing for lack of history, leaving a question: 0/0/1. Each should have reported the conflict alone; the contract shares the blame, since a remediation example has no history to cite.

Change review: revenue filter changed (`change_daily_revenue_filter`). The change keeps `status != 'cancelled'`, so refunded orders now count while the catalog still excludes them. I expect SQL/metadata drift, answered by asking whether refunds belong in revenue or proposing a metadata update. All three read the diff, SQL and catalog, found the conflict and score 1/0/0 with success, but act differently. The steward proposed review and asked which statuses count, but understated the change ("not explicitly excluded", despite `refunded` in its schema evidence; a cache replay). Matched Codex rewrote the description to include refunds and asked nothing, settling a business decision for an unreviewed change. Frontier Codex confirmed a refunded row in the data and patched likewise, then asked if refunds were intended, noting the stale `completed_*` column names. Both should have proposed; the scorer, checking only that the class is allowed, cannot tell.

Limitations. Each cell is one sample; in the paired check, matched Codex succeeded on the filter change in two of three samples (paired-check `README.md`). AI agents built the examples and labels, and both clean controls contain real unlabelled gaps; crediting those the audit identifies would give 7, 7 and 8 successes (not a re-scoring). The scorer checks exact labels, resolvable evidence and allowed action classes, not whether evidence supports a claim or an action suits the example. A one- or two-example gap supports no ranking, and nothing here shows that the steward's design improves scored outcomes.

4 ASSETS

Repository: `https://github.com/alfenn/agentic-catalog-interface` (Feng, 2026): `README.md` (setup, reproduction), `src/catalog_steward/`, `data/` (fixture, examples), `experiments/results/`. Midpoint demo video: **[VIDEO URL TO BE ADDED]**.

5 TIMELINE (SUMMARY OF PROGRESS: NEXT STEPS AND RISKS)

Milestones. Course deadlines are Demo Day on December 9 and the final 8-page report on December 11; intermediate dates are our targets.

- *By November 13:* a new frozen example version: documented seeds, truly clean controls, an issue-type precedence rule checked independently of the model's label, and human review of the AI-built labels.
- *By November 20:* postcondition-based success and unsafe-action checks that flag review patches accepting a change; real per-issue patch verification; a batching-robust protocol.
- *By December 4:* repeated samples, tool-versus-workflow ablations against matched Codex, and growth toward 30–50 audited examples.
- *December 9 and 11:* live demo of both modes; final report.

Obstacles and concerns. No credential or pipeline blocker remains. The main concern is validity: label choices and protocol behaviour move results as much as the workflow, so fixes go into a new frozen version, not a rescoring.

Risks and mitigations. *Scope growth:* a frozen five-type contract with hard limits. *Ambiguous ground truth* (seen in both clean controls): documented seeds, a precedence rule, human label review. *Unsupported claims* (one invented-evidence run passed): claim–evidence support checks and manual audit. *Warning overload* (six steward extras): clean controls, a five-finding cap, flagging only gaps a change introduces. *Small pilot:* per-example reporting, more examples.

REFERENCES

dbt Labs. dbt Core, version 1.12.6. GitHub repository `dbt-labs/dbt-core` (Apache-2.0), 2026. URL `https://github.com/dbt-labs/dbt-core`.

Alex Feng. agentic-catalog-interface: Catalog steward midpoint prototype, hygiene contract, episode manifest, evaluation configuration, and pilot results. GitHub repository; paths in the text are relative to its root, 2026. URL `https://github.com/alfenn/agentic-catalog-interface`.

Vasileios Lakafosis, Hannes Roth, Benjamin Renard, Wenlong Dong, Zhonghu Gao, and Dave Kurtzberg. How Meta understands data at scale. Engineering at Meta Blog, April 28, 2025, 2025. URL `https://engineering.fb.com/2025/04/28/security/how-meta-understands-data-at-scale/`.

Toby Mao. SQLGlot: An easily customizable SQL parser and transpiler, version 29.0.1. GitHub repository `tobymao/sqlglot` (MIT), 2026. URL `https://github.com/tobymao/sqlglot`.

OpenAI. Codex CLI. GitHub repository. URL `https://github.com/openai/codex`. Accessed November 8, 2026.

Mark Raasveldt and Hannes Mühleisen. DuckDB: An embeddable analytical database. In *Proceedings of the 2019 International Conference on Management of Data (SIGMOD)*, 2019.

John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. SWE-agent: Agent-computer interfaces enable automated software engineering. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

AI-USE DISCLOSURE STATEMENT

Generative AI agents did most of the implementation and writing at this stage. Codex also ran the two-case baseline and revised this report in response to human feedback. AI agents built the matched Codex baseline runner and its tests, ran the paired check and the full matched and frontier Codex runs (Codex being the system compared against), audited all 20 Codex traces, and rewrote the results around them. OpenAI Codex agents implemented the prototype (environment setup, agent harness, hygiene contract, evidence tools, steward workflow, and baseline runners), built the dbt/DuckDB fixtures and the ten evaluation examples and their labels, wrote the evaluation and scoring code, ran and audited the static pilot, and drafted the README and an initial version of this report. Claude (Anthropic) agents then audited, tested, fixed, and finished the work, including the preflight audit of the paid-run pipeline and its fixes, running the preliminary runs and the three-condition pilot, the manual audit of every pilot trace, typesetting this report in the ICLR template, the references, the script that generates the charts and results table from saved results, and the revision of this report around the audit. Because AI agents constructed the examples and labels as well as the system under test, the ground truth reflects their design choices and needs independent human review. **[AUTHOR TO COMPLETE: describe the human verification actually performed, e.g., which code, example labels, results, and report claims the author reviewed.]** AI tools are not authors; the author takes full responsibility for the content of this work.