[MIDWAY REPORT] IS THE GAP AN INTERFACE GAP? AGENT TOOL INTERFACES FOR DATA CATALOGS

Alex Feng

1 PROBLEM STATEMENT (PROBLEM SPECIFICATION)

Lakehouse maintainers need trustworthy catalog metadata (ownership, grain, filters, lifecycle state). This metadata drifts from the code: annotations "can become outdated or incorrect" as data models evolve (Lakafosis et al., 2025). The evidence to correct it is scattered across catalog metadata, SQL, lineage, tests and data. I am building a *catalog steward*, prototyped on dbt and DuckDB, with two triggers over one workflow: *remediation* of existing hygiene debt and *change review* of a proposed contribution. Our question: **does a specialized evidence-gathering, risk-aware action, and verification workflow produce more complete, grounded, and safe maintenance outcomes than a general-purpose coding agent with access to the same repository and warehouse?**

2 METHODOLOGY

2.1 ENVIRONMENT & DATA

Environment and data. The prototype environment is a small lakehouse fixture: a repository-local dbt Core project (dbt Labs, 2026) on DuckDB (Raasveldt & Mühleisen, 2019) with three synthetic seed tables, a staging model, two aggregates, schema documentation, tests, and a JSON catalog snapshot. A versioned hygiene contract (`design/hygiene_contract.yaml`) binds the task to five issue types (missing required metadata, SQL/metadata drift, grain or join drift, unsupported reliability claims, lifecycle drift) and three action classes (patch, propose, report). The evaluation suite (`data/episodes/manifest.yaml`) has ten hand-built examples: four *remediation* cases, four *flawed changes*, and two *clean controls*. Each example comes with an answer key: the problems a careful reviewer should report, each named by its issue type and the table it affects (e.g., SQL/metadata drift on `daily_revenue`), plus the acceptable and unsafe responses.

Evaluation. Each condition runs once on an identical, freshly built copy of each example. Codex's answer is converted to the steward's plan form, and the harness then diffs its workspace and applies the steward's patch verification. A reported problem counts as correct only if both its issue type and its table match an entry in the answer key; otherwise it is an *extra* (a false positive), and the number of extras measures how much noise a harness puts in front of a reviewer. Every trace is also audited, with AI assistance, for what the scorer cannot check: whether each claim is true of the fixture, whether each action suits the example, and whether each extra is a real gap the labels miss.

2.2 METHODS

What I built. The catalog steward (Figure 1) pairs a domain-specific evidence interface for catalog hygiene with an inspect–plan–act–verify workflow under a risk-aware action policy, shared by both triggers (change review adds the proposed diff). This pairing is the contribution. Rather than leaving a model to search a repository and edit files, the steward first gathers the facts hygiene decisions rest on into an evidence bundle (catalog metadata, dbt schema and manifest, model SQL with facts parsed by SQLGlot (Mao, 2026), lineage, bounded data profiles), each item carrying a stable, content-hashed ID. Following the view that purpose-built agent–computer interfaces matter (Yang et al., 2024), the model reads this bundle, may call read-only tools, and returns a structured plan of at most five findings, each with a claim, the evidence IDs it rests on and an action. A deterministic validator rejects a plan that breaks the schema or the contract's scope, evidence or action rules. It then routes each finding to a patch, a review proposal or a report, and logs every outcome in a ledger. Only reversible technical metadata may be patched, and only in an example-local override file.

Limits. Verification is weak. A patch is kept only if the written field equals the model's declared value and `dbt parse` succeeds. Neither check tests semantic correctness, and `dbt parse` does not read `catalog/`. The contract's per-issue checks (dashed in the figure) are planned.




Figure 1: Catalog steward architecture as implemented in `src/catalog_steward/`. Both triggers feed one workflow. The model reads a bundle of content-hashed evidence, may call read-only tools, and returns a structured plan. A deterministic validator accepts the plan or returns it once for repair, and each accepted finding is then patched, proposed or reported, and logged. The only planned element is dashed: the contract's per-issue verification checks.

Conditions. The *steward* runs on the agentic harness I built (evidence bundle, read-only tools, validator and executor) with `gpt-6-luna` at low reasoning effort for at most 12 turns. Two Codex comparisons run OpenAI Codex CLI 0.167.0 (OpenAI): *Codex, matched* on the same model and effort, so only the harness differs, and *Codex, frontier* on `gpt-6.1-sol` at medium effort. Both get the steward's task specification, including the hygiene contract (Section 2.1), the same dbt project and warehouse, and, for change review, the proposed diff. Instead of the steward's harness, they get general shell and file tools in a sandbox writable only inside the workspace, with no network and no turn limit within a 30-minute timeout, and answer in a JSON output schema.

2.3 What Did Not Work, and Pivots

From question answering to data hygiene. My proposal planned a general-purpose data agent for question answering over a data lake, but its task categories and examples were too myopic for the problem I want to solve: keeping lakehouse metadata trustworthy as the lakehouse changes. Reframing the project around the data-hygiene process itself, through its two workflows (remediating existing debt and reviewing proposed changes), tackles that problem directly.

From a bespoke baseline to Codex. My first comparison agent was a simple custom agent with four raw tools (list files, read a file, read the diff, run a bounded SQL query) on the steward's model. It was easy to inspect and differed from the steward only in its tools, but it is not representative of the alternative someone would actually use to fix these hygiene issues. I replaced it with Codex, a frontier agent harness, and reran the comparison on all ten examples (`experiments/results/codex_baseline_v1/`), trading the simpler agent's comparability and ease of inspection for a comparison against a frontier harness.

3 Results (Summary of Progress)

3.1 Reported Results

In Table 1, the steward succeeds on 5/10 examples (precision 0.60, recall 0.90), matched-Codex on 6/10 (0.58, 0.70) and frontier-Codex on 7/10 (0.73, 0.80). The steward finds the most answer-key problems but also reports the most extras: 6, against 5 for matched-Codex and 3 for frontier-Codex.

Table 1: Per-example outcomes, one run each. TP: a reported problem matching an answer-key entry (same issue type and table); FP: an *extra*, a reported problem matching none; FN: an answer-key entry no reported problem matches. An example *succeeds* if the run completes with no FP or FN, no forbidden action class and no failed verification. Precision and recall are micro-averaged because per-example (macro) recall divides by the number of answer-key entries, which is zero for the *clean control* examples. The last row counts forbidden action classes, failed verifications and edits outside the override file (n/a for the steward, which cannot make them).

	Steward		Codex, matched		Codex, frontier	
Example	TP/FP/FN	Success	TP/FP/FN	Success	TP/FP/FN	Success
Remediation						
Stale revenue-filter description	1/0/0	yes	1/0/0	yes	1/0/0	yes
Wrong customer-order grain	0/1/1	no	0/1/1	no	1/0/0	yes
Missing owner	1/0/0	yes	1/0/0	yes	1/0/0	yes
Legacy copy still active	1/1/0	no	0/1/1	no	0/0/1	no
Flawed change						
Revenue filter changed	1/0/0	yes	1/0/0	yes	1/0/0	yes
Grain changed, metadata not	2/2/0	no	1/2/1	no	1/2/1	no
New undocumented model	1/0/0	yes	1/0/0	yes	1/0/0	yes
Rename without lifecycle change	2/0/0	yes	2/0/0	yes	2/0/0	yes
Clean control						
Documented new model	0/1/0	no	0/1/0	no	0/1/0	no
Documented revenue metric	0/1/0	no	0/0/0	yes	0/0/0	yes
Total TP / FP (extras) / FN	9/6/1		7/5/3		8/3/2	
Example successes	5/10		6/10		7/10	
Micro precision / recall	0.60 / 0.90		0.58 / 0.70		0.73 / 0.80	
Forbidden / failed / other edits	0 / 0 / n/a		0 / 0 / 0		0 / 0 / 0	

3.2 Results Discussion and Observations

Linked example names open their run files in `experiments/results/codex_baseline_v1/` (the steward's are in `midpoint_v1_2_pilot/`), audited in `analysis.md`.

Steward vs. matched-Codex. With the same model, the steward's harness finds more: its bundle covers every table in scope, so only it caught the failing uniqueness claim (*Grain changed, metadata not*) and the stale legacy copy (*Legacy copy still active*). It also reports more extras, and one borderline extra (*Documented revenue metric*) decides the one-example gap. Both filed the wrong grain as SQL/metadata drift and patched it (*Wrong customer-order grain*), so the error is the model's.

Steward vs. frontier-Codex. The gap comes mostly from the stronger model, which labelled the wrong grain correctly and reported half the extras (3 vs. 6). It still missed both steward-only finds: the uniqueness claim, and the legacy copy, which it saw but would not file without repository history.

Why Codex scored higher. Success is all-or-nothing, so one extra fails an example: four of the steward's five failures miss nothing and fail on extras alone. The steward shows the model every table in scope, so it comments on more, and half its extras are real gaps the labels miss; Codex reads only what it chooses and reports less. The scorer misses the largest difference: in change review the steward only proposed, while Codex patched the catalog in 3 and 4 of six runs, e.g., rewriting the revenue description to accept an unreviewed change (*Revenue filter changed*, scored 1/0/0 for all).

3.3 Limitations and Next Steps

Evaluation limits. Each cell is one run (matched-Codex passed the filter change in two of three earlier tries), and with ten examples a gap of one or two supports no ranking. AI agents built the examples and labels, and both examples meant to have no hygiene problems contain real gaps the labels miss (crediting them gives 7, 7 and 8 successes). The scorer checks neither evidence support nor action fit.

How to improve the steward. Frontier-Codex chose what to read and query and reported half the steward's extras, suggesting a stronger model filters its own context. The steward should filter for a weaker model instead: give it only the evidence each candidate issue needs, in change review flag only gaps the change introduces, and drop findings the model itself calls unestablished. The validator should check evidence content, not presence (the legacy-copy finding cited an empty diff), and an issue-type precedence should stop a grain problem being patched as drift.

Next steps (Section 5)**.** About 50 human-reviewed examples, repeated runs, the steward on the frontier model (to separate model from harness), and scoring patches that accept unreviewed changes as unsafe.

More baselines. Pi, another open-source coding-agent harness, and standard data-hygiene automations (e.g., dbt-project-evaluator, Great Expectations) run in CI on every change.

4 Assets

Repository: `https://github.com/alfenn/agentic-catalog-interface` (Feng, 2026): `README.md` (setup, reproduction), `src/catalog_steward/`, `data/` (fixture, examples), `experiments/results/`. Midpoint demo video: **[VIDEO URL TO BE ADDED]**.

5 Timeline (Summary of Progress: Next Steps and Risks)

Milestones. Demo Day is December 9 and the final report December 11; the rest are my targets.

- *By November 13:* a revised example set, locked before new runs: documented seeds, truly clean controls, a label-independent issue-type precedence rule, human label review.
- *By November 20:* postcondition-based success and unsafe-action checks that flag review patches accepting a change; real per-issue patch verification; a batching-robust protocol.
- *By December 4:* repeated samples, ablations and about 50 audited examples.

Risks and mitigations. *Scope growth:* a contract held at five issue types. *Ambiguous ground truth* (seen in both clean controls): documented seeds, a precedence rule, human label review. *Unsupported claims* (one invented-evidence run passed): claim–evidence checks and manual audit.

References

dbt Labs. dbt Core, version 1.12.6. GitHub repository `dbt-labs/dbt-core` (Apache-2.0), 2026. URL https://github.com/dbt-labs/dbt-core.

Alex Feng. agentic-catalog-interface: Catalog steward prototype, evaluation and results. GitHub repository; paths in the text are relative to its root, 2026. URL https://github.com/alfenn/agentic-catalog-interface.

Vasileios Lakafosis, Hannes Roth, Benjamin Renard, Wenlong Dong, Zhonghu Gao, and Dave Kurtzberg. How Meta understands data at scale. Engineering at Meta Blog, April 28, 2025, 2025. URL https://engineering.fb.com/2025/04/28/security/how-meta-understands-data-at-scale/.

Toby Mao. SQLGlot: An easily customizable SQL parser and transpiler, version 29.0.1. GitHub repository `tobymao/sqlglot` (MIT), 2026. URL https://github.com/tobymao/sqlglot.

OpenAI. Codex CLI. GitHub repository. URL https://github.com/openai/codex. Accessed November 8, 2026.

Mark Raasveldt and Hannes Mühleisen. DuckDB: An embeddable analytical database. In *Proceedings of the 2019 International Conference on Management of Data (SIGMOD)*, 2019.

John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. SWE-agent: Agent-computer interfaces enable automated software engineering. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

AI-USE DISCLOSURE STATEMENT

In this work, I used generative AI tools to refine the hypothesis, to brainstorm task formulations, and to give feedback on the research methodology. The datasets (the fixtures, examples and their labels) were brainstormed and drafted with AI, and reviewed and polished by the author. Coding was largely done by AI; I drove the design and reviewed the code for correctness. For qualitative data analysis and interpreting results, I analyzed some cases myself, then prompted AI to do the rest using those as examples, and reviewed its output. Additionally, I used generative AI tools for brainstorming, identifying gaps in prior work, searching for and summarizing relevant literature, and providing editing suggestions for readability. I have reviewed all AI-assisted work, including the literature summaries, for accuracy, and I take responsibility for the final content of this work, including text, claims, or artifacts produced with the aid of generative AI.