paths.py

`src/moe_pruning/utils/paths.py · 134 lines · module moe_pruning.utils.paths`

What it does

Defines where every artifact lives, in one place, plus small JSON and hashing helpers.

How it works

- `ArtifactPaths` exposes each artifact path (statistics, scores, selection, checkpoints, caches, evaluation outputs, logs) derived from the configuration.
- `require()` stops a script with a message naming the script that produces a missing input.
- `write_json()` writes atomically; `file_sha256()` and `fingerprint()` identify inputs and settings.

Defined in this file

Extracted from the source code (classes, public functions and methods).

Name	Description
`class MissingArtifactError`	Raised when a stage depends on an artifact that has not been produced yet.
`class ArtifactPaths`	Locations of all artifacts of the configured experiment.
`.architecture_report() [property]`	Location of the architecture report artifact.
`.expert_stats() [property]`	Location of the expert stats artifact.
`.expert_stats_manifest() [property]`	Location of the expert stats manifest artifact.
`.expert_scores_json() [property]`	Location of the expert scores json artifact.
`.expert_scores_csv() [property]`	Location of the expert scores csv artifact.
`.expert_selection() [property]`	Location of the expert selection artifact.
`.replaced_model_dir() [property]`	Location of the replaced model dir artifact.
`.trained_model_dir() [property]`	Location of the trained model dir artifact.
`.bias_initialization_report() [property]`	Location of the bias initialization report artifact.
`.layer_cache_dir() [property]`	Location of the layer cache dir artifact.
`.training_report() [property]`	Location of the training report artifact.
`.eval_dir() [property]`	Location of the eval dir artifact.
`.eval_metrics(stage)`	Metrics file of an evaluation stage.
`.eval_per_example(stage)`	Per-example results of an evaluation stage.
`.eval_comparison_json() [property]`	Location of the eval comparison json artifact.
`.eval_comparison_md() [property]`	Location of the eval comparison md artifact.
`.eval_examples_cache() [property]`	Location of the eval examples cache artifact.
`.log_file() [property]`	Location of the log file artifact.
`.config_snapshot_dir() [property]`	Location of the config snapshot dir artifact.
`.require(path, produced_by)`	Return the path, or stop with the command that produces it.
`write_json(path, data)`	Write JSON atomically (temporary file, then rename).
`read_json(path)`	Read a JSON file.
`file_sha256(path, chunk_size)`	SHA-256 of a file (identifies datasets in fingerprints).
`fingerprint(data)`	Stable short hash of a JSON-serialisable object.

Settings it reads

`CACHE_DIR/EXPERIMENT_NAME`, `EXPERIMENT_DIR/EXPERIMENT_NAME`, `STATS_DIR/EXPERIMENT_NAME`

Connections

Uses: `moe_pruning.config`

Used by: `scripts/build_c4_support_eval.py`, `scripts/collect_stats.py`, `scripts/convert_model.py`, `scripts/evaluate.py`, `scripts/export_model.py`, `scripts/inspect_model.py`, `scripts/replace_experts.py`, `scripts/score_experts.py`, `scripts/train_biases.py`, `src/moe_pruning/data/calibration.py`, `src/moe_pruning/evaluation/evaluator.py`, `src/moe_pruning/serialization/checkpoint.py`, `src/moe_pruning/training/bias_trainer.py`, `src/moe_pruning/utils/cli.py`